NEON2: Finding Local Minima via First-Order Oracles

Zeyuan Allen-Zhu and Yuanzhi Li

NeurIPS 2018

List item 50 / Ref 77 | Tags: S, D, E, G / F, B | Tier: Must read

The paper in one minute

Question: Can a method using Hessian-vector products be replaced by a purely first-order method without losing its theoretical oracle performance?
Model/Method: NEON2 detects negative curvature with stochastic or full gradient differences; the detector is plugged into existing stationary-point optimizers.
Finding: A modular reduction converts GD, SGD, SVRG, SCSG and Natasha2 variants to approximate second-order stationary-point methods, with first-order oracles only.
Why we care: Efficient saddle-escape routines need not build Hessians or even evaluate Hessian-vector products; gradients can be sufficient.

1. Why replace the Hessian-vector oracle?

An algorithm may efficiently find points where $\|\nabla f(x)\| \le \varepsilon$, yet return a saddle because $\lambda_{\min}(\nabla^2 f(x)) \ll 0$. Some methods add *Hessian-vector products* to find a negative direction. NEON2 aims to eliminate that additional oracle while retaining comparable guarantees. Its target is

$$\|\nabla f(x)\| \le \varepsilon, \qquad \nabla^2 f(x) \succeq -\delta I.$$

The paper uses the expression *approximate local minimum* for this second-order condition. It does *not* assert that the returned point is an actual local minimum for every nonconvex function.

The gradient-difference trick

Let x_0 be the reference point. For a small displacement u and a sampled component function f_i, consider

$$\nabla f_i(x_0 + u) - \nabla f_i(x_0) \approx \nabla^2 f_i(x_0)u.$$

Averaging over a random sample index i approximates the full Hessian's action on u. This replaces *one Hessian-vector product* by a gradient-difference operation using first-order oracles.

Worked example: sample-gradient offsets cancel

Take two component losses in $\mathbb{R}^2$:

$$f_1(u) = \tfrac{1}{2}u^T Hu + (2,-1)^T u, \quad f_2(u) = \tfrac{1}{2}u^T Hu + (-2,1)^T u, \quad H = \mathrm{diag}(2,-1).$$

At reference $x_0 = 0$, either sample yields

$$\nabla f_i(u) - \nabla f_i(0) = (Hu + a_i) - a_i = Hu.$$

With $u = (0.1, 0.1)$, this is $(0.2, -0.1)$. A centered step of size 0.2 gives $u^+ = (0.06, 0.12)$; the negative-curvature component grows. In real stochastic problems the sample Hessians differ, so the cancellation is only of baseline offsets, not all noise. This is a pedagogical illustration.

2. NEON2's two principal settings

Online/stochastic NEON2 (Algorithm 1–2, Theorem 1)

Starting from $x_1 = x_0 + \xi$ with a small random perturbation, the weak detector performs

$$x_{t+1} = x_t - \eta\big(\nabla f_i(x_t) - \nabla f_i(x_0)\big),$$

with fresh sample indices. This is approximately a randomized power iteration on $I - \eta H$; negative eigenmodes expand. A verification stage checks whether the proposed direction truly has sufficiently negative curvature, with the confidence boosted by repetitions. Under the theorem's Lipschitz gradient/Hessian assumptions, the online detector uses $\widetilde{O}(1/\delta^2)$ stochastic gradients (with hidden smoothness/logarithmic factors) to either return a unit vector v with $v^T H v \le -\delta/2$, or certify $H \succeq -\delta I$ to specified confidence.

Offline deterministic and finite-sum versions

The deterministic NEON2 uses a different first-order construction based on Chebyshev-style polynomial acceleration, obtaining a bound of order $\widetilde{O}(1/\sqrt{\delta})$ *full gradients* (or its finite-sum conversion) for negative-curvature search; the complexity includes hidden smoothness and n factors in appropriate oracle units. The paper also describes a finite-sum NEON2 variant for cases where n is moderate.

The modular reduction

Combine any suitable first-order stationary-point finder with NEON2. When the gradient is large, the base optimizer makes progress. When the gradient is small, call NEON2: either curvature is approximately nonnegative, or use the found direction to decrease the loss. The improvement in the oracle complexity is the *negative-curvature detector*, not a new proof that all nonconvex functions lack spurious local minima.

Read carefully: Section 1.1 and its Theorems 1–7 (informal overview), Section 3 Algorithms 1–2 / Theorem 1, Section 4 (deterministic), Section 5 (finite-sum). Compare Figure 1 with the independent NEON paper, Ref 76.

3. Contribution, assumptions, and limits

Contributions. NEON2 is a general-purpose *reduction*: it supplies a negative-curvature detection ingredient compatible with a variety of existing algorithms. The authors analyze online, deterministic and finite-sum oracles, and give improved first-order complexity bounds for multiple combinations (SGD, SCSG, GD, SVRG, Natasha2). **Assumptions.** Component functions have Lipschitz gradients and Hessians as required by the theorems, and the algorithms use randomized initialization, calibrated target curvature δ, confidence parameters and step sizes. Some results require finite-sum or online sampling access. Bounds are in *gradient evaluations*, not wall-clock seconds. **Limitations.** Curvature detection still consumes multiple gradient computations and relies on smoothness. An approximate second-order stationary point is not guaranteed to be globally optimal or even an exact local minimum. The claimed reductions are theoretical complexity results; practical ranking may change with hardware and data.

Connections to earlier papers

NEON (Xu–Jin–Yang, Ref 76) also amplifies negative Hessian eigenmodes using gradients, but NEON2 develops a different stochastic estimator and deterministic Chebyshev-based formulation. **Reddi et al. (Ref 74)** provides a generic first/second-order hybrid architecture that can benefit from cheaper negative-curvature routines. **Daneshmand (2018)** instead assumes stochastic gradients have energy along negative-curvature directions (CNC).

Quick reference

Term	Meaning
(ε, δ)-minimum	$\|\nabla f\| \le \varepsilon$ and $\lambda_{\min}(H) \ge -\delta$.
Gradient difference	$\nabla f_i(x+u) - \nabla f_i(x)$ approximates $H_i u$.
Online NEON2	Stochastic gradients; $\widetilde{O}(1/\delta^2)$ NC detection under assumptions.
Deterministic NEON2	Full gradients; accelerated NC detection of order $\widetilde{O}(1/\sqrt{\delta})$ in gradient calls.
Reduction	Upgrade a first-order stationary-point method with a curvature check.

Papers Master note

Allen-Zhu and Li introduce NEON2, a gradient-only negative-curvature detector for stochastic, deterministic and finite-sum settings. Plugging it into GD/SGD/SVRG/SCSG/Natasha2 yields approximate second-order stationarity without Hessian-vector oracles, under smoothness and specified oracle-complexity assumptions.

Source: original NeurIPS 2018, Sections 1–5, Algorithms 1–3, Theorems 1–7.