A Mean-Field Analysis of Deep ResNet and Beyond

Yiping Lu, Chao Ma, Yulong Lu, Jianfeng Lu, Lexing Ying

ICML 2020

Paper 62 | Ref 90 | Tags: G, D, A / B | Skim

The paper in one minute

Question: Can deep residual networks inherit the favorable mean-field geometry of shallow models as depth increases?
Model/Method: Treat each residual block as a particle; use a continuous-depth ODE with time-dependent parameter distribution and adjoint sensitivity analysis.
Finding: In the constructed continuum model, positive loss admits a descent direction, so every local minimizer in the stated domain is global. A gradient-flow convergence conclusion requires extra homogeneity, support and convergence assumptions.
Why we care: Depth itself can act as an overparameterization mechanism in a special limit, but continuum guarantees do not automatically cover ordinary finite ResNets.

1. A deep ResNet as many small corrections

A residual block modifies a state rather than replacing it:

$$X_{\ell+1} = X_\ell + \frac{1}{L} f(X_\ell, \theta_\ell), \qquad \ell = 0, \dots, L-1.$$

The factor $1/L$ makes each of the L corrections small. If $t = \ell/L$ and depth grows, the recursion resembles Euler's discretization of an ODE:

$$\dot{X}(t) = \int f(X(t), \theta)\, \rho_t(d\theta), \quad X(0) = x.$$

Here ρ_t is the distribution of residual-block parameters at *network depth* t, not the time used for optimization. Training time is a different variable, often denoted s.

Worked example: why $1/L$ matters

Use the scalar block $X_{\ell+1} = X_\ell + (a/L)X_\ell$. Starting at $X_0 = 1$, after L blocks,

$$X_L = (1 + a/L)^L \longrightarrow e^a.$$

For $a = 1$, $L = 2$ gives 2.25, $L = 10$ gives about 2.594, and the continuum limit is $e \approx 2.718$. Without the $1/L$ scaling, $X_L = (1 + a)^L$ would typically explode. This is a pedagogical scalar Euler example, not an architecture-specific theorem.

Why a distribution of blocks?

Different blocks correspond to different parameter locations. In the large-depth limit, replace their empirical collection by a time-indexed measure $\rho(\theta, t)$. The network's output is determined by the ODE solution $X_\rho(x, 1)$. The risk $E(\rho)$ is then a functional of this entire distribution.

First-principles link: Standard two-layer mean-field theory averages many parallel neurons. Here the authors average many small *sequential* residual contributions using a special scaling and ODE limit.

2. Why the continuous model can lack bad local minima

Differentiate through the ODE

The adjoint $p_\rho(x,t)$ is a backwards-in-depth sensitivity: it tells how changing the state at depth t would change final loss. Theorem 2 expresses the functional derivative of the risk schematically as

$$\frac{\delta E}{\delta \rho}(\theta,t) = \mathbb{E}_x\big[p_\rho(x,t)\cdot f(X_\rho(x,t),\theta)\big].$$

The point is analogous to backpropagation: gradients of early blocks must be propagated backwards through all later blocks. The proof uses *adjoint sensitivity* rather than differentiating a fixed stack of matrices.

Theorem 3: a descent direction exists when loss is positive

Under the paper's regularity and universal-kernel assumptions, if $E(\rho) > 0$, the authors construct another parameter distribution ν such that

$$\left\langle \frac{\delta E}{\delta \rho}, \nu - \rho \right\rangle < 0.$$

Because $(1-\epsilon)\rho + \epsilon\nu$ is a valid probability measure for small $\epsilon > 0$, the first-order change in loss is negative. Therefore ρ cannot be a local minimum. By contrast, a zero-loss distribution achieves the global loss floor.

A simpler illustrative analogy

For $E(p) = (p-2)^2$ on the scalar line, $E(0) = 4$ and moving toward $p = 2$ decreases loss. The actual paper is harder because its variable is a *probability distribution*, not a scalar; the direction $\nu - \rho$ changes the mass allocated to parameter values.

Theorem 4 adds conditions to obtain training convergence

The convergence claim concerns a Wasserstein gradient flow with a positively homogeneous residual block. It further assumes the flow converges and the limiting distribution has a particular support/separation property. *No theorem here asserts global convergence for arbitrary finite ResNets trained with SGD.*

> **Critical distinction:** "Every local minimum is global" (landscape property) and "an algorithm reaches a global minimum" (dynamical property) are different statements. The latter is conditional in this paper.

3. Contributions, limits, and cross-paper role

Contributions. A continuous-depth distributional ResNet model; rigorous sensitivity formulae; positive-loss descent directions implying benign local minima for the mean-field objective; conditional gradient-flow convergence and exploratory layer-reordering training schemes. **Assumptions.** Bounded input and targets, Lipschitz-in-depth distributions, a universal-kernel condition, controlled local derivatives/parameter support (Assumption 1), plus homogeneity and convergence/support-separation conditions for Theorem 4. The model uses specially scaled residual updates and a continuum limit. **Limitations.** Formal landscape results are for the proposed distributional ODE objective, not a generic finite-width/depth residual network. The global-flow conclusion is conditional. Layer-reordering benefits are empirical and should not be described as guaranteed.

Survey connections

Mei et al. (Ref 89) gives mean-field dynamics for wide shallow networks; Lu et al. build a depth-based analogue. **Du (2019)** proves GD reaches zero training loss under finite-architecture width and smooth-activation assumptions rather than a continuum-depth limit. **Nguyen (Ref 88)** explains convergence from a well-conditioned finite feature layer. **Ge (2017)** likewise illustrates how favorable nonconvex geometry depends on structure.

Quick reference

Object	Interpretation
$X_{\ell+1} = X_\ell + L^{-1} f(\cdot)$	Euler-style residual block scaled by depth.
ρ_t	Parameter distribution at network depth t.
$X_\rho(x, t)$	State following the continuum ResNet ODE.
Adjoint p_ρ	Backpropagation sensitivity through the ODE.
Theorems 3–4	Benign local geometry; conditional flow-to-global result.

Papers Master note

Lu et al. (2020) formulate a mean-field/continuous-depth ResNet whose positive-loss distributions admit descent directions, so its local minima are global under structural assumptions. Global convergence of its Wasserstein gradient flow needs additional homogeneity and support/convergence conditions; this is not a blanket theorem for finite ResNets.

Source: ICML 2020 original, Assumption 1, Theorems 2–4, Sections 2–4. Scalar example pedagogical.