Ref. [35] — Taming Stochastic Gradient Descent

V. Apidopoulos, I. Lytras, P. Mertikopoulos | ICML 2026

1. Problem: why standard SGD theory can be too restrictive

Many stochastic-convergence proofs assume a globally Lipschitz gradient, $\|\nabla f(x) - \nabla f(y)\| \le L\|x - y\|$. In neural-network objectives, local curvature may increase with gradient magnitude; thus a global L may not exist. This paper asks whether suitably modified SGD can still *converge almost surely* and avoid strict saddles in these more general landscapes.

2. The relaxed smoothness idea

A representative twice-differentiable form is

$$\|\nabla^2 f(x)\| \le L_0 + L_1\|\nabla f(x)\|,$$

allowing local curvature to grow with gradient magnitude rather than remain uniformly bounded. The authors analyze a generalized (L_0, L_1)-smoothness framework sufficiently broad to permit superlinear and even exponential gradient growth. These statements describe the *regularity class*; they do not establish that all neural networks satisfy it.

3. What "taming" changes

Ordinary SGD uses $x_{t+1} = x_t - \eta_t g_t$, where g_t estimates $\nabla f(x_t)$. When $\|g_t\|$ can be huge, a single update may invalidate a local-smoothness argument. A generic teaching example of a bounded-length modification is

$$x_{t+1} = x_t - \eta_t \frac{g_t}{1 + \eta_t\|g_t\|}; \qquad \left\|\eta_t \frac{g_t}{1 + \eta_t\|g_t\|}\right\| < 1.$$

This formula illustrates taming; it is not asserted to be the exact update of either algorithm in the paper. The actual contribution is *two* rigorously analyzed taming schemes, the second incorporating a more flexible dissipative mechanism.

4. Two schemes and their distinct noise hypotheses

The authors first obtain almost-sure convergence for a taming construction under a generalized *ABC-type* stochastic-gradient noise condition. They then introduce a *dissipative taming* variant that converges under less restrictive moment-bound hypotheses. Thus the two theorems should not be collapsed into one result with a single noise assumption.

5. First-principles intuition for saddle avoidance

At a smooth strict saddle $x^\star$ there is a unit vector v with

$$\nabla f(x^\star) = 0, \qquad v^\top \nabla^2 f(x^\star) v = -\gamma < 0.$$

For the local quadratic model, an ordinary GD displacement z_t along v approximately follows

$$z_{t+1} \approx (1 + \eta_t\gamma) z_t.$$

The factor is greater than one: tiny displacements along negative curvature grow. Proving that a *stochastic, tamed* trajectory does not remain trapped requires additional control of the noise and diminishing steps; the local calculation is an explanatory reason, not a substitute for that proof.

Reported result (authors). Under their respective assumptions, both taming schemes give almost-sure convergence and almost-sure avoidance of strict saddle points and/or strict-saddle manifolds; therefore, generically, limit points are local minimizers. "Almost surely" describes the probability of an infinite-run event, *not* a finite-time bound for escaping a saddle.

6. Assumptions, limits, and survey relevance

The framework depends on generalized smoothness, stochastic moment/noise conditions, step-size requirements and structural assumptions around saddles. It does not provide a universal escape-time guarantee for degenerate saddles, nonsmooth ReLU kinks, or large-step Adam training. The landscape may also have spurious local minima. This paper directly informs **RQ2** (stochastic dynamics) and **RQ4** (theory beyond classical smoothness), and qualifies interpretations of **RQ3**.

> **Verification scope.** The title, two algorithms, assumptions at the abstract level and principal qualitative results are confirmed on the original ICML proceedings page. Exact theorem-numbered step rules and proof constants are not reconstructed here; do not insert invented formulas into a survey theorem table.

7. Our notes

This paper strengthens the older story that stochastic methods avoid strict saddles: it also handles losses whose curvature can grow with the gradient, using carefully controlled updates. The conclusion is almost-sure convergence and avoidance under stated conditions, not a practical claim that ordinary SGD always escapes quickly. **Original source:** `https://proceedings.mlr.press/v306/apidopoulos26a.html`.