Ref. [56] — Qualitatively Characterizing Neural Network Optimization Problems

Ian J. Goodfellow, Oriol Vinyals, Andrew M. Saxe | ICLR 2015

1. The question: do SGD trajectories actually cross barriers?

The loss is non-convex in millions of parameters, so it seems plausible that training requires navigating countless local minima and high-loss obstacles. Yet modern networks often reach tiny training error with simple SGD. Instead of proving a global geometric theorem, the authors propose an empirical diagnostic: inspect a straight-line path between initialization and a trained solution.

2. The main method, from first principles

Let θ_0 be initial weights and θ_T the final trained weights. Define a path in parameter space by

$$\boxed{\theta(\alpha) = (1-\alpha)\theta_0 + \alpha\theta_T, \qquad 0 \le \alpha \le 1.}$$

Then evaluate the same loss on the same data at intermediate weights:

$$\ell(\alpha) = L(\theta(\alpha)).$$

These evaluations do *not* retrain the network; they probe its loss on a predetermined geometric segment. By the chain rule,

$$\ell'(\alpha) = \nabla L(\theta(\alpha))^\top (\theta_T - \theta_0),$$

which measures the loss slope along that straight segment. A nearly monotone decrease means this chosen slice shows no major barrier along the line, not that L is globally convex.

3. What the paper actually finds

The authors examine multiple neural-network optimization problems and find that the loss along the segment from initialization to the solution reached by SGD often decreases without substantial intermediate obstacles. This empirical observation is surprising given the non-convexity of the full parameterized objective. The result does not claim that the actual curved trajectory of SGD follows the straight segment, that every pair of points is linearly connected at low loss, or that saddle points are absent.

Paper result. A simple one-dimensional interpolation test finds that several successfully trained neural networks have no substantial loss barrier *on the particular line* connecting initialization and final weights.

4. Why a 1D visualization cannot prove the geometry

Imagine a saddle $f(x, y) = x^2 - y^2$. Its restriction to the x-axis is $f(x, 0) = x^2$, which looks like a minimum, while its restriction to the y-axis is $f(0, y) = -y^2$, which looks like a maximum. A line probe loses information about all orthogonal directions. More generally, a 1D slice cannot characterize all critical points, Hessian eigenvalues, or basin connectivity of a high-dimensional objective. This distinction is central to our survey's **RQ4**: the line plots are valuable empirical evidence about some successful training paths, not a universal theorem about benign neural-network losses.

5. Limits, relation to later papers

The result depends on trained architectures, objectives, data and initialization; it is a qualitative diagnostic and not an SOSP or global-convergence guarantee. Later loss-surface visualization work by Li et al. (2018) adds filter-normalized two-dimensional slices to address distortions from scale symmetries, but even those slices cannot reveal all directions.

Careful wording. "No obstacles along the straight segment from initialization to the trained solution" must not be rewritten as "SGD encounters no saddles" or "the loss landscape is convex."

6. Our notes

This is a good reminder that visual experiments can challenge the usual scary picture of non-convex landscapes, without proving the landscape is easy everywhere. The authors looked at a simple line between the starting weights and the trained weights and often saw a smooth decrease. That tells us something useful about successful solutions, but almost nothing about all the other directions in parameter space. **Original source:** https://www.saxelab.org/assets/papers/Goodfellow2015.pdf. **Verification:** original ICLR manuscript and author-hosted description checked.