

Class 08: Breast Cancer Mini Project

Farnam Tavakoli (PID:A17628539)

Before we get stuck into project work we will have a quick look at applying PCA to some example RNAseq data (tail end of lab 7)

```
url2 <- "https://tinyurl.com/expression-CSV"
rna.data <- read.csv(url2, row.names=1)
head(rna.data)
```

	wt1	wt2	wt3	wt4	wt5	ko1	ko2	ko3	ko4	ko5
gene1	439	458	408	429	420	90	88	86	90	93
gene2	219	200	204	210	187	427	423	434	433	426
gene3	1006	989	1030	1017	973	252	237	238	226	210
gene4	783	792	829	856	760	849	856	835	885	894
gene5	181	249	204	244	225	277	305	272	270	279
gene6	460	502	491	491	493	612	594	577	618	638

Q1. How many genes are in this dataset?


```
nrow(rna.data)
```

```
[1] 100
```

Run PCA

```
## Again we have to take the transpose of our data
pca <- prcomp(t(rna.data), scale=TRUE)

## Simple un polished plot of pc1 and pc2
plot(pca$x[,1], pca$x[,2], xlab="PC1", ylab="PC2")
```



```
summary(pca)
```

Importance of components:


	PC1	PC2	PC3	PC4	PC5	PC6	PC7
Standard deviation	9.6237	1.5198	1.05787	1.05203	0.88062	0.82545	0.80111
Proportion of Variance	0.9262	0.0231	0.01119	0.01107	0.00775	0.00681	0.00642
Cumulative Proportion	0.9262	0.9493	0.96045	0.97152	0.97928	0.98609	0.99251

	PC8	PC9	PC10
Standard deviation	0.62065	0.60342	3.345e-15
Proportion of Variance	0.00385	0.00364	0.000e+00
Cumulative Proportion	0.99636	1.00000	1.000e+00

```
# We have 5 wt and 5 ko samples
mycols <- c(rep("blue", 5), rep("red", 5))
mycols
```

```
[1] "blue" "blue" "blue" "blue" "blue" "red" "red" "red" "red" "red"
```

```
plot(pca$x[,1], pca$x[,2], xlab="PC1", ylab="PC2", col= mycols)
```



I could examine which gens contribute most to this first PC

```
head(sort(abs(pca$rotation[,1]), decreasing = T))
```

```
gene100    gene66    gene45    gene68    gene98    gene60
0.1038708 0.1038455 0.1038402 0.1038395 0.1038372 0.1038055
```

Analysis of Breast Cancer FNA data.

The data itself comes from the Wisconsin Breast Cancer Diagnostic Data Set.

Values in this data set describe characteristics of the cell nuclei present in digitized images of a fine needle aspiration (FNA) of a breast mass.

First we will read the data:

```
wisc.df <- read.csv("WisconsinCancer.csv", row.names=1)
head(wisc.df)
```

```
      diagnosis radius_mean texture_mean perimeter_mean area_mean
842302         M      17.99       10.38         122.80      1001.0
```

842517	M	20.57	17.77	132.90	1326.0
84300903	M	19.69	21.25	130.00	1203.0
84348301	M	11.42	20.38	77.58	386.1
84358402	M	20.29	14.34	135.10	1297.0
843786	M	12.45	15.70	82.57	477.1
	smoothness_mean	compactness_mean	concavity_mean	concave.points_mean	
842302	0.11840	0.27760	0.3001	0.14710	
842517	0.08474	0.07864	0.0869	0.07017	
84300903	0.10960	0.15990	0.1974	0.12790	
84348301	0.14250	0.28390	0.2414	0.10520	
84358402	0.10030	0.13280	0.1980	0.10430	
843786	0.12780	0.17000	0.1578	0.08089	
	symmetry_mean	fractal_dimension_mean	radius_se	texture_se	perimeter_se
842302	0.2419	0.07871	1.0950	0.9053	8.589
842517	0.1812	0.05667	0.5435	0.7339	3.398
84300903	0.2069	0.05999	0.7456	0.7869	4.585
84348301	0.2597	0.09744	0.4956	1.1560	3.445
84358402	0.1809	0.05883	0.7572	0.7813	5.438
843786	0.2087	0.07613	0.3345	0.8902	2.217
	area_se	smoothness_se	compactness_se	concavity_se	concave.points_se
842302	153.40	0.006399	0.04904	0.05373	0.01587
842517	74.08	0.005225	0.01308	0.01860	0.01340
84300903	94.03	0.006150	0.04006	0.03832	0.02058
84348301	27.23	0.009110	0.07458	0.05661	0.01867
84358402	94.44	0.011490	0.02461	0.05688	0.01885
843786	27.19	0.007510	0.03345	0.03672	0.01137
	symmetry_se	fractal_dimension_se	radius_worst	texture_worst	
842302	0.03003	0.006193	25.38	17.33	
842517	0.01389	0.003532	24.99	23.41	
84300903	0.02250	0.004571	23.57	25.53	
84348301	0.05963	0.009208	14.91	26.50	
84358402	0.01756	0.005115	22.54	16.67	
843786	0.02165	0.005082	15.47	23.75	
	perimeter_worst	area_worst	smoothness_worst	compactness_worst	
842302	184.60	2019.0	0.1622	0.6656	
842517	158.80	1956.0	0.1238	0.1866	
84300903	152.50	1709.0	0.1444	0.4245	
84348301	98.87	567.7	0.2098	0.8663	
84358402	152.20	1575.0	0.1374	0.2050	
843786	103.40	741.6	0.1791	0.5249	
	concavity_worst	concave.points_worst	symmetry_worst		
842302	0.7119	0.2654	0.4601		
842517	0.2416	0.1860	0.2750		

84300903	0.4504	0.2430	0.3613
84348301	0.6869	0.2575	0.6638
84358402	0.4000	0.1625	0.2364
843786	0.5355	0.1741	0.3985
fractal_dimension_worst			
842302	0.11890		
842517	0.08902		
84300903	0.08758		
84348301	0.17300		
84358402	0.07678		
843786	0.12440		

Note that the first column here `wisc.df$diagnosis` is a pathologist provided expert diagnosis.

```
diagnosis <- as.factor(wisc.df$diagnosis)
```

Now I want to make sure I remove that column from my data set for analysis.

```
wisc.data <- wisc.df[,-1]
head(wisc.data)
```

	radius_mean	texture_mean	perimeter_mean	area_mean	smoothness_mean	
842302	17.99	10.38	122.80	1001.0	0.11840	
842517	20.57	17.77	132.90	1326.0	0.08474	
84300903	19.69	21.25	130.00	1203.0	0.10960	
84348301	11.42	20.38	77.58	386.1	0.14250	
84358402	20.29	14.34	135.10	1297.0	0.10030	
843786	12.45	15.70	82.57	477.1	0.12780	
	compactness_mean	concavity_mean	concave.points_mean	symmetry_mean		
842302	0.27760	0.3001		0.14710	0.2419	
842517	0.07864	0.0869		0.07017	0.1812	
84300903	0.15990	0.1974		0.12790	0.2069	
84348301	0.28390	0.2414		0.10520	0.2597	
84358402	0.13280	0.1980		0.10430	0.1809	
843786	0.17000	0.1578		0.08089	0.2087	
	fractal_dimension_mean	radius_se	texture_se	perimeter_se	area_se	
842302		0.07871	1.0950	0.9053	8.589	153.40
842517		0.05667	0.5435	0.7339	3.398	74.08
84300903		0.05999	0.7456	0.7869	4.585	94.03
84348301		0.09744	0.4956	1.1560	3.445	27.23
84358402		0.05883	0.7572	0.7813	5.438	94.44
843786		0.07613	0.3345	0.8902	2.217	27.19

	smoothness_se	compactness_se	concavity_se	concave.points_se
842302	0.006399	0.04904	0.05373	0.01587
842517	0.005225	0.01308	0.01860	0.01340
84300903	0.006150	0.04006	0.03832	0.02058
84348301	0.009110	0.07458	0.05661	0.01867
84358402	0.011490	0.02461	0.05688	0.01885
843786	0.007510	0.03345	0.03672	0.01137

	symmetry_se	fractal_dimension_se	radius_worst	texture_worst
842302	0.03003	0.006193	25.38	17.33
842517	0.01389	0.003532	24.99	23.41
84300903	0.02250	0.004571	23.57	25.53
84348301	0.05963	0.009208	14.91	26.50
84358402	0.01756	0.005115	22.54	16.67
843786	0.02165	0.005082	15.47	23.75

	perimeter_worst	area_worst	smoothness_worst	compactness_worst
842302	184.60	2019.0	0.1622	0.6656
842517	158.80	1956.0	0.1238	0.1866
84300903	152.50	1709.0	0.1444	0.4245
84348301	98.87	567.7	0.2098	0.8663
84358402	152.20	1575.0	0.1374	0.2050
843786	103.40	741.6	0.1791	0.5249

	concavity_worst	concave.points_worst	symmetry_worst
842302	0.7119	0.2654	0.4601
842517	0.2416	0.1860	0.2750
84300903	0.4504	0.2430	0.3613
84348301	0.6869	0.2575	0.6638
84358402	0.4000	0.1625	0.2364
843786	0.5355	0.1741	0.3985

	fractal_dimension_worst
842302	0.11890
842517	0.08902
84300903	0.08758
84348301	0.17300
84358402	0.07678
843786	0.12440

How many patients?

```
nrow(wisc.df)
```

```
[1] 569
```

Q1. How many observations are in this dataset?

```
ncol(wisc.data)
```

```
[1] 30
```

Q2. How many of the observations have a malignant diagnosis?

```
table(wisc.df$diagnosis )
```

```
  B   M  
357 212
```

Q3. How many variables/features in the data are suffixed with `_mean`?

```
length(grep("_mean", colnames(wisc.data)))
```

```
[1] 10
```

Principal Component Analysis

Here we will use `prcomp()` on the `wisc.data` object - the one without the diagnosis column.

First, we have to decide whether to use the `scale=TRUE` argument when we run `prcomp()`.

We can look at the means and sd of each column. If they are similar then we are all good to go. If not we should use `Scale=TRUE`

```
colMeans(wisc.data)
```

radius_mean	texture_mean	perimeter_mean
1.412729e+01	1.928965e+01	9.196903e+01
area_mean	smoothness_mean	compactness_mean
6.548891e+02	9.636028e-02	1.043410e-01
concavity_mean	concave.points_mean	symmetry_mean
8.879932e-02	4.891915e-02	1.811619e-01
fractal_dimension_mean	radius_se	texture_se
6.279761e-02	4.051721e-01	1.216853e+00
perimeter_se	area_se	smoothness_se
2.866059e+00	4.033708e+01	7.040979e-03
compactness_se	concavity_se	concave.points_se

2.547814e-02	3.189372e-02	1.179614e-02
symmetry_se	fractal_dimension_se	radius_worst
2.054230e-02	3.794904e-03	1.626919e+01
texture_worst	perimeter_worst	area_worst
2.567722e+01	1.072612e+02	8.805831e+02
smoothness_worst	compactness_worst	concavity_worst
1.323686e-01	2.542650e-01	2.721885e-01
concave.points_worst	symmetry_worst	fractal_dimension_worst
1.146062e-01	2.900756e-01	8.394582e-02

```
apply(wisc.data, 2, sd)
```

radius_mean	texture_mean	perimeter_mean
3.524049e+00	4.301036e+00	2.429898e+01
area_mean	smoothness_mean	compactness_mean
3.519141e+02	1.406413e-02	5.281276e-02
concavity_mean	concave.points_mean	symmetry_mean
7.971981e-02	3.880284e-02	2.741428e-02
fractal_dimension_mean	radius_se	texture_se
7.060363e-03	2.773127e-01	5.516484e-01
perimeter_se	area_se	smoothness_se
2.021855e+00	4.549101e+01	3.002518e-03
compactness_se	concavity_se	concave.points_se
1.790818e-02	3.018606e-02	6.170285e-03
symmetry_se	fractal_dimension_se	radius_worst
8.266372e-03	2.646071e-03	4.833242e+00
texture_worst	perimeter_worst	area_worst
6.146258e+00	3.360254e+01	5.693570e+02
smoothness_worst	compactness_worst	concavity_worst
2.283243e-02	1.573365e-01	2.086243e-01
concave.points_worst	symmetry_worst	fractal_dimension_worst
6.573234e-02	6.186747e-02	1.806127e-02

These are very different so we should Sale=TRUE.

```
wisc.pr <- prcomp(wisc.data, scale= TRUE)
summary(wisc.pr)
```

Importance of components:

PC1	PC2	PC3	PC4	PC5	PC6	PC7
-----	-----	-----	-----	-----	-----	-----

Standard deviation	3.6444	2.3857	1.67867	1.40735	1.28403	1.09880	0.82172
Proportion of Variance	0.4427	0.1897	0.09393	0.06602	0.05496	0.04025	0.02251
Cumulative Proportion	0.4427	0.6324	0.72636	0.79239	0.84734	0.88759	0.91010
	PC8	PC9	PC10	PC11	PC12	PC13	PC14
Standard deviation	0.69037	0.6457	0.59219	0.5421	0.51104	0.49128	0.39624
Proportion of Variance	0.01589	0.0139	0.01169	0.0098	0.00871	0.00805	0.00523
Cumulative Proportion	0.92598	0.9399	0.95157	0.9614	0.97007	0.97812	0.98335
	PC15	PC16	PC17	PC18	PC19	PC20	PC21
Standard deviation	0.30681	0.28260	0.24372	0.22939	0.22244	0.17652	0.1731
Proportion of Variance	0.00314	0.00266	0.00198	0.00175	0.00165	0.00104	0.0010
Cumulative Proportion	0.98649	0.98915	0.99113	0.99288	0.99453	0.99557	0.9966
	PC22	PC23	PC24	PC25	PC26	PC27	PC28
Standard deviation	0.16565	0.15602	0.1344	0.12442	0.09043	0.08307	0.03987
Proportion of Variance	0.00091	0.00081	0.0006	0.00052	0.00027	0.00023	0.00005
Cumulative Proportion	0.99749	0.99830	0.9989	0.99942	0.99969	0.99992	0.99997
	PC29	PC30					
Standard deviation	0.02736	0.01153					
Proportion of Variance	0.00002	0.00000					
Cumulative Proportion	1.00000	1.00000					

Q4. From your results, what proportion of the original variance is captured by the first principal components (PC1)?

44.27%

Q5. How many principal components (PCs) are required to describe at least 70% of the original variance in the data?

3 PCs capture 72.6% of the original variance.

Q6. How many principal components (PCs) are required to describe at least 90% of the original variance in the data?

7 PCs capture 91.0% of the original variance.

Q7. What stands out to you about this plot? Is it easy or difficult to understand? Why?

Plotting the PCA results

```
# biplot(wisc.pr)
```


We need to make our own plot.

```
attributes(wisc.pr)
```


```
$names  
[1] "sdev"      "rotation" "center"    "scale"     "x"
```

```
$class  
[1] "prcomp"
```

```
plot(wisc.pr$x[,1], wisc.pr$x[,2], col=diagnosis)
```



```
library(ggplot2)  
  
pc <- as.data.frame(wisc.pr$x)  
  
ggplot(pc) +  
  aes(PC1, PC2, col=diagnosis) +  
  geom_point()
```



Communicating PCA results

Q9. For the first principal component, what is the component of the loading vector (i.e. `wisc.pr$rotation[,1]`) for the feature `concave.points_mean`?

```
wisc.pr$rotation["concave.points_mean",1]
```

```
[1] -0.2608538
```

Q10. What is the minimum number of principal components required to explain 80% of the variance of the data?

```
tbl <- summary(wisc.pr)
which(tbl$importance[3,] > 0.8)[1]
```


```
PC5
```

```
5
```

Hierarchical Clustering


The main function for hierarchical clustering is called `hclust()` it takes a distance matrix as input

```
d <- dist( scale(wisc.data))  
wisc.hclust <- hclust(d)  
plot(wisc.hclust)
```



```
plot(wisc.hclust)  
abline(h=18, col="red")
```

Cluster Dendrogram



d
hclust (*, "complete")


```
grps <- cutree(wisc.hclust, h=18)
table(grps)
```

grps

1	2	3	4	5
177	5	383	2	2

Come back here. Later to see how our cluster grps correspond to M or B groups.

```
ggplot(pc) +
  aes(PC1, PC2, col=diagnosis) +
  geom_point()
```




5. Combining Methods

Here we will perform clustering on our PCA results rather than the original data.

In other words we will clustering using `wisc.pr$x` - our new better variables or PCs. We can choose s many or as few PCs to us as we like. It is your call!

```
d.pc <- dist(wisc.pr$x[, 1:3])
wisc.pr.hclust <- hclust(d.pc, method="ward.D2")
plot(wisc.pr.hclust)
abline(h=80, col="red")
```

Cluster Dendrogram



```
d.pc
hclust (*, "ward.D2")
```

```
grps <- cutree(wisc.pr.hclust, h=80)
table(grps)
```

```
grps
  1   2
203 366
```

We can use `table()` function to make a cross-table as well as just a count table.

```
table(diagnosis)
```

```
diagnosis
  B   M
357 212
```

```
table(grps, diagnosis)
```

```
diagnosis
grps   B   M
```

```
1 24 179
2 333 33
```

Write a note here about how to read this cross-table results. The results indicate that our cluster 1 mostly captures cancer (M) and our cluster 2 mostly captures healthy (B) samples/individuals.


7. Prediction

```
#url <- "new_samples.csv"
url <- "https://tinyurl.com/new-samples-CSV"
new <- read.csv(url)
npc <- predict(wisc.pr, newdata=new)
npc
```

	PC1	PC2	PC3	PC4	PC5	PC6	PC7
[1,]	2.576616	-3.135913	1.3990492	-0.7631950	2.781648	-0.8150185	-0.3959098
[2,]	-4.754928	-3.009033	-0.1660946	-0.6052952	-1.140698	-1.2189945	0.8193031
	PC8	PC9	PC10	PC11	PC12	PC13	PC14
[1,]	-0.2307350	0.1029569	-0.9272861	0.3411457	0.375921	0.1610764	1.187882
[2,]	-0.3307423	0.5281896	-0.4855301	0.7173233	-1.185917	0.5893856	0.303029
	PC15	PC16	PC17	PC18	PC19	PC20	
[1,]	0.3216974	-0.1743616	-0.07875393	-0.11207028	-0.08802955	-0.2495216	
[2,]	0.1299153	0.1448061	-0.40509706	0.06565549	0.25591230	-0.4289500	
	PC21	PC22	PC23	PC24	PC25	PC26	
[1,]	0.1228233	0.09358453	0.08347651	0.1223396	0.02124121	0.078884581	
[2,]	-0.1224776	0.01732146	0.06316631	-0.2338618	-0.20755948	-0.009833238	
	PC27	PC28	PC29	PC30			
[1,]	0.220199544	-0.02946023	-0.015620933	0.005269029			
[2,]	-0.001134152	0.09638361	0.002795349	-0.019015820			

And plot this up

```
plot(wisc.pr$x[,1:2], col=grps)
points(npc[,1], npc[,2], col="blue", pch=16, cex=3)
text(npc[,1], npc[,2], c(1,2), col="white")
```

Q18. which patient?

patient number 2