

# Class 13: Transcriptomics and the analysis of RNA-Seq data

Farnam (PID: !17628539)

```
library(BiocManager)
library(DESeq2)
```

Loading required package: S4Vectors

Loading required package: stats4

Loading required package: BiocGenerics

Attaching package: 'BiocGenerics'

The following objects are masked from 'package:stats':

IQR, mad, sd, var, xtabs

The following objects are masked from 'package:base':

anyDuplicated, aperm, append, as.data.frame, basename, cbind,  
colnames, dirname, do.call, duplicated, eval, evalq, Filter, Find,  
get, grep, grepl, intersect, is.unsorted, lapply, Map, mapply,  
match, mget, order, paste, pmax, pmax.int, pmin, pmin.int,  
Position, rank, rbind, Reduce, rownames, sapply, setdiff, sort,  
table, tapply, union, unique, unsplit, which.max, which.min

Attaching package: 'S4Vectors'

The following object is masked from 'package:utils':

findMatches

The following objects are masked from 'package:base':

expand.grid, I, unname

Loading required package: IRanges

Loading required package: GenomicRanges

Loading required package: GenomeInfoDb

Loading required package: SummarizedExperiment

Loading required package: MatrixGenerics

Loading required package: matrixStats

Attaching package: 'MatrixGenerics'

The following objects are masked from 'package:matrixStats':

colAlls, colAnyNAs, colAnys, colAvgsPerRowSet, colCollapse,  
colCounts, colCummaxs, colCummins, colCumprods, colCumsums,  
colDiffs, colIQRDiffs, colIQRs, colLogSumExps, colMadDiffs,  
colMads, colMaxs, colMeans2, colMedians, colMins, colOrderStats,  
colProds, colQuantiles, colRanges, colRanks, colSdDiffs, colSds,  
colSums2, colTabulates, colVarDiffs, colVars, colWeightedMads,  
colWeightedMeans, colWeightedMedians, colWeightedSds,  
colWeightedVars, rowAlls, rowAnyNAs, rowAnys, rowAvgsPerColSet,  
rowCollapse, rowCounts, rowCummaxs, rowCummins, rowCumprods,  
rowCumsums, rowDiffs, rowIQRDiffs, rowIQRs, rowLogSumExps,  
rowMadDiffs, rowMads, rowMaxs, rowMeans2, rowMedians, rowMins,  
rowOrderStats, rowProds, rowQuantiles, rowRanges, rowRanks,  
rowSdDiffs, rowSds, rowSums2, rowTabulates, rowVarDiffs, rowVars,  
rowWeightedMads, rowWeightedMeans, rowWeightedMedians,  
rowWeightedSds, rowWeightedVars

Loading required package: Biobase

Welcome to Bioconductor

Vignettes contain introductory material; view with  
'browseVignettes()'. To cite Bioconductor, see  
'citation("Biobase")', and for packages 'citation("pkgname")'.

Attaching package: 'Biobase'

The following object is masked from 'package:MatrixGenerics':

rowMedians

The following objects are masked from 'package:matrixStats':

anyMissing, rowMedians

```
# Complete the missing code
counts <- read.csv("airway_scaledcounts.csv", row.names=1)
metadata <- read.csv("airway_metadata.csv")
```

```
head(counts)
```

	SRR1039508	SRR1039509	SRR1039512	SRR1039513	SRR1039516
ENSG000000000003	723	486	904	445	1170
ENSG000000000005	0	0	0	0	0
ENSG000000000419	467	523	616	371	582
ENSG000000000457	347	258	364	237	318
ENSG000000000460	96	81	73	66	118
ENSG000000000938	0	0	1	0	2
	SRR1039517	SRR1039520	SRR1039521		
ENSG000000000003	1097	806	604		
ENSG000000000005	0	0	0		
ENSG000000000419	781	417	509		
ENSG000000000457	447	330	324		
ENSG000000000460	94	102	74		
ENSG000000000938	0	0	0		

```
head(metadata)
```

```
      id      dex celltype      geo_id
1 SRR1039508 control   N61311 GSM1275862
2 SRR1039509 treated   N61311 GSM1275863
3 SRR1039512 control   N052611 GSM1275866
4 SRR1039513 treated   N052611 GSM1275867
5 SRR1039516 control   N080611 GSM1275870
6 SRR1039517 treated   N080611 GSM1275871
```

```
control <- metadata[metadata[,"dex"]=="control",]
control.counts <- counts[ ,control$id]
control.mean <- rowSums( control.counts )/4
head(control.mean)
```

```
ENSG000000000003 ENSG000000000005 ENSG000000000419 ENSG000000000457 ENSG000000000460
      900.75           0.00           520.50           339.75           97.25
ENSG000000000938
      0.75
```

```
library(dplyr)
```

Attaching package: 'dplyr'

The following object is masked from 'package:Biobase':

combine

The following object is masked from 'package:matrixStats':

count

The following objects are masked from 'package:GenomicRanges':

intersect, setdiff, union

The following object is masked from 'package:GenomeInfoDb':

intersect

The following objects are masked from 'package:IRanges':

collapse, desc, intersect, setdiff, slice, union

The following objects are masked from 'package:S4Vectors':

first, intersect, rename, setdiff, setequal, union

The following objects are masked from 'package:BiocGenerics':

combine, intersect, setdiff, union

The following objects are masked from 'package:stats':

filter, lag

The following objects are masked from 'package:base':

intersect, setdiff, setequal, union

```
control <- metadata %>% filter(dex=="control")
control.counts <- counts %>% select(control$id)
control.mean <- rowSums(control.counts)/4
head(control.mean)
```

```
ENSG00000000003 ENSG00000000005 ENSG00000000419 ENSG00000000457 ENSG00000000460
          900.75           0.00           520.50           339.75           97.25
ENSG000000000938
          0.75
```

```
treated <- metadata[metadata[, "dex"]=="treated",]
treated.counts <- counts[, treated$id]
treated.mean <- rowSums( treated.counts )/4
head(treated.mean)
```

```

ENSG000000000003  ENSG000000000005  ENSG000000000419  ENSG000000000457  ENSG000000000460
      658.00           0.00           546.00           316.50           78.75
ENSG000000000938
      0.00

```

```

meancounts <- data.frame(control.mean, treated.mean)

```

```

meancounts$log2fc <- log2(meancounts[, "treated.mean"] / meancounts[, "control.mean"])
head(meancounts)

```

```

      control.mean treated.mean      log2fc
ENSG000000000003    900.75      658.00 -0.45303916
ENSG000000000005      0.00       0.00      NaN
ENSG000000000419    520.50      546.00  0.06900279
ENSG000000000457    339.75      316.50 -0.10226805
ENSG000000000460     97.25       78.75 -0.30441833
ENSG000000000938      0.75       0.00      -Inf

```

```

zero.vals <- which(meancounts[, 1:2] == 0, arr.ind=TRUE)

```

```

to.rm <- unique(zero.vals[, 1])
mycounts <- meancounts[-to.rm, ]
head(mycounts)

```

```

      control.mean treated.mean      log2fc
ENSG000000000003    900.75      658.00 -0.45303916
ENSG000000000419    520.50      546.00  0.06900279
ENSG000000000457    339.75      316.50 -0.10226805
ENSG000000000460     97.25       78.75 -0.30441833
ENSG000000000971    5219.00     6687.50  0.35769358
ENSG000000001036    2327.00     1785.75 -0.38194109

```

```

up.ind <- mycounts$log2fc > 2
down.ind <- mycounts$log2fc < (-2)

```

```

library(DESeq2)
citation("DESeq2")

```

To cite package 'DESeq2' in publications use:

Love, M.I., Huber, W., Anders, S. Moderated estimation of fold change and dispersion for RNA-seq data with DESeq2 Genome Biology 15(12):550 (2014)

A BibTeX entry for LaTeX users is

```
@Article{,
  title = {Moderated estimation of fold change and dispersion for RNA-seq data with DESeq2},
  author = {Michael I. Love and Wolfgang Huber and Simon Anders},
  year = {2014},
  journal = {Genome Biology},
  doi = {10.1186/s13059-014-0550-8},
  volume = {15},
  issue = {12},
  pages = {550},
}
```

```
dds <- DESeqDataSetFromMatrix(countData=counts,
                               colData=metadata,
                               design=~dex)
```

converting counts to integer mode


Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in design formula are characters, converting to factors

```
dds
```

```
class: DESeqDataSet
dim: 38694 8
metadata(1): version
assays(1): counts
rownames(38694): ENSG000000000003 ENSG000000000005 ... ENSG00000283120
               ENSG00000283123
rowData names(0):
colnames(8): SRR1039508 SRR1039509 ... SRR1039520 SRR1039521
colData names(4): id dex celltype geo_id
```

```
vsd <- vst(dds, blind = FALSE)
plotPCA(vsd, intgroup = c("dex"))
```

using ntop=500 top features by variance



```
pcaData <- plotPCA(vsd, intgroup=c("dex"), returnData=TRUE)
```

using ntop=500 top features by variance


```
head(pcaData)
```

	PC1	PC2	group	dex	name
SRR1039508	-17.607922	-10.225252	control	control	SRR1039508
SRR1039509	4.996738	-7.238117	treated	treated	SRR1039509
SRR1039512	-5.474456	-8.113993	control	control	SRR1039512
SRR1039513	18.912974	-6.226041	treated	treated	SRR1039513
SRR1039516	-14.729173	16.252000	control	control	SRR1039516
SRR1039517	7.279863	21.008034	treated	treated	SRR1039517



```
# Calculate percent variance per PC for the plot axis labels
percentVar <- round(100 * attr(pcaData, "percentVar"))
```

```
library(ggplot2)
ggplot(pcaData) +
  aes(x = PC1, y = PC2, color = dex) +
  geom_point(size = 3) +
  xlab(paste0("PC1: ", percentVar[1], "% variance")) +
  ylab(paste0("PC2: ", percentVar[2], "% variance")) +
  coord_fixed() +
  theme_bw()
```



```
dds <- DESeq(dds)
```

estimating size factors

estimating dispersions

gene-wise dispersion estimates

mean-dispersion relationship

final dispersion estimates

fitting model and testing

```
res <- results(dds)
head(res)
```

log2 fold change (MLE): dex treated vs control

Wald test p-value: dex treated vs control

DataFrame with 6 rows and 6 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG000000000003	747.194195	-0.3507030	0.168246	-2.084470	0.0371175
ENSG000000000005	0.000000	NA	NA	NA	NA
ENSG000000000419	520.134160	0.2061078	0.101059	2.039475	0.0414026
ENSG000000000457	322.664844	0.0245269	0.145145	0.168982	0.8658106
ENSG000000000460	87.682625	-0.1471420	0.257007	-0.572521	0.5669691
ENSG000000000938	0.319167	-1.7322890	3.493601	-0.495846	0.6200029
	padj				
	<numeric>				
ENSG000000000003	0.163035				
ENSG000000000005	NA				
ENSG000000000419	0.176032				
ENSG000000000457	0.961694				
ENSG000000000460	0.815849				
ENSG000000000938	NA				

```
summary(res)
```

out of 25258 with nonzero total read count

adjusted p-value < 0.1

LFC > 0 (up) : 1563, 6.2%

LFC < 0 (down) : 1188, 4.7%

outliers [1] : 142, 0.56%

low counts [2] : 9971, 39%

(mean count < 10)

[1] see 'cooksCutoff' argument of ?results

[2] see 'independentFiltering' argument of ?results

```
res05 <- results(dds, alpha=0.05)
summary(res05)
```

```
out of 25258 with nonzero total read count
adjusted p-value < 0.05
LFC > 0 (up)      : 1236, 4.9%
LFC < 0 (down)    : 933, 3.7%
outliers [1]      : 142, 0.56%
low counts [2]    : 9033, 36%
(mean count < 6)
[1] see 'cooksCutoff' argument of ?results
[2] see 'independentFiltering' argument of ?results
```

```
#Head(res)
library("AnnotationDbi")
```

Attaching package: 'AnnotationDbi'

The following object is masked from 'package:dplyr':

```
select
```

```
library("org.Hs.eg.db")
```

```
columns(org.Hs.eg.db)
```

[1]	"ACCNUM"	"ALIAS"	"ENSEMBL"	"ENSEMBLPROT"	"ENSEMBLTRANS"
[6]	"ENTREZID"	"ENZYME"	"EVIDENCE"	"EVIDENCEALL"	"GENENAME"
[11]	"GENETYPE"	"GO"	"GOALL"	"IPI"	"MAP"
[16]	"OMIM"	"ONTOLOGY"	"ONTOLOGYALL"	"PATH"	"PFAM"
[21]	"PMID"	"PROSITE"	"REFSEQ"	"SYMBOL"	"UCSCKG"
[26]	"UNIPROT"				

```
res$symbol <- mapIds(org.Hs.eg.db,
                     keys=row.names(res), # Our genenames
                     keytype="ENSEMBL",  # The format of our genenames
                     column="SYMBOL",     # The new format we want to add
                     multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
head(res)
```

log2 fold change (MLE): dex treated vs control

Wald test p-value: dex treated vs control

DataFrame with 6 rows and 7 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG000000000003	747.194195	-0.3507030	0.168246	-2.084470	0.0371175
ENSG000000000005	0.000000	NA	NA	NA	NA
ENSG000000000419	520.134160	0.2061078	0.101059	2.039475	0.0414026
ENSG000000000457	322.664844	0.0245269	0.145145	0.168982	0.8658106
ENSG000000000460	87.682625	-0.1471420	0.257007	-0.572521	0.5669691
ENSG000000000938	0.319167	-1.7322890	3.493601	-0.495846	0.6200029
	padj	symbol			
	<numeric>	<character>			
ENSG000000000003	0.163035	TSPAN6			
ENSG000000000005	NA	TNMD			
ENSG000000000419	0.176032	DPM1			
ENSG000000000457	0.961694	SCYL3			
ENSG000000000460	0.815849	FIRRM			
ENSG000000000938	NA	FGR			

I also want Entrez IDs

```
res$entrez <- mapIds(org.Hs.eg.db,
                     keys=row.names(res), # Our genenames
                     keytype="ENSEMBL",  # The format of our genenames
                     column="ENTREZID",   # The new format we want to add
                     multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
head(res)
```

log2 fold change (MLE): dex treated vs control


Wald test p-value: dex treated vs control

DataFrame with 6 rows and 8 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG000000000003	747.194195	-0.3507030	0.168246	-2.084470	0.0371175
ENSG000000000005	0.000000	NA	NA	NA	NA
ENSG000000000419	520.134160	0.2061078	0.101059	2.039475	0.0414026
ENSG000000000457	322.664844	0.0245269	0.145145	0.168982	0.8658106
ENSG000000000460	87.682625	-0.1471420	0.257007	-0.572521	0.5669691
ENSG000000000938	0.319167	-1.7322890	3.493601	-0.495846	0.6200029
	padj	symbol	entrez		
	<numeric>	<character>	<character>		
ENSG000000000003	0.163035	TSPAN6	7105		
ENSG000000000005	NA	TNMD	64102		
ENSG000000000419	0.176032	DPM1	8813		
ENSG000000000457	0.961694	SCYL3	57147		
ENSG000000000460	0.815849	FIRRM	55732		
ENSG000000000938	NA	FGR	2268		

## section 9: volcano plot

```
plot( res$log2FoldChange, -log(res$padj),  
      xlab="Log2(FoldChange)",  
      ylab="-Log(P-value)")
```



## Pathway analysis

Now that I have added the necessary annotation data I can talk to different databases that use these IDs,

We will use the `gage` package to do geneset analysis (a.;a. pathway analysis, geneset enrichment, overlap analysis)

```
library(pathview)
```

```
#####
Pathview is an open source software package distributed under GNU General
Public License version 3 (GPLv3). Details of GPLv3 is available at
http://www.gnu.org/licenses/gpl-3.0.html. Particullary, users are required to
formally cite the original Pathview paper (not just mention it) in publications
or products. For details, do citation("pathview") within R.
```

```
The pathview downloads and uses KEGG data. Non-academic uses may require a KEGG
license agreement (details at http://www.kegg.jp/kegg/legal.html).
```

```
#####
```

```
library(gage)
```

```
library(gageData)
```

We will use KEGG first

```
data(kegg.sets.hs)
head(kegg.sets.hs, 2)
```

```
$`hsa00232 Caffeine metabolism`
```

```
[1] "10" "1544" "1548" "1549" "1553" "7498" "9"
```

```
$`hsa00983 Drug metabolism - other enzymes`
```

```
[1] "10" "1066" "10720" "10941" "151531" "1548" "1549" "1551"
[9] "1553" "1576" "1577" "1806" "1807" "1890" "221223" "2990"
[17] "3251" "3614" "3615" "3704" "51733" "54490" "54575" "54576"
[25] "54577" "54578" "54579" "54600" "54657" "54658" "54659" "54963"
[33] "574537" "64816" "7083" "7084" "7172" "7363" "7364" "7365"
[41] "7366" "7367" "7371" "7372" "7378" "7498" "79799" "83549"
[49] "8824" "8833" "9" "978"
```

The main `gage()` function requires a named vector of fold changes, where the names of the values are the Entrez gene IDs.

```
foldchange <- res$log2FoldChange
names(foldchange) = res$entrez
head(foldchange)
```

```
      7105      64102      8813      57147      55732      2268
-0.35070302      NA  0.20610777  0.02452695 -0.14714205 -1.73228897
```

Run the analysis

```
# Get the results
keggres = gage(foldchange, gsets=kegg.sets.hs)
```

Let's look at what is in our results here

```
attributes(keggres)
```

```
$names
```

```
[1] "greater" "less"    "stats"
```

```
# Look at the first three down (less) pathways
head(keggres$less, 3)
```

	p.geomean	stat.mean	p.val
hsa05332 Graft-versus-host disease	0.0004250461	-3.473346	0.0004250461
hsa04940 Type I diabetes mellitus	0.0017820293	-3.002352	0.0017820293
hsa05310 Asthma	0.0020045888	-3.009050	0.0020045888

	q.val	set.size	exp1
hsa05332 Graft-versus-host disease	0.09053483	40	0.0004250461
hsa04940 Type I diabetes mellitus	0.14232581	42	0.0017820293
hsa05310 Asthma	0.14232581	29	0.0020045888

I can now use the returned pathway IDs from KEGG as input to the `pathview` package to make pathway figures with our DEGs highlighted.

```
pathview(gene.data=foldchange, pathway.id="hsa05310")
```

```
Info: Downloading xml files for hsa05310, 1/1 pathways..
```

```
Info: Downloading png files for hsa05310, 1/1 pathways..
```

```
'select()' returned 1:1 mapping between keys and columns
```

```
Info: Working in directory /Users/farnamtavakoli/Downloads/School Documents/UCSD Classes/Win
```

```
Info: Writing image file hsa05310.pathview.png
```



