

軟體測試

教師：王凡

授課時間：每週 9：10—12：00

博理館 113

課程代號：EE 5170

識別碼：921 U9550

民國壹佰零四年秋季班

期末考

考試中，請勿參閱資料。

1. Below is a graph, defined by the sets of nodes, initial nodes, final nodes, edges, and defs and uses.

Answer the following questions about the graph.

Graph: $N = \{0, 1, 2, 3, 4, 5, 6, 7\}$

$N_0 = \{0\}$

$N_f = \{6\}$

$E = \{(0, 1), (1, 2), (2, 7), (7, 0), (2, 3), (2, 4), (3, 4), (4, 5), (5, 6), (4, 6), (6, 2)\}$

$\text{def}(0) = \text{def}(5) = \text{use}(3) = \text{use}(2) = \{x\}$

$\text{def}(1) = \text{def}(2, 4) = \text{use}(5) = \text{use}(6) = \{y\}$

All the other define and use sets are empty.

- (a) Draw the graph. (5pts/5)

(b) List the test requirements for edge-pair coverage. (5pts/10)

(c) Please list a set of test paths for full edge-pair coverage. (5pts/15)

(d) List the test requirements for prime-path coverage (PPC). (5pts/20)

(e) Write down a test set for the full PPC. (5pts/25)

(f) List all of the du-paths with respect to x and y . (Note: Include all du-paths, even those that are subpaths of some other du-path). (5pts/30)

(g) Write down a minimal test set that satisfies all-defs coverage with respect to x and y . (Direct tours only.) (5pts/35)

- (h) Write down a minimal test set that satisfies all-uses coverage with respect to x and y .
(Direct tours only.) (5pts/40)

2. Use the following predicate to answer the following questions.

$$p = a \vee (\neg a \wedge \neg b) \vee (b \wedge c) \vee (\neg c \wedge d)$$

(a) Identify the clauses (*atoms* in standard logic terms) that determine predicate p .
(5pts/45)

(b) Compute (and simplify) the conditions under which each of the clauses determines predicate p . (5pts/50)

- (c) Write the complete truth table for all clauses. Label your rows starting from 0 at the top. Use the format that row 0 should be all clauses true. You should include columns for the conditions under which each clause determines the predicate, and also a column for the predicate itself. (5pts/55)
- (d) Identify all pairs of rows from your table that satisfy *general active clause coverage* (*GACC*) with respect to each clause. (5pts/60)

(e) Identify all pairs of rows from your table that satisfy *correlated active clause coverage (CACC)* with respect to each clause. (5pts/65)

(f) Identify all rows from your table that satisfy *implicant coverage (IC)* with respect to each implicant. (5pts/70)

3. Assume that we have a web program for music sharing with the following screen layout.



The topmost box is one text input field. When the *Upload* button is depressed, the file specified with the path string in the input text field will be uploaded to the cloud. When the *Query* button is depressed, the program answers whether the music with name specified in the text input field is in the database of the program. When the *Download* button is depressed, the program sends a file containing the music with name specified in the text input field, if it exists, to the desktop of the computer. Finally, when the *Clear* button is depressed, the text input field is cleared.

- (a) Define characteristics of inputs to the web interface and list them. (5pts/75)

(b) Partition the characteristics into blocks and write them down. (5pts/80)

(c) Define and list values for the blocks. (5pts/85)

4. Assume that we have the following program with two mutants.

Original program:

```
public static int search(int[] x, int y) {  
    c = -1;  
    for (int j = 0; j < x.length; j++)  
        if (x[j] == y) c = j;  
    if (c >= 0)  
        return c;  
}
```

- (a) Please write down a test input that kills mutant 1 in the following. Explain why it kills the mutant? (5pts/90)

Mutant 1:

```
public static int count(int[] x, int y) {  
    c = -1;  
    for (int j = 0; j < x.length; j++)  
        if (x[j] == y) c = y;  
    if (c >= 0)  
        return c;  
}
```

(b) Please write down a test input that kills mutant 2 in the following! Please explain why it kills the mutant. (5pts/95)

Mutant 2:

```
public static int search(int[] x, int y) {  
    c = -1;  
    for (int j = 1; j < x.length; j++)  
        if (x[j] == y) c = j;  
    if (c >= 0)  
        return c;  
}
```

5. Please explain the RIP model in software testing. (5pts/100)