TahakomAVRLibDoc

1.0

Generated by Doxygen 1.8.17

Chapter 1

Namespace Index

1.1 Namespace List

Here is a list of all namespaces with brief descriptions:

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Chapter 4

File Index

4.1 File List

Here is a list of all files with brief descriptions:

Chapter 5

Namespace Documentation

5.1 component Namespace Reference

Classes

- class Buzzer
- class DCMotor
- class Led
- class PushButton
- class ServoMotor
- class StepperMotor

Enumerations

- enum mode : uint8_t { mode::fullStep =0, mode::halfStep }

5.1.1 Enumeration Type Documentation

5.1.1.1 mode

```
enum component::mode : uint8_t [strong]
```

Enumerator

fullStep	
halfStep	

Definition at line 70 of file StepperMotor.h.

```
00070                     : uint8_t {
00071     fullStep=0,
00072     halfStep,
00073 };
```

5.2 core Namespace Reference

Classes

- class ADConverter
- class AnalogComparator
- class ExternInterrupt
- class MCU
- class TimerCounter
- class TimerCounter0
- class TimerCounter1
- class TimerCounter2
- class WatchdogTimer

Enumerations

- enum resolution : uint8_t {
  resolution::res_8bit =0, resolution::res_9bit, resolution::res_10bit, resolution::res_11bit,
  resolution::res_12bit, resolution::res_13bit, resolution::res_14bit, resolution::res_15bit,
  resolution::res_16bit }
- enum referenceVoltage : uint8_t { referenceVoltage::AREF =0, referenceVoltage::AVCC, referenceVoltage::internal
  }
- enum clockPrescaler : uint8_t {
  clockPrescaler::PS_2 = 1, clockPrescaler::PS_4, clockPrescaler::PS_8, clockPrescaler::PS_16,
  clockPrescaler::PS_32, clockPrescaler::PS_64, clockPrescaler::PS_128 }
- enum autoTriggerSource : uint8_t {
  autoTriggerSource::freeRunning, autoTriggerSource::analogComparator, autoTriggerSource::extInterrupt,
  autoTriggerSource::timer0Compare,
  autoTriggerSource::timer0Overflow, autoTriggerSource::timer1CompareB, autoTriggerSource::timer1Overflow,
  autoTriggerSource::timer1Capture }
- enum senseControl : uint8_t { senseControl::lowLevel =0, senseControl::logicalChange, senseControl::fallingEdge,
  senseControl::risingEdge }
- enum pinChangePort : uint8_t { pinChangePort::PCINTB =0, pinChangePort::PCINTC, pinChangePort::PCINTD
  }
- enum BODMode : uint8_t { BODMode::enabled =0, BODMode::disabled }
- enum sleepMode : uint8_t {
  sleepMode::Idle =0, sleepMode::ADC_NoiseReduction, sleepMode::powerDown, sleepMode::powerSave,
  sleepMode::standby =6, sleepMode::extendedStandby }
- enum channel : uint8_t { channel::A =0, channel::B }
- enum compareOutputMode : uint8_t { compareOutputMode::normal =0, compareOutputMode::toggle,
  compareOutputMode::clear, compareOutputMode::set }
- enum operationMode : uint8_t {
  operationMode::normal =0, operationMode::PWM_PC, operationMode::PWM_PC_8bit, operationMode::PWM_PC_9bit,
  operationMode::PWM_PC_10bit, operationMode::PWM_PFC_ICR, operationMode::PWM_PFC_OCR,
  operationMode::PWM_PC_ICR,
  operationMode::PWM_PC_OCR, operationMode::fast_PWM, operationMode::fast_PWM_8bit, operationMode::fast_PWM_9bit
  operationMode::fast_PWM_10bit, operationMode::fast_PWM_ICR, operationMode::fast_PWM_OCR,
  operationMode::CTC_OCR,
  operationMode::CTC_ICR, operationMode::interrupt =1, operationMode::reset, operationMode::interrupt_reset
  }
- enum clockSource : uint16_t {
  clockSource::noClock =0, clockSource::PS_1, clockSource::PS_8, clockSource::PS_32,
  clockSource::PS_64, clockSource::PS_128, clockSource::PS_256, clockSource::PS_1024,
  clockSource::extern_Clock_T0_Falling_Edge, clockSource::extern_Clock_T0_Rising_Edge }

- enum timeOut : uint8_t {
  timeOut::to_16ms =0, timeOut::to_32ms, timeOut::to_64ms, timeOut::to_125ms,
  timeOut::to_250ms, timeOut::to_500ms, timeOut::to_1s, timeOut::to_2s,
  timeOut::to_4s, timeOut::to_8s }
- enum operationMode : uint8_t {
  operationMode::normal =0, operationMode::PWM_PC, operationMode::PWM_PC_8bit, operationMode::PWM_PC_9bit,
  operationMode::PWM_PC_10bit, operationMode::PWM_PFC_ICR, operationMode::PWM_PFC_OCR,
  operationMode::PWM_PC_ICR,
  operationMode::PWM_PC_OCR, operationMode::fast_PWM, operationMode::fast_PWM_8bit, operationMode::fast_PWM_9bit
  operationMode::fast_PWM_10bit, operationMode::fast_PWM_ICR, operationMode::fast_PWM_OCR,
  operationMode::CTC_OCR,
  operationMode::CTC_ICR, operationMode::interrupt =1, operationMode::reset, operationMode::interrupt_reset
  }

5.2.1 Enumeration Type Documentation

5.2.1.1 autoTriggerSource

enum core::autoTriggerSource : uint8_t [strong]

Enumerator

freeRunning	
analogComparator	
extInterrupt	
timer0Compare	
timer0Overflow	
timer1CompareB	
timer1Overflow	
timer1Capture	

Definition at line 118 of file ADC.h.

```
00118                                    : uint8_t {
00119      freeRunning,
00120      analogComparator,
00121      extInterrupt,
00122      timer0Compare,
00123      timer0Overflow,
00124      timer1CompareB,
00125      timer1Overflow,
00126      timer1Capture
00127 };
```

5.2.1.2 BODMode

enum core::BODMode : uint8_t [strong]

Enumerator

enabled	
disabled	

Definition at line 77 of file MCU.h.

```
00077                      : uint8_t {
00078      enabled=0,
00079      disabled,
00080 };
```

5.2.1.3 channel

enum core::channel : uint8_t [strong]

Enumerator

A	
B	

Definition at line 470 of file TimerCounter.h.

```
00470                      : uint8_t {
00471      A=0,
00472      B,
00473 };
```

5.2.1.4 clockPrescaler

enum core::clockPrescaler : uint8_t [strong]

Enumerator

PS_2	
PS_4	
PS_8	
PS_16	
PS_32	
PS_64	
PS_128	

Definition at line 108 of file ADC.h.

```
00108                          : uint8_t {
00109      PS_2 = 1,
00110      PS_4,
00111      PS_8,
00112      PS_16,
00113      PS_32,
00114      PS_64,
00115      PS_128
00116 };
```

5.2.1.5 clockSource

enum core::clockSource : uint16_t [strong]

Enumerator

noClock	
PS_1	
PS_8	
PS_32	
PS_64	
PS_128	
PS_256	
PS_1024	
extern_Clock_T0_Falling_Edge	
extern_Clock_T0_Rising_Edge	

Definition at line 504 of file TimerCounter.h.

```
00504                              : uint16_t {
00505        noClock=0,
00506        PS_1,
00507        PS_8,
00508        PS_32,
00509        PS_64,
00510        PS_128,
00511        PS_256,
00512        PS_1024,
00513        extern_Clock_T0_Falling_Edge,
00514        extern_Clock_T0_Rising_Edge,
00515 };
```

5.2.1.6 compareOutputMode

enum core::compareOutputMode : uint8_t [strong]

Enumerator

normal	
toggle	
clear	
set	

Definition at line 476 of file TimerCounter.h.

```
00476                              : uint8_t {
00477        normal=0,
00478        toggle,
00479        clear,
00480        set,
00481 };
```

5.2.1.7 operationMode [1/2]

enum core::operationMode : uint8_t [strong]

Enumerator

normal	

Enumerator

PWM_PC	
PWM_PC_8bit	
PWM_PC_9bit	
PWM_PC_10bit	
PWM_PFC_ICR	
PWM_PFC_OCR	
PWM_PC_ICR	
PWM_PC_OCR	
fast_PWM	
fast_PWM_8bit	
fast_PWM_9bit	
fast_PWM_10bit	
fast_PWM_ICR	
fast_PWM_OCR	
CTC_OCR	
CTC_ICR	
interrupt	
reset	
interrupt_reset	

Definition at line 78 of file WatchdogTimer.h.

```
00078                                 : uint8_t {
00079     interrupt=1,
00080     reset,
00081     interrupt_reset,
00082 };
```

5.2.1.8 operationMode [2/2]

enum core::operationMode : uint8_t [strong]

Enumerator

normal	
PWM_PC	
PWM_PC_8bit	
PWM_PC_9bit	
PWM_PC_10bit	
PWM_PFC_ICR	
PWM_PFC_OCR	
PWM_PC_ICR	
PWM_PC_OCR	
fast_PWM	
fast_PWM_8bit	
fast_PWM_9bit	
fast_PWM_10bit	
fast_PWM_ICR	
fast_PWM_OCR	

Enumerator

CTC_OCR	
CTC_ICR	
interrupt	
reset	
interrupt_reset	

Definition at line 485 of file TimerCounter.h.

```
00485                             : uint8_t {
00486     normal=0,
00487     PWM_PC,
00488     PWM_PC_8bit,
00489     PWM_PC_9bit,
00490     PWM_PC_10bit,
00491     PWM_PFC_ICR,
00492     PWM_PFC_OCR,
00493     PWM_PC_ICR,
00494     PWM_PC_OCR,
00495     fast_PWM,
00496     fast_PWM_8bit,
00497     fast_PWM_9bit,
00498     fast_PWM_10bit,
00499     fast_PWM_ICR,
00500     fast_PWM_OCR,
00501     CTC_OCR,
00502     CTC_ICR,
00503 };
```

5.2.1.9 pinChangePort

enum core::pinChangePort : uint8_t [strong]

Enumerator

PCINTB	
PCINTC	
PCINTD	

Definition at line 156 of file ExternInterrupt.h.

```
00156                             : uint8_t {
00157     PCINTB=0,
00158     PCINTC,
00159     PCINTD,
00160 };
```

5.2.1.10 referenceVoltage

enum core::referenceVoltage : uint8_t [strong]

Enumerator

AREF	external AREF pin voltage reference, internal 1.1V voltage reference turned off
AVCC	AVCC voltage reference with external capacitor at AREF pin.
internal	internal 1.1V voltage reference with external capacitor at AREF pin

Definition at line 100 of file ADC.h.

```
00100                                  : uint8_t {
00101      AREF=0,
00102      AVCC,
00103      internal
00104 };
```

5.2.1.11 resolution

enum core::resolution : uint8_t [strong]

Enumerator

res_8bit	
res_9bit	
res_10bit	
res_11bit	
res_12bit	
res_13bit	
res_14bit	
res_15bit	
res_16bit	

Definition at line 87 of file ADC.h.

```
00087                                  : uint8_t {
00088      res_8bit=0,
00089      res_9bit,
00090      res_10bit,
00091      res_11bit,
00092      res_12bit,
00093      res_13bit,
00094      res_14bit,
00095      res_15bit,
00096      res_16bit
00097 };
```

5.2.1.12 senseControl

enum core::senseControl : uint8_t [strong]

Enumerator

lowLevel	
logicalChange	
fallingEdge	
risingEdge	

Definition at line 149 of file ExternInterrupt.h.

```
00149                                  : uint8_t {
00150      lowLevel=0,
00151      logicalChange,
00152      fallingEdge,
00153      risingEdge
```

```
00154 };
```

5.2.1.13 sleepMode

enum core::sleepMode : uint8_t [strong]

Enumerator

Idle	
ADC_NoiseReduction	
powerDown	
powerSave	
standby	
extendedStandby	

Definition at line 82 of file MCU.h.
```
00082                      : uint8_t {
00083      Idle=0,
00084      ADC_NoiseReduction,
00085      powerDown,
00086      powerSave,
00087      standby=6,
00088      extendedStandby,
00089 };
```

5.2.1.14 timeOut

enum core::timeOut : uint8_t [strong]

Enumerator

to_16ms	
to_32ms	
to_64ms	
to_125ms	
to_250ms	
to_500ms	
to_1s	
to_2s	
to_4s	
to_8s	

Definition at line 65 of file WatchdogTimer.h.
```
00065                     : uint8_t {
00066      to_16ms=0,
00067      to_32ms,
00068      to_64ms,
00069      to_125ms,
00070      to_250ms,
00071      to_500ms,
00072      to_1s,
```

```
00073     to_2s,
00074     to_4s,
00075     to_8s,
00076 };
```

5.3 io Namespace Reference

Classes

- class Pin
- struct Port

    Structure.

- class SPI
- class USART0

Enumerations

- enum operationMode : uint8_t { operationMode::master =0, operationMode::slave, operationMode::submaster, operationMode::disable }
- enum clockPrescaler : uint8_t { clockPrescaler::PS_4 = 0, clockPrescaler::PS_16, clockPrescaler::PS_64, clockPrescaler::PS_128, clockPrescaler::PS_2, clockPrescaler::PS_8, clockPrescaler::PS_32 }
- enum dataMode : uint8_t { dataMode::mode_0 = 0, dataMode::mode_1, dataMode::mode_2, dataMode::mode_3 }
- enum dataOrder : uint8_t { dataOrder::first_MSB = 0, dataOrder::first_LSB }
- enum transmissionMode : uint8_t { transmissionMode::async =0, transmissionMode::sync, transmissionMode::masterSPI }
- enum communicationMode : uint8_t { communicationMode::duplex =0, communicationMode::transmit, communicationMode::receive }
- enum parityMode : uint8_t { parityMode::noParity =0, parityMode::evenParity, parityMode::oddParity }
- enum frameSize : uint8_t { frameSize::eightBits =0, frameSize::fiveBits, frameSize::sixBits, frameSize::sevenBits, frameSize::neineBits }
- enum stopBit : uint8_t { stopBit::oneStopBit =0, stopBit::twoStopBits }

Variables

- static io::Port PortB = { &DDRB, &PORTB, &PINB }

    global static Port B object

- static io::Port PortC = { &DDRC, &PORTC, &PINC }

    global static Port C object

- static io::Port PortD = { &DDRD, &PORTD, &PIND }

    global static Port D object

5.3.1 Enumeration Type Documentation

5.3.1.1 clockPrescaler

```
enum io::clockPrescaler : uint8_t [strong]
```

Enumerator

PS_4	
PS_16	
PS_64	
PS_128	
PS_2	
PS_8	
PS_32	

Definition at line 63 of file SPI.h.

```
00063                                : uint8_t  {
00064        PS_4 = 0,
00065        PS_16,
00066        PS_64,
00067        PS_128,
00068        PS_2,
00069        PS_8,
00070        PS_32
00071 };
```

5.3.1.2 communicationMode

enum io::communicationMode : uint8_t [strong]

Enumerator

duplex	full duplex mode
transmit	transmit mode
receive	receive mode

Definition at line 85 of file USART0.h.

```
00085                                : uint8_t {
00086        duplex=0,
00087        transmit,
00088        receive,
00090 };
```

5.3.1.3 dataMode

enum io::dataMode : uint8_t [strong]

Enumerator

mode↩_0	
mode↩_1	
mode↩_2	
mode↩_3	

Definition at line 73 of file SPI.h.

```
00073                          : uint8_t  {
00074       mode_0 = 0,
00075       mode_1,
00076       mode_2,
00077       mode_3,
00078 };
```

5.3.1.4   dataOrder

enum io::dataOrder : uint8_t [strong]

Enumerator

first_MSB	
first_LSB	

Definition at line 80 of file SPI.h.

```
00080                          : uint8_t  {
00081       first_MSB = 0,
00082       first_LSB
00083 };
```

5.3.1.5   frameSize

enum io::frameSize : uint8_t [strong]

Enumerator

eightBits	8 bits frame size
fiveBits	5 bits frame size
sixBits	6 bits frame size
sevenBits	7 bits frame size
neineBits	9 bits frame size

Definition at line 98 of file USART0.h.

```
00098                          : uint8_t {
00099       eightBits=0,
00100       fiveBits,
00101       sixBits,
00102       sevenBits,
00103       neineBits
00104 };
```

5.3.1.6   operationMode

enum io::operationMode : uint8_t [strong]

Enumerator

master	
slave	
submaster	
disable	

Definition at line 56 of file SPI.h.

```
00056                                 : uint8_t {
00057     master=0,
00058     slave,
00059     submaster,
00060     disable,
00061 };
```

5.3.1.7 parityMode

enum io::parityMode : uint8_t [strong]

Enumerator

noParity	no parity check mode
evenParity	even parity check mode
oddParity	odd parity check mode

Definition at line 92 of file USART0.h.

```
00092                               : uint8_t {
00093     noParity=0,
00094     evenParity,
00095     oddParity
00096 };
```

5.3.1.8 stopBit

enum io::stopBit : uint8_t [strong]

Enumerator

oneStopBit	1 stop bit
twoStopBits	2 stop bits

Definition at line 106 of file USART0.h.

```
00106                              : uint8_t{
00107     oneStopBit=0,
00108     twoStopBits
00109 };
```

5.3.1.9 transmissionMode

enum io::transmissionMode : uint8_t [strong]

Enumerator

async	asynchronous mode
sync	synchronous mode
masterSPI	masterSPI mode

Definition at line 79 of file USART0.h.

```
00079                                : uint8_t {
00080     async=0,
00081     sync,
00082     masterSPI
00083 };
```

5.3.2 Variable Documentation

5.3.2.1 PortB

io::Port io::PortB = { &DDRB, &PORTB, &PINB } [static]

global static Port B object

Definition at line 72 of file Pin.h.

5.3.2.2 PortC

io::Port io::PortC = { &DDRC, &PORTC, &PINC } [static]

global static Port C object

Definition at line 73 of file Pin.h.

5.3.2.3 PortD

io::Port io::PortD = { &DDRD, &PORTD, &PIND } [static]

global static Port D object

Definition at line 74 of file Pin.h.

5.4 utils Namespace Reference

Functions

- long map (long x, long in_min, long in_max, long out_min, long out_max)

5.4.1 Function Documentation

5.4.1.1 map()

```
long utils::map (
            long x,
            long in_min,
            long in_max,
            long out_min,
            long out_max )
```

Definition at line 3 of file utils_m328p.cpp.

```
00004 {
00005   return (x - in_min) * (out_max - out_min) / (in_max - in_min) + out_min;
00006 }
```

Chapter 6

Class Documentation

6.1   core::ADConverter Class Reference

```
#include <ADC.h>
```

Public Member Functions

- void start ()
- void stop ()
- void selectReferenceVoltage (const referenceVoltage &ar_refVoltage)
- void selectAnalogInput (io::Pin a_pin)
- void selectClockPrescaler (const clockPrescaler &ar_clockPrescaler)
- void enableConversionCompleteInterrupt (const uint8_t a_enable)
- void enableAutoTrigger (const uint8_t a_enable)
- void selectAutoTriggerSource (const autoTriggerSource &ar_autoTriggerSource)
- uint8_t conversionComplete ()
- void getConversionResult (uint16_t ∗ap_resultData, const resolution &ar_resolution=resolution::res_10bit)

Static Public Member Functions

- static ADConverter & getInstance (const referenceVoltage &ar_refVoltage=referenceVoltage::AVCC, const clockPrescaler &ar_clockPrescaler=clockPrescaler::PS_128, const autoTriggerSource &ar_autoTrigger↩
Source=autoTriggerSource::freeRunning, const io::Pin &ar_pin=io::Pin(0, io::PortC))
- static void conversionCompleteServiceRoutine () __asm__(STR(ADC_CONVERSION_COMPLETE_INTERRUPT))
__attribute__((__signal__

Public Attributes

- static void __used__
- static void __externally_visible__

Private Member Functions

- ADConverter (const referenceVoltage &ar_refVoltage, const clockPrescaler &ar_clockPrescaler, const autoTriggerSource &ar_autoTriggerSource, const io::Pin &ar_pin)
- ∼ADConverter ()

    Destructor.
- ADConverter (const ADConverter &)

    Overried Copy constructor.
- const ADConverter & operator= (const ADConverter &)

    Override assign operator.

Static Private Attributes

- static volatile uint16_t ∗ mp_conversionResult = nullptr

    pointer to receiver buffer
- static uint8_t m_resolution = 10

    pointer to receiver buffer
- static volatile uint8_t m_conversionComplete = 0

    ready to receive flag

6.1.1 Detailed Description

Definition at line 129 of file ADC.h.

6.1.2 Constructor & Destructor Documentation

6.1.2.1 ADConverter() [1/2]

```
core::ADConverter::ADConverter (
            const referenceVoltage & ar_refVoltage,
            const clockPrescaler & ar_clockPrescaler,
            const autoTriggerSource & ar_autoTriggerSource,
            const io::Pin & ar_pin )  [private]
```

Definition at line 23 of file ADC.cpp.
```
00027 {
00028     core::MCU::enableADC(1);
00029     selectAnalogInput(ar_pin);
00030     selectReferenceVoltage(ar_refVoltage);
00031     selectClockPrescaler(ar_clockPrescaler);
00032     enableAutoTrigger(1);
00033     selectAutoTriggerSource(ar_autoTriggerSource);
00034     sei();
00035     enableConversionCompleteInterrupt(1);
00036
00037
00038 }
```

References core::MCU::enableADC().

6.1.2.2 ∼ADConverter()

```
core::ADConverter::∼ADConverter ( )  [private]
```

Destructor.

Definition at line 41 of file ADC.cpp.

```
00042 {
00043
00044 }
```

6.1.2.3 ADConverter() **[2/2]**

```
core::ADConverter::ADConverter (
            const ADConverter &  )  [private]
```

Overried Copy constructor.

6.1.3 Member Function Documentation

6.1.3.1 conversionComplete()

```
uint8_t core::ADConverter::conversionComplete ( )
```

Definition at line 255 of file ADC.cpp.

```
00256 {
00257     return m_conversionComplete;
00258
00259 }
```

6.1.3.2 conversionCompleteServiceRoutine()

```
void core::ADConverter::conversionCompleteServiceRoutine ( )  [static]
```

Definition at line 109 of file ADC.cpp.

```
00110 {
00111
00112     static uint32_t l_resultData = 0;
00113     static uint16_t l_resultDataIndex = 0;
00114
00115     m_conversionComplete = 0;
00116     switch (m_resolution)
00117     {
00118         case 8:
00119         {
00120             *mp_conversionResult = ADC » 8;
00121             m_conversionComplete = 1;
00122             break;
00123         }
00124         case 9:
00125         {
00126             *mp_conversionResult = ADC » 7;
00127             m_conversionComplete = 1;
```

```
00128               break;
00129           }
00130           case 10:
00131           {
00132               *mp_conversionResult = ADC;
00133               m_conversionComplete = 1;
00134               break;
00135           }
00136           case 11:
00137           {
00138
00139               if (l_resultDataIndex < 4)
00140               {
00141                   l_resultData += ADC;
00142                   l_resultDataIndex++;
00143
00144               }
00145               else
00146               {
00147                   *mp_conversionResult = l_resultData » 1;
00148                   l_resultData = 0;
00149                   l_resultDataIndex = 0;
00150                   m_conversionComplete = 1;
00151
00152               }
00153
00154               break;
00155           }
00156           case 12:
00157           {
00158               if (l_resultDataIndex < 16)
00159               {
00160                   l_resultData += ADC;
00161                   l_resultDataIndex++;
00162
00163               }
00164               else
00165               {
00166                   *mp_conversionResult = l_resultData » 2;
00167                   l_resultData = 0;
00168                   l_resultDataIndex = 0;
00169                   m_conversionComplete = 1;
00170
00171               }
00172               break;
00173           }
00174           case 13:
00175           {
00176               if (l_resultDataIndex < 64)
00177               {
00178                   l_resultData += ADC;
00179                   l_resultDataIndex++;
00180
00181               }
00182               else
00183               {
00184                   *mp_conversionResult = l_resultData » 3;
00185                   l_resultData = 0;
00186                   l_resultDataIndex = 0;
00187                   m_conversionComplete = 1;
00188
00189               }
00190               break;
00191           }
00192           case 14:
00193           {
00194               if (l_resultDataIndex < 256)
00195               {
00196                   l_resultData += ADC;
00197                   l_resultDataIndex++;
00198
00199               }
00200               else
00201               {
00202                   *mp_conversionResult = l_resultData » 4;
00203                   l_resultData = 0;
00204                   l_resultDataIndex = 0;
00205                   m_conversionComplete = 1;
00206
00207               }
00208               break;
00209           }
00210           case 15:
00211           {
00212               if (l_resultDataIndex < 1024)
00213               {
00214                   l_resultData += ADC;
```

```
00215                    l_resultDataIndex++;
00216
00217              }
00218              else
00219              {
00220                    *mp_conversionResult = l_resultData » 5;
00221                    l_resultData = 0;
00222                    l_resultDataIndex = 0;
00223                    m_conversionComplete = 1;
00224
00225              }
00226          break;
00227          }
00228      case 16:
00229      {
00230          if (l_resultDataIndex < 4096)
00231          {
00232
00233                l_resultData += ADC;
00234                l_resultDataIndex++;
00235
00236          }
00237          else
00238          {
00239                *mp_conversionResult = l_resultData » 6;
00240                l_resultData = 0;
00241                l_resultDataIndex = 0;
00242                m_conversionComplete = 1;
00243
00244          }
00245          break;
00246      }
00247  }
00248  }
00249
00250
00251
00252
00253 }
```

6.1.3.3 enableAutoTrigger()

```
void core::ADConverter::enableAutoTrigger (
             const uint8_t a_enable )
```

Definition at line 73 of file ADC.cpp.
```
00074 {
00075      if (a_enable) {
00076          ADC_ENABLE_AUTOTRIGGER;
00077
00078      } else {
00079          ADC_DISABLE_AUTOTRIGGER;
00080      }
00081
00082 }
```

References ADC_DISABLE_AUTOTRIGGER, and ADC_ENABLE_AUTOTRIGGER.

6.1.3.4 enableConversionCompleteInterrupt()

```
void core::ADConverter::enableConversionCompleteInterrupt (
             const uint8_t a_enable )
```

Definition at line 84 of file ADC.cpp.
```
00085 {
00086      if (a_enable) {
00087          ADC_ENABLE_CONVERSION_COMPLETE_INTERRUPT;
00088
```

```
00089      } else {
00090          ADC_DISABLE_CONVERSION_COMPLETE_INTERRUPT;
00091      }
00092
00093 }
```

References ADC_DISABLE_CONVERSION_COMPLETE_INTERRUPT, and ADC_ENABLE_CONVERSION_COMPLETE_INTERR

6.1.3.5 getConversionResult()

```
void core::ADConverter::getConversionResult (
              uint16_t * ap_resultData,
              const resolution & ar_resolution = resolution::res_10bit )
```

Definition at line 262 of file ADC.cpp.

```
00263 {
00264      mp_conversionResult = ap_resultData;
00265
00266      switch (ar_resolution)
00267      {
00268          case core::resolution::res_8bit:
00269          {
00270              ADC_ADJUST_RESULT_LEFT;
00271              m_resolution = 8;
00272              break;
00273          }
00274          case core::resolution::res_9bit:
00275          {
00276              ADC_ADJUST_RESULT_LEFT;
00277              m_resolution = 9;
00278              break;
00279          }
00280          case core::resolution::res_10bit:
00281          {
00282              ADC_ADJUST_RESULT_RIGHT;
00283              m_resolution = 10;
00284              break;
00285          }
00286          case core::resolution::res_11bit:
00287          {
00288
00289              m_resolution = 11;
00290              break;
00291          }
00292          case core::resolution::res_12bit:
00293          {
00294              m_resolution = 12;
00295              break;
00296          }
00297          case core::resolution::res_13bit:
00298          {
00299              m_resolution = 13;
00300              break;
00301          }
00302          case core::resolution::res_14bit:
00303          {
00304              m_resolution = 14;
00305              break;
00306          }
00307          case core::resolution::res_15bit:
00308          {
00309              m_resolution = 15;
00310              break;
00311          }
00312          case core::resolution::res_16bit:
00313          {
00314              m_resolution = 16;
00315              break;
00316          }
00317      }
00318
00319
00320 }
```

References ADC_ADJUST_RESULT_LEFT, ADC_ADJUST_RESULT_RIGHT, core::res_10bit, core::res_11bit, core::res_12bit, core::res_13bit, core::res_14bit, core::res_15bit, core::res_16bit, core::res_8bit, and core::res_9bit.

6.1.3.6 getInstance()

```
core::ADConverter & core::ADConverter::getInstance (
            const referenceVoltage & ar_refVoltage = referenceVoltage::AVCC,
            const clockPrescaler & ar_clockPrescaler = clockPrescaler::PS_128,
            const autoTriggerSource & ar_autoTriggerSource = autoTriggerSource::freeRunning,
            const io::Pin & ar_pin = io::Pin(0,io::PortC) )  [static]
```

Definition at line 9 of file ADC.cpp.

```
00013 {
00014
00015     static ADConverter l_instance(ar_refVoltage,
00016                                   ar_clockPrescaler,
00017                                   ar_autoTriggerSource,
00018                                   ar_pin);
00019
00020     return l_instance;
00021 }
```

6.1.3.7 operator=()

```
const ADConverter& core::ADConverter::operator= (
            const ADConverter & )  [private]
```

Override assign operator.

6.1.3.8 selectAnalogInput()

```
void core::ADConverter::selectAnalogInput (
            io::Pin a_pin )
```

Definition at line 53 of file ADC.cpp.

```
00054 {
00055     a_pin.toInput(0);
00056     ADC_SELECT_ANALOG_INPUT(a_pin.getPinNumber());
00057     ADC_DISABLE_DIGITAL_INPUT_REGISTER(a_pin.getPinNumber());
00058
00059 }
```

References ADC_DISABLE_DIGITAL_INPUT_REGISTER, ADC_SELECT_ANALOG_INPUT, io::Pin::getPinNumber(), and io::Pin::toInput().

6.1.3.9 selectAutoTriggerSource()

```
void core::ADConverter::selectAutoTriggerSource (
            const autoTriggerSource & ar_autoTriggerSource )
```

Definition at line 102 of file ADC.cpp.

```
00103 {
00104     ADC_SELECT_AUTO_TRIGGER_SOURCE(static_cast<uint8_t>(ar_autoTriggerSource));
00105
00106
00107 }
```

References ADC_SELECT_AUTO_TRIGGER_SOURCE.

6.1.3.10 selectClockPrescaler()

```
void core::ADConverter::selectClockPrescaler (
            const clockPrescaler & ar_clockPrescaler )
```

Definition at line 95 of file ADC.cpp.

```
00096 {
00097     ADC_SELECT_CLOCK_PRESCALER(static_cast<uint8_t>(ar_clockPrescaler));
00098
00099 }
```

References ADC_SELECT_CLOCK_PRESCALER.

6.1.3.11 selectReferenceVoltage()

```
void core::ADConverter::selectReferenceVoltage (
            const referenceVoltage & ar_refVoltage )
```

Definition at line 47 of file ADC.cpp.

```
00048 {
00049     ADC_SELECT_REF_VOLTAGE(static_cast<uint8_t>(ar_refVoltage));
00050
00051 }
```

References ADC_SELECT_REF_VOLTAGE.

6.1.3.12 start()

```
void core::ADConverter::start ( )
```

Definition at line 61 of file ADC.cpp.

```
00062 {
00063     ADC_ENABLE;
00064     ADC_START_CONVERSION;
00065 }
```

References ADC_ENABLE, and ADC_START_CONVERSION.

6.1.3.13 stop()

```
void core::ADConverter::stop ( )
```

Definition at line 67 of file ADC.cpp.

```
00068 {
00069     ADC_STOP_CONVERSION;
00070     ADC_DISABLE;
00071 }
```

References ADC_DISABLE, and ADC_STOP_CONVERSION.

6.1.4 Member Data Documentation

6.1.4.1 __externally_visible__

```
void core::ADConverter::__externally_visible__
```

Definition at line 160 of file ADC.h.

6.1.4.2 __used__

```
void core::ADConverter::__used__
```

Definition at line 160 of file ADC.h.

6.1.4.3 m_conversionComplete

```
volatile uint8_t core::ADConverter::m_conversionComplete = 0  [static], [private]
```

ready to receive flag

Definition at line 192 of file ADC.h.

6.1.4.4 m_resolution

```
uint8_t core::ADConverter::m_resolution = 10  [static], [private]
```

pointer to receiver buffer

Definition at line 190 of file ADC.h.

6.1.4.5 mp_conversionResult

```
volatile uint16_t * core::ADConverter::mp_conversionResult = nullptr  [static], [private]
```

pointer to receiver buffer

Definition at line 187 of file ADC.h.

6.2 core::AnalogComparator Class Reference

```
#include <AnalogComparator.h>
```

6.2.1 Detailed Description

Definition at line 24 of file AnalogComparator.h.

6.3 component::Buzzer Class Reference

```
#include <Buzzer.h>
```

Collaboration diagram for component::Buzzer:

Public Member Functions

- Buzzer (const io::Pin &ar_pin)
- ~Buzzer ()
- void buzz (const uint16_t &ar_period_us, const uint16_t &ar_duration_ms)
- template<typename TC >
  void buzz (TC &ar_timerCounter, const uint16_t &ar_period_us, uint16_t &ar_duration_ms, const core::channel &ar_channel=core::channel::A, const core::clockSource &ar_clockSource=core::clockSource::PS_64)

Private Attributes

- io::Pin m_pin
  - *pin object*

6.3.1 Detailed Description

Definition at line 69 of file Buzzer.h.

6.3.2 Constructor & Destructor Documentation

6.3.2.1 Buzzer()

```
component::Buzzer::Buzzer (
            const io::Pin & ar_pin )
```

Definition at line 4 of file Buzzer.cpp.
```
00005                     : m_pin(ar_pin)
00006 {
00007     m_pin.toOutput();
00008
00009 }
```

References m_pin, and io::Pin::toOutput().

6.3.2.2 ∼Buzzer()

```
component::Buzzer::∼Buzzer ( )
```

Definition at line 11 of file Buzzer.cpp.
```
00012 {
00013
00014 }
```

6.3.3 Member Function Documentation

6.3.3.1 buzz() [1/2]

```
void component::Buzzer::buzz (
            const uint16_t & ar_period_us,
            const uint16_t & ar_duration_ms )
```

Definition at line 18 of file Buzzer.cpp.
```
00019 {
00020     uint32_t l_duration_us = ar_duration_ms*1000UL;
00021
00022     for (uint32_t i = 0; i < l_duration_us; i += ar_period_us)
00023     {
00024         /* For loop with variable delay selects the pitch */
00025         // _delay_us() needs a constant defined at compile time
00026         for (uint16_t j = 0; j < ar_period_us; j++)
00027         {
00028             _delay_us(1);
00029         }
00030         m_pin.toggle();
00031     }
00032     m_pin.setLow();
00033
00034 }
```

6.3.3.2 buzz() [2/2]

```
template<typename TC >
void component::Buzzer::buzz (
            TC & ar_timerCounter,
            const uint16_t & ar_period_us,
            uint16_t & ar_duration_ms,
            const core::channel & ar_channel = core::channel::A,
            const core::clockSource & ar_clockSource = core::clockSource::PS_64 )  [inline]
```

Definition at line 81 of file Buzzer.h.

```
00087    {
00088        ar_timerCounter.selectOperationMode(core::operationMode::CTC_OCR);
00089        ar_timerCounter.selectCompareOutputMode(ar_channel, core::compareOutputMode::toggle);
00090        ar_timerCounter.setCounter(0);
00091        ar_timerCounter.setOutputCompareRegister(ar_channel, ar_period_us);
00092        // start timer
00093        ar_timerCounter.start();
00094        // wait for the pitch duration
00095        while (ar_duration_ms) {
00096          _delay_ms(1);
00097          ar_duration_ms--;
00098        }
00099        // no buzz
00100        ar_timerCounter.selectCompareOutputMode(ar_channel, core::compareOutputMode::normal);
00101        ar_timerCounter.stop();
00102    }
```

References core::CTC_OCR, core::normal, and core::toggle.

6.3.4 Member Data Documentation

6.3.4.1 m_pin

```
io::Pin component::Buzzer::m_pin  [private]
```

pin object

Definition at line 109 of file Buzzer.h.

Referenced by Buzzer().

6.4 component::DCMotor Class Reference

```
#include <DCMotor.h>
```

Collaboration diagram for component::DCMotor:

Public Member Functions

- DCMotor (const io::Pin &ar_pin)
- ∼DCMotor ()
- void on ()

    Turn servo motor On.
- void off ()

    Turn servo motor Off.
- void toggle ()

    Toggle servo motor state.
- template<typename TC >
  void spin (TC &ar_timerCounter, const uint16_t &ar_speed, const core::channel &ar_channel=core::channel::A)
- template<typename TC >
  void stop (TC &ar_timerCounter)
- template<typename TC >
  void connect (TC &ar_timerCounter, const core::channel &ar_channel=core::channel::A)
- template<typename TC >
  void disconnect (TC &ar_timerCounter, const core::channel &ar_channel=core::channel::A)

Private Attributes

- io::Pin m_pin

    pin object

6.4.1 Detailed Description

Definition at line 126 of file DCMotor.h.

6.4.2 Constructor & Destructor Documentation

6.4.2.1 DCMotor()

```
component::DCMotor::DCMotor (
            const io::Pin & ar_pin )
```

Definition at line 3 of file DCMotor.cpp.

```
00004        : m_pin(ar_pin)
00005 {
00006     m_pin.toOutput();
00007
00008 }
```

References m_pin, and io::Pin::toOutput().

6.4.2.2 ∼DCMotor()

```
component::DCMotor::∼DCMotor ( )
```

Definition at line 11 of file DCMotor.cpp.

```
00012 {
00013
00014 }
```

6.4.3 Member Function Documentation

6.4.3.1 connect()

```
template<typename TC >
void component::DCMotor::connect (
            TC & ar_timerCounter,
            const core::channel & ar_channel = core::channel::A )  [inline]
```

Definition at line 164 of file DCMotor.h.

```
00166     {
00167         ar_timerCounter.selectOperationMode(core::operationMode::fast_PWM);
00168         ar_timerCounter.selectCompareOutputMode(ar_channel, core::compareOutputMode::clear);
00169         ar_timerCounter.setCounter(0);
00170
00171     }
```

References core::clear, and core::fast_PWM.

6.4.3.2 disconnect()

```
template<typename TC >
void component::DCMotor::disconnect (
            TC & ar_timerCounter,
            const core::channel & ar_channel = core::channel::A ) [inline]
```

Definition at line 174 of file DCMotor.h.

```
00176      {
00177          ar_timerCounter.selectCompareOutputMode(ar_channel, core::compareOutputMode::normal);
00178          ar_timerCounter.stop();
00179      }
```

References core::normal.

6.4.3.3 off()

```
void component::DCMotor::off ( )
```

Turn servo motor Off.

Definition at line 21 of file DCMotor.cpp.

```
00022 {
00023      m_pin.setLow();
00024 }
```

6.4.3.4 on()

```
void component::DCMotor::on ( )
```

Turn servo motor On.

Definition at line 16 of file DCMotor.cpp.

```
00017 {
00018      m_pin.setHigh();
00019 }
```

6.4.3.5 spin()

```
template<typename TC >
void component::DCMotor::spin (
            TC & ar_timerCounter,
            const uint16_t & ar_speed,
            const core::channel & ar_channel = core::channel::A ) [inline]
```

Definition at line 144 of file DCMotor.h.

```
00148      {
00149
00150          ar_timerCounter.setOutputCompareRegister(ar_channel, ar_speed);
00151          ar_timerCounter.start();
00152
00153
00154      }
```

6.4.3.6 stop()

```
template<typename TC >
void component::DCMotor::stop (
            TC & ar_timerCounter ) [inline]
```

Definition at line 156 of file DCMotor.h.

```
00157     {
00158         ar_timerCounter.stop();
00159
00160
00161     }
```

6.4.3.7 toggle()

```
void component::DCMotor::toggle ( )
```

Toggle servo motor state.

Definition at line 26 of file DCMotor.cpp.

```
00027 {
00028     m_pin.toggle();
00029
00030 }
```

6.4.4 Member Data Documentation

6.4.4.1 m_pin

```
io::Pin component::DCMotor::m_pin  [private]
```

pin object

Definition at line 185 of file DCMotor.h.

Referenced by DCMotor().

6.5 core::ExternInterrupt Class Reference

```
#include <ExternInterrupt.h>
```

Public Member Functions

- void setInt0SenseControl (const senseControl &ar_senseControl)
- void setInt1SenseControl (const senseControl &ar_senseControl)
- void enableInt0 (const uint8_t a_enable)
- void enableInt1 (const uint8_t a_enable)
- void enablePinChange (const pinChangePort &ar_pinChangePort, const uint8_t a_enable)
- void enablePinChangeMaskPortB (const uint8_t a_pinNumber, const uint8_t a_enable)
- void enablePinChangeMaskPortC (const uint8_t a_pinNumber, const uint8_t a_enable)
- void enablePinChangeMaskPortD (const uint8_t a_pinNumber, const uint8_t a_enable)

Static Public Member Functions

- static ExternInterrupt & getInstance ()
- static void Int0ServiceRoutine () __asm__(STR(EXT_INT_INT0_INTERRUPT)) __attribute__((__signal__
- static void Int1ServiceRoutine () __asm__(STR(EXT_INT_INT1_INTERRUPT)) __attribute__((__signal__
- static void pinChangePortBServiceRoutine () __asm__(STR(EXT_INT_PIN_CHANGE_PORTB_INTERRUPT)) __attribute__((__signal__
- static void pinChangePortCServiceRoutine () __asm__(STR(EXT_INT_PIN_CHANGE_PORTC_INTERRUPT)) __attribute__((__signal__
- static void pinChangePortDServiceRoutine () __asm__(STR(EXT_INT_PIN_CHANGE_PORTD_INTERRUPT)) __attribute__((__signal__

Public Attributes

- static void __used__
- static void __externally_visible__

Private Member Functions

- ExternInterrupt ()
- ∼ExternInterrupt ()

    Destructor.

- ExternInterrupt (const ExternInterrupt &)

    Overried Copy constructor.

- const ExternInterrupt & operator= (const ExternInterrupt &)

    Override assign operator.

6.5.1 Detailed Description

Definition at line 162 of file ExternInterrupt.h.

6.5.2 Constructor & Destructor Documentation

6.5.2.1 ExternInterrupt() [1/2]

```
core::ExternInterrupt::ExternInterrupt ( ) [private]
```

Definition at line 11 of file ExternInterrupt.cpp.

```
00012 {
00013     sei();
00014
00015 }
```

6.5.2.2 ∼ExternInterrupt()

```
core::ExternInterrupt::∼ExternInterrupt ( ) [private]
```

Destructor.

Definition at line 17 of file ExternInterrupt.cpp.

```
00018 {
00019
00020 }
```

6.5.2.3 ExternInterrupt() [2/2]

```
core::ExternInterrupt::ExternInterrupt (
            const ExternInterrupt & ) [private]
```

Overried Copy constructor.

6.5.3 Member Function Documentation

6.5.3.1 enableInt0()

```
void core::ExternInterrupt::enableInt0 (
            const uint8_t a_enable )
```

Definition at line 34 of file ExternInterrupt.cpp.

```
00035 {
00036     if (a_enable) {
00037         EXT_INT_ENABLE_INT0;
00038
00039     } else {
00040         EXT_INT_DISABLE_INT0;
00041     }
00042
00043 }
```

References EXT_INT_DISABLE_INT0, and EXT_INT_ENABLE_INT0.

6.5.3.2 enableInt1()

```
void core::ExternInterrupt::enableInt1 (
            const uint8_t a_enable )
```

Definition at line 45 of file ExternInterrupt.cpp.

```
00046 {
00047     if (a_enable) {
00048         EXT_INT_ENABLE_INT1;
00049
00050     } else {
00051         EXT_INT_DISABLE_INT1;
00052     }
00053 }
```

References EXT_INT_DISABLE_INT1, and EXT_INT_ENABLE_INT1.

6.5.3.3 enablePinChange()

```
void core::ExternInterrupt::enablePinChange (
            const pinChangePort & ar_pinChangePort,
            const uint8_t a_enable )
```

Definition at line 56 of file ExternInterrupt.cpp.

```
00057 {
00058     if (a_enable) {
00059         EXT_INT_ENABLE_PIN_CHANGE_INTERRUPT(static_cast<uint8_t>(ar_pinChangePort));
00060
00061     } else {
00062         EXT_INT_DISABLE_PIN_CHANGE_INTERRUPT(static_cast<uint8_t>(ar_pinChangePort));
00063     }
00064
00065 }
```

References EXT_INT_DISABLE_PIN_CHANGE_INTERRUPT, and EXT_INT_ENABLE_PIN_CHANGE_INTERRUPT.

6.5.3.4 enablePinChangeMaskPortB()

```
void core::ExternInterrupt::enablePinChangeMaskPortB (
            const uint8_t a_pinNumber,
            const uint8_t a_enable )
```

Definition at line 67 of file ExternInterrupt.cpp.

```
00068 {
00069     if (a_enable) {
00070         EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTB(a_pinNumber);
00071
00072     } else {
00073         EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTB(a_pinNumber);
00074     }
00075
00076 }
```

References EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTB.

6.5.3.5 enablePinChangeMaskPortC()

```
void core::ExternInterrupt::enablePinChangeMaskPortC (
            const uint8_t a_pinNumber,
            const uint8_t a_enable )
```

Definition at line 79 of file ExternInterrupt.cpp.

```
00080 {
00081     if (a_enable) {
00082         EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTC(a_pinNumber);
00083
00084     } else {
00085         EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTC(a_pinNumber);
00086     }
00087
00088 }
```

References EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTC.

6.5.3.6 enablePinChangeMaskPortD()

```
void core::ExternInterrupt::enablePinChangeMaskPortD (
            const uint8_t a_pinNumber,
            const uint8_t a_enable )
```

Definition at line 90 of file ExternInterrupt.cpp.

```
00091 {
00092     if (a_enable) {
00093         EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTD(a_pinNumber);
00094
00095     } else {
00096         EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTD(a_pinNumber);
00097     }
00098 }
```

References EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTD.

6.5.3.7 getInstance()

```
core::ExternInterrupt & core::ExternInterrupt::getInstance ( )  [static]
```

Definition at line 3 of file ExternInterrupt.cpp.

```
00004 {
00005     static ExternInterrupt l_instance;
00006     return l_instance;
00007
00008 }
```

6.5.3.8 Int0ServiceRoutine()

```
static void core::ExternInterrupt::Int0ServiceRoutine ( )  [static]
```

6.5.3.9 Int1ServiceRoutine()

```
static void core::ExternInterrupt::Int1ServiceRoutine ( )  [static]
```

6.5.3.10 operator=()

```
const ExternInterrupt& core::ExternInterrupt::operator= (
            const ExternInterrupt &  )  [private]
```

Override assign operator.

6.5.3.11 pinChangePortBServiceRoutine()

```
static void core::ExternInterrupt::pinChangePortBServiceRoutine ( )  [static]
```

6.5.3.12 pinChangePortCServiceRoutine()

```
static void core::ExternInterrupt::pinChangePortCServiceRoutine ( )  [static]
```

6.5.3.13 pinChangePortDServiceRoutine()

```
static void core::ExternInterrupt::pinChangePortDServiceRoutine ( )  [static]
```

6.5.3.14 setInt0SenseControl()

```
void core::ExternInterrupt::setInt0SenseControl (
            const senseControl & ar_senseControl )
```

Definition at line 22 of file ExternInterrupt.cpp.

```
00023 {
00024     EXT_INT_SET_INT0_SENSE_CONTROL(static_cast<uint8_t>(ar_senseControl));
00025
00026 }
```

References EXT_INT_SET_INT0_SENSE_CONTROL.

6.5.3.15 setInt1SenseControl()

```
void core::ExternInterrupt::setInt1SenseControl (
            const senseControl & ar_senseControl )
```

Definition at line 28 of file ExternInterrupt.cpp.

```
00029 {
00030     EXT_INT_SET_INT1_SENSE_CONTROL(static_cast<uint8_t>(ar_senseControl));
00031
00032 }
```

References EXT_INT_SET_INT1_SENSE_CONTROL.

6.5.4 Member Data Documentation

6.5.4.1 __externally_visible__

`static void core::ExternInterrupt::__externally_visible__`

Definition at line 185 of file ExternInterrupt.h.

6.5.4.2 __used__

`static void core::ExternInterrupt::__used__`

Definition at line 185 of file ExternInterrupt.h.

6.6 component::Led Class Reference

`#include <Led.h>`

Collaboration diagram for component::Led:

Public Member Functions

- Led (const io::Pin &ar_pin)

    Constructor.
- ∼Led ()

    Destructor.
- void on ()

    Turn led On.
- void off ()

    Turn led Off.
- void toggle ()

    Toggle led state.
- uint8_t isOn ()

    Is led On.
- uint8_t isOff ()

    Is led Off.

Private Attributes

- io::Pin m_pin

    pin object

6.6.1 Detailed Description

Definition at line 32 of file Led.h.

6.6.2 Constructor & Destructor Documentation

6.6.2.1 Led()

```
component::Led::Led (
            const io::Pin & ar_pin )
```

Constructor.

Initalizes the led object

Parameters

ar_pin	constant reference to pin object

Definition at line 3 of file Led.cpp.

```
00004             : m_pin(ar_pin)
00005 {
00006     m_pin.toOutput();
00007 }
```

References m_pin, and io::Pin::toOutput().

6.6.2.2 ∼Led()

```
component::Led::∼Led ( )
```

Destructor.

Definition at line 9 of file Led.cpp.

```
00010 {
00011
00012 }
```

6.6.3 Member Function Documentation

6.6.3.1 isOff()

```
uint8_t component::Led::isOff ( )
```

Is led Off.

Definition at line 41 of file Led.cpp.

```
00042 {
00043     return m_pin.isLow();
00044
00045 }
```

6.6.3.2 isOn()

```
uint8_t component::Led::isOn ( )
```

Is led On.

Definition at line 34 of file Led.cpp.

```
00035 {
00036     return m_pin.isHigh();
00037
00038 }
```

6.6.3.3 off()

```
void component::Led::off ( )
```

Turn led Off.

Definition at line 21 of file Led.cpp.

```
00022 {
00023     m_pin.setLow();
00024
00025 }
```

6.6.3.4 on()

```
void component::Led::on ( )
```

Turn led On.

Definition at line 15 of file Led.cpp.

```
00016 {
00017     m_pin.setHigh();
00018
00019 }
```

6.6.3.5 toggle()

```
void component::Led::toggle ( )
```

Toggle led state.

Definition at line 28 of file Led.cpp.

```
00029 {
00030     m_pin.toggle();
00031
00032 }
```

6.6.4 Member Data Documentation

6.6.4.1 m_pin

```
io::Pin component::Led::m_pin  [private]
```

pin object

Definition at line 67 of file Led.h.

Referenced by Led().

6.7 core::MCU Class Reference

```
#include <MCU.h>
```

Static Public Member Functions

- static void init ()
- static void selectSleepMode (const sleepMode &a_sleepMode)
- static void goToSleep (const BODMode &a_BODMode)
- static void sleepEnable (const uint8_t ar_enable)
- static void enableUSART0 (const uint8_t a_enable)
- static void enableTimerCounter0 (const uint8_t a_enable)
- static void enableTimerCounter1 (const uint8_t a_enable)
- static void enableTimerCounter2 (const uint8_t a_enable)
- static void enableTWI (const uint8_t a_enable)
- static void enableSPI (const uint8_t a_enable)
- static void enableADC (const uint8_t a_enable)
- static void disableBOD ()

6.7.1 Detailed Description

Definition at line 91 of file MCU.h.

6.7.2 Member Function Documentation

6.7.2.1 disableBOD()

```
void core::MCU::disableBOD ( )  [static]
```

Definition at line 126 of file MCU.cpp.

```
00127 {
00128     MCU_BOD_DISABLE;
00129 }
```

References MCU_BOD_DISABLE.

6.7.2.2 enableADC()

```
void core::MCU::enableADC (
            const uint8_t a_enable )  [static]
```

Definition at line 117 of file MCU.cpp.

```
00118 {
00119     if (a_enable) {
00120         MCU_ADC_ENABLE;
00121     } else {
00122         MCU_ADC_DISABLE;
00123     }
00124 }
```

References MCU_ADC_DISABLE, and MCU_ADC_ENABLE.

Referenced by core::ADConverter::ADConverter(), and init().

6.7.2.3 enableSPI()

```
void core::MCU::enableSPI (
            const uint8_t a_enable )  [static]
```

Definition at line 107 of file MCU.cpp.

```
00108 {
00109     if (a_enable) {
00110         MCU_SPI_ENABLE;
00111     } else {
00112         MCU_SPI_DISABLE;
00113     }
00114
00115 }
```

References MCU_SPI_DISABLE, and MCU_SPI_ENABLE.

Referenced by init(), and io::SPI::SPI().

6.7.2.4 enableTimerCounter0()

```
void core::MCU::enableTimerCounter0 (
            const uint8_t a_enable )  [static]
```

Definition at line 67 of file MCU.cpp.

```
00068 {
00069     if (a_enable) {
00070         MCU_TIMER0_ENABLE;
00071     } else {
00072         MCU_TIMER0_DISABLE;
00073     }
00074
00075 }
```

References MCU_TIMER0_DISABLE, and MCU_TIMER0_ENABLE.

Referenced by init(), and core::TimerCounter0::TimerCounter0().

6.7.2.5 enableTimerCounter1()

```
void core::MCU::enableTimerCounter1 (
            const uint8_t a_enable )  [static]
```

Definition at line 77 of file MCU.cpp.

```
00078 {
00079     if (a_enable) {
00080         MCU_TIMER1_ENABLE;
00081     } else {
00082         MCU_TIMER1_DISABLE;
00083     }
00084
00085 }
```

References MCU_TIMER1_DISABLE, and MCU_TIMER1_ENABLE.

Referenced by init(), and core::TimerCounter1::TimerCounter1().

6.7.2.6 enableTimerCounter2()

```
void core::MCU::enableTimerCounter2 (
            const uint8_t a_enable )  [static]
```

Definition at line 87 of file MCU.cpp.

```
00088 {
00089     if (a_enable) {
00090         MCU_TIMER2_ENABLE;
00091     } else {
00092         MCU_TIMER2_DISABLE;
00093     }
00094
00095 }
```

References MCU_TIMER2_DISABLE, and MCU_TIMER2_ENABLE.

Referenced by init(), and core::TimerCounter2::TimerCounter2().

6.7.2.7 enableTWI()

```
void core::MCU::enableTWI (
              const uint8_t a_enable ) [static]
```

Definition at line 97 of file MCU.cpp.

```
00098 {
00099     if (a_enable) {
00100         MCU_TWI_ENABLE;
00101     } else {
00102         MCU_TWI_DISABLE;
00103     }
00104
00105 }
```

References MCU_TWI_DISABLE, and MCU_TWI_ENABLE.

Referenced by init().

6.7.2.8 enableUSART0()

```
void core::MCU::enableUSART0 (
              const uint8_t a_enable ) [static]
```

Definition at line 57 of file MCU.cpp.

```
00058 {
00059     if (a_enable) {
00060         MCU_USART0_ENABLE;
00061     } else {
00062         MCU_USART0_DISABLE;
00063     }
00064
00065 }
```

References MCU_USART0_DISABLE, and MCU_USART0_ENABLE.

Referenced by init(), and io::USART0::USART0().

6.7.2.9 goToSleep()

```
void core::MCU::goToSleep (
              const BODMode & a_BODMode ) [static]
```

Definition at line 21 of file MCU.cpp.

```
00022 {
00023     cli();
00024     switch (a_BODMode)
00025     {
00026         case core::BODMode::enabled:
00027         {
00028             sleepEnable(1);
00029             sei();
00030             sleep_cpu();
00031             sleepEnable(0);
00032             break;
00033         }
00034         case core::BODMode::disabled:
00035         {
00036             sleepEnable(1);
00037             disableBOD();
00038             sei();
00039             sleep_cpu();
00040             sleepEnable(0);
00041             break;
00042         }
00043     }
00044
00045 }
```

References core::disabled, and core::enabled.

6.7.2.10 init()

```
void core::MCU::init ( ) [static]
```

Definition at line 3 of file MCU.cpp.

```
00004 {
00005     enableUSART0(0);
00006     enableTimerCounter0(0);
00007     enableTimerCounter1(0);
00008     enableTimerCounter2(0);
00009     enableTWI(0);
00010     enableSPI(0);
00011     enableADC(0);
00012
00013 }
```

References enableADC(), enableSPI(), enableTimerCounter0(), enableTimerCounter1(), enableTimerCounter2(), enableTWI(), and enableUSART0().

6.7.2.11 selectSleepMode()

```
void core::MCU::selectSleepMode (
            const sleepMode & a_sleepMode ) [static]
```

Definition at line 15 of file MCU.cpp.

```
00016 {
00017     MCU_SELECT_SLEEP_MODE(static_cast<uint8_t>(a_sleepMode));
00018
00019 }
```

References MCU_SELECT_SLEEP_MODE.

6.7.2.12 sleepEnable()

```
void core::MCU::sleepEnable (
            const uint8_t ar_enable ) [static]
```

Definition at line 47 of file MCU.cpp.

```
00048 {
00049     if (a_enable) {
00050         MCU_SLEEP_ENABLE;
00051     } else {
00052         MCU_SLEEP_DISABLE;
00053     }
00054
00055 }
```

References MCU_SLEEP_DISABLE, and MCU_SLEEP_ENABLE.

6.8 io::Pin Class Reference

```
#include <Pin.h>
```

Collaboration diagram for io::Pin:

Public Member Functions

- **Pin** (const uint8_t a_pinNumber, const **Port** &ar_portName)

  Constructor.
- **∼Pin** ()

  Destructor.
- void **toOutput** ()

  Configures pin to output.
- void **toInput** (const uint8_t &ar_useInternalPullUp)

  Configures pin to input.
- void **setLow** ()

  Set pin to logic low.
- void **setHigh** ()

  Set pin to logic high.
- void **toggle** ()

  Toggle pin state.
- uint8_t **isHigh** ()

  Check if pin is logic high.
- uint8_t **isLow** ()

  Check if pin is logic low.
- uint8_t **getPinNumber** ()

  Get pin number.

Private Attributes

- const **Port** & **mr_portName**

  constant reference to port object
- const uint8_t **m_pinNumber**

  pin number

6.8.1 Detailed Description

Definition at line 20 of file Pin.h.

6.8.2 Constructor & Destructor Documentation

6.8.2.1 Pin()

```
io::Pin::Pin (
            const uint8_t a_pinNumber,
            const Port & ar_portName )
```

Constructor.

Initalizes the pin object

```
@param ar_portName defines the port name of the avr chip
@param ar_pinNumber defines the pin number of the avr chip
```

Definition at line 4 of file Pin.cpp.
```
00005          : mr_portName(mr_portName), m_pinNumber(a_pinNumber)
00006 {
00007
00008 }
```

6.8.2.2 ∼Pin()

```
io::Pin::∼Pin ( )
```

Destructor.

Definition at line 11 of file Pin.cpp.
```
00013 {
00014
00015 }
```

6.8.3 Member Function Documentation

6.8.3.1 getPinNumber()

```
uint8_t io::Pin::getPinNumber ( )
```

Get pin number.

Definition at line 73 of file Pin.cpp.
```
00074 {
00075     return m_pinNumber;
00076 }
```

Referenced by core::ADConverter::selectAnalogInput().

6.8.3.2 isHigh()

```
uint8_t io::Pin::isHigh ( )
```

Check if pin is logic high.

Definition at line 63 of file Pin.cpp.

```
00064 {
00065     return  *mr_portName.mp_pinReg & (1 « m_pinNumber);
00066 }
```

6.8.3.3 isLow()

```
uint8_t io::Pin::isLow ( )
```

Check if pin is logic low.

Definition at line 68 of file Pin.cpp.

```
00069 {
00070     return  !(*mr_portName.mp_pinReg & (1 « m_pinNumber));
00071 }
```

6.8.3.4 setHigh()

```
void io::Pin::setHigh ( )
```

Set pin to logic high.

Definition at line 47 of file Pin.cpp.

```
00048 {
00049     if (*mr_portName.mp_ddrReg & (1 « m_pinNumber))
00050     {
00051         *mr_portName.mp_portReg |=  (1 « m_pinNumber);
00052     }
00053 }
```

6.8.3.5 setLow()

```
void io::Pin::setLow ( )
```

Set pin to logic low.

Definition at line 39 of file Pin.cpp.

```
00040 {
00041     if (*mr_portName.mp_ddrReg & (1 « m_pinNumber))
00042     {
00043         *mr_portName.mp_portReg &= ~(1 « m_pinNumber);
00044     }
00045 }
```

6.8.3.6 toggle()

```
void io::Pin::toggle ( )
```

Toggle pin state.

Definition at line 55 of file Pin.cpp.
```
00056 {
00057     if (*mr_portName.mp_ddrReg & (1 « m_pinNumber))
00058     {
00059         *mr_portName.mp_portReg ^=   1 « m_pinNumber;
00060     }
00061 }
```

6.8.3.7 toInput()

```
void io::Pin::toInput (
              const uint8_t & ar_useInternalPullUp )
```

Configures pin to input.

Parameters

ar_useInternalPullUp	indicates if internal pull up resistor is used

Definition at line 22 of file Pin.cpp.
```
00023 {
00024     if (ar_useInternalPullUp)
00025     {
00026         *mr_portName.mp_portReg |= (1 « m_pinNumber);
00027         *mr_portName.mp_ddrReg  &= ~(1 « m_pinNumber);
00028
00029
00030     }
00031     else
00032     {
00033         *mr_portName.mp_portReg &= ~(1 « m_pinNumber);
00034         *mr_portName.mp_ddrReg  &= ~(1 « m_pinNumber);
00035     }
00036
00037 }
```

Referenced by component::PushButton::PushButton(), and core::ADConverter::selectAnalogInput().

6.8.3.8 toOutput()

```
void io::Pin::toOutput ( )
```

Configures pin to output.

Definition at line 17 of file Pin.cpp.
```
00018 {
00019     *mr_portName.mp_ddrReg  |=  (1 « m_pinNumber);
00020 }
```

Referenced by component::Buzzer::Buzzer(), component::DCMotor::DCMotor(), component::Led::Led(), component::ServoMotor::Ser
and component::StepperMotor::StepperMotor().

6.8.4 Member Data Documentation

6.8.4.1 m_pinNumber

```
const uint8_t io::Pin::m_pinNumber  [private]
```

pin number

Definition at line 66 of file Pin.h.

6.8.4.2 mr_portName

```
const Port& io::Pin::mr_portName  [private]
```

constant reference to port object

Definition at line 65 of file Pin.h.

6.9 io::Port Struct Reference

Structure.

```
#include <Pin.h>
```

Public Attributes

- volatile uint8_t ∗ mp_ddrReg
    pointer to the data direction register
- volatile uint8_t ∗ mp_portReg
    pointer to the port register
- volatile uint8_t ∗ mp_pinReg
    pointer to the pin register

6.9.1 Detailed Description

Structure.

Contains pointers to the Port's registers

Definition at line 11 of file Pin.h.

6.9.2 Member Data Documentation

6.9.2.1 mp_ddrReg

`volatile uint8_t* io::Port::mp_ddrReg`

pointer to the data direction register

Definition at line 13 of file Pin.h.

6.9.2.2 mp_pinReg

`volatile uint8_t* io::Port::mp_pinReg`

pointer to the pin register

Definition at line 17 of file Pin.h.

6.9.2.3 mp_portReg

`volatile uint8_t* io::Port::mp_portReg`

pointer to the port register

Definition at line 15 of file Pin.h.

6.10 component::PushButton Class Reference

`#include <PushButton.h>`

Collaboration diagram for component::PushButton:

Public Member Functions

- **PushButton** (const io::Pin &ar_pin, const uint8_t &ar_useInternalPullUp=1, const uint8_t &ar_isActiveLow=1)

    Constructor.
- ∼PushButton ()

    Destructor.
- uint8_t isPressed ()

    Is pushbutton pressed.
- uint8_t getPressedCount () const

    Get pushbutton pressed count.
- void resetPressedCount ()

    Reset pushbutton pressed count.

Private Attributes

- io::Pin m_pin

    pin object
- const uint8_t & mr_isActiveLow

    indicates led active state
- const uint8_t & mr_useInternalPullUp

    indicates if internal pullup resistor used

- uint8_t m_buttonPressed

    pushbutton pressed count

6.10.1 Detailed Description

Definition at line 95 of file PushButton.h.

6.10.2 Constructor & Destructor Documentation

6.10.2.1 PushButton()

```
component::PushButton::PushButton (
            const io::Pin & ar_pin,
            const uint8_t & ar_useInternalPullUp = 1,
            const uint8_t & ar_isActiveLow = 1 )
```

Constructor.

Initializes pushbutton object

```
@param ar_pin pin object
@param ar_useInternalPullUp indicates if internal pull up resistor used
```

Definition at line 3 of file PushButton.cpp.
```
00004                                   : m_pin(ar_pin),
00005                                     mr_isActiveLow(ar_isActiveLow),
00006                                     mr_useInternalPullUp(ar_useInternalPullUp)
00007
00008
00009 {
00010     m_pin.toInput(mr_useInternalPullUp);
00011     m_buttonPressed = 0;
00012 }
```

References m_buttonPressed, m_pin, mr_useInternalPullUp, and io::Pin::toInput().

6.10.2.2 ∼**PushButton()**

```
component::PushButton::~PushButton ( )
```

Destructor.

Definition at line 14 of file PushButton.cpp.
```
00015 {
00016
00017 }
```

6.10.3 Member Function Documentation

6.10.3.1 getPressedCount()

```
uint8_t component::PushButton::getPressedCount ( ) const
```

Get pushbutton pressed count.

Definition at line 46 of file PushButton.cpp.
```
00047 {
00048
00049     return m_buttonPressed;
00050
00051 }
```

6.10.3.2 isPressed()

```
uint8_t component::PushButton::isPressed ( )
```

Is pushbutton pressed.

Definition at line 20 of file PushButton.cpp.
```
00021 {
00022     if (mr_isActiveLow || mr_useInternalPullUp) {
00023         if (m_pin.isLow()) {
00024             _delay_us(PUSHBUTTON_DEBOUNCE_TIME_US);
00025             if (m_pin.isLow()) {
00026                 ++m_buttonPressed;
00027                 return 1;
00028             }
00029         }
00030     } else {
00031
00032         if (m_pin.isHigh()) {
00033             _delay_us(PUSHBUTTON_DEBOUNCE_TIME_US);
00034             if (m_pin.isHigh()) {
00035                 ++m_buttonPressed;
00036                 return 1;
00037             }
00038         }
00039
00040     }
00041     m_buttonPressed = 0;
00042     return 0;
00043
00044 }
```

References PUSHBUTTON_DEBOUNCE_TIME_US.

6.10.3.3 resetPressedCount()

```
void component::PushButton::resetPressedCount ( )
```

Reset pushbutton pressed count.

Definition at line 53 of file PushButton.cpp.

```
00054 {
00055     m_buttonPressed = 0;
00056
00057 }
```

6.10.4 Member Data Documentation

6.10.4.1 m_buttonPressed

```
uint8_t component::PushButton::m_buttonPressed  [private]
```

pushbutton pressed count

Definition at line 125 of file PushButton.h.

Referenced by PushButton().

6.10.4.2 m_pin

```
io::Pin component::PushButton::m_pin  [private]
```

pin object

Definition at line 122 of file PushButton.h.

Referenced by PushButton().

6.10.4.3 mr_isActiveLow

```
const uint8_t& component::PushButton::mr_isActiveLow  [private]
```

indicates led active state

Definition at line 123 of file PushButton.h.

6.10.4.4 mr_useInternalPullUp

`const uint8_t& component::PushButton::mr_useInternalPullUp [private]`

indicates if internal pullup resistor used

Definition at line 124 of file PushButton.h.

Referenced by PushButton().

6.11 component::ServoMotor Class Reference

`#include <ServoMotor.h>`

Collaboration diagram for component::ServoMotor:

Public Member Functions

- ServoMotor (const io::Pin &ar_pin, const uint16_t &ar_pulseCycle=0, const uint16_t &ar_pulseWidthMin=0, const uint16_t &ar_pulseWidthMid=0, const uint16_t &ar_pulseWidthMax=0)
- ∼ServoMotor ()
- void on ()
  - *Turn servo motor On.*
- void off ()
  - *Turn servo motor Off.*
- void toggle ()
  - *Toggle servo motor state.*
- uint16_t computePulseCycleCount (const uint16_t &ar_clockPrescaler)
- uint16_t computePulseWidthMinCount (const uint16_t &ar_clockPrescaler)
- uint16_t computePulseWidthMidCount (const uint16_t &ar_clockPrescaler)
- uint16_t computePulseWidthMaxCount (const uint16_t &ar_clockPrescaler)
- uint16_t computeRotationAngleCount (const uint8_t &ar_angle_deg, const uint16_t &ar_clockPrescaler)
- void rotate (core::TimerCounter1 &ar_timerCounter1, const uint8_t &ar_angle_deg, const core::channel &ar_channel=core::channel::A)
- void connect (core::TimerCounter1 &ar_timerCounter1, const core::channel &ar_channel=core::channel::A)
- void disconnect (core::TimerCounter1 &ar_timerCounter1, const core::channel &ar_channel=core::channel::A)

Private Attributes

- • io::Pin m_pin

    pin object
- • uint16_t m_pulseCycle

    pulse cycle [us]
- • uint16_t m_pulseWidthMin

    pulse width min [us]
- • uint16_t m_pulseWidthMid

    pulse width mid [us]
- • uint16_t m_pulseWidthMax

    pulse width max [us]

6.11.1 Detailed Description

Definition at line 138 of file ServoMotor.h.

6.11.2 Constructor & Destructor Documentation

6.11.2.1 ServoMotor()

```
component::ServoMotor::ServoMotor (
            const io::Pin & ar_pin,
            const uint16_t & ar_pulseCycle = 0,
            const uint16_t & ar_pulseWidthMin = 0,
            const uint16_t & ar_pulseWidthMid = 0,
            const uint16_t & ar_pulseWidthMax = 0 )
```

Definition at line 5 of file ServoMotor.cpp.
```
00010                         : m_pin(ar_pin),
00011                           m_pulseCycle(ar_pulseCycle),
00012                           m_pulseWidthMin(ar_pulseWidthMin),
00013                           m_pulseWidthMid(ar_pulseWidthMid),
00014                           m_pulseWidthMax(ar_pulseWidthMax)
00015 {
00016     m_pin.toOutput();
00017
00018 }
```

References m_pin, and io::Pin::toOutput().

6.11.2.2 ∼ServoMotor()

```
component::ServoMotor::∼ServoMotor ( )
```

Definition at line 20 of file ServoMotor.cpp.
```
00021 {
00022
00023 }
```

6.11.3 Member Function Documentation

6.11.3.1 computePulseCycleCount()

```
uint16_t component::ServoMotor::computePulseCycleCount (
            const uint16_t & ar_clockPrescaler )
```

Definition at line 44 of file ServoMotor.cpp.

```
00045 {
00046      return SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT(m_pulseCycle,ar_clockPrescaler);
00047 }
```

References SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT.

6.11.3.2 computePulseWidthMaxCount()

```
uint16_t component::ServoMotor::computePulseWidthMaxCount (
            const uint16_t & ar_clockPrescaler )
```

Definition at line 54 of file ServoMotor.cpp.

```
00055 {
00056      return SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT(m_pulseWidthMax,ar_clockPrescaler);
00057 }
```

References SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT.

6.11.3.3 computePulseWidthMidCount()

```
uint16_t component::ServoMotor::computePulseWidthMidCount (
            const uint16_t & ar_clockPrescaler )
```

Definition at line 59 of file ServoMotor.cpp.

```
00060 {
00061      return SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT(m_pulseWidthMid,ar_clockPrescaler);
00062 }
```

References SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT.

6.11.3.4 computePulseWidthMinCount()

```
uint16_t component::ServoMotor::computePulseWidthMinCount (
            const uint16_t & ar_clockPrescaler )
```

Definition at line 49 of file ServoMotor.cpp.

```
00050 {
00051      return SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT(m_pulseWidthMin,ar_clockPrescaler);
00052 }
```

References SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT.

6.11.3.5 computeRotationAngleCount()

```
uint16_t component::ServoMotor::computeRotationAngleCount (
            const uint8_t & ar_angle_deg,
            const uint16_t & ar_clockPrescaler )
```

Definition at line 64 of file ServoMotor.cpp.

```
00065 {
00066     return
       static_cast<uint16_t>(SERVOMOTOR_TIMER_ANGLE_COUNT(ar_angle_deg,static_cast<long>(computePulseWidthMinCount(ar_clockPre
00067 }
```

References SERVOMOTOR_TIMER_ANGLE_COUNT.

6.11.3.6 connect()

```
void component::ServoMotor::connect (
            core::TimerCounter1 & ar_timerCounter1,
            const core::channel & ar_channel = core::channel::A )
```

Definition at line 85 of file ServoMotor.cpp.

```
00087 {
00088
00089
00090
       ar_timerCounter1.setInputCaptureRegister(computePulseCycleCount(ar_timerCounter1.getClockPrescaler()));
00091     ar_timerCounter1.selectOperationMode(core::operationMode::fast_PWM_ICR);
00092     ar_timerCounter1.selectCompareOutputMode(ar_channel, core::compareOutputMode::clear);
00093     ar_timerCounter1.setCounter(0);
00094
00095 }
```

References core::clear, core::fast_PWM_ICR, core::TimerCounter1::getClockPrescaler(), core::TimerCounter1::selectCompareOutpu
core::TimerCounter1::selectOperationMode(), core::TimerCounter1::setCounter(), and core::TimerCounter1::setInputCaptureRegister

6.11.3.7 disconnect()

```
void component::ServoMotor::disconnect (
            core::TimerCounter1 & ar_timerCounter1,
            const core::channel & ar_channel = core::channel::A )
```

Definition at line 97 of file ServoMotor.cpp.

```
00099 {
00100     ar_timerCounter1.selectCompareOutputMode(ar_channel, core::compareOutputMode::normal);
00101     // stop timer
00102     ar_timerCounter1.stop();
00103 }
```

References core::normal, core::TimerCounter1::selectCompareOutputMode(), and core::TimerCounter1::stop().

6.11.3.8 off()

```
void component::ServoMotor::off ( )
```

Turn servo motor Off.

Definition at line 33 of file ServoMotor.cpp.

```
00034 {
00035     m_pin.setLow();
00036 }
```

6.11.3.9 on()

```
void component::ServoMotor::on ( )
```

Turn servo motor On.

Definition at line 28 of file ServoMotor.cpp.

```
00029 {
00030     m_pin.setHigh();
00031 }
```

6.11.3.10 rotate()

```
void component::ServoMotor::rotate (
            core::TimerCounter1 & ar_timerCounter1,
            const uint8_t & ar_angle_deg,
            const core::channel & ar_channel = core::channel::A )
```

Definition at line 71 of file ServoMotor.cpp.

```
00074 {
00075
00076     ar_timerCounter1.setOutputCompareRegister(ar_channel,
      computeRotationAngleCount(ar_angle_deg,ar_timerCounter1.getClockPrescaler()));
00077
00078     // start timer
00079     ar_timerCounter1.start();
00080
00081
00082 }
```

References core::TimerCounter1::getClockPrescaler(), core::TimerCounter1::setOutputCompareRegister(), and core::TimerCounter1::start().

6.11.3.11 toggle()

```
void component::ServoMotor::toggle ( )
```

Toggle servo motor state.

Definition at line 38 of file ServoMotor.cpp.

```
00039 {
00040     m_pin.toggle();
00041
00042 }
```

6.11.4 Member Data Documentation

6.11.4.1 m_pin

`io::Pin component::ServoMotor::m_pin [private]`

pin object

Definition at line 188 of file ServoMotor.h.

Referenced by ServoMotor().

6.11.4.2 m_pulseCycle

`uint16_t component::ServoMotor::m_pulseCycle [private]`

pulse cycle [us]

Definition at line 190 of file ServoMotor.h.

6.11.4.3 m_pulseWidthMax

`uint16_t component::ServoMotor::m_pulseWidthMax [private]`

pulse width max [us]

Definition at line 196 of file ServoMotor.h.

6.11.4.4 m_pulseWidthMid

`uint16_t component::ServoMotor::m_pulseWidthMid [private]`

pulse width mid [us]

Definition at line 194 of file ServoMotor.h.

6.11.4.5 m_pulseWidthMin

```
uint16_t component::ServoMotor::m_pulseWidthMin [private]
```

pulse width min [us]

Definition at line 192 of file ServoMotor.h.

6.12 io::SPI Class Reference

```
#include <SPI.h>
```

Collaboration diagram for io::SPI:

Public Member Functions

- void selectDataMode (const dataMode &ar_dataMode)
- void selectDataOrder (const dataOrder &ar_dataOrder)
- void selectOperationMode (const operationMode &ar_operationMode)
- void selectClockPrescaler (const clockPrescaler &ar_clockPrescaler)
- void selectSlave (const uint8_t a_select)
- uint8_t writeCollision ()

  Is there write collision.
- uint8_t transferComplete ()

  Is serial transfer complete.
- void masterSendByte (const uint8_t &ar_byte)
- void masterReceiveByte (uint8_t &ar_byte)
- void slaveReceiveByte (uint8_t &ar_byte)

Static Public Member Functions

- static SPI & getInstance (const io::Pin &ar_pinSCK, const io::Pin &ar_pinMISO, const io::Pin &ar_pinMOSI, const io::Pin &ar_pinSS)
- static void enableTransferCompleteInterrupt (const uint8_t a_enable)
- static void transferCompleteServiceRoutine () __asm__(STR(SPI_TRANSFER_COMPLETE_INTERRUPT)) __attribute__((__signal__

    Serial transfer complete ISR.

Public Attributes

- static void __used__
- static void __externally_visible__

Private Member Functions

- SPI (const io::Pin &ar_pinSCK, const io::Pin &ar_pinMISO, const io::Pin &ar_pinMOSI, const io::Pin &ar_↩ pinSS)

    Constructor.

- ∼SPI ()

    Destructor.

- SPI (const SPI &)

    Overried Copy constructor.

- const SPI & operator= (const SPI &)

    Override assign operator.

Private Attributes

- io::Pin m_pinSCK

    pin object

- io::Pin m_pinMISO

    pin object

- io::Pin m_pinMOSI

    pin object

- io::Pin m_pinSS

    pin object

Static Private Attributes

- static volatile uint8_t m_data = 0

6.12.1 Detailed Description

Definition at line 86 of file SPI.h.

6.12.2 Constructor & Destructor Documentation

6.12.2.1 SPI() [1/2]

```
io::SPI::SPI (
            const io::Pin & ar_pinSCK,
            const io::Pin & ar_pinMISO,
            const io::Pin & ar_pinMOSI,
            const io::Pin & ar_pinSS )   [private]
```

Constructor.

Initalizes the USART0 object

```
@param ar_transMode defines transmission mode
@param ar_comMode defines communication mode
@param ar_frameSize defines data frame size
@param ar_stopBit defines number of stop bits
@param ar_parityMode defines parity mode
```

Definition at line 22 of file SPI.cpp.

```
00026          : m_pinSCK(ar_pinSCK),
00027            m_pinMISO(ar_pinMISO),
00028            m_pinMOSI(ar_pinMOSI),
00029            m_pinSS(ar_pinSS)
00030 {
00031     core::MCU::enableSPI(1);
00032     sei();
00033     enableTransferCompleteInterrupt(1);
00034
00035 }
```

References core::MCU::enableSPI(), and enableTransferCompleteInterrupt().

6.12.2.2 ∼SPI()

```
io::SPI::∼SPI ( )   [private]
```

Destructor.

Definition at line 37 of file SPI.cpp.

```
00038 {
00039
00040 }
```

6.12.2.3 SPI() [2/2]

```
io::SPI::SPI (
            const SPI & )   [private]
```

Overried Copy constructor.

6.12.3 Member Function Documentation

6.12.3.1 enableTransferCompleteInterrupt()

```
void io::SPI::enableTransferCompleteInterrupt (
            const uint8_t a_enable ) [static]
```

Definition at line 110 of file SPI.cpp.
```
00111 {
00112     if (a_enable) {
00113         SPI_ENABLE_TRANSFER_COMPLETE_INTERRUPT;
00114     } else {
00115         SPI_DISABLE_TRANSFER_COMPLETE_INTERRUPT;
00116     }
00117 }
```

References SPI_DISABLE_TRANSFER_COMPLETE_INTERRUPT, and SPI_ENABLE_TRANSFER_COMPLETE_INTERRUPT.

Referenced by SPI().

6.12.3.2 getInstance()

```
io::SPI & io::SPI::getInstance (
            const io::Pin & ar_pinSCK,
            const io::Pin & ar_pinMISO,
            const io::Pin & ar_pinMOSI,
            const io::Pin & ar_pinSS ) [static]
```

Definition at line 8 of file SPI.cpp.
```
00012 {
00013     static SPI l_instance(ar_pinSCK,
00014                          ar_pinMISO,
00015                          ar_pinMOSI,
00016                          ar_pinSS);
00017
00018     return l_instance;
00019
00020 }
```

6.12.3.3 masterReceiveByte()

```
void io::SPI::masterReceiveByte (
            uint8_t & ar_byte )
```

Definition at line 147 of file SPI.cpp.
```
00148 {
00149     masterSendByte(0);
00150     ar_byte = m_data;
00151
00152 }
```

6.12.3.4 masterSendByte()

```
void io::SPI::masterSendByte (
            const uint8_t & ar_byte )
```

Definition at line 135 of file SPI.cpp.

```
00136 {
00137
00138     SPI_DATA_REGISTER = ar_byte;
00139     selectSlave(1);
00140     while(!transferComplete()){};
00141     selectSlave(0);
00142
00143
00144
00145 }
```

References SPI_DATA_REGISTER.

6.12.3.5 operator=()

```
const SPI& io::SPI::operator= (
            const SPI & )  [private]
```

Override assign operator.

6.12.3.6 selectClockPrescaler()

```
void io::SPI::selectClockPrescaler (
            const clockPrescaler & ar_clockPrescaler )
```

Definition at line 53 of file SPI.cpp.

```
00054 {
00055     SPI_SELECT_CLOCK_PRESCALER(static_cast<uint8_t>(ar_clockPrescaler));
00056
00057 }
```

References SPI_SELECT_CLOCK_PRESCALER.

6.12.3.7 selectDataMode()

```
void io::SPI::selectDataMode (
            const dataMode & ar_dataMode )
```

Definition at line 99 of file SPI.cpp.

```
00100 {
00101     SPI_SELECT_DATA_MODE(static_cast<uint8_t>(ar_dataMode));
00102 }
```

References SPI_SELECT_DATA_MODE.

6.12.3.8 selectDataOrder()

```
void io::SPI::selectDataOrder (
            const dataOrder & ar_dataOrder )
```

Definition at line 104 of file SPI.cpp.

```
00105 {
00106     SPI_SELECT_DATA_ORDER(static_cast<uint8_t>(ar_dataOrder));
00107
00108 }
```

References SPI_SELECT_DATA_ORDER.

6.12.3.9 selectOperationMode()

```
void io::SPI::selectOperationMode (
            const operationMode & ar_operationMode )
```

Definition at line 59 of file SPI.cpp.

```
00060 {
00061     switch (ar_operationMode)
00062     {
00063         case operationMode::master:
00064         {
00065             m_pinMOSI.toOutput();
00066             m_pinSCK.toOutput();
00067             m_pinMISO.toInput(1);
00068             m_pinSS.toOutput();
00069             m_pinSS.setHigh();
00070             SPI_SELECT_MASTER_MODE;
00071             SPI_ENABLE;
00072             break;
00073         }
00074         case operationMode::slave:
00075         {
00076             m_pinMISO.toOutput();
00077             SPI_SELECT_SLAVE_MODE;
00078             SPI_ENABLE;
00079             break;
00080         }
00081         case operationMode::submaster:
00082         {
00083             m_pinMOSI.toOutput();
00084             m_pinSCK.toOutput();
00085             m_pinMISO.toInput(1);
00086             m_pinSS.toInput(1);
00087             SPI_SELECT_MASTER_MODE;
00088             SPI_ENABLE;
00089             break;
00090         }
00091         case operationMode::disable:
00092         {
00093             SPI_DISABLE;
00094             break;
00095         }
00096     }
00097 }
```

References io::disable, io::master, io::slave, SPI_DISABLE, SPI_ENABLE, SPI_SELECT_MASTER_MODE, SPI_SELECT_SLAVE_MODE, and io::submaster.

6.12.3.10 selectSlave()

```
void io::SPI::selectSlave (
            const uint8_t a_select )
```

Definition at line 119 of file SPI.cpp.

```
00120 {
00121     if (a_select) {
00122         m_pinSS.setLow();
00123
00124     } else {
00125         m_pinSS.setHigh();
00126     }
00127
00128 }
```

6.12.3.11 slaveReceiveByte()

```
void io::SPI::slaveReceiveByte (
            uint8_t & ar_byte )
```

Definition at line 154 of file SPI.cpp.

```
00155 {
00156     ar_byte = m_data;
00157
00158 }
```

6.12.3.12 transferComplete()

```
uint8_t io::SPI::transferComplete ( )
```

Is serial transfer complete.

Definition at line 48 of file SPI.cpp.

```
00049 {
00050     return (SPI_STATUS_REGISTER & (1 « SPI_TRANSFER_COMPLETE));
00051 }
```

References SPI_STATUS_REGISTER, and SPI_TRANSFER_COMPLETE.

6.12.3.13 transferCompleteServiceRoutine()

```
void io::SPI::transferCompleteServiceRoutine ( )  [static]
```

Serial transfer complete ISR.

Definition at line 129 of file SPI.cpp.

```
00130 {
00131
00132         m_data = SPI_DATA_REGISTER;
00133 }
```

References SPI_DATA_REGISTER.

6.12.3.14 writeCollision()

```
uint8_t io::SPI::writeCollision ( )
```

Is there write collision.

Definition at line 42 of file SPI.cpp.

```
00043 {
00044     return (SPI_STATUS_REGISTER & (1 « SPI_WRITE_COLLISION));
00045 }
```

References SPI_STATUS_REGISTER, and SPI_WRITE_COLLISION.

6.12.4 Member Data Documentation

6.12.4.1 __externally_visible__

```
void io::SPI::__externally_visible__
```

Definition at line 124 of file SPI.h.

6.12.4.2 __used__

```
void io::SPI::__used__
```

Definition at line 124 of file SPI.h.

6.12.4.3 m_data

```
volatile uint8_t io::SPI::m_data = 0  [static], [private]
```

Definition at line 154 of file SPI.h.

6.12.4.4 m_pinMISO

```
io::Pin io::SPI::m_pinMISO  [private]
```

pin object

Definition at line 157 of file SPI.h.

6.12.4.5 m_pinMOSI

`io::Pin io::SPI::m_pinMOSI [private]`

pin object

Definition at line 158 of file SPI.h.

6.12.4.6 m_pinSCK

`io::Pin io::SPI::m_pinSCK [private]`

pin object

Definition at line 156 of file SPI.h.

6.12.4.7 m_pinSS

`io::Pin io::SPI::m_pinSS [private]`

pin object

Definition at line 159 of file SPI.h.

6.13 component::StepperMotor Class Reference

`#include <StepperMotor.h>`

Collaboration diagram for component::StepperMotor:

Public Member Functions

- StepperMotor (const mode &ar_mode, const io::Pin &ar_pinCoil1, const io::Pin &ar_pinCoil2, const io::Pin &ar_pinCoil3, const io::Pin &ar_pinCoil4)
- ~StepperMotor ()
- void step (const int16_t a_step, const uint16_t a_speed)

  Turn servo motor On.
- void step (const int16_t a_step, const uint16_t a_speed, const float a_stepAngle)
- void step (const int16_t a_step, const uint16_t a_speed, const uint16_t a_accel, const uint16_t a_decel)
- void stepPulse (const uint8_t a_stepPulse)
- void stepDelay (uint8_t a_stepDelay)
- uint8_t goalReached ()
- void setCurrentPos (uint16_t a_currentPos)
- uint16_t currentPos ()
- uint8_t computeStepDelay (uint16_t a_step, const uint16_t a_speed, const uint16_t a_accel, const uint16_t a_decel)

Public Attributes

- uint16_t m_accelTime

  pulse delay in ms
- uint16_t m_decelTime

  pulse delay in ms
- uint16_t m_constSpeedTime

  pulse delay in ms

Private Attributes

- io::Pin m_pinCoil1

  pin object
- io::Pin m_pinCoil2

  pin object
- io::Pin m_pinCoil3

  pin object
- io::Pin m_pinCoil4

  pin object
- mode stepMode

  steps per revolution
- uint8_t m_goalReached
- uint16_t m_currentPos

  pulse delay in ms

6.13.1 Detailed Description

Definition at line 75 of file StepperMotor.h.

6.13.2 Constructor & Destructor Documentation

6.13.2.1 StepperMotor()

```
component::StepperMotor::StepperMotor (
            const mode & ar_mode,
            const io::Pin & ar_pinCoil1,
            const io::Pin & ar_pinCoil2,
            const io::Pin & ar_pinCoil3,
            const io::Pin & ar_pinCoil4 )
```

Definition at line 8 of file StepperMotor.cpp.

```
00013    : m_pinCoil1(ar_pinCoil1),
00014      m_pinCoil2(ar_pinCoil2),
00015      m_pinCoil3(ar_pinCoil3),
00016      m_pinCoil4(ar_pinCoil4),
00017      stepMode(ar_mode)
00018 {
00019
00020    m_pinCoil1.toOutput();
00021    m_pinCoil2.toOutput();
00022    m_pinCoil3.toOutput();
00023    m_pinCoil4.toOutput();
00024    m_goalReached = 0;
00025    m_currentPos = 0;
00026
00027
00028 }
```

References m_currentPos, m_goalReached, m_pinCoil1, m_pinCoil2, m_pinCoil3, m_pinCoil4, and io::Pin::toOutput().

6.13.2.2 ∼StepperMotor()

```
component::StepperMotor::∼StepperMotor ( )
```

Definition at line 30 of file StepperMotor.cpp.

```
00031 {
00032
00033 }
```

6.13.3 Member Function Documentation

6.13.3.1 computeStepDelay()

```
uint8_t component::StepperMotor::computeStepDelay (
            uint16_t a_step,
            const uint16_t a_speed,
            const uint16_t a_accel,
            const uint16_t a_decel )
```

Definition at line 127 of file StepperMotor.cpp.

```
00131 {
00132
00133
00134    uint32_t l_accelTime= (1000UL*a_speed/a_accel);
00135    uint16_t l_decelTime = (1000UL*a_speed/a_decel);
00136    int16_t l_constSpeedTime=((1000UL*a_step/a_speed)-(l_accelTime/2)-(l_decelTime/2));
00137    static uint32_t l_time=0;
00138    static uint32_t l_speed=0;
00139    static uint64_t l_speed_time_product=0;
```

```
00140    static uint64_t l_current_position=0;
00141
00142
00143
00144
00145
00146
00147
00148    if (l_constSpeedTime<0)
00149    {
00150        l_constSpeedTime=0;
00151        l_accelTime = static_cast<uint32_t>(1000UL*sqrtf(a_step/a_accel));
00152        a_speed=l_accelTime*a_accel/1000UL;
00153        l_decelTime = 1000UL*a_speed/a_decel;
00154
00155    }
00156
00157
00158
00159
00160    if (l_time<=l_accelTime)
00161    {
00162        l_speed=a_accel*l_time;
00163
00164    }
00165    else if ((l_time>l_accelTime) && (l_time<=(l_accelTime+l_constSpeedTime)))
00166    {
00167         l_speed=1000UL*a_speed;
00168
00169    }
00170    else if
    ((l_time>(l_accelTime+l_constSpeedTime))&&(l_time<=l_accelTime+l_constSpeedTime+l_decelTime))
00171    {
00172        l_speed= (1000UL*a_speed)-a_decel*(l_time-l_accelTime-l_constSpeedTime);
00173
00174
00175    }
00176
00177
00178    l_time=l_time+1;
00179
00180
00181    l_speed_time_product = l_speed_time_product+l_speed;
00182
00183    if (l_speed_time_product - l_current_position >= 1000000UL)
00184    {
00185        l_current_position=l_current_position+1000000UL;
00186        return 1;
00187    }
00188    else
00189    {
00190        stepDelay(1);
00191        return 0;
00192    }
00193
00194
00195
00196
00197
00198 }
```

6.13.3.2   currentPos()

```
uint16_t component::StepperMotor::currentPos ( )
```

Definition at line 40 of file StepperMotor.cpp.
```
00041 {
00042     return m_currentPos;
00043 }
```

6.13.3.3 goalReached()

```
uint8_t component::StepperMotor::goalReached ( )
```

Definition at line 403 of file StepperMotor.cpp.

```
00404 {
00405     return m_goalReached;
00406
00407 }
```

6.13.3.4 setCurrentPos()

```
void component::StepperMotor::setCurrentPos (
            uint16_t a_currentPos )
```

Definition at line 35 of file StepperMotor.cpp.

```
00036 {
00037     m_currentPos = a_currentPos;
00038 }
```

6.13.3.5 step() [1/3]

```
void component::StepperMotor::step (
            const int16_t a_step,
            const uint16_t a_speed )
```

Turn servo motor On.

Definition at line 201 of file StepperMotor.cpp.

```
00202 {
00203     static int16_t l_stepNumber = 0;
00204     static uint8_t l_stepDelay_ms = static_cast<uint8_t>(1000UL/a_speed);
00205
00206     if (a_step<=0)
00207     {
00208         if (l_stepNumber== -a_step)
00209         {
00210             m_goalReached = 1;
00211
00212         } else {
00213             l_stepNumber++;
00214             m_currentPos++;
00215         }
00216
00217
00218     } else {
00219
00220         if (l_stepNumber == -a_step)
00221         {
00222             m_goalReached = 1;
00223
00224         } else {
00225             l_stepNumber--;
00226             m_currentPos--;
00227
00228         }
00229     }
00230
00231
00232     if (m_goalReached == 0)
00233     {
00234
00235         switch (stepMode)
00236         {
00237             case mode::fullStep:
```

```
00238                    {
00239                        // equivalent to l_stepNumber % 4
00240                        // 1 3 5 7 <->
00241                        stepPulse(2*(l_stepNumber & 3)+1);
00242                        break;
00243                    }
00244
00245                case mode::halfStep:
00246                    {
00247                        // equivalent to l_stepNumber % 8
00248                        // 0 1 2 3 4 5 6 7 <->
00249                        stepPulse(l_stepNumber & 7);
00250                        break;
00251                    }
00252            }
00253
00254            stepDelay(l_stepDelay_ms);
00255
00256    }
00257 }
```

References component::fullStep, and component::halfStep.

6.13.3.6 step() [2/3]

```
void component::StepperMotor::step (
            const int16_t a_step,
            const uint16_t a_speed,
            const float a_stepAngle )
```

Definition at line 259 of file StepperMotor.cpp.

```
00260 {
00261     static int16_t l_stepNumber = 0;
00262     static uint8_t l_stepDelay_ms = static_cast<uint8_t>(1000UL*a_stepAngle/a_speed);
00263
00264     if (a_step<=0)
00265     {
00266         if (l_stepNumber== -a_step)
00267         {
00268             m_goalReached = 1;
00269
00270         } else {
00271             l_stepNumber++;
00272             m_currentPos++;
00273         }
00274
00275
00276     } else {
00277
00278         if (l_stepNumber == -a_step)
00279         {
00280             m_goalReached = 1;
00281
00282         } else {
00283             l_stepNumber--;
00284             m_currentPos--;
00285
00286         }
00287     }
00288
00289
00290     if (m_goalReached == 0)
00291     {
00292
00293         switch (stepMode)
00294         {
00295            case mode::fullStep:
00296                {
00297                    // equivalent to l_stepNumber % 4
00298                    // 1 3 5 7 <->
00299                    stepPulse(2*(l_stepNumber & 3)+1);
00300                    break;
00301                }
00302
00303            case mode::halfStep:
00304                {
```

```
00305                    // equivalent to l_stepNumber % 8
00306                    // 0 1 2 3 4 5 6 7 <->
00307                    stepPulse(l_stepNumber & 7);
00308                    break;
00309                }
00310            }
00311
00312            stepDelay(l_stepDelay_ms);
00313
00314        }
00315
00316
00317 }
```

References component::fullStep, and component::halfStep.

6.13.3.7 step() [3/3]

```
void component::StepperMotor::step (
            const int16_t a_step,
            const uint16_t a_speed,
            const uint16_t a_accel,
            const uint16_t a_decel )
```

Definition at line 47 of file StepperMotor.cpp.

```
00051 {
00052     static int16_t l_stepNumber = 0;
00053     uint8_t l_stepDelay_ms = 0;
00054     uint16_t l_step=0;
00055
00056     if (a_step<=0)
00057     {
00058        l_step = -a_step;
00059     } else
00060     {
00061         l_step = a_step;
00062     }
00063
00064     l_stepDelay_ms = computeStepDelay(l_step,
00065                                      a_speed,
00066                                      a_accel,
00067                                      a_decel);
00068
00069 if (l_stepDelay_ms>0)
00070 {
00071
00072     if (a_step<=0)
00073     {
00074         if (l_stepNumber== -a_step)
00075         {
00076             m_goalReached = 1;
00077
00078         } else {
00079             l_stepNumber++;
00080             m_currentPos++;
00081         }
00082
00083
00084     } else {
00085
00086         if (l_stepNumber == -a_step)
00087         {
00088             m_goalReached = 1;
00089
00090         } else {
00091             l_stepNumber--;
00092             m_currentPos--;
00093
00094         }
00095     }
00096
00097
00098     if (m_goalReached == 0)
00099     {
00100
00101         switch (stepMode)
```

```
00102             {
00103                 case mode::fullStep:
00104                 {
00105                     // equivalent to l_stepNumber % 4
00106                     // 1 3 5 7 <->
00107                     stepPulse(2*(l_stepNumber & 3)+1);
00108                     break;
00109                 }
00110
00111                 case mode::halfStep:
00112                 {
00113                     // equivalent to l_stepNumber % 8
00114                     // 0 1 2 3 4 5 6 7 <->
00115                     stepPulse(l_stepNumber & 7);
00116                     break;
00117                 }
00118             }
00119
00120             stepDelay(l_stepDelay_ms);
00121
00122     }
00123 }
00124
00125 }
```

References component::fullStep, and component::halfStep.

6.13.3.8   stepDelay()

```
void component::StepperMotor::stepDelay (
            uint8_t a_stepDelay )
```

Definition at line 395 of file StepperMotor.cpp.
```
00396 {
00397     while(a_stepDelay--)
00398     {
00399         _delay_ms(1);
00400     }
00401 }
```

6.13.3.9   stepPulse()

```
void component::StepperMotor::stepPulse (
            const uint8_t a_stepPulse )
```

Definition at line 320 of file StepperMotor.cpp.
```
00321 {
00322
00323     switch (a_stepPulse) {
00324       case 0:    // 1000
00325       {
00326         m_pinCoil1.setHigh();
00327         m_pinCoil2.setLow();
00328         m_pinCoil3.setLow();
00329         m_pinCoil4.setLow();
00330         break;
00331       }
00332       case 1:    // 1100
00333       {
00334         m_pinCoil1.setHigh();
00335         m_pinCoil2.setHigh();
00336         m_pinCoil3.setLow();
00337         m_pinCoil4.setLow();
00338         break;
00339       }
00340       case 2:    //0100
00341       {
00342         m_pinCoil1.setLow();
```

```
00343          m_pinCoil2.setHigh();
00344          m_pinCoil3.setLow();
00345          m_pinCoil4.setLow();
00346          break;
00347        }
00348        case 3:    //0110
00349        {
00350          m_pinCoil1.setLow();
00351          m_pinCoil2.setHigh();
00352          m_pinCoil3.setHigh();
00353          m_pinCoil4.setLow();
00354          break;
00355        }
00356        case 4:    //0010
00357        {
00358          m_pinCoil1.setLow();
00359          m_pinCoil2.setLow();
00360          m_pinCoil3.setHigh();
00361          m_pinCoil4.setLow();
00362          break;
00363        }
00364        case 5:    //0011
00365        {
00366          m_pinCoil1.setLow();
00367          m_pinCoil2.setLow();
00368          m_pinCoil3.setHigh();
00369          m_pinCoil4.setHigh();
00370          break;
00371        }
00372        case 6:    //0001
00373        {
00374          m_pinCoil1.setLow();
00375          m_pinCoil2.setLow();
00376          m_pinCoil3.setLow();
00377          m_pinCoil4.setHigh();
00378          break;
00379        }
00380        case 7:    //1001
00381        {
00382          m_pinCoil1.setHigh();
00383          m_pinCoil2.setLow();
00384          m_pinCoil3.setLow();
00385          m_pinCoil4.setHigh();
00386          break;
00387        }
00388      }
00389
00390
00391 }
```

6.13.4 Member Data Documentation

6.13.4.1 m_accelTime

```
uint16_t component::StepperMotor::m_accelTime
```

pulse delay in ms

Definition at line 118 of file StepperMotor.h.

6.13.4.2 m_constSpeedTime

```
uint16_t component::StepperMotor::m_constSpeedTime
```

pulse delay in ms

Definition at line 120 of file StepperMotor.h.

6.13.4.3 m_currentPos

`uint16_t component::StepperMotor::m_currentPos [private]`

pulse delay in ms

Definition at line 139 of file StepperMotor.h.

Referenced by StepperMotor().

6.13.4.4 m_decelTime

`uint16_t component::StepperMotor::m_decelTime`

pulse delay in ms

Definition at line 119 of file StepperMotor.h.

6.13.4.5 m_goalReached

`uint8_t component::StepperMotor::m_goalReached [private]`

Definition at line 138 of file StepperMotor.h.

Referenced by StepperMotor().

6.13.4.6 m_pinCoil1

`io::Pin component::StepperMotor::m_pinCoil1 [private]`

pin object

Definition at line 132 of file StepperMotor.h.

Referenced by StepperMotor().

6.13.4.7 m_pinCoil2

`io::Pin component::StepperMotor::m_pinCoil2 [private]`

pin object

Definition at line 133 of file StepperMotor.h.

Referenced by StepperMotor().

6.13.4.8 m_pinCoil3

io::Pin component::StepperMotor::m_pinCoil3 [private]

pin object

Definition at line 134 of file StepperMotor.h.

Referenced by StepperMotor().

6.13.4.9 m_pinCoil4

io::Pin component::StepperMotor::m_pinCoil4 [private]

pin object

Definition at line 135 of file StepperMotor.h.

Referenced by StepperMotor().

6.13.4.10 stepMode

mode component::StepperMotor::stepMode [private]

steps per revolution

Definition at line 137 of file StepperMotor.h.

6.14 core::TimerCounter Class Reference

#include <TimerCounter.h>

Inheritance diagram for core::TimerCounter:

Public Member Functions

- virtual void selectOperationMode (const operationMode &ar_operationMode)=0
- virtual void start ()=0
- virtual void stop ()=0
- virtual void selectClockSource (const clockSource &ar_clockSource)=0
- virtual void selectCompareOutputMode (const channel &ar_channel, const compareOutputMode &ar_↵ compareOutputMode)=0
- virtual void setCounter (const uint16_t &ar_dataBuffer)=0
- virtual uint16_t getCounter () const =0
- virtual void setOutputCompareRegister (const channel &ar_channel, const uint16_t &ar_dataBuffer)=0
- virtual uint16_t getOutputCompareRegister (const channel &ar_channel) const =0
- virtual void enableOutputCompareMatchInterrupt (const channel &ar_channel, const uint8_t a_enable)=0
- virtual void enableOverflowInterrupt (const uint8_t a_enable)=0
- virtual uint16_t getClockPrescaler ()=0

6.14.1 Detailed Description

Definition at line 517 of file TimerCounter.h.

6.14.2 Member Function Documentation

6.14.2.1 enableOutputCompareMatchInterrupt()

```
virtual void core::TimerCounter::enableOutputCompareMatchInterrupt (
            const channel & ar_channel,
            const uint8_t a_enable ) [pure virtual]
```

Implemented in core::TimerCounter1, core::TimerCounter0, and core::TimerCounter2.

6.14.2.2 enableOverflowInterrupt()

```
virtual void core::TimerCounter::enableOverflowInterrupt (
            const uint8_t a_enable ) [pure virtual]
```

Implemented in core::TimerCounter1, core::TimerCounter0, and core::TimerCounter2.

6.14.2.3 getClockPrescaler()

```
virtual uint16_t core::TimerCounter::getClockPrescaler ( ) [pure virtual]
```

Implemented in core::TimerCounter1, core::TimerCounter0, and core::TimerCounter2.

6.14.2.4 getCounter()

```
virtual uint16_t core::TimerCounter::getCounter ( ) const  [pure virtual]
```

Implemented in core::TimerCounter1, core::TimerCounter0, and core::TimerCounter2.

6.14.2.5 getOutputCompareRegister()

```
virtual uint16_t core::TimerCounter::getOutputCompareRegister (
            const channel & ar_channel ) const  [pure virtual]
```

Implemented in core::TimerCounter1, core::TimerCounter0, and core::TimerCounter2.

6.14.2.6 selectClockSource()

```
virtual void core::TimerCounter::selectClockSource (
            const clockSource & ar_clockSource )  [pure virtual]
```

Implemented in core::TimerCounter0, core::TimerCounter1, and core::TimerCounter2.

6.14.2.7 selectCompareOutputMode()

```
virtual void core::TimerCounter::selectCompareOutputMode (
            const channel & ar_channel,
            const compareOutputMode & ar_compareOutputMode )  [pure virtual]
```

Implemented in core::TimerCounter1, core::TimerCounter0, and core::TimerCounter2.

6.14.2.8 selectOperationMode()

```
virtual void core::TimerCounter::selectOperationMode (
            const operationMode & ar_operationMode )  [pure virtual]
```

Implemented in core::TimerCounter0, core::TimerCounter1, and core::TimerCounter2.

6.14.2.9 setCounter()

```
virtual void core::TimerCounter::setCounter (
            const uint16_t & ar_dataBuffer )  [pure virtual]
```

Implemented in core::TimerCounter1, core::TimerCounter0, and core::TimerCounter2.

6.14.2.10 setOutputCompareRegister()

```
virtual void core::TimerCounter::setOutputCompareRegister (
          const channel & ar_channel,
          const uint16_t & ar_dataBuffer ) [pure virtual]
```

Implemented in core::TimerCounter1, core::TimerCounter0, and core::TimerCounter2.

6.14.2.11 start()

```
virtual void core::TimerCounter::start ( ) [pure virtual]
```

Implemented in core::TimerCounter0, core::TimerCounter1, and core::TimerCounter2.

6.14.2.12 stop()

```
virtual void core::TimerCounter::stop ( ) [pure virtual]
```

Implemented in core::TimerCounter0, core::TimerCounter1, and core::TimerCounter2.

6.15 core::TimerCounter0 Class Reference

```
#include <TimerCounter0.h>
```

Inheritance diagram for core::TimerCounter0:

Collaboration diagram for core::TimerCounter0:

```
┌─────────────────────┐
│  core::TimerCounter │
└─────────────────────┘
           ▲
           │
┌─────────────────────┐
│  core::TimerCounter0 │
└─────────────────────┘
```

Public Member Functions

- void selectOperationMode (const operationMode &ar_operationMode) override
- void start () override
- void stop () override
- void selectClockSource (const clockSource &ar_clockSource) override
- void selectCompareOutputMode (const channel &ar_channel, const compareOutputMode &ar_compare↩
  OutputMode) override
- void setCounter (const uint16_t &ar_dataBuffer) override
- uint16_t getCounter () const override
- void setOutputCompareRegister (const channel &ar_channel, const uint16_t &ar_dataBuffer) override
- uint16_t getOutputCompareRegister (const channel &ar_channel) const override
- void enableOutputCompareMatchInterrupt (const channel &ar_channel, const uint8_t a_enable) override
- void enableOverflowInterrupt (const uint8_t a_enable) override
- uint16_t getClockPrescaler () override

Static Public Member Functions

- static TimerCounter0 & getInstance (const channel &ar_channel=channel::A, const operationMode &ar↩
  _operationMode=operationMode::normal, const clockSource &ar_clockSource=clockSource::noClock, const
  compareOutputMode &ar_compareOutputMode=compareOutputMode::normal)
- static void outputCompareMatchAServiceRoutine () __asm__(STR(TIMER0_COM_CHANNEL_A_INTERRUPT))
  __attribute__((__signal__
- static void outputCompareMatchBServiceRoutine () __asm__(STR(TIMER0_COM_CHANNEL_B_INTERRUPT))
  __attribute__((__signal__
- static void overflowServiceRoutine () __asm__(STR(TIMER0_OVERFLOW_INTERRUPT)) __attribute__((↩
  __signal__

Public Attributes

- static void __used__
- static void __externally_visible__

Private Member Functions

- TimerCounter0 (const channel &ar_channel, const operationMode &ar_operationMode, const clockSource &ar_clockSource, const compareOutputMode &ar_compareOutputMode)
- ∼TimerCounter0 ()
- TimerCounter0 (const TimerCounter0 &)

    Overried Copy constructor.
- const TimerCounter0 & operator= (const TimerCounter0 &)

    Override assign operator.

Private Attributes

- uint16_t m_clockPrescaler
- uint8_t m_clockSource

6.15.1 Detailed Description

Definition at line 279 of file TimerCounter0.h.

6.15.2 Constructor & Destructor Documentation

6.15.2.1 TimerCounter0() [1/2]

```
core::TimerCounter0::TimerCounter0 (
            const channel & ar_channel,
            const operationMode & ar_operationMode,
            const clockSource & ar_clockSource,
            const compareOutputMode & ar_compareOutputMode )  [private]
```

Definition at line 20 of file TimerCounter0.cpp.

```
00024 {
00025     core::MCU::enableTimerCounter0(1);
00026     stop();
00027     selectOperationMode(ar_operationMode);
00028     selectClockSource(ar_clockSource);
00029     selectCompareOutputMode(ar_channel,ar_compareOutputMode);
00030
00031
00032
00033 }
```

References core::MCU::enableTimerCounter0().

6.15.2.2 ∼TimerCounter0()

```
core::TimerCounter0::∼TimerCounter0 ( )  [private]
```

Definition at line 34 of file TimerCounter0.cpp.

```
00035 {
00036
00037 }
```

6.15.2.3 TimerCounter0() [2/2]

```
core::TimerCounter0::TimerCounter0 (
            const TimerCounter0 &  )  [private]
```

Overried Copy constructor.

6.15.3 Member Function Documentation

6.15.3.1 enableOutputCompareMatchInterrupt()

```
void core::TimerCounter0::enableOutputCompareMatchInterrupt (
            const channel & ar_channel,
            const uint8_t a_enable )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 216 of file TimerCounter0.cpp.

```
00217 {
00218     switch (ar_channel)
00219     {
00220         case core::channel::A:
00221         {
00222             if (a_enable) {
00223
00224                 TIMER0_ENABLE_COM_CHANNEL_A_INTERRUPT;
00225
00226             } else {
00227
00228                 TIMER0_DISABLE_COM_CHANNEL_A_INTERRUPT;
00229             }
00230             break;
00231         }
00232         case core::channel::B:
00233         {
00234             if (a_enable) {
00235
00236                 TIMER0_ENABLE_COM_CHANNEL_B_INTERRUPT;
00237
00238             } else {
00239
00240                 TIMER0_DISABLE_COM_CHANNEL_B_INTERRUPT;
00241
00242             }
00243             break;
00244         }
00245     }
00246
00247 }
```

References core::A, core::B, TIMER0_DISABLE_COM_CHANNEL_A_INTERRUPT, TIMER0_DISABLE_COM_CHANNEL_B_INTER TIMER0_ENABLE_COM_CHANNEL_A_INTERRUPT, and TIMER0_ENABLE_COM_CHANNEL_B_INTERRUPT.

6.15.3.2 enableOverflowInterrupt()

```
void core::TimerCounter0::enableOverflowInterrupt (
            const uint8_t a_enable )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 251 of file TimerCounter0.cpp.

```
00252 {
00253
00254     if (a_enable) {
00255
00256         TIMER0_ENABLE_OVERFLOW_INTERRUPT;
00257
00258     } else {
00259
00260         TIMER0_DISABLE_OVERFLOW_INTERRUPT;
00261     }
00262
00263 }
```

References TIMER0_DISABLE_OVERFLOW_INTERRUPT, and TIMER0_ENABLE_OVERFLOW_INTERRUPT.

6.15.3.3 getClockPrescaler()

```
uint16_t core::TimerCounter0::getClockPrescaler ( )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 141 of file TimerCounter0.cpp.

```
00142 {
00143     return m_clockPrescaler;
00144 }
```

6.15.3.4 getCounter()

```
uint16_t core::TimerCounter0::getCounter ( ) const  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 176 of file TimerCounter0.cpp.

```
00177 {
00178     return TCNT0;
00179 }
```

6.15.3.5 getInstance()

```
core::TimerCounter0 & core::TimerCounter0::getInstance (
            const channel & ar_channel = channel::A,
            const operationMode & ar_operationMode = operationMode::normal,
            const clockSource & ar_clockSource = clockSource::noClock,
            const compareOutputMode & ar_compareOutputMode = compareOutputMode::normal )
[static]
```

Definition at line 5 of file TimerCounter0.cpp.

```
00009 {
00010     static TimerCounter0 l_instance(ar_channel,
00011                                    ar_operationMode,
00012                                    ar_clockSource,
00013                                    ar_compareOutputMode);
00014
00015     return l_instance;
00016
00017
00018 }
```

6.15.3.6 getOutputCompareRegister()

```
uint16_t core::TimerCounter0::getOutputCompareRegister (
            const channel & ar_channel ) const  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 201 of file TimerCounter0.cpp.

```
00202 {
00203     switch (ar_channel)
00204     {
00205         case core::channel::A:
00206         {
00207             return OCR0A;
00208         }
00209         case core::channel::B:
00210         {
00211             return OCR0B;
00212         }
00213     }
00214 }
```

References core::A, and core::B.

6.15.3.7 operator=()

```
const TimerCounter0& core::TimerCounter0::operator= (
            const TimerCounter0 & )  [private]
```

Override assign operator.

6.15.3.8 outputCompareMatchAServiceRoutine()

```
static void core::TimerCounter0::outputCompareMatchAServiceRoutine ( )  [static]
```

6.15.3.9   outputCompareMatchBServiceRoutine()

```
static void core::TimerCounter0::outputCompareMatchBServiceRoutine ( )  [static]
```

6.15.3.10   overflowServiceRoutine()

```
static void core::TimerCounter0::overflowServiceRoutine ( )  [static]
```

6.15.3.11   selectClockSource()

```
void core::TimerCounter0::selectClockSource (
            const clockSource & ar_clockSource )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 39 of file TimerCounter0.cpp.

```
00040 {
00041     switch (ar_clockSource)
00042     {
00043         case core::clockSource::noClock:
00044         {
00045             m_clockPrescaler=0;
00046             m_clockSource=0;
00047             break;
00048         }
00049         case core::clockSource::PS_1:
00050         {
00051             m_clockPrescaler=1;
00052             m_clockSource=1;
00053             break;
00054         }
00055         case core::clockSource::PS_8:
00056         {
00057             m_clockPrescaler=8;
00058             m_clockSource=2;
00059             break;
00060         }
00061         case core::clockSource::PS_64:
00062         {
00063             m_clockPrescaler=64;
00064             m_clockSource=3;
00065             break;
00066         }
00067         case core::clockSource::PS_256:
00068         {
00069             m_clockPrescaler=256;
00070             m_clockSource=4;
00071             break;
00072         }
00073         case core::clockSource::PS_1024:
00074         {
00075             m_clockPrescaler=1024;
00076             m_clockSource=5;
00077             break;
00078         }
00079         case core::clockSource::extern_Clock_T0_Falling_Edge:
00080         {
00081             m_clockPrescaler=0;
00082             m_clockSource=6;
00083             break;
00084         }
00085         case core::clockSource::extern_Clock_T0_Rising_Edge:
00086         {
00087             m_clockPrescaler=0;
00088             m_clockSource=7;
00089             break;
00090         }
00091     }
```

```
00092
00093
00094 }
```

References core::extern_Clock_T0_Falling_Edge, core::extern_Clock_T0_Rising_Edge, core::noClock, core::PS_1,
core::PS_1024, core::PS_256, core::PS_64, and core::PS_8.

6.15.3.12 selectCompareOutputMode()

```
void core::TimerCounter0::selectCompareOutputMode (
            const channel & ar_channel,
            const compareOutputMode & ar_compareOutputMode )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 152 of file TimerCounter0.cpp.

```
00153 {
00154     switch (ar_channel)
00155     {
00156         case core::channel::A:
00157         {
00158             TIMER0_SELECT_COM_CHANNEL_A(static_cast<uint8_t>(ar_compareOutputMode));
00159             break;
00160         }
00161         case core::channel::B:
00162         {
00163             TIMER0_SELECT_COM_CHANNEL_B(static_cast<uint8_t>(ar_compareOutputMode));
00164             break;
00165         }
00166     }
00167 }
```

References core::A, core::B, TIMER0_SELECT_COM_CHANNEL_A, and TIMER0_SELECT_COM_CHANNEL_B.

6.15.3.13 selectOperationMode()

```
void core::TimerCounter0::selectOperationMode (
            const operationMode & ar_operationMode )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 96 of file TimerCounter0.cpp.

```
00097 {
00098     switch (ar_operationMode)
00099     {
00100         case core::operationMode::normal:
00101         {
00102             TIMER0_SELECT_OPERATION_MODE(0);
00103             break;
00104         }
00105         case core::operationMode::PWM_PC:
00106         {
00107             TIMER0_SELECT_OPERATION_MODE(1);
00108             break;
00109         }
00110         case core::operationMode::CTC_OCR:
00111         {
00112             TIMER0_SELECT_OPERATION_MODE(2);
00113             break;
00114         }
00115         case core::operationMode::fast_PWM:
00116         {
00117             TIMER0_SELECT_OPERATION_MODE(3);
00118             break;
```

```
00119          }
00120          case core::operationMode::PWM_PC_OCR:
00121          {
00122              TIMER0_SELECT_OPERATION_MODE(5);
00123              break;
00124          }
00125          case core::operationMode::fast_PWM_OCR:
00126          {
00127              TIMER0_SELECT_OPERATION_MODE(7);
00128              break;
00129          }
00130
00131      }
00132
00133 }
```

References core::CTC_OCR, core::fast_PWM, core::fast_PWM_OCR, core::normal, core::PWM_PC, core::PWM_PC_OCR, and TIMER0_SELECT_OPERATION_MODE.

6.15.3.14 setCounter()

```
void core::TimerCounter0::setCounter (
            const uint16_t & ar_dataBuffer )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 171 of file TimerCounter0.cpp.
```
00172 {
00173      TCNT0 = static_cast<uint8_t>(ar_dataBuffer);
00174 }
```

6.15.3.15 setOutputCompareRegister()

```
void core::TimerCounter0::setOutputCompareRegister (
            const channel & ar_channel,
            const uint16_t & ar_dataBuffer )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 181 of file TimerCounter0.cpp.
```
00182 {
00183      switch (ar_channel)
00184      {
00185          case core::channel::A:
00186          {
00187              OCR0A = static_cast<uint8_t>(ar_dataBuffer);
00188              break;
00189          }
00190          case core::channel::B:
00191          {
00192              OCR0B = static_cast<uint8_t>(ar_dataBuffer);
00193              break;
00194          }
00195
00196      }
00197 }
```

References core::A, and core::B.

6.15.3.16 start()

```
void core::TimerCounter0::start ( )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 136 of file TimerCounter0.cpp.

```
00137 {
00138     TIMER0_SELECT_CLOCK_SOURCE(m_clockSource);
00139 }
```

References TIMER0_SELECT_CLOCK_SOURCE.

6.15.3.17 stop()

```
void core::TimerCounter0::stop ( )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 146 of file TimerCounter0.cpp.

```
00147 {
00148     TIMER0_STOP;
00149 }
```

References TIMER0_STOP.

6.15.4 Member Data Documentation

6.15.4.1 __externally_visible__

```
static void core::TimerCounter0::__externally_visible__
```

Definition at line 313 of file TimerCounter0.h.

6.15.4.2 __used__

```
static void core::TimerCounter0::__used__
```

Definition at line 313 of file TimerCounter0.h.

6.15.4.3 m_clockPrescaler

`uint16_t core::TimerCounter0::m_clockPrescaler [private]`

Definition at line 340 of file TimerCounter0.h.

6.15.4.4 m_clockSource

`uint8_t core::TimerCounter0::m_clockSource [private]`

Definition at line 342 of file TimerCounter0.h.

6.16 core::TimerCounter1 Class Reference

`#include <TimerCounter1.h>`

Inheritance diagram for core::TimerCounter1:

Collaboration diagram for core::TimerCounter1:

Public Member Functions

- void selectOperationMode (const operationMode &ar_operationMode) override
- void start () override
- void stop () override
- void selectClockSource (const clockSource &ar_clockSource) override
- void selectCompareOutputMode (const channel &ar_channel, const compareOutputMode &ar_compare↩
OutputMode) override
- void setCounter (const uint16_t &ar_dataBuffer) override
- uint16_t getCounter () const override
- void setOutputCompareRegister (const channel &ar_channel, const uint16_t &ar_dataBuffer) override
- uint16_t getOutputCompareRegister (const channel &ar_channel) const override
- void setInputCaptureRegister (const uint16_t &ar_dataBuffer)
- uint16_t getInputCaptureRegister () const
- void enableOutputCompareMatchInterrupt (const channel &ar_channel, const uint8_t a_enable) override
- void enableOverflowInterrupt (const uint8_t a_enable) override
- void enableInputCaptureInterrupt (const uint8_t a_enable)
- uint16_t getClockPrescaler () override

Static Public Member Functions

- static TimerCounter1 & getInstance (const channel &ar_channel=channel::A, const operationMode &ar↩
_operationMode=operationMode::normal, const clockSource &ar_clockSource=clockSource::noClock, const
compareOutputMode &ar_compareOutputMode=compareOutputMode::normal)
- static void outputCompareMatchAServiceRoutine () __asm__(STR(TIMER1_COM_CHANNEL_A_INTERRUPT))
__attribute__((__signal__
- static void outputCompareMatchBServiceRoutine () __asm__(STR(TIMER1_COM_CHANNEL_B_INTERRUPT))
__attribute__((__signal__
- static void overflowServiceRoutine () __asm__(STR(TIMER1_OVERFLOW_INTERRUPT)) __attribute__((↩
__signal__
- static void inputCaptureServiceRoutine () __asm__(STR(TIMER1_INPUT_CAPTURE_INTERRUPT)) __↩
attribute__((__signal__

Public Attributes

- static void __used__
- static void __externally_visible__

Private Member Functions

- TimerCounter1 (const channel &ar_channel, const operationMode &ar_operationMode, const clockSource
&ar_clockSource, const compareOutputMode &ar_compareOutputMode)
- ∼TimerCounter1 ()
- TimerCounter1 (const TimerCounter1 &)

    Overried Copy constructor.
- const TimerCounter1 & operator= (const TimerCounter1 &)

    Override assign operator.

Private Attributes

- uint16_t m_clockPrescaler
- uint8_t m_clockSource

6.16.1 Detailed Description

Definition at line 279 of file TimerCounter1.h.

6.16.2 Constructor & Destructor Documentation

6.16.2.1 TimerCounter1() [1/2]

```
core::TimerCounter1::TimerCounter1 (
            const channel & ar_channel,
            const operationMode & ar_operationMode,
            const clockSource & ar_clockSource,
            const compareOutputMode & ar_compareOutputMode )  [private]
```

Definition at line 20 of file TimerCounter1.cpp.
```
00024 {
00025     core::MCU::enableTimerCounter1(1);
00026     stop();
00027     selectOperationMode(ar_operationMode);
00028     selectClockSource(ar_clockSource);
00029     selectCompareOutputMode(ar_channel,ar_compareOutputMode);
00030
00031
00032 }
```

References core::MCU::enableTimerCounter1().

6.16.2.2 ∼TimerCounter1()

```
core::TimerCounter1::∼TimerCounter1 ( )  [private]
```

Definition at line 33 of file TimerCounter1.cpp.
```
00034 {
00035
00036 }
```

6.16.2.3 TimerCounter1() [2/2]

```
core::TimerCounter1::TimerCounter1 (
            const TimerCounter1 & )  [private]
```

Overried Copy constructor.

6.16.3 Member Function Documentation

6.16.3.1 enableInputCaptureInterrupt()

```
void core::TimerCounter1::enableInputCaptureInterrupt (
            const uint8_t a_enable )
```

Definition at line 309 of file TimerCounter1.cpp.

```
00310 {
00311     if (a_enable) {
00312
00313         TIMER1_ENABLE_INPUT_CAPTURE_INTERRUPT;
00314
00315     } else {
00316
00317         TIMER1_DISABLE_INPUT_CAPTURE_INTERRUPT;
00318     }
00319 }
```

References TIMER1_DISABLE_INPUT_CAPTURE_INTERRUPT, and TIMER1_ENABLE_INPUT_CAPTURE_INTERRUPT.

6.16.3.2 enableOutputCompareMatchInterrupt()

```
void core::TimerCounter1::enableOutputCompareMatchInterrupt (
            const channel & ar_channel,
            const uint8_t a_enable )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 260 of file TimerCounter1.cpp.

```
00261 {
00262     switch (ar_channel)
00263     {
00264         case core::channel::A:
00265         {
00266             if (a_enable) {
00267
00268                 TIMER1_ENABLE_COM_CHANNEL_A_INTERRUPT;
00269
00270             } else {
00271
00272                 TIMER1_DISABLE_COM_CHANNEL_A_INTERRUPT;
00273             }
00274             break;
00275         }
00276         case core::channel::B:
00277         {
00278             if (a_enable) {
00279
00280                 TIMER1_ENABLE_COM_CHANNEL_B_INTERRUPT;
00281
00282             } else {
00283
00284                 TIMER1_DISABLE_COM_CHANNEL_B_INTERRUPT;
00285
00286             }
00287             break;
00288         }
00289     }
00290
00291 }
```

References core::A, core::B, TIMER1_DISABLE_COM_CHANNEL_A_INTERRUPT, TIMER1_DISABLE_COM_CHANNEL_B_INTER
TIMER1_ENABLE_COM_CHANNEL_A_INTERRUPT, and TIMER1_ENABLE_COM_CHANNEL_B_INTERRUPT.

6.16.3.3 enableOverflowInterrupt()

```
void core::TimerCounter1::enableOverflowInterrupt (
            const uint8_t a_enable ) [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 295 of file TimerCounter1.cpp.

```
00296 {
00297
00298     if (a_enable) {
00299
00300         TIMER1_ENABLE_OVERFLOW_INTERRUPT;
00301
00302     } else {
00303
00304         TIMER1_DISABLE_OVERFLOW_INTERRUPT;
00305     }
00306
00307 }
```

References TIMER1_DISABLE_OVERFLOW_INTERRUPT, and TIMER1_ENABLE_OVERFLOW_INTERRUPT.

6.16.3.4 getClockPrescaler()

```
uint16_t core::TimerCounter1::getClockPrescaler ( )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 186 of file TimerCounter1.cpp.

```
00187 {
00188     return m_clockPrescaler;
00189 }
```

Referenced by component::ServoMotor::connect(), and component::ServoMotor::rotate().

6.16.3.5 getCounter()

```
uint16_t core::TimerCounter1::getCounter ( ) const  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 221 of file TimerCounter1.cpp.

```
00222 {
00223     return TCNT1;
00224 }
```

6.16.3.6 getInputCaptureRegister()

```
uint16_t core::TimerCounter1::getInputCaptureRegister ( ) const
```

Definition at line 327 of file TimerCounter1.cpp.

```
00328 {
00329     return ICR1;
00330 }
```

6.16.3.7 getInstance()

```
core::TimerCounter1 & core::TimerCounter1::getInstance (
            const channel & ar_channel = channel::A,
            const operationMode & ar_operationMode = operationMode::normal,
            const clockSource & ar_clockSource = clockSource::noClock,
            const compareOutputMode & ar_compareOutputMode = compareOutputMode::normal )
[static]
```

Definition at line 5 of file TimerCounter1.cpp.

```
00009 {
00010     static TimerCounter1 l_instance(ar_channel,
00011                                    ar_operationMode,
00012                                    ar_clockSource,
00013                                    ar_compareOutputMode);
00014
00015     return l_instance;
00016
00017
00018 }
```

6.16.3.8 getOutputCompareRegister()

```
uint16_t core::TimerCounter1::getOutputCompareRegister (
            const channel & ar_channel ) const  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 245 of file TimerCounter1.cpp.

```
00246 {
00247     switch (ar_channel)
00248     {
00249         case core::channel::A:
00250         {
00251             return OCR1A;
00252         }
00253         case core::channel::B:
00254         {
00255             return OCR1B;
00256         }
00257     }
00258 }
```

References core::A, and core::B.

6.16.3.9 inputCaptureServiceRoutine()

```
static void core::TimerCounter1::inputCaptureServiceRoutine ( )  [static]
```

6.16.3.10 operator=()

```
const TimerCounter1& core::TimerCounter1::operator= (
            const TimerCounter1 & )  [private]
```

Override assign operator.

6.16.3.11 outputCompareMatchAServiceRoutine()

```
static void core::TimerCounter1::outputCompareMatchAServiceRoutine ( )  [static]
```

6.16.3.12 outputCompareMatchBServiceRoutine()

```
static void core::TimerCounter1::outputCompareMatchBServiceRoutine ( )  [static]
```

6.16.3.13 overflowServiceRoutine()

```
static void core::TimerCounter1::overflowServiceRoutine ( )  [static]
```

6.16.3.14 selectClockSource()

```
void core::TimerCounter1::selectClockSource (
            const clockSource & ar_clockSource )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 38 of file TimerCounter1.cpp.

```
00039 {
00040     switch (ar_clockSource)
00041     {
00042         case core::clockSource::noClock:
00043         {
00044             m_clockPrescaler=0;
00045             m_clockSource=0;
00046             break;
00047         }
00048         case core::clockSource::PS_1:
00049         {
00050             m_clockPrescaler=1;
00051             m_clockSource=1;
00052             break;
00053         }
00054         case core::clockSource::PS_8:
00055         {
00056             m_clockPrescaler=8;
00057             m_clockSource=2;
00058             break;
00059         }
00060         case core::clockSource::PS_64:
00061         {
00062             m_clockPrescaler=64;
00063             m_clockSource=3;
00064             break;
00065         }
00066         case core::clockSource::PS_256:
00067         {
00068             m_clockPrescaler=256;
00069             m_clockSource=4;
00070             break;
00071         }
00072         case core::clockSource::PS_1024:
00073         {
00074             m_clockPrescaler=1024;
00075             m_clockSource=5;
00076             break;
00077         }
00078         case core::clockSource::extern_Clock_T0_Falling_Edge:
```

```
00079           {
00080                 m_clockPrescaler=0;
00081                 m_clockSource=6;
00082                 break;
00083           }
00084           case core::clockSource::extern_Clock_T0_Rising_Edge:
00085           {
00086                 m_clockPrescaler=0;
00087                 m_clockSource=7;
00088                 break;
00089           }
00090      }
00091
00092
00093 }
```

References core::extern_Clock_T0_Falling_Edge, core::extern_Clock_T0_Rising_Edge, core::noClock, core::PS_1, core::PS_1024, core::PS_256, core::PS_64, and core::PS_8.

6.16.3.15 selectCompareOutputMode()

```
void core::TimerCounter1::selectCompareOutputMode (
              const channel & ar_channel,
              const compareOutputMode & ar_compareOutputMode )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 197 of file TimerCounter1.cpp.

```
00198 {
00199      switch (ar_channel)
00200      {
00201           case core::channel::A:
00202           {
00203                 TIMER1_SELECT_COM_CHANNEL_A(static_cast<uint8_t>(ar_compareOutputMode));
00204                 break;
00205           }
00206           case core::channel::B:
00207           {
00208                 TIMER1_SELECT_COM_CHANNEL_B(static_cast<uint8_t>(ar_compareOutputMode));
00209                 break;
00210           }
00211      }
00212
00213 }
```

References core::A, core::B, TIMER1_SELECT_COM_CHANNEL_A, and TIMER1_SELECT_COM_CHANNEL_B.

Referenced by component::ServoMotor::connect(), and component::ServoMotor::disconnect().

6.16.3.16 selectOperationMode()

```
void core::TimerCounter1::selectOperationMode (
              const operationMode & ar_operationMode )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 95 of file TimerCounter1.cpp.

```
00096 {
00097      switch (ar_operationMode)
00098      {
00099           case core::operationMode::normal:
00100           {
00101                 TIMER1_SELECT_OPERATION_MODE(0);
```

```
00102                 break;
00103         }
00104         case core::operationMode::PWM_PC_8bit:
00105         {
00106             TIMER1_SELECT_OPERATION_MODE(1);
00107             break;
00108         }
00109         case core::operationMode::PWM_PC_9bit:
00110         {
00111             TIMER1_SELECT_OPERATION_MODE(2);
00112             break;
00113         }
00114         case core::operationMode::PWM_PC_10bit:
00115         {
00116             TIMER1_SELECT_OPERATION_MODE(3);
00117             break;
00118         }
00119         case core::operationMode::CTC_OCR:
00120         {
00121             TIMER1_SELECT_OPERATION_MODE(4);
00122             break;
00123         }
00124         case core::operationMode::fast_PWM_8bit:
00125         {
00126             TIMER1_SELECT_OPERATION_MODE(5);
00127             break;
00128         }
00129         case core::operationMode::fast_PWM_9bit:
00130         {
00131             TIMER1_SELECT_OPERATION_MODE(6);
00132             break;
00133         }
00134         case core::operationMode::fast_PWM_10bit:
00135         {
00136             TIMER1_SELECT_OPERATION_MODE(7);
00137             break;
00138         }
00139         case core::operationMode::PWM_PFC_ICR:
00140         {
00141             TIMER1_SELECT_OPERATION_MODE(8);
00142             break;
00143         }
00144         case core::operationMode::PWM_PFC_OCR:
00145         {
00146             TIMER1_SELECT_OPERATION_MODE(9);
00147             break;
00148         }
00149         case core::operationMode::PWM_PC_ICR:
00150         {
00151             TIMER1_SELECT_OPERATION_MODE(10);
00152             break;
00153         }
00154         case core::operationMode::PWM_PC_OCR:
00155         {
00156             TIMER1_SELECT_OPERATION_MODE(11);
00157             break;
00158         }
00159         case core::operationMode::CTC_ICR:
00160         {
00161             TIMER1_SELECT_OPERATION_MODE(12);
00162             break;
00163         }
00164         case core::operationMode::fast_PWM_ICR:
00165         {
00166             TIMER1_SELECT_OPERATION_MODE(14);
00167             break;
00168         }
00169         case core::operationMode::fast_PWM_OCR:
00170         {
00171             TIMER1_SELECT_OPERATION_MODE(15);
00172             break;
00173         }
00174
00175     }
00176
00177
00178 }
```

References core::CTC_ICR, core::CTC_OCR, core::fast_PWM_10bit, core::fast_PWM_8bit, core::fast_PWM_9bit, core::fast_PWM_ICR, core::fast_PWM_OCR, core::normal, core::PWM_PC_10bit, core::PWM_PC_8bit, core::PWM_PC_9bit, core::PWM_PC_ICR, core::PWM_PC_OCR, core::PWM_PFC_ICR, core::PWM_PFC_OCR, and TIMER1_SELECT_OPERATION_MODE.

Referenced by component::ServoMotor::connect().

6.16.3.17 setCounter()

```
void core::TimerCounter1::setCounter (
            const uint16_t & ar_dataBuffer ) [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 216 of file TimerCounter1.cpp.

```
00217 {
00218     TCNT1 = ar_dataBuffer;
00219 }
```

Referenced by component::ServoMotor::connect().

6.16.3.18 setInputCaptureRegister()

```
void core::TimerCounter1::setInputCaptureRegister (
            const uint16_t & ar_dataBuffer )
```

Definition at line 321 of file TimerCounter1.cpp.

```
00322 {
00323     ICR1 = ar_dataBuffer;
00324 }
```

Referenced by component::ServoMotor::connect().

6.16.3.19 setOutputCompareRegister()

```
void core::TimerCounter1::setOutputCompareRegister (
            const channel & ar_channel,
            const uint16_t & ar_dataBuffer ) [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 226 of file TimerCounter1.cpp.

```
00227 {
00228     switch (ar_channel)
00229     {
00230         case core::channel::A:
00231         {
00232             OCR1A = ar_dataBuffer;
00233             break;
00234         }
00235         case core::channel::B:
00236         {
00237             OCR1B = ar_dataBuffer;
00238             break;
00239         }
00240     }
00241 }
```

References core::A, and core::B.

Referenced by component::ServoMotor::rotate().

6.16.3.20 start()

```
void core::TimerCounter1::start ( ) [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 181 of file TimerCounter1.cpp.

```
00182 {
00183     TIMER1_SELECT_CLOCK_SOURCE(m_clockSource);
00184 }
```

References TIMER1_SELECT_CLOCK_SOURCE.

Referenced by component::ServoMotor::rotate().

6.16.3.21 stop()

```
void core::TimerCounter1::stop ( ) [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 191 of file TimerCounter1.cpp.

```
00192 {
00193     TIMER1_STOP;
00194 }
```

References TIMER1_STOP.

Referenced by component::ServoMotor::disconnect().

6.16.4 Member Data Documentation

6.16.4.1 __externally_visible__

```
static void core::TimerCounter1::__externally_visible__
```

Definition at line 320 of file TimerCounter1.h.

6.16.4.2 __used__

```
static void core::TimerCounter1::__used__
```

Definition at line 320 of file TimerCounter1.h.

6.16.4.3 m_clockPrescaler

`uint16_t core::TimerCounter1::m_clockPrescaler [private]`

Definition at line 349 of file TimerCounter1.h.

6.16.4.4 m_clockSource

`uint8_t core::TimerCounter1::m_clockSource [private]`

Definition at line 351 of file TimerCounter1.h.

6.17 core::TimerCounter2 Class Reference

`#include <TimerCounter2.h>`

Inheritance diagram for core::TimerCounter2:

Collaboration diagram for core::TimerCounter2:

Public Member Functions

- void selectOperationMode (const operationMode &ar_operationMode) override
- void start () override
- void stop () override
- void selectClockSource (const clockSource &ar_clockSource) override
- void selectCompareOutputMode (const channel &ar_channel, const compareOutputMode &ar_compare↩
  OutputMode) override
- void setCounter (const uint16_t &ar_dataBuffer) override
- uint16_t getCounter () const override
- void setOutputCompareRegister (const channel &ar_channel, const uint16_t &ar_dataBuffer) override
- uint16_t getOutputCompareRegister (const channel &ar_channel) const override
- void enableOutputCompareMatchInterrupt (const channel &ar_channel, const uint8_t a_enable) override
- void enableOverflowInterrupt (const uint8_t a_enable) override
- uint16_t getClockPrescaler () override

Static Public Member Functions

- static TimerCounter2 & getInstance (const channel &ar_channel=channel::A, const operationMode &ar↩
  _operationMode=operationMode::normal, const clockSource &ar_clockSource=clockSource::noClock, const
  compareOutputMode &ar_compareOutputMode=compareOutputMode::normal)
- static void outputCompareMatchAServiceRoutine () __asm__(STR(TIMER2_COM_CHANNEL_A_INTERRUPT))
  __attribute__((__signal__
- static void outputCompareMatchBServiceRoutine () __asm__(STR(TIMER2_COM_CHANNEL_B_INTERRUPT))
  __attribute__((__signal__
- static void overflowServiceRoutine () __asm__(STR(TIMER2_OVERFLOW_INTERRUPT)) __attribute__((↩
  __signal__

Public Attributes

- static void __used__
- static void __externally_visible__

Private Member Functions

- TimerCounter2 (const channel &ar_channel, const operationMode &ar_operationMode, const clockSource
  &ar_clockSource, const compareOutputMode &ar_compareOutputMode)
- ∼TimerCounter2 ()
- TimerCounter2 (const TimerCounter2 &)

    Overried Copy constructor.
- const TimerCounter2 & operator= (const TimerCounter2 &)

    Override assign operator.

Private Attributes

- uint16_t m_clockPrescaler
- uint8_t m_clockSource

6.17.1 Detailed Description

Definition at line 279 of file TimerCounter2.h.

6.17.2 Constructor & Destructor Documentation

6.17.2.1 TimerCounter2() [1/2]

```
core::TimerCounter2::TimerCounter2 (
            const channel & ar_channel,
            const operationMode & ar_operationMode,
            const clockSource & ar_clockSource,
            const compareOutputMode & ar_compareOutputMode ) [private]
```

Definition at line 20 of file TimerCounter2.cpp.
```
00024 {
00025     core::MCU::enableTimerCounter2(1);
00026     stop();
00027     selectOperationMode(ar_operationMode);
00028     selectClockSource(ar_clockSource);
00029     selectCompareOutputMode(ar_channel, ar_compareOutputMode);
00030
00031 }
```

References core::MCU::enableTimerCounter2().

6.17.2.2 ∼TimerCounter2()

```
core::TimerCounter2::∼TimerCounter2 ( )  [private]
```

Definition at line 32 of file TimerCounter2.cpp.
```
00033 {
00034
00035 }
```

6.17.2.3 TimerCounter2() [2/2]

```
core::TimerCounter2::TimerCounter2 (
            const TimerCounter2 &  )  [private]
```

Overried Copy constructor.

6.17.3 Member Function Documentation

6.17.3.1 enableOutputCompareMatchInterrupt()

```
void core::TimerCounter2::enableOutputCompareMatchInterrupt (
            const channel & ar_channel,
            const uint8_t a_enable ) [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 215 of file TimerCounter2.cpp.
```
00216 {
00217      switch (ar_channel)
00218      {
00219          case core::channel::A:
00220          {
00221              if (a_enable) {
00222
00223                  TIMER2_ENABLE_COM_CHANNEL_A_INTERRUPT;
00224
00225              } else {
00226
00227                  TIMER2_DISABLE_COM_CHANNEL_A_INTERRUPT;
00228              }
00229              break;
00230          }
00231          case core::channel::B:
00232          {
00233              if (a_enable) {
00234
00235                  TIMER2_ENABLE_COM_CHANNEL_B_INTERRUPT;
00236
00237              } else {
00238
00239                  TIMER2_DISABLE_COM_CHANNEL_B_INTERRUPT;
00240
00241              }
00242              break;
00243          }
00244      }
00245
00246 }
```

References core::A, core::B, TIMER2_DISABLE_COM_CHANNEL_A_INTERRUPT, TIMER2_DISABLE_COM_CHANNEL_B_INTERRUPT, TIMER2_ENABLE_COM_CHANNEL_A_INTERRUPT, and TIMER2_ENABLE_COM_CHANNEL_B_INTERRUPT.

6.17.3.2 enableOverflowInterrupt()

```
void core::TimerCounter2::enableOverflowInterrupt (
            const uint8_t a_enable ) [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 250 of file TimerCounter2.cpp.
```
00251 {
00252
00253      if (a_enable) {
00254
00255          TIMER2_ENABLE_OVERFLOW_INTERRUPT;
00256
00257      } else {
00258
00259          TIMER2_DISABLE_OVERFLOW_INTERRUPT;
00260      }
00261
00262 }
```

References TIMER2_DISABLE_OVERFLOW_INTERRUPT, and TIMER2_ENABLE_OVERFLOW_INTERRUPT.

6.17.3.3 getClockPrescaler()

```
uint16_t core::TimerCounter2::getClockPrescaler ( )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 138 of file TimerCounter2.cpp.
```
00139 {
00140     return m_clockPrescaler;
00141 }
```

6.17.3.4 getCounter()

```
uint16_t core::TimerCounter2::getCounter ( ) const  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 176 of file TimerCounter2.cpp.
```
00177 {
00178     return TCNT2;
00179 }
```

6.17.3.5 getInstance()

```
core::TimerCounter2 & core::TimerCounter2::getInstance (
            const channel & ar_channel = channel::A,
            const operationMode & ar_operationMode = operationMode::normal,
            const clockSource & ar_clockSource = clockSource::noClock,
            const compareOutputMode & ar_compareOutputMode = compareOutputMode::normal )
[static]
```

Definition at line 5 of file TimerCounter2.cpp.
```
00009 {
00010     static TimerCounter2 l_instance(ar_channel,
00011                                    ar_operationMode,
00012                                    ar_clockSource,
00013                                    ar_compareOutputMode);
00014
00015     return l_instance;
00016
00017
00018 }
```

6.17.3.6 getOutputCompareRegister()

```
uint16_t core::TimerCounter2::getOutputCompareRegister (
            const channel & ar_channel ) const  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 199 of file TimerCounter2.cpp.
```
00200 {
00201     switch (ar_channel)
00202     {
00203         case core::channel::A:
00204         {
00205             return OCR2A;
00206         }
00207         case core::channel::B:
00208         {
00209             return OCR2B;
00210         }
00211     }
00212
00213 }
```

References core::A, and core::B.

6.17.3.7 operator=()

```
const TimerCounter2& core::TimerCounter2::operator= (
            const TimerCounter2 & )  [private]
```

Override assign operator.

6.17.3.8 outputCompareMatchAServiceRoutine()

```
static void core::TimerCounter2::outputCompareMatchAServiceRoutine ( )  [static]
```

6.17.3.9 outputCompareMatchBServiceRoutine()

```
static void core::TimerCounter2::outputCompareMatchBServiceRoutine ( )  [static]
```

6.17.3.10 overflowServiceRoutine()

```
static void core::TimerCounter2::overflowServiceRoutine ( )  [static]
```

6.17.3.11 selectClockSource()

```
void core::TimerCounter2::selectClockSource (
            const clockSource & ar_clockSource ) [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 37 of file TimerCounter2.cpp.

```
00038 {
00039     switch (ar_clockSource)
00040     {
00041         case core::clockSource::noClock:
00042         {
00043             m_clockPrescaler=0;
00044             m_clockSource=0;
00045             break;
00046         }
00047         case core::clockSource::PS_1:
00048         {
00049             m_clockPrescaler=1;
00050             m_clockSource=1;
00051             break;
00052         }
00053         case core::clockSource::PS_8:
00054         {
00055             m_clockPrescaler=8;
00056             m_clockSource=2;
00057             break;
00058         }
00059         case core::clockSource::PS_32:
00060         {
00061             m_clockPrescaler=32;
00062             m_clockSource=3;
00063             break;
00064         }
00065         case core::clockSource::PS_64:
00066         {
00067             m_clockPrescaler=64;
00068             m_clockSource=4;
00069             break;
00070         }
00071         case core::clockSource::PS_128:
00072         {
00073             m_clockPrescaler=128;
00074             m_clockSource=5;
00075             break;
00076         }
00077         case core::clockSource::PS_256:
00078         {
00079             m_clockPrescaler=256;
00080             m_clockSource=6;
00081             break;
00082         }
00083         case core::clockSource::PS_1024:
00084         {
00085             m_clockPrescaler=1024;
00086             m_clockSource=7;
00087             break;
00088         }
00089     }
00090
00091 }
```

References core::noClock, core::PS_1, core::PS_1024, core::PS_128, core::PS_256, core::PS_32, core::PS_64, and core::PS_8.

6.17.3.12 selectCompareOutputMode()

```
void core::TimerCounter2::selectCompareOutputMode (
            const channel & ar_channel,
            const compareOutputMode & ar_compareOutputMode ) [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 150 of file TimerCounter2.cpp.

```
00151 {
00152     switch (ar_channel)
00153     {
00154         case core::channel::A:
00155         {
00156             TIMER2_SELECT_COM_CHANNEL_A(static_cast<uint8_t>(ar_compareOutputMode));
00157             break;
00158         }
00159         case core::channel::B:
00160         {
00161             TIMER2_SELECT_COM_CHANNEL_B(static_cast<uint8_t>(ar_compareOutputMode));
00162             break;
00163         }
00164     }
00165
00166
00167 }
```

References core::A, core::B, TIMER2_SELECT_COM_CHANNEL_A, and TIMER2_SELECT_COM_CHANNEL_B.

6.17.3.13 selectOperationMode()

```
void core::TimerCounter2::selectOperationMode (
            const operationMode & ar_operationMode ) [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 93 of file TimerCounter2.cpp.

```
00094 {
00095     switch (ar_operationMode)
00096     {
00097         case core::operationMode::normal:
00098         {
00099             TIMER2_SELECT_OPERATION_MODE(0);
00100             break;
00101         }
00102         case core::operationMode::PWM_PC:
00103         {
00104             TIMER2_SELECT_OPERATION_MODE(1);
00105             break;
00106         }
00107         case core::operationMode::CTC_OCR:
00108         {
00109             TIMER2_SELECT_OPERATION_MODE(2);
00110             break;
00111         }
00112         case core::operationMode::fast_PWM:
00113         {
00114             TIMER2_SELECT_OPERATION_MODE(3);
00115             break;
00116         }
00117         case core::operationMode::PWM_PC_OCR:
00118         {
00119             TIMER2_SELECT_OPERATION_MODE(5);
00120             break;
00121         }
00122         case core::operationMode::fast_PWM_OCR:
00123         {
00124             TIMER2_SELECT_OPERATION_MODE(7);
00125             break;
00126         }
00127
00128     }
00129
00130 }
```

References core::CTC_OCR, core::fast_PWM, core::fast_PWM_OCR, core::normal, core::PWM_PC, core::PWM_PC_OCR, and TIMER2_SELECT_OPERATION_MODE.

6.17.3.14 setCounter()

```
void core::TimerCounter2::setCounter (
            const uint16_t & ar_dataBuffer )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 171 of file TimerCounter2.cpp.

```
00172 {
00173     TCNT2 = static_cast<uint8_t>(ar_dataBuffer);
00174 }
```

6.17.3.15 setOutputCompareRegister()

```
void core::TimerCounter2::setOutputCompareRegister (
            const channel & ar_channel,
            const uint16_t & ar_dataBuffer )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 181 of file TimerCounter2.cpp.

```
00182 {
00183     switch (ar_channel)
00184     {
00185         case core::channel::A:
00186         {
00187             OCR2A = static_cast<uint8_t>(ar_dataBuffer);
00188             break;
00189         }
00190         case core::channel::B:
00191         {
00192             OCR2B = static_cast<uint8_t>(ar_dataBuffer);
00193             break;
00194         }
00195     }
00196 }
```

References core::A, and core::B.

6.17.3.16 start()

```
void core::TimerCounter2::start ( )  [override], [virtual]
```

Implements core::TimerCounter.

Definition at line 133 of file TimerCounter2.cpp.

```
00134 {
00135     TIMER2_SELECT_CLOCK_SOURCE(m_clockSource);
00136 }
```

References TIMER2_SELECT_CLOCK_SOURCE.

6.17.3.17 stop()

```
void core::TimerCounter2::stop ( ) [override], [virtual]
```

Implements [core::TimerCounter](#).

Definition at line [144](#) of file [TimerCounter2.cpp](#).

```
00145 {
00146     TIMER2_STOP;
00147 }
```

References [TIMER2_STOP](#).

6.17.4 Member Data Documentation

6.17.4.1 __externally_visible__

```
static void core::TimerCounter2::__externally_visible__
```

Definition at line [313](#) of file [TimerCounter2.h](#).

6.17.4.2 __used__

```
static void core::TimerCounter2::__used__
```

Definition at line [313](#) of file [TimerCounter2.h](#).

6.17.4.3 m_clockPrescaler

```
uint16_t core::TimerCounter2::m_clockPrescaler [private]
```

Definition at line [338](#) of file [TimerCounter2.h](#).

6.17.4.4 m_clockSource

```
uint8_t core::TimerCounter2::m_clockSource [private]
```

Definition at line [340](#) of file [TimerCounter2.h](#).

6.18 io::USART0 Class Reference

```
#include <USART0.h>
```

Public Member Functions

- void setBaudRate ()

    Set baud rate.
- void setTransmissionMode (const transmissionMode &ar_transMode)

    Set transnmission mode.
- void setCommunicationMode (const communicationMode &ar_comMode)

    Set communication mode.
- void setParityMode (const parityMode &ar_parityMode)

    Set parity mode in data frame.
- void setFrameSize (const frameSize &ar_frameSize)

    Set data frame size.
- void setStopBit (const stopBit &ar_stopBit)

    Set number of stop bits in data frame.
- void sendFrames (const uint8_t ∗ap_dataBuffer, const uint8_t a_size)

    Transmit data frames.
- void sendString (const char ∗ap_string)

    Transmit string.
- void receiveString (const char ∗ap_string)

    Transmit string.
- void sendChar (const uint8_t &ar_char)

    Transmit character.
- void sendByte (const uint8_t &ar_byte)

    Transmit byte.
- void sendWord (const uint16_t &ar_word)

    Transmit word.
- void sendLong (const uint32_t &ar_long)

    Transmit word.
- void receiveChar (uint8_t &ar_char)

    Receive character.
- void receiveFrames (uint8_t ∗ap_dataBuffer, const uint8_t a_size)

    Receive data frames.
- void enableTransmitCompleteInterrupt (const uint8_t ar_enable)

    Enable transmit complete interrupt.
- void enableReceiveCompleteInterrupt (const uint8_t ar_enable)

    Enable receive complete interrupt.
- uint8_t frameError ()

    Is there frame error in received data.
- uint8_t dataOverrun ()

    Is there data overrun in received data.
- uint8_t parityError ()

    Is there partity error in received data.
- uint16_t getNumberBytesReceived ()

    Get number of bytes received.
- uint16_t getNumberBytesSent ()

    Get number of bytes sent.
- uint8_t ready2Send ()

    Is ready to send.
- void resetNumberBytesReceived ()

    Reset number of bytes received.

Static Public Member Functions

- static USART0 & getInstance (const transmissionMode &ar_transMode=transmissionMode::async, const communicationMode &ar_comMode=communicationMode::duplex, const frameSize &ar_frame↩ Size=frameSize::eightBits, const stopBit &ar_stopBit=stopBit::oneStopBit, const parityMode &ar_parity↩ Mode=parityMode::noParity)

  Create a single instance of the USART0 object.

- static void enableDataRegisterEmptyInterrupt (const uint8_t ar_enable)

  Enable data register empty interrupt.

- static void receiveCompleteServiceRoutine () __asm__(STR(USART0_RECEIVE_COMPLETE_INTERRUPT)) __attribute__((__signal__

  Receive complete ISR.

- static void dataRegisterEmptyServiceRoutine () __asm__(STR(USART0_DATA_REGISTER_EMPTY_INTERRUPT)) __attribute__((__signal__

  Data register empty ISR.

- static void transmitCompleteServiceRoutine () __asm__(STR(USART0_TRANSMIT_COMPLETE_INTERRUPT)) __attribute__((__signal__

  Transmit complete ISR.

Public Attributes

- static void __used__
- static void __externally_visible__

Private Member Functions

- USART0 (const transmissionMode &ar_transMode, const communicationMode &ar_comMode, const frameSize &ar_frameSize, const stopBit &ar_stopBit, const parityMode &ar_parityMode)

  Constructor.

- ∼USART0 ()

  Destructor.

- USART0 (const USART0 &)

  Overried Copy constructor.

- const USART0 & operator= (const USART0 &)

  Override assign operator.

Static Private Attributes

- static volatile uint8_t m_status = 0

  received data status

- static const uint8_t ∗ mp_data2Send = nullptr

  pointer to transmitter buffer

- static uint8_t ∗ mp_data2Receive = nullptr

  pointer to receiver buffer

- static uint16_t m_sizeData2Send = 0

  size of data to be transmitted

- static uint16_t m_sizeData2Receive = 0

  size of data to be received

- static volatile uint16_t m_numberBytesReceived = 0

  number of bytes received

- static volatile uint16_t m_numberBytesSent = 0

  number of bytes sent

- static volatile uint8_t m_ready2Send = 1

  ready to send flag

6.18.1 Detailed Description

Definition at line 112 of file USART0.h.

6.18.2 Constructor & Destructor Documentation

6.18.2.1 USART0() [1/2]

```
io::USART0::USART0 (
            const transmissionMode & ar_transMode,
            const communicationMode & ar_comMode,
            const frameSize & ar_frameSize,
            const stopBit & ar_stopBit,
            const parityMode & ar_parityMode )  [private]
```

Constructor.

Initalizes the USART0 object

```
@param ar_transMode defines transmission mode
@param ar_comMode defines communication mode
@param ar_frameSize defines data frame size
@param ar_stopBit defines number of stop bits
@param ar_parityMode defines parity mode
```

Definition at line 34 of file USART0.cpp.
```
00040 {
00041     core::MCU::enableUSART0(1);
00042     setBaudRate();
00043     setTransmissionMode(ar_transMode);
00044     setCommunicationMode(ar_comMode);
00045     setParityMode(ar_parityMode);
00046     setFrameSize(ar_frameSize);
00047     setStopBit(ar_stopBit);
00048     sei();
00049     enableReceiveCompleteInterrupt(1);
00050 }
```

References core::MCU::enableUSART0().

6.18.2.2 ∼USART0()

```
io::USART0::∼USART0 ( )  [private]
```

Destructor.

Definition at line 52 of file USART0.cpp.
```
00053 {
00054
00055 }
```

6.18.2.3 USART0() [2/2]

```
io::USART0::USART0 (
            const USART0 &  ) [private]
```

Overried Copy constructor.

6.18.3 Member Function Documentation

6.18.3.1 dataOverrun()

```
uint8_t io::USART0::dataOverrun ( )
```

Is there data overrun in received data.

Definition at line 195 of file USART0.cpp.

```
00196 {
00197     return (m_status & (1 « USART0_DATA_OVERRUN));
00198
00199 }
```

References USART0_DATA_OVERRUN.

6.18.3.2 dataRegisterEmptyServiceRoutine()

```
void io::USART0::dataRegisterEmptyServiceRoutine ( )  [static]
```

Data register empty ISR.

Definition at line 331 of file USART0.cpp.

```
00332 {
00333
00334     if (m_sizeData2Send)
00335     {
00336         m_ready2Send = 0;
00337         USART0_DATA_REGISTER = *mp_data2Send++;
00338         m_sizeData2Send--;
00339         m_numberBytesSent++;
00340
00341     }
00342     else
00343     {
00344         enableDataRegisterEmptyInterrupt(0);
00345         m_numberBytesSent = 0;
00346         m_ready2Send = 1;
00347
00348     }
00349
00350 }
```

References USART0_DATA_REGISTER.

6.18.3.3 enableDataRegisterEmptyInterrupt()

```
void io::USART0::enableDataRegisterEmptyInterrupt (
            const uint8_t ar_enable ) [static]
```

Enable data register empty interrupt.

```
@param ar_enable indicates if interrupt is enabled
```

Definition at line 374 of file USART0.cpp.

```
00375 {
00376     if (ar_enable) {
00377         USART0_ENABLE_DATA_REGISTER_EMPTY_INTERRUPT;
00378
00379     } else {
00380         USART0_DISABLE_DATA_REGISTER_EMPTY_INTERRUPT;
00381     }
00382
00383 }
```

References USART0_DISABLE_DATA_REGISTER_EMPTY_INTERRUPT, and USART0_ENABLE_DATA_REGISTER_EMPTY_IN

6.18.3.4 enableReceiveCompleteInterrupt()

```
void io::USART0::enableReceiveCompleteInterrupt (
            const uint8_t ar_enable )
```

Enable receive complete interrupt.

```
@param ar_enable indicates if interrupt is enabled
```

Definition at line 363 of file USART0.cpp.

```
00364 {
00365     if (ar_enable) {
00366         USART0_ENABLE_RECEIVE_COMPLETE_INTERRUPT;
00367
00368     } else {
00369         USART0_DISABLE_RECEIVE_COMPLETE_INTERRUPT;
00370     }
00371
00372 }
```

References USART0_DISABLE_RECEIVE_COMPLETE_INTERRUPT, and USART0_ENABLE_RECEIVE_COMPLETE_INTERRUP

6.18.3.5 enableTransmitCompleteInterrupt()

```
void io::USART0::enableTransmitCompleteInterrupt (
            const uint8_t ar_enable )
```

Enable transmit complete interrupt.

```
@param ar_enable indicates if interrupt is enabled
```

Definition at line 353 of file USART0.cpp.

```
00354 {
00355     if (ar_enable) {
00356         USART0_ENABLE_TRANSMIT_COMPLETE_INTERRUPT;
00357     } else {
00358         USART0_DISABLE_TRANSMIT_COMPLETE_INTERRUPT;
00359     }
00360
00361 }
```

References USART0_DISABLE_TRANSMIT_COMPLETE_INTERRUPT, and USART0_ENABLE_TRANSMIT_COMPLETE_INTERR

6.18.3.6 frameError()

```
uint8_t io::USART0::frameError ( )
```

Is there frame error in received data.

Definition at line 189 of file USART0.cpp.

```
00190 {
00191     return (m_status & (1 « USART0_FRAME_ERROR));
00192
00193 }
```

References USART0_FRAME_ERROR.

6.18.3.7 getInstance()

```
io::USART0 & io::USART0::getInstance (
            const transmissionMode & ar_transMode = transmissionMode::async,
            const communicationMode & ar_comMode = communicationMode::duplex,
            const frameSize & ar_frameSize = frameSize::eightBits,
            const stopBit & ar_stopBit = stopBit::oneStopBit,
            const parityMode & ar_parityMode = parityMode::noParity )  [static]
```

Create a single instance of the USART0 object.

```
@param ar_transMode defines transmission mode
@param ar_comMode defines communication mode
@param ar_frameSize defines data frame size
@param ar_stopBit defines number of stop bits
@param ar_parityMode defines parity mode
```

Definition at line 17 of file USART0.cpp.

```
00022 {
00023     static USART0 l_instance(ar_transMode,
00024                             ar_comMode,
00025                             ar_frameSize,
00026                             ar_stopBit,
00027                             ar_parityMode);
00028
00029     return l_instance;
00030 }
```

6.18.3.8 getNumberBytesReceived()

```
uint16_t io::USART0::getNumberBytesReceived ( )
```

Get number of bytes received.

Definition at line 395 of file USART0.cpp.

```
00396 {
00397     return m_numberBytesReceived;
00398 }
```

6.18.3.9 getNumberBytesSent()

```
uint16_t io::USART0::getNumberBytesSent ( )
```

Get number of bytes sent.

Definition at line 390 of file USART0.cpp.

```
00391 {
00392     return m_numberBytesSent;
00393 }
```

6.18.3.10 operator=()

```
const USART0& io::USART0::operator= (
            const USART0 &  )  [private]
```

Override assign operator.

6.18.3.11 parityError()

```
uint8_t io::USART0::parityError ( )
```

Is there partity error in received data.

Definition at line 201 of file USART0.cpp.

```
00202 {
00203     return (m_status & (1 << USART0_PARITY_ERROR));
00204
00205 }
```

References USART0_PARITY_ERROR.

6.18.3.12 ready2Send()

```
uint8_t io::USART0::ready2Send ( )
```

Is ready to send.

Definition at line 405 of file USART0.cpp.

```
00406 {
00407     return m_ready2Send;
00408
00409 }
```

6.18.3.13 receiveChar()

```
void io::USART0::receiveChar (
            uint8_t & ar_char )
```

Receive character.

```
@param ar_char defines charcter to be received
```

Definition at line 284 of file USART0.cpp.
```
00285 {
00286     m_sizeData2Receive = 1;
00287     mp_data2Receive = &ar_char;
00288 }
```

6.18.3.14 receiveCompleteServiceRoutine()

```
void io::USART0::receiveCompleteServiceRoutine ( )  [static]
```

Receive complete ISR.

Definition at line 306 of file USART0.cpp.
```
00307 {
00308     static volatile uint8_t *lp_dataReceived = mp_data2Receive;
00309     static uint16_t l_dataSize = m_sizeData2Receive;
00310
00311     m_status = USART0_CONTROL_STATUS_REGISTER;
00312
00313
00314
00315         if (l_dataSize)
00316         {
00317
00318             *lp_dataReceived++ = USART0_DATA_REGISTER;
00319             l_dataSize--;
00320             m_numberBytesReceived++;
00321
00322         }
00323         else
00324         {
00325             l_dataSize = m_sizeData2Receive;
00326             lp_dataReceived = mp_data2Receive;
00327         }
00328
00329 }
```

References USART0_CONTROL_STATUS_REGISTER, and USART0_DATA_REGISTER.

6.18.3.15 receiveFrames()

```
void io::USART0::receiveFrames (
            uint8_t * ap_dataBuffer,
            const uint8_t a_size )
```

Receive data frames.

```
@param ap_dataBuffer defines pointer to receiver buffer
@param a_size defines size of receiver buffer
@param a_ready2Receive indicates if chip ready to receive data
```

Definition at line 291 of file USART0.cpp.
```
00292 {
00293     m_sizeData2Receive = a_size;
00294     mp_data2Receive = ap_dataBuffer;
00295
00296
00297
00298 }
```

6.18.3.16 receiveString()

```
void io::USART0::receiveString (
            const char * ap_string )
```

Transmit string.

@param ap_string defines pointer to string

Definition at line 300 of file USART0.cpp.

```
00301 {
00302
00303 }
```

6.18.3.17 resetNumberBytesReceived()

```
void io::USART0::resetNumberBytesReceived ( )
```

Reset number of bytes received.

Definition at line 400 of file USART0.cpp.

```
00401 {
00402     m_numberBytesReceived = 0;
00403 }
```

6.18.3.18 sendByte()

```
void io::USART0::sendByte (
            const uint8_t & ar_byte )
```

Transmit byte.

@param ar_byte defines byte to be sent

Definition at line 226 of file USART0.cpp.

```
00227 {
00228     static uint8_t l_byte2Send[3];
00229     l_byte2Send[0] = '0' + (ar_byte / 100);
00230     l_byte2Send[1] = '0' + ((ar_byte / 10) % 10);
00231     l_byte2Send[2] = '0' + (ar_byte % 10);
00232
00233     while (!ready2Send()){};
00234     m_sizeData2Send = 3;
00235     mp_data2Send = l_byte2Send;
00236     enableDataRegisterEmptyInterrupt(1);
00237
00238 }
```

6.18.3.19 sendChar()

```
void io::USART0::sendChar (
            const uint8_t & ar_char )
```

Transmit character.

@param ar_char defines character to be sent

Definition at line 275 of file USART0.cpp.

```
00276 {
00277     while (!ready2Send()){};
00278     m_sizeData2Send = 1;
00279     mp_data2Send = &ar_char;
00280     enableDataRegisterEmptyInterrupt(1);
00281
00282 }
```

6.18.3.20 sendFrames()

```
void io::USART0::sendFrames (
            const uint8_t * ap_dataBuffer,
            const uint8_t a_size )
```

Transmit data frames.

@param ap_dataBuffer defines pointer to transmitter buffer
@param a_size defines size of transmitter buffer

Definition at line 207 of file USART0.cpp.

```
00208 {
00209     while (!ready2Send()){};
00210     m_sizeData2Send = a_size;
00211     mp_data2Send = ap_dataBuffer;
00212     enableDataRegisterEmptyInterrupt(1);
00213 }
```

6.18.3.21 sendLong()

```
void io::USART0::sendLong (
            const uint32_t & ar_long )
```

Transmit word.

@param ar_word defines word to be sent

Definition at line 239 of file USART0.cpp.

```
00240 {
00241     static uint8_t l_word2Send[10];
00242     l_word2Send[0] = '0' + (ar_long / 1000000000);
00243     l_word2Send[1] = '0' + ((ar_long / 100000000) % 10);
00244     l_word2Send[2] = '0' + ((ar_long /  10000000) % 10);
00245     l_word2Send[3] = '0' + ((ar_long /   1000000) % 10);
00246     l_word2Send[4] = '0' + ((ar_long /    100000) % 10);
00247     l_word2Send[5] = '0' + ((ar_long /     10000) % 10);
00248     l_word2Send[6] = '0' + ((ar_long /      1000) % 10);
00249     l_word2Send[7] = '0' + ((ar_long /       100) % 10);
00250     l_word2Send[8] = '0' + ((ar_long /        10) % 10);
00251     l_word2Send[9] = '0' + (ar_long % 10);
00252
00253     while (!ready2Send()){};
00254     m_sizeData2Send = 10;
00255     mp_data2Send = l_word2Send;
00256     enableDataRegisterEmptyInterrupt(1);
00257
00258 }
```

6.18.3.22 sendString()

```
void io::USART0::sendString (
            const char * ap_string )
```

Transmit string.

@param ap_string defines pointer to string

Definition at line 216 of file USART0.cpp.

```
00217 {
00218     while (!ready2Send()){};
00219     m_sizeData2Send = strlen(ap_string);
00220     mp_data2Send = reinterpret_cast<const uint8_t*>(ap_string);
00221     enableDataRegisterEmptyInterrupt(1);
00222
00223 }
```

6.18.3.23 sendWord()

```
void io::USART0::sendWord (
            const uint16_t & ar_word )
```

Transmit word.

@param ar_word defines word to be sent

Definition at line 259 of file USART0.cpp.

```
00260 {
00261     static uint8_t l_word2Send[5];
00262     l_word2Send[0] = '0' + (ar_word / 10000);
00263     l_word2Send[1] = '0' + ((ar_word / 1000) % 10);
00264     l_word2Send[2] = '0' + ((ar_word /  100) % 10);
00265     l_word2Send[3] = '0' + ((ar_word /   10) % 10);
00266     l_word2Send[4] = '0' + (ar_word %    10);
00267
00268     while (!ready2Send()){};
00269     m_sizeData2Send = 5;
00270     mp_data2Send = l_word2Send;
00271     enableDataRegisterEmptyInterrupt(1);
00272
00273 }
```

6.18.3.24 setBaudRate()

```
void io::USART0::setBaudRate ( )
```

Set baud rate.

Definition at line 57 of file USART0.cpp.

```
00058 {
00059     USART0_SET_BAUDRATE_HIGH_REGISTER;
00060     USART0_SET_BAUDRATE_LOW_REGISTER;
00061
00062 }
```

References USART0_SET_BAUDRATE_HIGH_REGISTER, and USART0_SET_BAUDRATE_LOW_REGISTER.

6.18.3.25 setCommunicationMode()

```
void io::USART0::setCommunicationMode (
            const communicationMode & ar_comMode )
```

Set communication mode.

@param ar_comMode defines communication mode

Definition at line 89 of file USART0.cpp.

```
00090 {
00091     switch (ar_comMode)
00092     {
00093         case communicationMode::duplex:
00094         {
00095             USART0_ENABLE_TRANSMITTER;
00096             USART0_ENABLE_RECEIVER;
00097             break;
00098         }
00099         case communicationMode::receive:
00100         {
00101             USART0_ENABLE_RECEIVER;
00102             USART0_DISABLE_TRANSMITTER;
00103             break;
00104         }
00105         case communicationMode::transmit:
00106         {
00107             USART0_ENABLE_TRANSMITTER;
00108             USART0_DISABLE_RECEIVER;
00109             break;
00110         }
00111     }
00112
00113 }
```

References io::duplex, io::receive, io::transmit, USART0_DISABLE_RECEIVER, USART0_DISABLE_TRANSMITTER, USART0_ENABLE_RECEIVER, and USART0_ENABLE_TRANSMITTER.

6.18.3.26 setFrameSize()

```
void io::USART0::setFrameSize (
            const frameSize & ar_frameSize )
```

Set data frame size.

@param ar_frameSize defines data frame size

Definition at line 138 of file USART0.cpp.

```
00139 {
00140     switch (ar_frameSize)
00141     {
00142         case frameSize::eightBits:
00143         {
00144             USART0_SET_8BIT_FRAME_SIZE;
00145             break;
00146         }
00147         case frameSize::sevenBits:
00148         {
00149             USART0_SET_7BIT_FRAME_SIZE;
00150             break;
00151         }
00152         case frameSize::sixBits:
00153         {
00154             USART0_SET_6BIT_FRAME_SIZE;
00155             break;
00156         }
```

```
00157          case frameSize::fiveBits:
00158          {
00159              USART0_SET_5BIT_FRAME_SIZE;
00160              break;
00161          }
00162          case frameSize::neineBits:
00163          {
00164              USART0_SET_9BIT_FRAME_SIZE;
00165              break;
00166          }
00167      }
00168
00169 }
```

References io::eightBits, io::fiveBits, io::neineBits, io::sevenBits, io::sixBits, USART0_SET_5BIT_FRAME_SIZE, USART0_SET_6BIT_FRAME_SIZE, USART0_SET_7BIT_FRAME_SIZE, USART0_SET_8BIT_FRAME_SIZE, and USART0_SET_9BIT_FRAME_SIZE.

6.18.3.27 setParityMode()

```
void io::USART0::setParityMode (
            const parityMode & ar_parityMode )
```

Set parity mode in data frame.

```
@param ar_parityMode defines parity mode
```

Definition at line 115 of file USART0.cpp.
```
00116 {
00117      switch (ar_parityMode)
00118      {
00119          case parityMode::noParity:
00120          {
00121              USART0_DISABLE_PARITY_MODE;
00122              break;
00123          }
00124          case parityMode::evenParity:
00125          {
00126              USART0_ENABLE_EVEN_PARITY_MODE;
00127              break;
00128          }
00129          case parityMode::oddParity:
00130          {
00131              USART0_ENABLE_ODD_PARITY_MODE;
00132              break;
00133          }
00134      }
00135
00136 }
```

References io::evenParity, io::noParity, io::oddParity, USART0_DISABLE_PARITY_MODE, USART0_ENABLE_EVEN_PARITY_MOI and USART0_ENABLE_ODD_PARITY_MODE.

6.18.3.28 setStopBit()

```
void io::USART0::setStopBit (
            const stopBit & ar_stopBit )
```

Set number of stop bits in data frame.

```
@param ar_stopBit defines number of stop bits
```

Definition at line 170 of file USART0.cpp.

```
00171 {
00172     switch (ar_stopBit)
00173     {
00174         case stopBit::oneStopBit:
00175         {
00176             USART0_SET_ONE_STOP_BIT;
00177             break;
00178         }
00179         case stopBit::twoStopBits:
00180         {
00181             USART0_SET_TWO_STOP_BITS;
00182             break;
00183         }
00184     }
00185
00186 }
```

References io::oneStopBit, io::twoStopBits, USART0_SET_ONE_STOP_BIT, and USART0_SET_TWO_STOP_BITS.

6.18.3.29 setTransmissionMode()

```
void io::USART0::setTransmissionMode (
            const transmissionMode & ar_transMode )
```

Set transnmission mode.

```
@param ar_transMode defines transmission mode
```

Definition at line 64 of file USART0.cpp.

```
00065 {
00066     switch (ar_transMode)
00067     {
00068         case transmissionMode::async:
00069         {
00070             USART0_ENABLE_ASYNC_TRANSMISSION_MODE;
00071             break;
00072         }
00073         case transmissionMode::sync:
00074         {
00075             USART0_DISABLE_DOUBLE_SPEED_MODE;
00076             USART0_ENABLE_SYNC_TRANSMISSION_MODE;
00077             break;
00078         }
00079     case transmissionMode::masterSPI:
00080         {
00081             USART0_ENABLE_MASTER_SPI_MODE;
00082             break;
00083         }
00084     }
00085
00086
00087 }
```

References io::async, io::masterSPI, io::sync, USART0_DISABLE_DOUBLE_SPEED_MODE, USART0_ENABLE_ASYNC_TRANSM
USART0_ENABLE_MASTER_SPI_MODE, and USART0_ENABLE_SYNC_TRANSMISSION_MODE.

6.18.3.30 transmitCompleteServiceRoutine()

```
void io::USART0::transmitCompleteServiceRoutine ( )  [static]
```

Transmit complete ISR.

Definition at line 385 of file USART0.cpp.

```
00386 {
00387
00388 }
```

6.18.4 Member Data Documentation

6.18.4.1 __externally_visible__

```
static void io::USART0::__externally_visible__
```

Definition at line 249 of file USART0.h.

6.18.4.2 __used__

```
static void io::USART0::__used__
```

Definition at line 249 of file USART0.h.

6.18.4.3 m_numberBytesReceived

```
volatile uint16_t io::USART0::m_numberBytesReceived = 0  [static], [private]
```

number of bytes received

Definition at line 300 of file USART0.h.

6.18.4.4 m_numberBytesSent

```
volatile uint16_t io::USART0::m_numberBytesSent = 0  [static], [private]
```

number of bytes sent

Definition at line 302 of file USART0.h.

6.18.4.5 m_ready2Send

```
volatile uint8_t io::USART0::m_ready2Send = 1  [static], [private]
```

ready to send flag

Definition at line 304 of file USART0.h.

6.18.4.6 m_sizeData2Receive

```
uint16_t io::USART0::m_sizeData2Receive = 0  [static], [private]
```

size of data to be received

Definition at line 298 of file USART0.h.

6.18.4.7 m_sizeData2Send

```
uint16_t io::USART0::m_sizeData2Send = 0  [static], [private]
```

size of data to be transmitted

Definition at line 296 of file USART0.h.

6.18.4.8 m_status

```
volatile uint8_t io::USART0::m_status = 0  [static], [private]
```

received data status

Definition at line 290 of file USART0.h.

6.18.4.9 mp_data2Receive

```
uint8_t * io::USART0::mp_data2Receive = nullptr  [static], [private]
```

pointer to receiver buffer

Definition at line 294 of file USART0.h.

6.18.4.10 mp_data2Send

```
const uint8_t * io::USART0::mp_data2Send = nullptr  [static], [private]
```

pointer to transmitter buffer

Definition at line 292 of file USART0.h.

6.19 core::WatchdogTimer Class Reference

```
#include <WatchdogTimer.h>
```

Public Member Functions

- void selectTimeOut (const timeOut &ar_timeOut)
- void reset ()
- void start (const operationMode &ar_operationMode)
- void start (const operationMode &ar_operationMode, const timeOut &ar_timeOut)
- void stop ()

Static Public Member Functions

- static WatchdogTimer & getInstance ()
- static void timeOutServiceRoutine () __asm__(STR(WATCHDOG_TIMEOUT_INTERRUPT)) __attribute_↩
  _((__signal__

Public Attributes

- static void __used__
- static void __externally_visible__

Private Member Functions

- WatchdogTimer ()
- ∼WatchdogTimer ()
    Destructor.
- WatchdogTimer (const WatchdogTimer &)
    Overried Copy constructor.
- const WatchdogTimer & operator= (const WatchdogTimer &)
    Override assign operator.

Private Attributes

- uint8_t m_timeOut
- uint8_t m_operationMode

6.19.1 Detailed Description

Definition at line 84 of file WatchdogTimer.h.

6.19.2 Constructor & Destructor Documentation

6.19.2.1 WatchdogTimer() [1/2]

```
core::WatchdogTimer::WatchdogTimer ( )  [private]
```

Definition at line 11 of file WatchdogTimer.cpp.

```
00012 {
00013     sei();
00014     stop();
00015 }
```

6.19.2.2 ∼WatchdogTimer()

```
core::WatchdogTimer::∼WatchdogTimer ( )  [private]
```

Destructor.

Definition at line 17 of file WatchdogTimer.cpp.

```
00018 {
00019
00020 }
```

6.19.2.3 WatchdogTimer() [2/2]

```
core::WatchdogTimer::WatchdogTimer (
            const WatchdogTimer &  )  [private]
```

Overried Copy constructor.

6.19.3 Member Function Documentation

6.19.3.1 getInstance()

```
core::WatchdogTimer & core::WatchdogTimer::getInstance ( )  [static]
```

Definition at line 4 of file WatchdogTimer.cpp.

```
00005 {
00006     static WatchdogTimer l_instance;
00007     return l_instance;
00008
00009 }
```

6.19.3.2 operator=()

```
const WatchdogTimer& core::WatchdogTimer::operator= (
            const WatchdogTimer &  )  [private]
```

Override assign operator.

6.19.3.3 reset()

```
void core::WatchdogTimer::reset ( )
```

Definition at line 33 of file WatchdogTimer.cpp.

```
00034 {
00035     wdt_reset();
00036
00037 }
```

6.19.3.4 selectTimeOut()

```
void core::WatchdogTimer::selectTimeOut (
            const timeOut & ar_timeOut )
```

Definition at line 22 of file WatchdogTimer.cpp.

```
00023 {
00024     m_timeOut = static_cast<uint8_t>(ar_timeOut);
00025     m_timeOut = static_cast<uint8_t>((m_timeOut & 7) | ((m_timeOut & 8) << 2 ));
00026     cli();
00027     wdt_reset();
00028     WATCHDOG_SELECT_TIMEOUT(m_timeOut);
00029     sei();
00030
00031 }
```

References WATCHDOG_SELECT_TIMEOUT.

6.19.3.5 start() [1/2]

```
void core::WatchdogTimer::start (
            const operationMode & ar_operationMode )
```

Definition at line 39 of file WatchdogTimer.cpp.

```
00040 {
00041     m_operationMode = static_cast<uint8_t>(ar_operationMode);
00042     m_operationMode = static_cast<uint8_t>(((m_operationMode & 1) << 6) | ((m_operationMode & 2) << 3
     ));
00043     cli();
00044     wdt_reset();
00045     WATCHDOG_START(m_operationMode,m_timeOut);
00046     sei();
00047
00048 }
```

References WATCHDOG_START.

6.19.3.6 start() `[2/2]`

```
void core::WatchdogTimer::start (
            const operationMode & ar_operationMode,
            const timeOut & ar_timeOut )
```

Definition at line 50 of file WatchdogTimer.cpp.

```
00051 {
00052     m_timeOut = static_cast<uint8_t>(ar_timeOut);
00053     m_timeOut = static_cast<uint8_t>((m_timeOut & 7) | ((m_timeOut & 8) « 2 ));
00054     m_operationMode = static_cast<uint8_t>(ar_operationMode);
00055     m_operationMode = static_cast<uint8_t>(((m_operationMode & 1) « 6) | ((m_operationMode & 2) « 3
       ));
00056     cli();
00057     wdt_reset();
00058     WATCHDOG_START(m_operationMode,m_timeOut);
00059     sei();
00060
00061 }
```

References WATCHDOG_START.

6.19.3.7 stop()

```
void core::WatchdogTimer::stop ( )
```

Definition at line 63 of file WatchdogTimer.cpp.

```
00064 {
00065     cli();
00066     wdt_reset();
00067     WATCHDOG_STOP;
00068     sei();
00069
00070 }
```

References WATCHDOG_STOP.

6.19.3.8 timeOutServiceRoutine()

```
static void core::WatchdogTimer::timeOutServiceRoutine ( )  [static]
```

6.19.4 Member Data Documentation

6.19.4.1 __externally_visible__

```
void core::WatchdogTimer::__externally_visible__
```

Definition at line 102 of file WatchdogTimer.h.

6.19.4.2 __used__

```
void core::WatchdogTimer::__used__
```

Definition at line 102 of file WatchdogTimer.h.

6.19.4.3 m_operationMode

```
uint8_t core::WatchdogTimer::m_operationMode  [private]
```

Definition at line 125 of file WatchdogTimer.h.

6.19.4.4 m_timeOut

```
uint8_t core::WatchdogTimer::m_timeOut  [private]
```

Definition at line 123 of file WatchdogTimer.h.

Chapter 7

File Documentation

7.1 ADC.cpp File Reference

```
#include "ADC.h"
#include "MCU.h"
```
Include dependency graph for ADC.cpp:

7.2 ADC.cpp

```
00001 #include "ADC.h"
00002 #include "MCU.h"
00003
00004 volatile uint16_t* core::ADConverter::mp_conversionResult = nullptr;
00005 volatile uint8_t core::ADConverter::m_conversionComplete = 0;
00006 uint8_t core::ADConverter::m_resolution = 10;
00007
00008
00009 core::ADConverter& core::ADConverter::getInstance(const referenceVoltage &ar_refVoltage,
00010                                                    const clockPrescaler& ar_clockPrescaler,
00011                                                    const autoTriggerSource& ar_autoTriggerSource,
00012                                                    const io::Pin &ar_pin)
00013 {
00014
00015     static ADConverter l_instance(ar_refVoltage,
00016                                   ar_clockPrescaler,
00017                                   ar_autoTriggerSource,
00018                                   ar_pin);
```

```
00019
00020      return l_instance;
00021 }
00022
00023 core::ADConverter::ADConverter(const referenceVoltage &ar_refVoltage,
00024                                const clockPrescaler& ar_clockPrescaler,
00025                                const autoTriggerSource& ar_autoTriggerSource,
00026                                const io::Pin &ar_pin)
00027 {
00028      core::MCU::enableADC(1);
00029      selectAnalogInput(ar_pin);
00030      selectReferenceVoltage(ar_refVoltage);
00031      selectClockPrescaler(ar_clockPrescaler);
00032      enableAutoTrigger(1);
00033      selectAutoTriggerSource(ar_autoTriggerSource);
00034      sei();
00035      enableConversionCompleteInterrupt(1);
00036
00037
00038 }
00039
00040
00041 core::ADConverter::~ADConverter()
00042 {
00043
00044 }
00045
00046
00047 void core::ADConverter::selectReferenceVoltage(const referenceVoltage& ar_refVoltage)
00048 {
00049      ADC_SELECT_REF_VOLTAGE(static_cast<uint8_t>(ar_refVoltage));
00050
00051 }
00052
00053 void core::ADConverter::selectAnalogInput(io::Pin a_pin)
00054 {
00055      a_pin.toInput(0);
00056      ADC_SELECT_ANALOG_INPUT(a_pin.getPinNumber());
00057      ADC_DISABLE_DIGITAL_INPUT_REGISTER(a_pin.getPinNumber());
00058
00059 }
00060
00061 void core::ADConverter::start()
00062 {
00063      ADC_ENABLE;
00064      ADC_START_CONVERSION;
00065 }
00066
00067 void core::ADConverter::stop()
00068 {
00069      ADC_STOP_CONVERSION;
00070      ADC_DISABLE;
00071 }
00072
00073 void core::ADConverter::enableAutoTrigger(const uint8_t a_enable)
00074 {
00075      if (a_enable) {
00076          ADC_ENABLE_AUTOTRIGGER;
00077
00078      } else {
00079          ADC_DISABLE_AUTOTRIGGER;
00080      }
00081
00082 }
00083
00084 void core::ADConverter::enableConversionCompleteInterrupt(const uint8_t a_enable)
00085 {
00086      if (a_enable) {
00087          ADC_ENABLE_CONVERSION_COMPLETE_INTERRUPT;
00088
00089      } else {
00090          ADC_DISABLE_CONVERSION_COMPLETE_INTERRUPT;
00091      }
00092
00093 }
00094
00095 void core::ADConverter::selectClockPrescaler(const clockPrescaler& ar_clockPrescaler)
00096 {
00097      ADC_SELECT_CLOCK_PRESCALER(static_cast<uint8_t>(ar_clockPrescaler));
00098
00099 }
00100
00101
00102 void core::ADConverter::selectAutoTriggerSource(const autoTriggerSource& ar_autoTriggerSource)
00103 {
00104      ADC_SELECT_AUTO_TRIGGER_SOURCE(static_cast<uint8_t>(ar_autoTriggerSource));
00105
```

```
00106
00107 }
00108
00109 void core::ADConverter::conversionCompleteServiceRoutine()
00110 {
00111
00112     static uint32_t l_resultData = 0;
00113     static uint16_t l_resultDataIndex = 0;
00114
00115     m_conversionComplete = 0;
00116     switch (m_resolution)
00117     {
00118         case 8:
00119         {
00120             *mp_conversionResult = ADC » 8;
00121             m_conversionComplete = 1;
00122             break;
00123         }
00124         case 9:
00125         {
00126             *mp_conversionResult = ADC » 7;
00127             m_conversionComplete = 1;
00128             break;
00129         }
00130         case 10:
00131         {
00132             *mp_conversionResult = ADC;
00133             m_conversionComplete = 1;
00134             break;
00135         }
00136         case 11:
00137         {
00138
00139             if (l_resultDataIndex < 4)
00140             {
00141                 l_resultData += ADC;
00142                 l_resultDataIndex++;
00143
00144             }
00145             else
00146             {
00147                 *mp_conversionResult = l_resultData » 1;
00148                 l_resultData = 0;
00149                 l_resultDataIndex = 0;
00150                 m_conversionComplete = 1;
00151
00152             }
00153
00154             break;
00155         }
00156         case 12:
00157         {
00158             if (l_resultDataIndex < 16)
00159             {
00160                 l_resultData += ADC;
00161                 l_resultDataIndex++;
00162
00163             }
00164             else
00165             {
00166                 *mp_conversionResult = l_resultData » 2;
00167                 l_resultData = 0;
00168                 l_resultDataIndex = 0;
00169                 m_conversionComplete = 1;
00170
00171             }
00172             break;
00173         }
00174         case 13:
00175         {
00176             if (l_resultDataIndex < 64)
00177             {
00178                 l_resultData += ADC;
00179                 l_resultDataIndex++;
00180
00181             }
00182             else
00183             {
00184                 *mp_conversionResult = l_resultData » 3;
00185                 l_resultData = 0;
00186                 l_resultDataIndex = 0;
00187                 m_conversionComplete = 1;
00188
00189             }
00190             break;
00191         }
00192         case 14:
```

```
00193            {
00194                if (l_resultDataIndex < 256)
00195                {
00196                    l_resultData += ADC;
00197                    l_resultDataIndex++;
00198
00199                }
00200                else
00201                {
00202                    *mp_conversionResult = l_resultData >> 4;
00203                    l_resultData = 0;
00204                    l_resultDataIndex = 0;
00205                    m_conversionComplete = 1;
00206
00207                }
00208                break;
00209            }
00210            case 15:
00211            {
00212                if (l_resultDataIndex < 1024)
00213                {
00214                    l_resultData += ADC;
00215                    l_resultDataIndex++;
00216
00217                }
00218                else
00219                {
00220                    *mp_conversionResult = l_resultData >> 5;
00221                    l_resultData = 0;
00222                    l_resultDataIndex = 0;
00223                    m_conversionComplete = 1;
00224
00225                }
00226                break;
00227            }
00228            case 16:
00229            {
00230                if (l_resultDataIndex < 4096)
00231                {
00232
00233                    l_resultData += ADC;
00234                    l_resultDataIndex++;
00235
00236                }
00237                else
00238                {
00239                    *mp_conversionResult = l_resultData >> 6;
00240                    l_resultData = 0;
00241                    l_resultDataIndex = 0;
00242                    m_conversionComplete = 1;
00243
00244                }
00245                break;
00246            }
00247
00248        }
00249
00250
00251
00252
00253 }
00254
00255 uint8_t core::ADConverter::conversionComplete()
00256 {
00257      return m_conversionComplete;
00258
00259 }
00260
00261
00262 void core::ADConverter::getConversionResult(uint16_t *ap_resultData, const resolution& ar_resolution)
00263 {
00264      mp_conversionResult = ap_resultData;
00265
00266      switch (ar_resolution)
00267      {
00268          case core::resolution::res_8bit:
00269          {
00270              ADC_ADJUST_RESULT_LEFT;
00271              m_resolution = 8;
00272              break;
00273          }
00274          case core::resolution::res_9bit:
00275          {
00276              ADC_ADJUST_RESULT_LEFT;
00277              m_resolution = 9;
00278              break;
00279          }
```

```
00280            case core::resolution::res_10bit:
00281            {
00282                ADC_ADJUST_RESULT_RIGHT;
00283                m_resolution = 10;
00284                break;
00285            }
00286            case core::resolution::res_11bit:
00287            {
00288
00289                m_resolution = 11;
00290                break;
00291            }
00292            case core::resolution::res_12bit:
00293            {
00294                m_resolution = 12;
00295                break;
00296            }
00297            case core::resolution::res_13bit:
00298            {
00299                m_resolution = 13;
00300                break;
00301            }
00302            case core::resolution::res_14bit:
00303            {
00304                m_resolution = 14;
00305                break;
00306            }
00307            case core::resolution::res_15bit:
00308            {
00309                m_resolution = 15;
00310                break;
00311            }
00312            case core::resolution::res_16bit:
00313            {
00314                m_resolution = 16;
00315                break;
00316            }
00317        }
00318
00319
00320 }
```

7.3 ADC.h File Reference

Header file of the ADC class.

```
#include "ha_base.h"
#include "Pin.h"
```
Include dependency graph for ADC.h:

This graph shows which files directly or indirectly include this file:

Classes

- class core::ADConverter

Namespaces

- core

Enumerations

- enum core::resolution : uint8_t {
  core::resolution::res_8bit =0, core::resolution::res_9bit, core::resolution::res_10bit, core::resolution::res_11bit,
  core::resolution::res_12bit, core::resolution::res_13bit, core::resolution::res_14bit, core::resolution::res_15bit,
  core::resolution::res_16bit }
- enum core::referenceVoltage : uint8_t { core::referenceVoltage::AREF =0, core::referenceVoltage::AVCC,
  core::referenceVoltage::internal }
- enum core::clockPrescaler : uint8_t {
  core::clockPrescaler::PS_2 = 1, core::clockPrescaler::PS_4, core::clockPrescaler::PS_8, core::clockPrescaler::PS_16,
  core::clockPrescaler::PS_32, core::clockPrescaler::PS_64, core::clockPrescaler::PS_128 }
- enum core::autoTriggerSource : uint8_t {
  core::autoTriggerSource::freeRunning, core::autoTriggerSource::analogComparator, core::autoTriggerSource::extInterrupt,
  core::autoTriggerSource::timer0Compare,
  core::autoTriggerSource::timer0Overflow, core::autoTriggerSource::timer1CompareB, core::autoTriggerSource::timer1Overflow
  core::autoTriggerSource::timer1Capture }

7.3.1 Detailed Description

Header file of the ADC class.

Basic class for abstraction of the Analog to Digital Converter.

Usage example: #include "ADC.h" #include "USART0.h"

#define TRANSMIT_BUFFER_SIZE 7

int [main(void)](#) {

Init

instantiate the USART0 object [io::USART0](#) &myUSART0 = [io::USART0::getInstance()](#); transmit data buffer char l_data2Send[TRANSMIT_BUFFER_SIZE];

instantiate the ADC object [core::ADConverter](#) &myADC = [core::ADConverter::getInstance()](#);

select analog input myADC.selectAnalogInput(io::Pin(0,io::PortC));

variable to hold conversion result uint16_t l_conversionResult = 0;

enable and start conversion myADC.start();

---— Event loop ---— // while (1) {

```
    myADC.getConversionResult(&l_conversionResult, core::resolution::RES_16bit);

    if (myADC.conversionComplete())
    {
        l_data2Send[0] = '0' + (l_conversionResult / 10000);
        l_data2Send[1] = '0' + ((l_conversionResult / 1000) % 10);
        l_data2Send[2] = '0' + ((l_conversionResult / 100) % 10);
        l_data2Send[3] = '0' + ((l_conversionResult / 10) % 10);
        l_data2Send[4] = '0' + (l_conversionResult % 10);
        l_data2Send[5] = '\n';
        l_data2Send[6] = '\r';

        if (myUSART0.ready2Send())
        {
            myUSART0.sendFrame(reinterpret_cast<uint8_t*>(l_data2Send),TRANSMIT_BUFFER_SIZE);
        }

    }
}
}
return 0;
}
```

uint16_t value = 12345; char lo = value & 0xFF; char hi = value $>>$ 8;

Author

Farid Oubbati (https://github.com/faroub)

Date

March 2020

Definition in file [ADC.h](#).

7.4 ADC.h

```
00001
00078 #ifndef ADC_H
00079 #define ADC_H
00080 #include "ha_base.h"
00081 #include "Pin.h"
00082
00083
00084 namespace core
00085 {
00086
00087 enum class resolution : uint8_t {
00088     res_8bit=0,
00089     res_9bit,
00090     res_10bit,
00091     res_11bit,
00092     res_12bit,
00093     res_13bit,
00094     res_14bit,
00095     res_15bit,
00096     res_16bit
00097 };
00098
00099
00100 enum class referenceVoltage : uint8_t {
00101     AREF=0,
00102     AVCC,
00103     internal
00104 };
00105
00106
00107
00108 enum class clockPrescaler : uint8_t {
00109     PS_2 = 1,
00110     PS_4,
00111     PS_8,
00112     PS_16,
00113     PS_32,
00114     PS_64,
00115     PS_128
00116 };
00117
00118 enum class autoTriggerSource : uint8_t {
00119     freeRunning,
00120     analogComparator,
00121     extInterrupt,
00122     timer0Compare,
00123     timer0Overflow,
00124     timer1CompareB,
00125     timer1Overflow,
00126     timer1Capture
00127 };
00128
00129 class ADConverter
00130 {
00131 public:
00132
00133     static ADConverter& getInstance(const referenceVoltage& ar_refVoltage = referenceVoltage::AVCC,
00134                                     const clockPrescaler& ar_clockPrescaler = clockPrescaler::PS_128,
00135                                     const autoTriggerSource& ar_autoTriggerSource =
00136     autoTriggerSource::freeRunning,
00136                                     const io::Pin &ar_pin = io::Pin(0,io::PortC));
00137
00138     void start();
00139
00140     void stop();
00141
00142     void selectReferenceVoltage(const referenceVoltage& ar_refVoltage);
00143
00144     void selectAnalogInput(io::Pin a_pin);
00145
00146     void selectClockPrescaler(const clockPrescaler& ar_clockPrescaler);
00147
00148     void enableConversionCompleteInterrupt(const uint8_t a_enable);
00149
00150     void enableAutoTrigger(const uint8_t a_enable);
00151
00152     void selectAutoTriggerSource(const autoTriggerSource& ar_autoTriggerSource);
00153
00154     uint8_t conversionComplete();
00155
00156
00157     void getConversionResult(uint16_t *ap_resultData, const resolution& ar_resolution =
00158     resolution::res_10bit);
00158
00159
```

```
00160     static void conversionCompleteServiceRoutine() __asm__(STR(ADC_CONVERSION_COMPLETE_INTERRUPT))
          __attribute__((__signal__, __used__, __externally_visible__));
00161
00162
00163 protected:
00164
00165
00166
00167 private:
00168
00169     ADConverter(const referenceVoltage& ar_refVoltage,
00170                 const clockPrescaler& ar_clockPrescaler,
00171                 const autoTriggerSource &ar_autoTriggerSource,
00172                 const io::Pin &ar_pin);
00173
00176     ~ADConverter();
00177
00180     ADConverter(const ADConverter&);
00181
00184     const ADConverter& operator=(const ADConverter&);
00185
00186
00187     static volatile uint16_t *mp_conversionResult;
00190     static uint8_t m_resolution;
00192     static volatile uint8_t m_conversionComplete;
00199 };
00200
00201
00202
00203
00204
00205 }
00206 #endif
```

7.5 AnalogComparator.cpp File Reference

```
#include "AnalogComparator.h"
```
Include dependency graph for AnalogComparator.cpp:

7.6 AnalogComparator.cpp

```
00001 #include "AnalogComparator.h"
00002
00003
```

7.7 AnalogComparator.h File Reference

```
#include "ha_base.h"
```

Include dependency graph for AnalogComparator.h:

This graph shows which files directly or indirectly include this file:

Classes

- class [core::AnalogComparator](#)

Namespaces

- [core](#)

Macros

- #define [ANALOG_COMARATOR_H](#)

7.7.1 Macro Definition Documentation

7.7.1.1 ANALOG_COMARATOR_H

```
#define ANALOG_COMARATOR_H
```

Definition at line 13 of file [AnalogComparator.h](#).

7.8 AnalogComparator.h

```
00001
00012 #ifndef ANALOG_COMPARATOR_H
00013 #define ANALOG_COMARATOR_H
00014 #include "ha_base.h"
00015
00016
00017
00018 namespace core
00019 {
00020
00021
00022
00023
00024 class AnalogComparator
00025 {
00026
00027 public:
00028
00029
00030
00031
00032 protected:
00033
00034 private:
00035
00036
00037
00038 };
00039
00040 }
00041
00042
00043 #endif
```

7.9 Buzzer.cpp File Reference

```
#include "Buzzer.h"
```
Include dependency graph for Buzzer.cpp:

7.10 Buzzer.cpp

```
00001 #include "Buzzer.h"
00002
00003
00004 component::Buzzer::Buzzer(const io::Pin &ar_pin)
00005                 : m_pin(ar_pin)
00006 {
00007     m_pin.toOutput();
```

```
00008
00009 }
00010
00011 component::Buzzer::~Buzzer()
00012 {
00013
00014 }
00015
00016
00017
00018 void component::Buzzer::buzz(const uint16_t &ar_period_us , const uint16_t &ar_duration_ms)
00019 {
00020     uint32_t l_duration_us = ar_duration_ms*1000UL;
00021
00022     for (uint32_t i = 0; i < l_duration_us; i += ar_period_us)
00023     {
00024         /* For loop with variable delay selects the pitch */
00025         // _delay_us() needs a constant defined at compile time
00026         for (uint16_t j = 0; j < ar_period_us; j++)
00027         {
00028             _delay_us(1);
00029         }
00030         m_pin.toggle();
00031     }
00032     m_pin.setLow();
00033
00034 }
00035
00036
```

7.11 Buzzer.h File Reference

Header file of the Buzzer class.

```
#include "ha_base.h"
#include "Pin.h"
#include "TimerCounter.h"
```
Include dependency graph for Buzzer.h:

This graph shows which files directly or indirectly include this file:

Classes

- class component::Buzzer

Namespaces

- component

7.11.1 Detailed Description

Header file of the Buzzer class.

Usage example (test): #include "Buzzer.h" #include "TimerCounter0.h" #include "buzzer_pitches_8bit.h"

#define BUZZER 6

int main(void) {

Init instantiate the Buzzer object component::Buzzer Buzzer(io::Pin(BUZZER,io::PortD));

instantiate the TimerCounter0 object core::TimerCounter0 &myTimerCounter0 = core::TimerCounter0::getInstance();

notes in the melody: const uint16_t notes[] = {C2, E2, G2, C3};

```
for (uint8_t i = 0; i < sizeof (notes)/sizeof (uint16_t); i++)
{
    Buzzer.buzz(notes[i],200);

}

_delay_ms(1000);
_delay_ms(1000);
_delay_ms(1000);

for (uint8_t i = 0; i < sizeof (notes)/sizeof (uint16_t); i++)
{
    Buzzer.buzz(myTimerCounter0,notes[i],200);
}
```

-----— Event loop -----— // while (1) {

```
}
return 0;
```

```
}
```

Basic class for IO abstraction of Pin and Port

Author

> Farid Oubbati (https://github.com/faroub)

Date

> March 2020

Definition in file Buzzer.h.

7.12 Buzzer.h

```
00001
00058 #ifndef BUZZER_H
00059 #define BUZZER_H
00060 #include "ha_base.h"
00061 #include "Pin.h"
00062 #include "TimerCounter.h"
00063
00064 namespace component
00065 {
00066
00067
00068
00069 class Buzzer
00070 {
00071
00072 public:
00073
00074     Buzzer(const io::Pin &ar_pin);
00075
00076     ~Buzzer();
00077
00078     void buzz(const uint16_t &ar_period_us , const uint16_t &ar_duration_ms);
00079
00080     template<typename TC>
00081     void buzz(TC &ar_timerCounter,
00082             const uint16_t &ar_period_us,
00083             uint16_t &ar_duration_ms,
00084             const core::channel &ar_channel=core::channel::A,
00085             const core::clockSource &ar_clockSource= core::clockSource::PS_64
00086             )
00087     {
00088         ar_timerCounter.selectOperationMode(core::operationMode::CTC_OCR);
00089         ar_timerCounter.selectCompareOutputMode(ar_channel, core::compareOutputMode::toggle);
00090         ar_timerCounter.setCounter(0);
00091         ar_timerCounter.setOutputCompareRegister(ar_channel, ar_period_us);
00092         // start timer
00093         ar_timerCounter.start();
00094         // wait for the pitch duration
00095         while (ar_duration_ms) {
00096           _delay_ms(1);
00097           ar_duration_ms--;
00098         }
00099         // no buzz
00100         ar_timerCounter.selectCompareOutputMode(ar_channel, core::compareOutputMode::normal);
00101         ar_timerCounter.stop();
00102     }
00103
00104
00105 protected:
00106
00107 private:
00108
00109     io::Pin m_pin;
00112 };
00113 }
00114
00115
00116 #endif
```

7.13 buzzer_pitches_16bit.h File Reference

Macros

- #define C0 25000
- #define Cx0 23597
- #define D0 22272
- #define Dx0 21022
- #define E0 19843
- #define F0 18729
- #define Fx0 17678
- #define G0 16685
- #define Gx0 15749
- #define A0 14865
- #define Ax0 14031
- #define B0 13243
- #define C1 12500
- #define Cx1 11798
- #define D1 11136
- #define Dx1 10511
- #define E1 9921
- #define F1 9364
- #define Fx1 8839
- #define G1 8343
- #define Gx1 7875
- #define A1 7433
- #define Ax1 7015
- #define B1 6622
- #define C2 6250
- #define Cx2 5899
- #define D2 5568
- #define Dx2 5256
- #define E2 4961
- #define F2 4682
- #define Fx2 4419
- #define G2 4171
- #define Gx2 3937
- #define A2 3716
- #define Ax2 3508
- #define B2 3311
- #define C3 3125
- #define Cx3 2950
- #define D3 2784
- #define Dx3 2628
- #define E3 2480
- #define F3 2341
- #define Fx3 2210
- #define G3 2086
- #define Gx3 1969
- #define A3 1858
- #define Ax3 1754
- #define B3 1655
- #define C4 1562
- #define Cx4 1474

- #define D4 1392
- #define Dx4 1313
- #define E4 1240
- #define F4 1170
- #define Fx4 1105
- #define G4 1043
- #define Gx4 984
- #define A4 929
- #define Ax4 877
- #define B4 827
- #define C5 781
- #define Cx5 737
- #define D5 696
- #define Dx5 657
- #define E5 620
- #define F5 585
- #define Fx5 552
- #define G5 521
- #define Gx5 492
- #define A5 464
- #define Ax5 438
- #define B5 414
- #define C6 390
- #define Cx6 368
- #define D6 347
- #define Dx6 328
- #define E6 310
- #define F6 292
- #define Fx6 276
- #define G6 260
- #define Gx6 246
- #define A6 232
- #define Ax6 219
- #define B6 207
- #define C7 195
- #define Cx7 184
- #define D7 174
- #define Dx7 164
- #define E7 155
- #define F7 146
- #define Fx7 138
- #define G7 130
- #define Gx7 123
- #define A7 116
- #define Ax7 109
- #define B7 103

7.13.1 Macro Definition Documentation

7.13.1.1 A0

```
#define A0 14865
```

Definition at line 21 of file buzzer_pitches_16bit.h.

7.13.1.2 A1

```
#define A1 7433
```

Definition at line 33 of file buzzer_pitches_16bit.h.

7.13.1.3 A2

```
#define A2 3716
```

Definition at line 45 of file buzzer_pitches_16bit.h.

7.13.1.4 A3

```
#define A3 1858
```

Definition at line 57 of file buzzer_pitches_16bit.h.

7.13.1.5 A4

```
#define A4 929
```

Definition at line 69 of file buzzer_pitches_16bit.h.

7.13.1.6 A5

```
#define A5 464
```

Definition at line 81 of file buzzer_pitches_16bit.h.

7.13.1.7 A6

```
#define A6 232
```

Definition at line 93 of file buzzer_pitches_16bit.h.

7.13.1.8 A7

```
#define A7 116
```

Definition at line 105 of file buzzer_pitches_16bit.h.

7.13.1.9 Ax0

```
#define Ax0 14031
```

Definition at line 22 of file buzzer_pitches_16bit.h.

7.13.1.10 Ax1

```
#define Ax1 7015
```

Definition at line 34 of file buzzer_pitches_16bit.h.

7.13.1.11 Ax2

```
#define Ax2 3508
```

Definition at line 46 of file buzzer_pitches_16bit.h.

7.13.1.12 Ax3

```
#define Ax3 1754
```

Definition at line 58 of file buzzer_pitches_16bit.h.

7.13.1.13 Ax4

```
#define Ax4 877
```

Definition at line 70 of file buzzer_pitches_16bit.h.

7.13.1.14 Ax5

```
#define Ax5 438
```

Definition at line 82 of file buzzer_pitches_16bit.h.

7.13.1.15 Ax6

```
#define Ax6 219
```

Definition at line 94 of file buzzer_pitches_16bit.h.

7.13.1.16 Ax7

```
#define Ax7 109
```

Definition at line 106 of file buzzer_pitches_16bit.h.

7.13.1.17 B0

```
#define B0 13243
```

Definition at line 23 of file buzzer_pitches_16bit.h.

7.13.1.18 B1

```
#define B1 6622
```

Definition at line 35 of file buzzer_pitches_16bit.h.

7.13.1.19 B2

```
#define B2 3311
```

Definition at line 47 of file buzzer_pitches_16bit.h.

7.13.1.20 B3

```
#define B3 1655
```

Definition at line 59 of file buzzer_pitches_16bit.h.

7.13.1.21 B4

```
#define B4 827
```

Definition at line 71 of file buzzer_pitches_16bit.h.

7.13.1.22 B5

```
#define B5 414
```

Definition at line 83 of file buzzer_pitches_16bit.h.

7.13.1.23 B6

```
#define B6 207
```

Definition at line 95 of file buzzer_pitches_16bit.h.

7.13.1.24 B7

```
#define B7 103
```

Definition at line 107 of file buzzer_pitches_16bit.h.

7.13.1.25 C0

```
#define C0 25000
```

Definition at line 12 of file buzzer_pitches_16bit.h.

7.13.1.26 C1

```
#define C1 12500
```

Definition at line 24 of file buzzer_pitches_16bit.h.

7.13.1.27 C2

```
#define C2 6250
```

Definition at line 36 of file buzzer_pitches_16bit.h.

7.13.1.28 C3

```
#define C3 3125
```

Definition at line 48 of file buzzer_pitches_16bit.h.

7.13.1.29 C4

```
#define C4 1562
```

Definition at line 60 of file buzzer_pitches_16bit.h.

7.13.1.30 C5

```
#define C5 781
```

Definition at line 72 of file buzzer_pitches_16bit.h.

7.13.1.31 C6

```
#define C6 390
```

Definition at line 84 of file buzzer_pitches_16bit.h.

7.13.1.32 C7

```
#define C7 195
```

Definition at line 96 of file buzzer_pitches_16bit.h.

7.13.1.33 Cx0

```
#define Cx0 23597
```

Definition at line 13 of file buzzer_pitches_16bit.h.

7.13.1.34 Cx1

```
#define Cx1 11798
```

Definition at line 25 of file buzzer_pitches_16bit.h.

7.13.1.35 Cx2

```
#define Cx2 5899
```

Definition at line 37 of file buzzer_pitches_16bit.h.

7.13.1.36 Cx3

```
#define Cx3 2950
```

Definition at line 49 of file buzzer_pitches_16bit.h.

7.13.1.37 Cx4

```
#define Cx4 1474
```

Definition at line 61 of file buzzer_pitches_16bit.h.

7.13.1.38 Cx5

```
#define Cx5 737
```

Definition at line 73 of file buzzer_pitches_16bit.h.

7.13.1.39 Cx6

```
#define Cx6 368
```

Definition at line 85 of file buzzer_pitches_16bit.h.

7.13.1.40 Cx7

```
#define Cx7 184
```

Definition at line 97 of file buzzer_pitches_16bit.h.

7.13.1.41 D0

```
#define D0 22272
```

Definition at line 14 of file buzzer_pitches_16bit.h.

7.13.1.42 D1

```
#define D1 11136
```

Definition at line 26 of file buzzer_pitches_16bit.h.

7.13.1.43 D2

```
#define D2 5568
```

Definition at line 38 of file buzzer_pitches_16bit.h.

7.13.1.44 D3

```
#define D3 2784
```

Definition at line 50 of file buzzer_pitches_16bit.h.

7.13.1.45 D4

```
#define D4 1392
```

Definition at line 62 of file buzzer_pitches_16bit.h.

7.13.1.46 D5

```
#define D5 696
```

Definition at line 74 of file buzzer_pitches_16bit.h.

7.13.1.47 D6

```
#define D6 347
```

Definition at line 86 of file buzzer_pitches_16bit.h.

7.13.1.48 D7

```
#define D7 174
```

Definition at line 98 of file buzzer_pitches_16bit.h.

7.13.1.49 Dx0

```
#define Dx0 21022
```

Definition at line 15 of file buzzer_pitches_16bit.h.

7.13.1.50 Dx1

```
#define Dx1 10511
```

Definition at line 27 of file buzzer_pitches_16bit.h.

7.13.1.51 Dx2

```
#define Dx2 5256
```

Definition at line 39 of file buzzer_pitches_16bit.h.

7.13.1.52 Dx3

```
#define Dx3 2628
```

Definition at line 51 of file buzzer_pitches_16bit.h.

7.13.1.53 Dx4

```
#define Dx4 1313
```

Definition at line 63 of file buzzer_pitches_16bit.h.

7.13.1.54 Dx5

```
#define Dx5 657
```

Definition at line 75 of file buzzer_pitches_16bit.h.

7.13.1.55 Dx6

```
#define Dx6 328
```

Definition at line 87 of file buzzer_pitches_16bit.h.

7.13.1.56 Dx7

```
#define Dx7 164
```

Definition at line 99 of file buzzer_pitches_16bit.h.

7.13.1.57 E0

```
#define E0 19843
```

Definition at line 16 of file buzzer_pitches_16bit.h.

7.13.1.58 E1

```
#define E1 9921
```

Definition at line 28 of file buzzer_pitches_16bit.h.

7.13.1.59 E2

```
#define E2 4961
```

Definition at line 40 of file buzzer_pitches_16bit.h.

7.13.1.60 E3

```
#define E3 2480
```

Definition at line 52 of file buzzer_pitches_16bit.h.

7.13.1.61 E4

```
#define E4 1240
```

Definition at line 64 of file buzzer_pitches_16bit.h.

7.13.1.62 E5

```
#define E5 620
```

Definition at line 76 of file buzzer_pitches_16bit.h.

7.13.1.63 E6

```
#define E6 310
```

Definition at line 88 of file buzzer_pitches_16bit.h.

7.13.1.64 E7

```
#define E7 155
```

Definition at line 100 of file buzzer_pitches_16bit.h.

7.13.1.65 F0

```
#define F0 18729
```

Definition at line 17 of file buzzer_pitches_16bit.h.

7.13.1.66 F1

```
#define F1 9364
```

Definition at line 29 of file buzzer_pitches_16bit.h.

7.13.1.67 F2

```
#define F2 4682
```

Definition at line 41 of file buzzer_pitches_16bit.h.

7.13.1.68 F3

```
#define F3 2341
```

Definition at line 53 of file buzzer_pitches_16bit.h.

7.13.1.69 F4

```
#define F4 1170
```

Definition at line 65 of file buzzer_pitches_16bit.h.

7.13.1.70 F5

```
#define F5 585
```

Definition at line 77 of file buzzer_pitches_16bit.h.

7.13.1.71 F6

```
#define F6 292
```

Definition at line 89 of file buzzer_pitches_16bit.h.

7.13.1.72 F7

```
#define F7 146
```

Definition at line 101 of file buzzer_pitches_16bit.h.

7.13.1.73 Fx0

```
#define Fx0 17678
```

Definition at line 18 of file buzzer_pitches_16bit.h.

7.13.1.74 Fx1

```
#define Fx1 8839
```

Definition at line 30 of file buzzer_pitches_16bit.h.

7.13.1.75 Fx2

```
#define Fx2 4419
```

Definition at line 42 of file buzzer_pitches_16bit.h.

7.13.1.76 Fx3

```
#define Fx3 2210
```

Definition at line 54 of file buzzer_pitches_16bit.h.

7.13.1.77 Fx4

```
#define Fx4 1105
```

Definition at line 66 of file buzzer_pitches_16bit.h.

7.13.1.78 Fx5

```
#define Fx5 552
```

Definition at line 78 of file buzzer_pitches_16bit.h.

7.13.1.79 Fx6

```
#define Fx6 276
```

Definition at line 90 of file buzzer_pitches_16bit.h.

7.13.1.80 Fx7

```
#define Fx7 138
```

Definition at line 102 of file buzzer_pitches_16bit.h.

7.13.1.81 G0

```
#define G0 16685
```

Definition at line 19 of file buzzer_pitches_16bit.h.

7.13.1.82 G1

```
#define G1 8343
```

Definition at line 31 of file buzzer_pitches_16bit.h.

7.13.1.83 G2

```
#define G2 4171
```

Definition at line 43 of file buzzer_pitches_16bit.h.

7.13.1.84 G3

```
#define G3 2086
```

Definition at line 55 of file buzzer_pitches_16bit.h.

7.13.1.85 G4

```
#define G4 1043
```

Definition at line 67 of file buzzer_pitches_16bit.h.

7.13.1.86 G5

```
#define G5 521
```

Definition at line 79 of file buzzer_pitches_16bit.h.

7.13.1.87 G6

```
#define G6 260
```

Definition at line 91 of file buzzer_pitches_16bit.h.

7.13.1.88 G7

```
#define G7 130
```

Definition at line 103 of file buzzer_pitches_16bit.h.

7.13.1.89 Gx0

```
#define Gx0 15749
```

Definition at line 20 of file buzzer_pitches_16bit.h.

7.13.1.90 Gx1

```
#define Gx1 7875
```

Definition at line 32 of file buzzer_pitches_16bit.h.

7.13.1.91 Gx2

```
#define Gx2 3937
```

Definition at line 44 of file buzzer_pitches_16bit.h.

7.13.1.92 Gx3

```
#define Gx3 1969
```

Definition at line 56 of file buzzer_pitches_16bit.h.

7.13.1.93 Gx4

```
#define Gx4 984
```

Definition at line 68 of file buzzer_pitches_16bit.h.

7.13.1.94 Gx5

```
#define Gx5 492
```

Definition at line 80 of file buzzer_pitches_16bit.h.

7.13.1.95 Gx6

```
#define Gx6 246
```

Definition at line 92 of file buzzer_pitches_16bit.h.

7.13.1.96 Gx7

```
#define Gx7 123
```

Definition at line 104 of file buzzer_pitches_16bit.h.

7.14 buzzer_pitches_16bit.h

```
00001 /* Scale in the key of 1/25000 */
00002 /*
00003    These are 1/2 periods (us) -- if you delay this long,
00004    then toggle the speaker pin, you'll get approximate
00005    pitches.
00006
00007    This is the 16-bit version.  The pitches get less accurate
00008    as they get higher.
00009
00010 */
00011
00012 #define  C0    25000 // freq = 1000000/ (2*25000) = 20hz
00013 #define  Cx0   23597
00014 #define  D0    22272
00015 #define  Dx0   21022
00016 #define  E0    19843
00017 #define  F0    18729
00018 #define  Fx0   17678
00019 #define  G0    16685
00020 #define  Gx0   15749
00021 #define  A0    14865
00022 #define  Ax0   14031
00023 #define  B0    13243
00024 #define  C1    12500
00025 #define  Cx1   11798
00026 #define  D1    11136
00027 #define  Dx1   10511
00028 #define  E1     9921
00029 #define  F1     9364
00030 #define  Fx1    8839
00031 #define  G1     8343
00032 #define  Gx1    7875
00033 #define  A1     7433
00034 #define  Ax1    7015
00035 #define  B1     6622
00036 #define  C2     6250
00037 #define  Cx2    5899
00038 #define  D2     5568
00039 #define  Dx2    5256
00040 #define  E2     4961
00041 #define  F2     4682
00042 #define  Fx2    4419
00043 #define  G2     4171
00044 #define  Gx2    3937
00045 #define  A2     3716
00046 #define  Ax2    3508
00047 #define  B2     3311
00048 #define  C3     3125
00049 #define  Cx3    2950
00050 #define  D3     2784
00051 #define  Dx3    2628
00052 #define  E3     2480
00053 #define  F3     2341
00054 #define  Fx3    2210
00055 #define  G3     2086
00056 #define  Gx3    1969
00057 #define  A3     1858
00058 #define  Ax3    1754
00059 #define  B3     1655
00060 #define  C4     1562
00061 #define  Cx4    1474
00062 #define  D4     1392
00063 #define  Dx4    1313
00064 #define  E4     1240
00065 #define  F4     1170
00066 #define  Fx4    1105
00067 #define  G4     1043
00068 #define  Gx4     984
00069 #define  A4      929
00070 #define  Ax4     877
00071 #define  B4      827
00072 #define  C5      781
00073 #define  Cx5     737
00074 #define  D5      696
00075 #define  Dx5     657
00076 #define  E5      620
00077 #define  F5      585
00078 #define  Fx5     552
00079 #define  G5      521
00080 #define  Gx5     492
00081 #define  A5      464
00082 #define  Ax5     438
00083 #define  B5      414
00084 #define  C6      390
00085 #define  Cx6     368
```

```
00086 #define  D6     347
00087 #define  Dx6    328
00088 #define  E6     310
00089 #define  F6     292
00090 #define  Fx6    276
00091 #define  G6     260
00092 #define  Gx6    246
00093 #define  A6     232
00094 #define  Ax6    219
00095 #define  B6     207
00096 #define  C7     195
00097 #define  Cx7    184
00098 #define  D7     174
00099 #define  Dx7    164
00100 #define  E7     155
00101 #define  F7     146
00102 #define  Fx7    138
00103 #define  G7     130
00104 #define  Gx7    123
00105 #define  A7     116
00106 #define  Ax7    109
00107 #define  B7     103 // freq = 1000000/ (2*103) = 4.85 khz
```

7.15 buzzer_pitches_8bit.h File Reference

Macros

- #define Gx0 252
- #define A0 238
- #define Ax0 224
- #define B0 212
- #define C1 200
- #define Cx0 189
- #define D1 178
- #define Dx0 168
- #define E1 159
- #define F1 150
- #define Fx1 141
- #define G1 133
- #define Gx1 126
- #define A1 119
- #define Ax1 112
- #define B1 106
- #define C2 100
- #define Cx2 94
- #define D2 89
- #define Dx2 84
- #define E2 79
- #define F2 75
- #define Fx2 71
- #define G2 67
- #define Gx2 63
- #define A2 59
- #define Ax2 56
- #define B2 53
- #define C3 50
- #define Cx3 47
- #define D3 44
- #define Dx3 42
- #define E3 40
- #define F3 37
- #define Fx3 35
- #define G3 33

7.15.1 Macro Definition Documentation

7.15.1.1 A0

```
#define A0 238
```

Definition at line 14 of file buzzer_pitches_8bit.h.

7.15.1.2 A1

```
#define A1 119
```

Definition at line 26 of file buzzer_pitches_8bit.h.

7.15.1.3 A2

```
#define A2 59
```

Definition at line 38 of file buzzer_pitches_8bit.h.

7.15.1.4 Ax0

```
#define Ax0 224
```

Definition at line 15 of file buzzer_pitches_8bit.h.

7.15.1.5 Ax1

```
#define Ax1 112
```

Definition at line 27 of file buzzer_pitches_8bit.h.

7.15.1.6 Ax2

```
#define Ax2 56
```

Definition at line 39 of file buzzer_pitches_8bit.h.

7.15.1.7 B0

```
#define B0 212
```

Definition at line 16 of file buzzer_pitches_8bit.h.

7.15.1.8 B1

```
#define B1 106
```

Definition at line 28 of file buzzer_pitches_8bit.h.

7.15.1.9 B2

```
#define B2 53
```

Definition at line 40 of file buzzer_pitches_8bit.h.

7.15.1.10 C1

```
#define C1 200
```

Definition at line 17 of file buzzer_pitches_8bit.h.

7.15.1.11 C2

```
#define C2 100
```

Definition at line 29 of file buzzer_pitches_8bit.h.

7.15.1.12 C3

```
#define C3 50
```

Definition at line 41 of file buzzer_pitches_8bit.h.

7.15.1.13 Cx0

```
#define Cx0 189
```

Definition at line 18 of file buzzer_pitches_8bit.h.

7.15.1.14 Cx2

```
#define Cx2 94
```

Definition at line 30 of file buzzer_pitches_8bit.h.

7.15.1.15 Cx3

```
#define Cx3 47
```

Definition at line 42 of file buzzer_pitches_8bit.h.

7.15.1.16 D1

```
#define D1 178
```

Definition at line 19 of file buzzer_pitches_8bit.h.

7.15.1.17 D2

```
#define D2 89
```

Definition at line 31 of file buzzer_pitches_8bit.h.

7.15.1.18 D3

```
#define D3 44
```

Definition at line 43 of file buzzer_pitches_8bit.h.

7.15.1.19 Dx0

```
#define Dx0 168
```

Definition at line 20 of file buzzer_pitches_8bit.h.

7.15.1.20 Dx2

```
#define Dx2 84
```

Definition at line 32 of file buzzer_pitches_8bit.h.

7.15.1.21 Dx3

```
#define Dx3 42
```

Definition at line 44 of file buzzer_pitches_8bit.h.

7.15.1.22 E1

```
#define E1 159
```

Definition at line 21 of file buzzer_pitches_8bit.h.

7.15.1.23 E2

```
#define E2 79
```

Definition at line 33 of file buzzer_pitches_8bit.h.

7.15.1.24 E3

```
#define E3 40
```

Definition at line 45 of file buzzer_pitches_8bit.h.

7.15.1.25 F1

```
#define F1 150
```

Definition at line 22 of file buzzer_pitches_8bit.h.

7.15.1.26 F2

```
#define F2 75
```

Definition at line 34 of file buzzer_pitches_8bit.h.

7.15.1.27 F3

```
#define F3 37
```

Definition at line 46 of file buzzer_pitches_8bit.h.

7.15.1.28 Fx1

```
#define Fx1 141
```

Definition at line 23 of file buzzer_pitches_8bit.h.

7.15.1.29 Fx2

```
#define Fx2 71
```

Definition at line 35 of file buzzer_pitches_8bit.h.

7.15.1.30 Fx3

```
#define Fx3 35
```

Definition at line 47 of file buzzer_pitches_8bit.h.

7.15.1.31 G1

```
#define G1 133
```

Definition at line 24 of file buzzer_pitches_8bit.h.

7.15.1.32 G2

```
#define G2 67
```

Definition at line 36 of file buzzer_pitches_8bit.h.

7.15.1.33 G3

```
#define G3 33
```

Definition at line 48 of file buzzer_pitches_8bit.h.

7.15.1.34 Gx0

```
#define Gx0 252
```

Definition at line 13 of file buzzer_pitches_8bit.h.

7.15.1.35 Gx1

```
#define Gx1 126
```

Definition at line 25 of file buzzer_pitches_8bit.h.

7.15.1.36 Gx2

```
#define Gx2 63
```

Definition at line 37 of file buzzer_pitches_8bit.h.

7.16 buzzer_pitches_8bit.h

```
00001 /* Scale in the key of 1/200 */
00002
00003 /*
00004    These are 1/2 periods (us) -- if you delay this long,
00005    then toggle the speaker pin, you'll get approximate
00006    pitches.
00007
00008    This is the 8-bit version.  The pitches get less accurate
00009    as they get higher.
00010
00011 */
00012
00013 #define Gx0 252 // freq = 1000000/ (2*252) = 1.98 khz
00014 #define A0   238
00015 #define Ax0  224
00016 #define B0   212
00017 #define C1   200
00018 #define Cx0  189
00019 #define D1   178
00020 #define Dx0  168
00021 #define E1   159
00022 #define F1   150
00023 #define Fx1  141
00024 #define G1   133
00025 #define Gx1  126
00026 #define A1   119
00027 #define Ax1  112
00028 #define B1   106
00029 #define C2   100
00030 #define Cx2  94
00031 #define D2   89
00032 #define Dx2  84
00033 #define E2   79
00034 #define F2   75
00035 #define Fx2  71
00036 #define G2   67
00037 #define Gx2  63
00038 #define A2   59
00039 #define Ax2  56
00040 #define B2   53
00041 #define C3   50
00042 #define Cx3  47
00043 #define D3   44
00044 #define Dx3  42
00045 #define E3   40
00046 #define F3   37
00047 #define Fx3  35
00048 #define G3   33 // freq = 1000000/ (2*33) = 15.15 khz
```

7.17 CMakeCXXCompilerId.cpp File Reference

Macros

- #define COMPILER_ID ""
- #define STRINGIFY_HELPER(X) #X
- #define STRINGIFY(X) STRINGIFY_HELPER(X)
- #define PLATFORM_ID
- #define ARCHITECTURE_ID
- #define DEC(n)
- #define HEX(n)
- #define CXX_STD __cplusplus

Functions

- int main (int argc, char ∗argv[ ])

Variables

- char const ∗ info_compiler = "INFO" ":" "compiler[" COMPILER_ID "]"
- char const ∗ info_platform = "INFO" ":" "platform[" PLATFORM_ID "]"
- char const ∗ info_arch = "INFO" ":" "arch[" ARCHITECTURE_ID "]"
- const char ∗ info_language_dialect_default

7.17.1 Macro Definition Documentation

7.17.1.1 ARCHITECTURE_ID

```
#define ARCHITECTURE_ID
```

Definition at line 513 of file CMakeCXXCompilerId.cpp.

7.17.1.2 COMPILER_ID

```
#define COMPILER_ID ""
```

Definition at line 308 of file CMakeCXXCompilerId.cpp.

7.17.1.3 CXX_STD

```
#define CXX_STD __cplusplus
```

Definition at line 596 of file CMakeCXXCompilerId.cpp.

7.17.1.4 DEC

```
#define DEC(
              n )
```

Value:
```
  ('0' + (((n) / 10000000)%10)), \
  ('0' + (((n) / 1000000)%10)),  \
  ('0' + (((n) / 100000)%10)),   \
  ('0' + (((n) / 10000)%10)),    \
  ('0' + (((n) / 1000)%10)),     \
  ('0' + (((n) / 100)%10)),      \
  ('0' + (((n) / 10)%10)),       \
  ('0' +  ((n) % 10))
```

Definition at line 517 of file CMakeCXXCompilerId.cpp.

7.17.1.5 HEX

```
#define HEX(
                n )
```

Value:
```
   ('0' + ((n)»28 & 0xF)), \
   ('0' + ((n)»24 & 0xF)), \
   ('0' + ((n)»20 & 0xF)), \
   ('0' + ((n)»16 & 0xF)), \
   ('0' + ((n)»12 & 0xF)), \
   ('0' + ((n)»8  & 0xF)), \
   ('0' + ((n)»4  & 0xF)), \
   ('0' + ((n)    & 0xF))
```

Definition at line 528 of file CMakeCXXCompilerId.cpp.

7.17.1.6 PLATFORM_ID

```
#define PLATFORM_ID
```

Definition at line 430 of file CMakeCXXCompilerId.cpp.

7.17.1.7 STRINGIFY

```
#define STRINGIFY(
                X ) STRINGIFY_HELPER(X)
```

Definition at line 329 of file CMakeCXXCompilerId.cpp.

7.17.1.8 STRINGIFY_HELPER

```
#define STRINGIFY_HELPER(
                X ) #X
```

Definition at line 328 of file CMakeCXXCompilerId.cpp.

7.17.2 Function Documentation

7.17.2.1 main()

```
int main (
            int argc,
            char * argv[] )
```

Definition at line 615 of file CMakeCXXCompilerId.cpp.

```
00616 {
00617   int require = 0;
00618   require += info_compiler[argc];
00619   require += info_platform[argc];
00620 #ifdef COMPILER_VERSION_MAJOR
00621   require += info_version[argc];
00622 #endif
00623 #ifdef COMPILER_VERSION_INTERNAL
00624   require += info_version_internal[argc];
00625 #endif
00626 #ifdef SIMULATE_ID
00627   require += info_simulate[argc];
00628 #endif
00629 #ifdef SIMULATE_VERSION_MAJOR
00630   require += info_simulate_version[argc];
00631 #endif
00632 #if defined(__CRAYXE) || defined(__CRAYXC)
00633   require += info_cray[argc];
00634 #endif
00635   require += info_language_dialect_default[argc];
00636   (void)argv;
00637   return require;
00638 }
```

References info_compiler, info_language_dialect_default, and info_platform.

7.17.3 Variable Documentation

7.17.3.1 info_arch

```
char const* info_arch = "INFO" ":" "arch[" ARCHITECTURE_ID "]"
```

Definition at line 588 of file CMakeCXXCompilerId.cpp.

7.17.3.2 info_compiler

```
char const* info_compiler = "INFO" ":" "compiler[" COMPILER_ID "]"
```

Definition at line 315 of file CMakeCXXCompilerId.cpp.

Referenced by main().

7.17.3.3 info_language_dialect_default

const char* info_language_dialect_default

Initial value:
```
= "INFO" ":" "dialect_default["
  "98"
"]"
```

Definition at line 599 of file CMakeCXXCompilerId.cpp.

Referenced by main().

7.17.3.4 info_platform

char const* info_platform = "INFO" ":" "platform[" PLATFORM_ID "]"

Definition at line 587 of file CMakeCXXCompilerId.cpp.

Referenced by main().

7.18 CMakeCXXCompilerId.cpp

```
00001 /* This source file must have a .cpp extension so that all C++ compilers
00002    recognize the extension without flags.  Borland does not know .cxx for
00003    example.  */
00004 #ifndef __cplusplus
00005 # error "A C compiler has been selected for C++."
00006 #endif
00007
00008
00009 /* Version number components: V=Version, R=Revision, P=Patch
00010    Version date components:   YYYY=Year, MM=Month,   DD=Day  */
00011
00012 #if defined(__COMO__)
00013 # define COMPILER_ID "Comeau"
00014   /* __COMO_VERSION__ = VRR */
00015 # define COMPILER_VERSION_MAJOR DEC(__COMO_VERSION__ / 100)
00016 # define COMPILER_VERSION_MINOR DEC(__COMO_VERSION__ % 100)
00017
00018 #elif defined(__INTEL_COMPILER) || defined(__ICC)
00019 # define COMPILER_ID "Intel"
00020 # if defined(_MSC_VER)
00021 #  define SIMULATE_ID "MSVC"
00022 # endif
00023   /* __INTEL_COMPILER = VRP */
00024 # define COMPILER_VERSION_MAJOR DEC(__INTEL_COMPILER/100)
00025 # define COMPILER_VERSION_MINOR DEC(__INTEL_COMPILER/10 % 10)
00026 # if defined(__INTEL_COMPILER_UPDATE)
00027 #  define COMPILER_VERSION_PATCH DEC(__INTEL_COMPILER_UPDATE)
00028 # else
00029 #  define COMPILER_VERSION_PATCH DEC(__INTEL_COMPILER   % 10)
00030 # endif
00031 # if defined(__INTEL_COMPILER_BUILD_DATE)
00032   /* __INTEL_COMPILER_BUILD_DATE = YYYYMMDD */
00033 #  define COMPILER_VERSION_TWEAK DEC(__INTEL_COMPILER_BUILD_DATE)
00034 # endif
00035 # if defined(_MSC_VER)
00036   /* _MSC_VER = VVRR */
00037 #  define SIMULATE_VERSION_MAJOR DEC(_MSC_VER / 100)
00038 #  define SIMULATE_VERSION_MINOR DEC(_MSC_VER % 100)
00039 # endif
00040
00041 #elif defined(__PATHCC__)
00042 # define COMPILER_ID "PathScale"
00043 # define COMPILER_VERSION_MAJOR DEC(__PATHCC__)
00044 # define COMPILER_VERSION_MINOR DEC(__PATHCC_MINOR__)
00045 # if defined(__PATHCC_PATCHLEVEL__)
00046 #  define COMPILER_VERSION_PATCH DEC(__PATHCC_PATCHLEVEL__)
```

```
00047 # endif
00048
00049 #elif defined(__BORLANDC__) && defined(__CODEGEARC_VERSION__)
00050 # define COMPILER_ID "Embarcadero"
00051 # define COMPILER_VERSION_MAJOR HEX(__CODEGEARC_VERSION__»24 & 0x00FF)
00052 # define COMPILER_VERSION_MINOR HEX(__CODEGEARC_VERSION__»16 & 0x00FF)
00053 # define COMPILER_VERSION_PATCH DEC(__CODEGEARC_VERSION__    & 0xFFFF)
00054
00055 #elif defined(__BORLANDC__)
00056 # define COMPILER_ID "Borland"
00057  /* __BORLANDC__ = 0xVRR */
00058 # define COMPILER_VERSION_MAJOR HEX(__BORLANDC__»8)
00059 # define COMPILER_VERSION_MINOR HEX(__BORLANDC__ & 0xFF)
00060
00061 #elif defined(__WATCOMC__) && __WATCOMC__ < 1200
00062 # define COMPILER_ID "Watcom"
00063   /* __WATCOMC__ = VVRR */
00064 # define COMPILER_VERSION_MAJOR DEC(__WATCOMC__ / 100)
00065 # define COMPILER_VERSION_MINOR DEC((__WATCOMC__ / 10) % 10)
00066 # if (__WATCOMC__ % 10) > 0
00067 #  define COMPILER_VERSION_PATCH DEC(__WATCOMC__ % 10)
00068 # endif
00069
00070 #elif defined(__WATCOMC__)
00071 # define COMPILER_ID "OpenWatcom"
00072   /* __WATCOMC__ = VVRP + 1100 */
00073 # define COMPILER_VERSION_MAJOR DEC((__WATCOMC__ - 1100) / 100)
00074 # define COMPILER_VERSION_MINOR DEC((__WATCOMC__ / 10) % 10)
00075 # if (__WATCOMC__ % 10) > 0
00076 #  define COMPILER_VERSION_PATCH DEC(__WATCOMC__ % 10)
00077 # endif
00078
00079 #elif defined(__SUNPRO_CC)
00080 # define COMPILER_ID "SunPro"
00081 # if __SUNPRO_CC >= 0x5100
00082   /* __SUNPRO_CC = 0xVRRP */
00083 #  define COMPILER_VERSION_MAJOR HEX(__SUNPRO_CC»12)
00084 #  define COMPILER_VERSION_MINOR HEX(__SUNPRO_CC»4 & 0xFF)
00085 #  define COMPILER_VERSION_PATCH HEX(__SUNPRO_CC    & 0xF)
00086 # else
00087   /* __SUNPRO_CC = 0xVRP */
00088 #  define COMPILER_VERSION_MAJOR HEX(__SUNPRO_CC»8)
00089 #  define COMPILER_VERSION_MINOR HEX(__SUNPRO_CC»4 & 0xF)
00090 #  define COMPILER_VERSION_PATCH HEX(__SUNPRO_CC    & 0xF)
00091 # endif
00092
00093 #elif defined(__HP_aCC)
00094 # define COMPILER_ID "HP"
00095  /* __HP_aCC = VVRRPP */
00096 # define COMPILER_VERSION_MAJOR DEC(__HP_aCC/10000)
00097 # define COMPILER_VERSION_MINOR DEC(__HP_aCC/100 % 100)
00098 # define COMPILER_VERSION_PATCH DEC(__HP_aCC    % 100)
00099
00100 #elif defined(__DECCXX)
00101 # define COMPILER_ID "Compaq"
00102  /* __DECCXX_VER = VVRRTPPPP */
00103 # define COMPILER_VERSION_MAJOR DEC(__DECCXX_VER/10000000)
00104 # define COMPILER_VERSION_MINOR DEC(__DECCXX_VER/100000  % 100)
00105 # define COMPILER_VERSION_PATCH DEC(__DECCXX_VER        % 10000)
00106
00107 #elif defined(__IBMCPP__) && defined(__COMPILER_VER__)
00108 # define COMPILER_ID "zOS"
00109 # if defined(__ibmxl__)
00110 #  define COMPILER_VERSION_MAJOR DEC(__ibmxl_version__)
00111 #  define COMPILER_VERSION_MINOR DEC(__ibmxl_release__)
00112 #  define COMPILER_VERSION_PATCH DEC(__ibmxl_modification__)
00113 #  define COMPILER_VERSION_TWEAK DEC(__ibmxl_ptf_fix_level__)
00114 # else
00115   /* __IBMCPP__ = VRP */
00116 #  define COMPILER_VERSION_MAJOR DEC(__IBMCPP__/100)
00117 #  define COMPILER_VERSION_MINOR DEC(__IBMCPP__/10 % 10)
00118 #  define COMPILER_VERSION_PATCH DEC(__IBMCPP__    % 10)
00119 # endif
00120
00121
00122 #elif defined(__ibmxl__) || (defined(__IBMCPP__) && !defined(__COMPILER_VER__) && __IBMCPP__ >= 800)
00123 # define COMPILER_ID "XL"
00124 # if defined(__ibmxl__)
00125 #  define COMPILER_VERSION_MAJOR DEC(__ibmxl_version__)
00126 #  define COMPILER_VERSION_MINOR DEC(__ibmxl_release__)
00127 #  define COMPILER_VERSION_PATCH DEC(__ibmxl_modification__)
00128 #  define COMPILER_VERSION_TWEAK DEC(__ibmxl_ptf_fix_level__)
00129 # else
00130   /* __IBMCPP__ = VRP */
00131 #  define COMPILER_VERSION_MAJOR DEC(__IBMCPP__/100)
00132 #  define COMPILER_VERSION_MINOR DEC(__IBMCPP__/10 % 10)
00133 #  define COMPILER_VERSION_PATCH DEC(__IBMCPP__    % 10)
```

```
00134 # endif
00135
00136
00137 #elif defined(__IBMCPP__) && !defined(__COMPILER_VER__) && __IBMCPP__ < 800
00138 # define COMPILER_ID "VisualAge"
00139 # if defined(__ibmxl__)
00140 #  define COMPILER_VERSION_MAJOR DEC(__ibmxl_version__)
00141 #  define COMPILER_VERSION_MINOR DEC(__ibmxl_release__)
00142 #  define COMPILER_VERSION_PATCH DEC(__ibmxl_modification__)
00143 #  define COMPILER_VERSION_TWEAK DEC(__ibmxl_ptf_fix_level__)
00144 # else
00145   /* __IBMCPP__ = VRP */
00146 #  define COMPILER_VERSION_MAJOR DEC(__IBMCPP__/100)
00147 #  define COMPILER_VERSION_MINOR DEC(__IBMCPP__/10 % 10)
00148 #  define COMPILER_VERSION_PATCH DEC(__IBMCPP__    % 10)
00149 # endif
00150
00151
00152 #elif defined(__PGI)
00153 # define COMPILER_ID "PGI"
00154 # define COMPILER_VERSION_MAJOR DEC(__PGIC__)
00155 # define COMPILER_VERSION_MINOR DEC(__PGIC_MINOR__)
00156 # if defined(__PGIC_PATCHLEVEL__)
00157 #  define COMPILER_VERSION_PATCH DEC(__PGIC_PATCHLEVEL__)
00158 # endif
00159
00160 #elif defined(_CRAYC)
00161 # define COMPILER_ID "Cray"
00162 # define COMPILER_VERSION_MAJOR DEC(_RELEASE_MAJOR)
00163 # define COMPILER_VERSION_MINOR DEC(_RELEASE_MINOR)
00164
00165 #elif defined(__TI_COMPILER_VERSION__)
00166 # define COMPILER_ID "TI"
00167   /* __TI_COMPILER_VERSION__ = VVVRRRPPP */
00168 # define COMPILER_VERSION_MAJOR DEC(__TI_COMPILER_VERSION__/1000000)
00169 # define COMPILER_VERSION_MINOR DEC(__TI_COMPILER_VERSION__/1000   % 1000)
00170 # define COMPILER_VERSION_PATCH DEC(__TI_COMPILER_VERSION__        % 1000)
00171
00172 #elif defined(__FUJITSU) || defined(__FCC_VERSION) || defined(__fcc_version)
00173 # define COMPILER_ID "Fujitsu"
00174
00175 #elif defined(__ghs__)
00176 # define COMPILER_ID "GHS"
00177 /* __GHS_VERSION_NUMBER = VVVVRP */
00178 # ifdef __GHS_VERSION_NUMBER
00179 # define COMPILER_VERSION_MAJOR DEC(__GHS_VERSION_NUMBER / 100)
00180 # define COMPILER_VERSION_MINOR DEC(__GHS_VERSION_NUMBER / 10 % 10)
00181 # define COMPILER_VERSION_PATCH DEC(__GHS_VERSION_NUMBER      % 10)
00182 # endif
00183
00184 #elif defined(__SCO_VERSION__)
00185 # define COMPILER_ID "SCO"
00186
00187 #elif defined(__clang__) && defined(__apple_build_version__)
00188 # define COMPILER_ID "AppleClang"
00189 # if defined(_MSC_VER)
00190 #  define SIMULATE_ID "MSVC"
00191 # endif
00192 # define COMPILER_VERSION_MAJOR DEC(__clang_major__)
00193 # define COMPILER_VERSION_MINOR DEC(__clang_minor__)
00194 # define COMPILER_VERSION_PATCH DEC(__clang_patchlevel__)
00195 # if defined(_MSC_VER)
00196   /* _MSC_VER = VVRR */
00197 #  define SIMULATE_VERSION_MAJOR DEC(_MSC_VER / 100)
00198 #  define SIMULATE_VERSION_MINOR DEC(_MSC_VER % 100)
00199 # endif
00200 # define COMPILER_VERSION_TWEAK DEC(__apple_build_version__)
00201
00202 #elif defined(__clang__)
00203 # define COMPILER_ID "Clang"
00204 # if defined(_MSC_VER)
00205 #  define SIMULATE_ID "MSVC"
00206 # endif
00207 # define COMPILER_VERSION_MAJOR DEC(__clang_major__)
00208 # define COMPILER_VERSION_MINOR DEC(__clang_minor__)
00209 # define COMPILER_VERSION_PATCH DEC(__clang_patchlevel__)
00210 # if defined(_MSC_VER)
00211   /* _MSC_VER = VVRR */
00212 #  define SIMULATE_VERSION_MAJOR DEC(_MSC_VER / 100)
00213 #  define SIMULATE_VERSION_MINOR DEC(_MSC_VER % 100)
00214 # endif
00215
00216 #elif defined(__GNUC__) || defined(__GNUG__)
00217 # define COMPILER_ID "GNU"
00218 # if defined(__GNUC__)
00219 #  define COMPILER_VERSION_MAJOR DEC(__GNUC__)
00220 # else
```

```
00221 #  define COMPILER_VERSION_MAJOR DEC(__GNUG__)
00222 # endif
00223 # if defined(__GNUC_MINOR__)
00224 #  define COMPILER_VERSION_MINOR DEC(__GNUC_MINOR__)
00225 # endif
00226 # if defined(__GNUC_PATCHLEVEL__)
00227 #  define COMPILER_VERSION_PATCH DEC(__GNUC_PATCHLEVEL__)
00228 # endif
00229
00230 #elif defined(_MSC_VER)
00231 # define COMPILER_ID "MSVC"
00232   /* _MSC_VER = VVRR */
00233 # define COMPILER_VERSION_MAJOR DEC(_MSC_VER / 100)
00234 # define COMPILER_VERSION_MINOR DEC(_MSC_VER % 100)
00235 # if defined(_MSC_FULL_VER)
00236 #  if _MSC_VER >= 1400
00237     /* _MSC_FULL_VER = VVRRPPPPP */
00238 #   define COMPILER_VERSION_PATCH DEC(_MSC_FULL_VER % 100000)
00239 #  else
00240     /* _MSC_FULL_VER = VVRRPPPP */
00241 #   define COMPILER_VERSION_PATCH DEC(_MSC_FULL_VER % 10000)
00242 #  endif
00243 # endif
00244 # if defined(_MSC_BUILD)
00245 #  define COMPILER_VERSION_TWEAK DEC(_MSC_BUILD)
00246 # endif
00247
00248 #elif defined(__VISUALDSPVERSION__) || defined(__ADSPBLACKFIN__) || defined(__ADSPTS__) ||
      defined(__ADSP21000__)
00249 # define COMPILER_ID "ADSP"
00250 #if defined(__VISUALDSPVERSION__)
00251   /* __VISUALDSPVERSION__ = 0xVVRRPP00 */
00252 # define COMPILER_VERSION_MAJOR HEX(__VISUALDSPVERSION__»24)
00253 # define COMPILER_VERSION_MINOR HEX(__VISUALDSPVERSION__»16 & 0xFF)
00254 # define COMPILER_VERSION_PATCH HEX(__VISUALDSPVERSION__»8  & 0xFF)
00255 #endif
00256
00257 #elif defined(__IAR_SYSTEMS_ICC__) || defined(__IAR_SYSTEMS_ICC)
00258 # define COMPILER_ID "IAR"
00259 # if defined(__VER__) && defined(__ICCARM__)
00260 #  define COMPILER_VERSION_MAJOR DEC((__VER__) / 1000000)
00261 #  define COMPILER_VERSION_MINOR DEC(((__VER__) / 1000) % 1000)
00262 #  define COMPILER_VERSION_PATCH DEC((__VER__) % 1000)
00263 #  define COMPILER_VERSION_INTERNAL DEC(__IAR_SYSTEMS_ICC__)
00264 # elif defined(__VER__) && defined(__ICCAVR__)
00265 #  define COMPILER_VERSION_MAJOR DEC((__VER__) / 100)
00266 #  define COMPILER_VERSION_MINOR DEC((__VER__) - (((__VER__) / 100)*100))
00267 #  define COMPILER_VERSION_PATCH DEC(__SUBVERSION__)
00268 #  define COMPILER_VERSION_INTERNAL DEC(__IAR_SYSTEMS_ICC__)
00269 # endif
00270
00271 #elif defined(__ARMCC_VERSION)
00272 # define COMPILER_ID "ARMCC"
00273 #if __ARMCC_VERSION >= 1000000
00274   /* __ARMCC_VERSION = VRRPPPP */
00275   # define COMPILER_VERSION_MAJOR DEC(__ARMCC_VERSION/1000000)
00276   # define COMPILER_VERSION_MINOR DEC(__ARMCC_VERSION/10000 % 100)
00277   # define COMPILER_VERSION_PATCH DEC(__ARMCC_VERSION     % 10000)
00278 #else
00279   /* __ARMCC_VERSION = VRPPPP */
00280   # define COMPILER_VERSION_MAJOR DEC(__ARMCC_VERSION/100000)
00281   # define COMPILER_VERSION_MINOR DEC(__ARMCC_VERSION/10000 % 10)
00282   # define COMPILER_VERSION_PATCH DEC(__ARMCC_VERSION     % 10000)
00283 #endif
00284
00285
00286 #elif defined(_SGI_COMPILER_VERSION) || defined(_COMPILER_VERSION)
00287 # define COMPILER_ID "MIPSpro"
00288 # if defined(_SGI_COMPILER_VERSION)
00289   /* _SGI_COMPILER_VERSION = VRP */
00290 #  define COMPILER_VERSION_MAJOR DEC(_SGI_COMPILER_VERSION/100)
00291 #  define COMPILER_VERSION_MINOR DEC(_SGI_COMPILER_VERSION/10 % 10)
00292 #  define COMPILER_VERSION_PATCH DEC(_SGI_COMPILER_VERSION    % 10)
00293 # else
00294   /* _COMPILER_VERSION = VRP */
00295 #  define COMPILER_VERSION_MAJOR DEC(_COMPILER_VERSION/100)
00296 #  define COMPILER_VERSION_MINOR DEC(_COMPILER_VERSION/10 % 10)
00297 #  define COMPILER_VERSION_PATCH DEC(_COMPILER_VERSION    % 10)
00298 # endif
00299
00300
00301 /* These compilers are either not known or too old to define an
00302   identification macro.  Try to identify the platform and guess that
00303   it is the native compiler.  */
00304 #elif defined(__hpux) || defined(__hpua)
00305 # define COMPILER_ID "HP"
00306
```

```
00307 #else /* unknown compiler */
00308 # define COMPILER_ID ""
00309 #endif
00310
00311 /* Construct the string literal in pieces to prevent the source from
00312    getting matched.  Store it in a pointer rather than an array
00313    because some compilers will just produce instructions to fill the
00314    array rather than assigning a pointer to a static array.  */
00315 char const* info_compiler = "INFO" ":" "compiler[" COMPILER_ID "]";
00316 #ifdef SIMULATE_ID
00317 char const* info_simulate = "INFO" ":" "simulate[" SIMULATE_ID "]";
00318 #endif
00319
00320 #ifdef __QNXNTO__
00321 char const* qnxnto = "INFO" ":" "qnxnto[]";
00322 #endif
00323
00324 #if defined(__CRAYXE) || defined(__CRAYXC)
00325 char const *info_cray = "INFO" ":" "compiler_wrapper[CrayPrgEnv]";
00326 #endif
00327
00328 #define STRINGIFY_HELPER(X) #X
00329 #define STRINGIFY(X) STRINGIFY_HELPER(X)
00330
00331 /* Identify known platforms by name.  */
00332 #if defined(__linux) || defined(__linux__) || defined(linux)
00333 # define PLATFORM_ID "Linux"
00334
00335 #elif defined(__CYGWIN__)
00336 # define PLATFORM_ID "Cygwin"
00337
00338 #elif defined(__MINGW32__)
00339 # define PLATFORM_ID "MinGW"
00340
00341 #elif defined(__APPLE__)
00342 # define PLATFORM_ID "Darwin"
00343
00344 #elif defined(_WIN32) || defined(__WIN32__) || defined(WIN32)
00345 # define PLATFORM_ID "Windows"
00346
00347 #elif defined(__FreeBSD__) || defined(__FreeBSD)
00348 # define PLATFORM_ID "FreeBSD"
00349
00350 #elif defined(__NetBSD__) || defined(__NetBSD)
00351 # define PLATFORM_ID "NetBSD"
00352
00353 #elif defined(__OpenBSD__) || defined(__OPENBSD)
00354 # define PLATFORM_ID "OpenBSD"
00355
00356 #elif defined(__sun) || defined(sun)
00357 # define PLATFORM_ID "SunOS"
00358
00359 #elif defined(_AIX) || defined(__AIX) || defined(__AIX__) || defined(__aix) || defined(__aix__)
00360 # define PLATFORM_ID "AIX"
00361
00362 #elif defined(__hpux) || defined(__hpux__)
00363 # define PLATFORM_ID "HP-UX"
00364
00365 #elif defined(__HAIKU__)
00366 # define PLATFORM_ID "Haiku"
00367
00368 #elif defined(__BeOS) || defined(__BEOS__) || defined(_BEOS)
00369 # define PLATFORM_ID "BeOS"
00370
00371 #elif defined(__QNX__) || defined(__QNXNTO__)
00372 # define PLATFORM_ID "QNX"
00373
00374 #elif defined(__tru64) || defined(_tru64) || defined(__TRU64__)
00375 # define PLATFORM_ID "Tru64"
00376
00377 #elif defined(__riscos) || defined(__riscos__)
00378 # define PLATFORM_ID "RISCos"
00379
00380 #elif defined(__sinix) || defined(__sinix__) || defined(__SINIX__)
00381 # define PLATFORM_ID "SINIX"
00382
00383 #elif defined(__UNIX_SV__)
00384 # define PLATFORM_ID "UNIX_SV"
00385
00386 #elif defined(__bsdos__)
00387 # define PLATFORM_ID "BSDOS"
00388
00389 #elif defined(_MPRAS) || defined(MPRAS)
00390 # define PLATFORM_ID "MP-RAS"
00391
00392 #elif defined(__osf) || defined(__osf__)
00393 # define PLATFORM_ID "OSF1"
```

```
00394
00395 #elif defined(_SCO_SV) || defined(SCO_SV) || defined(sco_sv)
00396 # define PLATFORM_ID "SCO_SV"
00397
00398 #elif defined(__ultrix) || defined(__ultrix__) || defined(_ULTRIX)
00399 # define PLATFORM_ID "ULTRIX"
00400
00401 #elif defined(__XENIX__) || defined(_XENIX) || defined(XENIX)
00402 # define PLATFORM_ID "Xenix"
00403
00404 #elif defined(__WATCOMC__)
00405 # if defined(__LINUX__)
00406 #  define PLATFORM_ID "Linux"
00407
00408 # elif defined(__DOS__)
00409 #  define PLATFORM_ID "DOS"
00410
00411 # elif defined(__OS2__)
00412 #  define PLATFORM_ID "OS2"
00413
00414 # elif defined(__WINDOWS__)
00415 #  define PLATFORM_ID "Windows3x"
00416
00417 # else /* unknown platform */
00418 #  define PLATFORM_ID
00419 # endif
00420
00421 #elif defined(__INTEGRITY)
00422 # if defined(INT_178B)
00423 #  define PLATFORM_ID "Integrity178"
00424
00425 # else /* regular Integrity */
00426 #  define PLATFORM_ID "Integrity"
00427 # endif
00428
00429 #else /* unknown platform */
00430 # define PLATFORM_ID
00431
00432 #endif
00433
00434 /* For windows compilers MSVC and Intel we can determine
00435    the architecture of the compiler being used.  This is because
00436    the compilers do not have flags that can change the architecture,
00437    but rather depend on which compiler is being used
00438 */
00439 #if defined(_WIN32) && defined(_MSC_VER)
00440 # if defined(_M_IA64)
00441 #  define ARCHITECTURE_ID "IA64"
00442
00443 # elif defined(_M_X64) || defined(_M_AMD64)
00444 #  define ARCHITECTURE_ID "x64"
00445
00446 # elif defined(_M_IX86)
00447 #  define ARCHITECTURE_ID "X86"
00448
00449 # elif defined(_M_ARM64)
00450 #  define ARCHITECTURE_ID "ARM64"
00451
00452 # elif defined(_M_ARM)
00453 #  if _M_ARM == 4
00454 #   define ARCHITECTURE_ID "ARMV4I"
00455 #  elif _M_ARM == 5
00456 #   define ARCHITECTURE_ID "ARMV5I"
00457 #  else
00458 #   define ARCHITECTURE_ID "ARMV" STRINGIFY(_M_ARM)
00459 #  endif
00460
00461 # elif defined(_M_MIPS)
00462 #  define ARCHITECTURE_ID "MIPS"
00463
00464 # elif defined(_M_SH)
00465 #  define ARCHITECTURE_ID "SHx"
00466
00467 # else /* unknown architecture */
00468 #  define ARCHITECTURE_ID ""
00469 # endif
00470
00471 #elif defined(__WATCOMC__)
00472 # if defined(_M_I86)
00473 #  define ARCHITECTURE_ID "I86"
00474
00475 # elif defined(_M_IX86)
00476 #  define ARCHITECTURE_ID "X86"
00477
00478 # else /* unknown architecture */
00479 #  define ARCHITECTURE_ID ""
00480 # endif
```

```
00481
00482 #elif defined(__IAR_SYSTEMS_ICC__) || defined(__IAR_SYSTEMS_ICC)
00483 # if defined(__ICCARM__)
00484 #  define ARCHITECTURE_ID "ARM"
00485
00486 # elif defined(__ICCAVR__)
00487 #  define ARCHITECTURE_ID "AVR"
00488
00489 # else /* unknown architecture */
00490 #  define ARCHITECTURE_ID ""
00491 # endif
00492
00493 #elif defined(__ghs__)
00494 # if defined(__PPC64__)
00495 #  define ARCHITECTURE_ID "PPC64"
00496
00497 # elif defined(__ppc__)
00498 #  define ARCHITECTURE_ID "PPC"
00499
00500 # elif defined(__ARM__)
00501 #  define ARCHITECTURE_ID "ARM"
00502
00503 # elif defined(__x86_64__)
00504 #  define ARCHITECTURE_ID "x64"
00505
00506 # elif defined(__i386__)
00507 #  define ARCHITECTURE_ID "X86"
00508
00509 # else /* unknown architecture */
00510 #  define ARCHITECTURE_ID ""
00511 # endif
00512 #else
00513 #  define ARCHITECTURE_ID
00514 #endif
00515
00516 /* Convert integer to decimal digit literals.  */
00517 #define DEC(n)                  \
00518   ('0' + (((n) / 10000000)%10)), \
00519   ('0' + (((n) / 1000000)%10)),  \
00520   ('0' + (((n) / 100000)%10)),   \
00521   ('0' + (((n) / 10000)%10)),    \
00522   ('0' + (((n) / 1000)%10)),     \
00523   ('0' + (((n) / 100)%10)),      \
00524   ('0' + (((n) / 10)%10)),       \
00525   ('0' +  ((n) % 10))
00526
00527 /* Convert integer to hex digit literals.  */
00528 #define HEX(n)             \
00529   ('0' + ((n)>>28 & 0xF)), \
00530   ('0' + ((n)>>24 & 0xF)), \
00531   ('0' + ((n)>>20 & 0xF)), \
00532   ('0' + ((n)>>16 & 0xF)), \
00533   ('0' + ((n)>>12 & 0xF)), \
00534   ('0' + ((n)>>8  & 0xF)), \
00535   ('0' + ((n)>>4  & 0xF)), \
00536   ('0' + ((n)     & 0xF))
00537
00538 /* Construct a string literal encoding the version number components. */
00539 #ifdef COMPILER_VERSION_MAJOR
00540 char const info_version[] = {
00541   'I', 'N', 'F', 'O', ':',
00542   'c','o','m','p','i','l','e','r','_','v','e','r','s','i','o','n','[',
00543   COMPILER_VERSION_MAJOR,
00544 # ifdef COMPILER_VERSION_MINOR
00545   '.', COMPILER_VERSION_MINOR,
00546 #  ifdef COMPILER_VERSION_PATCH
00547   '.', COMPILER_VERSION_PATCH,
00548 #   ifdef COMPILER_VERSION_TWEAK
00549   '.', COMPILER_VERSION_TWEAK,
00550 #   endif
00551 #  endif
00552 # endif
00553  ']','\0'};
00554 #endif
00555
00556 /* Construct a string literal encoding the internal version number. */
00557 #ifdef COMPILER_VERSION_INTERNAL
00558 char const info_version_internal[] = {
00559   'I', 'N', 'F', 'O', ':',
00560   'c','o','m','p','i','l','e','r','_','v','e','r','s','i','o','n','_',
00561   'i','n','t','e','r','n','a','l','[',
00562   COMPILER_VERSION_INTERNAL,']','\0'};
00563 #endif
00564
00565 /* Construct a string literal encoding the version number components. */
00566 #ifdef SIMULATE_VERSION_MAJOR
00567 char const info_simulate_version[] = {
```

```
00568  'I','N','F','O',':',
00569  's','i','m','u','l','a','t','e','_','v','e','r','s','i','o','n','[',
00570  SIMULATE_VERSION_MAJOR,
00571 # ifdef SIMULATE_VERSION_MINOR
00572  '.', SIMULATE_VERSION_MINOR,
00573 #  ifdef SIMULATE_VERSION_PATCH
00574   '.', SIMULATE_VERSION_PATCH,
00575 #   ifdef SIMULATE_VERSION_TWEAK
00576    '.', SIMULATE_VERSION_TWEAK,
00577 #   endif
00578 #  endif
00579 # endif
00580  ']','\0'};
00581 #endif
00582
00583 /* Construct the string literal in pieces to prevent the source from
00584    getting matched.  Store it in a pointer rather than an array
00585    because some compilers will just produce instructions to fill the
00586    array rather than assigning a pointer to a static array.  */
00587 char const* info_platform = "INFO" ":" "platform[" PLATFORM_ID "]";
00588 char const* info_arch = "INFO" ":" "arch[" ARCHITECTURE_ID "]";
00589
00590
00591
00592
00593 #if defined(_MSC_VER) && defined(_MSVC_LANG)
00594 #define CXX_STD _MSVC_LANG
00595 #else
00596 #define CXX_STD __cplusplus
00597 #endif
00598
00599 const char* info_language_dialect_default = "INFO" ":" "dialect_default["
00600 #if CXX_STD > 201703L
00601  "20"
00602 #elif CXX_STD >= 201703L
00603  "17"
00604 #elif CXX_STD >= 201402L
00605  "14"
00606 #elif CXX_STD >= 201103L
00607  "11"
00608 #else
00609  "98"
00610 #endif
00611 "]";
00612
00613 /*--------------------------------------------------------------------------*/
00614
00615 int main(int argc, char* argv[])
00616 {
00617   int require = 0;
00618   require += info_compiler[argc];
00619   require += info_platform[argc];
00620 #ifdef COMPILER_VERSION_MAJOR
00621   require += info_version[argc];
00622 #endif
00623 #ifdef COMPILER_VERSION_INTERNAL
00624   require += info_version_internal[argc];
00625 #endif
00626 #ifdef SIMULATE_ID
00627   require += info_simulate[argc];
00628 #endif
00629 #ifdef SIMULATE_VERSION_MAJOR
00630   require += info_simulate_version[argc];
00631 #endif
00632 #if defined(__CRAYXE) || defined(__CRAYXC)
00633   require += info_cray[argc];
00634 #endif
00635   require += info_language_dialect_default[argc];
00636   (void)argv;
00637   return require;
00638 }
```

7.19   DCMotor.cpp File Reference

```
#include "DCMotor.h"
```

Include dependency graph for DCMotor.cpp:

7.20 DCMotor.cpp

```
00001 #include "DCMotor.h"
00002
00003 component::DCMotor::DCMotor(const io::Pin &ar_pin)
00004         : m_pin(ar_pin)
00005 {
00006     m_pin.toOutput();
00007
00008 }
00009
00010
00011 component::DCMotor::~DCMotor()
00012 {
00013
00014 }
00015
00016 void component::DCMotor::on()
00017 {
00018     m_pin.setHigh();
00019 }
00020
00021 void component::DCMotor::off()
00022 {
00023     m_pin.setLow();
00024 }
00025
00026 void component::DCMotor::toggle()
00027 {
00028     m_pin.toggle();
00029
00030 }
```

7.21 DCMotor.h File Reference

Header file of the DCMotor class.

```
#include "ha_base.h"
#include "Pin.h"
```

```
#include "TimerCounter.h"
```
Include dependency graph for DCMotor.h:

This graph shows which files directly or indirectly include this file:

Classes

- class component::DCMotor

Namespaces

- component

7.21.1 Detailed Description

Header file of the DCMotor class.

Usage example (test): #include "MCU.h" #include "TimerCounter0.h" #include "DCMotor.h"

#define DCMOTOR_NUMBER 6

int main(void) {

Init initialize MCU [core::MCU::init()](#);

instantiate the TimerCounter0 object [core::TimerCounter0](#) &myTimerCounter0 = [core::TimerCounter0::getInstance()](#); myTimerCounter0.selectClockSource(core::clockSource::PS_1024);

instantiate a DCMotor object [component::DCMotor](#) myDCMotor(io::Pin(DCMOTOR_NUMBER,io::PortD));

myDCMotor.connect(myTimerCounter0);

myDCMotor.spin(myTimerCounter0,0); _delay_ms(5000);

myDCMotor.spin(myTimerCounter0,75); _delay_ms(5000);

myDCMotor.spin(myTimerCounter0,190); _delay_ms(5000);

myDCMotor.spin(myTimerCounter0,200); _delay_ms(5000);

myDCMotor.disconnect(myTimerCounter0);

Mainloop while (1) {

} return 0; } Usage example (H Bridge):

#include "MCU.h" #include "TimerCounter0.h" #include "DCMotor.h"

#define DCMOTOR_NUMBER 6 #define DCMOTOR_BACKWARD 0 #define DCMOTOR_FORWARD 1

int [main(void)](#) {

Init initialize MCU [core::MCU::init()](#);

instantiate the TimerCounter0 object [core::TimerCounter0](#) &myTimerCounter0 = [core::TimerCounter0::getInstance()](#); myTimerCounter0.selectClockSource(core::clockSource::PS_256);

instantiate a DCMotor object [component::DCMotor](#) myDCMotor(io::Pin(DCMOTOR_NUMBER,io::PortD));

instantiate direction pins objects

[io::Pin](#) myPinForward = [io::Pin(DCMOTOR_FORWARD,io::PortB)](#); myPinForward.toOutput();

[io::Pin](#) myPinBackward = [io::Pin(DCMOTOR_BACKWARD,io::PortB)](#); myPinBackward.toOutput();

myDCMotor.connect(myTimerCounter0);

myPinForward.setHigh(); myPinBackward.setLow(); myDCMotor.spin(myTimerCounter0,30); _delay_ms(5000);

myPinForward.setLow(); myPinBackward.setHigh(); myDCMotor.spin(myTimerCounter0,30); _delay_ms(5000);

myDCMotor.disconnect(myTimerCounter0);

Mainloop while (1) {

} return 0; }

Basic class for IO abstraction of Pin and Port

Author

>   Farid Oubbati (https://github.com/faroub)

Date

>   March 2020

Definition in file [DCMotor.h](#).

7.22 DCMotor.h

```
00001
00117 #ifndef DCMOTOR_H
00118 #define DCMOTOR_H
00119 #include "ha_base.h"
00120 #include "Pin.h"
00121 #include "TimerCounter.h"
00122
00123 namespace component
00124 {
00125
00126 class DCMotor
00127 {
00128 public:
00129     DCMotor(const io::Pin &ar_pin);
00130
00131     ~DCMotor();
00132
00135     void on();
00138     void off();
00141     void toggle();
00142
00143     template<typename TC>
00144     void spin(TC &ar_timerCounter,
00145             //const uint8_t &ar_dir,
00146             const uint16_t &ar_speed,
00147            const core::channel &ar_channel=core::channel::A)
00148     {
00149
00150         ar_timerCounter.setOutputCompareRegister(ar_channel, ar_speed);
00151         ar_timerCounter.start();
00152
00153
00154     }
00155     template<typename TC>
00156     void stop(TC &ar_timerCounter)
00157     {
00158         ar_timerCounter.stop();
00159
00160
00161     }
00162
00163     template<typename TC>
00164     void connect(TC &ar_timerCounter,
00165                 const core::channel &ar_channel=core::channel::A)
00166     {
00167         ar_timerCounter.selectOperationMode(core::operationMode::fast_PWM);
00168         ar_timerCounter.selectCompareOutputMode(ar_channel, core::compareOutputMode::clear);
00169         ar_timerCounter.setCounter(0);
00170
00171     }
00172
00173     template<typename TC>
00174     void disconnect(TC &ar_timerCounter,
00175                 const core::channel &ar_channel=core::channel::A)
00176     {
00177         ar_timerCounter.selectCompareOutputMode(ar_channel, core::compareOutputMode::normal);
00178         ar_timerCounter.stop();
00179     }
00180
00181
00182
00183 private:
00184
00185     io::Pin m_pin;
00187 };
00188
00189 }
00190 #endif // DCMOTOR_H
```

7.23 ExternInterrupt.cpp File Reference

```
#include "ExternInterrupt.h"
```

Include dependency graph for ExternInterrupt.cpp:

7.24 ExternInterrupt.cpp

```
00001 #include "ExternInterrupt.h"
00002
00003 core::ExternInterrupt& core::ExternInterrupt::getInstance()
00004 {
00005     static ExternInterrupt l_instance;
00006     return l_instance;
00007
00008 }
00009
00010
00011 core::ExternInterrupt::ExternInterrupt()
00012 {
00013     sei();
00014
00015 }
00016
00017 core::ExternInterrupt::~ExternInterrupt()
00018 {
00019
00020 }
00021
00022 void core::ExternInterrupt::setInt0SenseControl(const senseControl& ar_senseControl)
00023 {
00024     EXT_INT_SET_INT0_SENSE_CONTROL(static_cast<uint8_t>(ar_senseControl));
00025
00026 }
00027
00028 void core::ExternInterrupt::setInt1SenseControl(const senseControl& ar_senseControl)
00029 {
00030     EXT_INT_SET_INT1_SENSE_CONTROL(static_cast<uint8_t>(ar_senseControl));
00031
00032 }
00033
00034 void core::ExternInterrupt::enableInt0(const uint8_t a_enable)
00035 {
00036     if (a_enable) {
00037         EXT_INT_ENABLE_INT0;
00038
00039     } else {
00040         EXT_INT_DISABLE_INT0;
00041     }
00042
00043 }
00044
00045 void core::ExternInterrupt::enableInt1(const uint8_t a_enable)
00046 {
00047     if (a_enable) {
00048         EXT_INT_ENABLE_INT1;
00049
00050     } else {
00051         EXT_INT_DISABLE_INT1;
00052     }
00053 }
00054
00055
00056 void core::ExternInterrupt::enablePinChange(const pinChangePort& ar_pinChangePort, const uint8_t
      a_enable)
```

```
00057 {
00058     if (a_enable) {
00059         EXT_INT_ENABLE_PIN_CHANGE_INTERRUPT(static_cast<uint8_t>(ar_pinChangePort));
00060
00061     } else {
00062         EXT_INT_DISABLE_PIN_CHANGE_INTERRUPT(static_cast<uint8_t>(ar_pinChangePort));
00063     }
00064
00065 }
00066
00067 void core::ExternInterrupt::enablePinChangeMaskPortB(const uint8_t a_pinNumber, const uint8_t
        a_enable)
00068 {
00069     if (a_enable) {
00070         EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTB(a_pinNumber);
00071
00072     } else {
00073         EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTB(a_pinNumber);
00074     }
00075
00076 }
00077
00078
00079 void core::ExternInterrupt::enablePinChangeMaskPortC(const uint8_t a_pinNumber, const uint8_t
        a_enable)
00080 {
00081     if (a_enable) {
00082         EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTC(a_pinNumber);
00083
00084     } else {
00085         EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTC(a_pinNumber);
00086     }
00087
00088 }
00089
00090 void core::ExternInterrupt::enablePinChangeMaskPortD(const uint8_t a_pinNumber, const uint8_t
        a_enable)
00091 {
00092     if (a_enable) {
00093         EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTD(a_pinNumber);
00094
00095     } else {
00096         EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTD(a_pinNumber);
00097     }
00098 }
```

7.25 ExternInterrupt.h File Reference

Header file of the ExternInterrupt class.

```
#include "ha_base.h"
```
Include dependency graph for ExternInterrupt.h:

This graph shows which files directly or indirectly include this file:

Classes

- class core::ExternInterrupt

Namespaces

- core

Enumerations

- enum core::senseControl : uint8_t { core::senseControl::lowLevel =0, core::senseControl::logicalChange, core::senseControl::fallingEdge, core::senseControl::risingEdge }
- enum core::pinChangePort : uint8_t { core::pinChangePort::PCINTB =0, core::pinChangePort::PCINTC, core::pinChangePort::PCINTD }

7.25.1 Detailed Description

Header file of the ExternInterrupt class.

class to handle externally triggered interrupts.

Usage example (external interrupt):

#include "PushButton.h" #include "Led.h" #include "ExternInterrupt.h"

#define PUSHBUTTON_NUMBER 2 #define MAIN_LED_NUMBER 0 #define INTERRUPT_LED_NUMBER 1 #define DELAYTIME 1000

instantiate a Led object declaration of global variables (shut up warning) extern component::Led MainLed; extern component::Led InterruptLed; component::Led MainLed(io::Pin(MAIN_LED_NUMBER,io::PortB)); component::Led InterruptLed(io::Pin(INTERRUPT_LED_NUMBER,io::PortB));

instantiate a Led object declaration of global variable (shut up warning) extern component::PushButton PushButton; component::PushButton PushButton(io::Pin(PUSHBUTTON_NUMBER,io::PortD));

int main(void) {

Init

instantiate the external interrupt manager core::ExternInterrupt &myExternInterrupt = core::ExternInterrupt::getInstance(); myExternInterrupt.enableInt0(1); myExternInterrupt.setInt0SenseControl(core::senseControl::logicalChange);

Mainloop while (1) {

MainLed.toggle(); _delay_ms(DELAYTIME);

} return 0; }

void core::ExternInterrupt::Int0ServiceRoutine() { if (PushButton.isPressed()) { InterruptLed.on(); } else { Interrupt↩ Led.off(); }

}

Usage example (pin change interrupt):

#include "PushButton.h" #include "Led.h" #include "ExternInterrupt.h"

#define PUSHBUTTON_1_NUMBER 2 #define PUSHBUTTON_2_NUMBER 3 #define MAIN_LED_NUMBER 0 #define INTERRUPT_LED_1_NUMBER 1 #define INTERRUPT_LED_2_NUMBER 2 #define DELAYTIME 1000

instantiate a Led objects declaration of global variables (shut up warning) extern component::Led MainLed; extern component::Led InterruptLed1; extern component::Led InterruptLed2; component::Led MainLed(io::Pin(M↩ AIN_LED_NUMBER,io::PortB)); component::Led InterruptLed1(io::Pin(INTERRUPT_LED_1_NUMBER,io::PortB)); component::Led InterruptLed2(io::Pin(INTERRUPT_LED_2_NUMBER,io::PortB));

instantiate a PushButton objects declaration of global variable (shut up warning) extern component::PushButton PushButton1; extern component::PushButton PushButton2; component::PushButton PushButton1(io::Pin(PUSH↩ BUTTON_1_NUMBER,io::PortD)); component::PushButton PushButton2(io::Pin(PUSHBUTTON_2_NUMBER,io↩ ::PortB));

int main(void) {

Init

instantiate the external interrupt manager core::ExternInterrupt &myExternInterrupt = core::ExternInterrupt::getInstance(); myExternInterrupt.enablePinChange(core::pinChangePort::PCINTD,1); myExternInterrupt.enablePinChange(core↩ ::pinChangePort::PCINTB,1); myExternInterrupt.enablePinChangeMaskPortD(PUSHBUTTON_1_NUMBER,1); myExternInterrupt.enablePinChangeMaskPortB(PUSHBUTTON_2_NUMBER,1);

Mainloop while (1) {

MainLed.toggle(); _delay_ms(DELAYTIME);

} return 0; }

void core::ExternInterrupt::pinChangePortDServiceRoutine() { if (PushButton1.isPressed()) { InterruptLed1.on();

} else { InterruptLed1.off();

} } void core::ExternInterrupt::pinChangePortBServiceRoutine() { if (PushButton2.isPressed()) { InterruptLed2.on(); } else { InterruptLed2.off(); }

}

Author

> Farid Oubbati (https://github.com/faroub)

Date

> March 2020

Definition in file ExternInterrupt.h.

7.26 ExternInterrupt.h

```
00001
00140 #ifndef EXTERN_INTERRUPTS_H
00141 #define EXTERN_INTERRUPTS_H
00142 #include "ha_base.h"
00143
00144
00145
00146 namespace core
00147 {
00148
00149 enum class senseControl : uint8_t {
00150     lowLevel=0,
00151     logicalChange,
00152     fallingEdge,
00153     risingEdge
00154 };
00155
00156 enum class pinChangePort : uint8_t {
00157     PCINTB=0,
00158     PCINTC,
00159     PCINTD,
00160 };
00161
00162 class ExternInterrupt
00163 {
00164
00165 public:
00166
00167     static ExternInterrupt& getInstance();
00168
00169     void setInt0SenseControl(const senseControl& ar_senseControl);
00170
00171     void setInt1SenseControl(const senseControl& ar_senseControl);
00172
00173     void enableInt0(const uint8_t a_enable);
00174
00175     void enableInt1(const uint8_t a_enable);
00176
00177     void enablePinChange(const pinChangePort& ar_pinChangePort, const uint8_t a_enable);
00178
00179     void enablePinChangeMaskPortB(const uint8_t a_pinNumber, const uint8_t a_enable);
00180
00181     void enablePinChangeMaskPortC(const uint8_t a_pinNumber, const uint8_t a_enable);
00182
00183     void enablePinChangeMaskPortD(const uint8_t a_pinNumber, const uint8_t a_enable);
00184
00185     static void Int0ServiceRoutine() __asm__(STR(EXT_INT_INT0_INTERRUPT)) __attribute__((__signal__,
      __used__, __externally_visible__));
00186
00187     static void Int1ServiceRoutine() __asm__(STR(EXT_INT_INT1_INTERRUPT)) __attribute__((__signal__,
      __used__, __externally_visible__));
00188
00189     static void pinChangePortBServiceRoutine() __asm__(STR(EXT_INT_PIN_CHANGE_PORTB_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
00190
00191     static void pinChangePortCServiceRoutine() __asm__(STR(EXT_INT_PIN_CHANGE_PORTC_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
00192
00193     static void pinChangePortDServiceRoutine() __asm__(STR(EXT_INT_PIN_CHANGE_PORTD_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
00194
00195
00196 protected:
00197
00198 private:
00199
00200     ExternInterrupt();
00201
00204     ~ExternInterrupt();
00205
00208     ExternInterrupt(const ExternInterrupt&);
00209
00212     const ExternInterrupt& operator=(const ExternInterrupt&);
00213
00214 };
00215 }
00216
00217
00218
00219
00220 #endif
```

7.27 ha_base.h File Reference

Base header file for the basic hardware abstraction macros.

```
#include <stdint.h>
#include <avr/io.h>
#include <avr/interrupt.h>
#include <util/delay.h>
#include <avr/sleep.h>
#include <avr/power.h>
#include <avr/wdt.h>
```
Include dependency graph for ha_base.h:

This graph shows which files directly or indirectly include this file:

Macros

- #define STRx(s) #s
- #define STR(s) STRx(s)

7.27.1 Detailed Description

Base header file for the basic hardware abstraction macros.

Author

Farid Oubbati (https://github.com/faroub)

Date

March 2020

Definition in file ha_base.h.

7.27.2 Macro Definition Documentation

7.27.2.1 STR

```
#define STR(
            s ) STRx(s)
```

Definition at line 16 of file ha_base.h.

7.27.2.2 STRx

```
#define STRx(
            s ) #s
```

Definition at line 15 of file ha_base.h.

7.28 ha_base.h

```
00001
00009 #ifndef HABASE_H
00010 #define HABASE_H
00011
00012 /*
00013  *  Helper construct to get interrupt numbers from names
00014  */
00015 #define STRx(s)   #s
00016 #define STR(s)    STRx(s)
00017
00018 /*
00019  *  Any class needs these includes from avr-libc
00020  */
00021 #include <stdint.h>
00022 #include <avr/io.h>
00023 #include <avr/interrupt.h>
00024 #include <util/delay.h>
00025 #include <avr/sleep.h>
00026 #include <avr/power.h>
00027 #include <avr/wdt.h>
00028
00029
00030 /*
00031  * include hardware abstraction the Atmega328p
00032  */
00033 #if   defined(__AVR_ATmega328P__)
00034
00035     #include "ha_m328p.h"
00036     #include "utils_m328p.h"
00037
00038 #endif
00039
00040
00041 #endif
```

7.29 ha_m328p.h File Reference

Header file for the hardware abstraction macros of the Atmega328p.

```
#include <util/setbaud.h>
```
Include dependency graph for ha_m328p.h:

Macros

- #define PUSHBUTTON_DEBOUNCE_TIME_US 1000
- #define PUSHBUTTON_SAMPLING 12
- #define USART0_SET_BAUDRATE_HIGH_REGISTER UBRR0H = UBRRH_VALUE
- #define USART0_SET_BAUDRATE_LOW_REGISTER UBRR0L = UBRRL_VALUE
- #define USART0_ENABLE_ASYNC_TRANSMISSION_MODE UCSR0C &= ~((1 << UMSEL01) | (1 << UMSEL00))
- #define USART0_ENABLE_SYNC_TRANSMISSION_MODE UCSR0C = (UCSR0C & ~(1 << UMSEL01)) | (1 << UMSEL00)
- #define USART0_ENABLE_MASTER_SPI_MODE UCSR0C |= (1 << UMSEL01) | (1 << UMSEL00)
- #define USART0_ENABLE_DOUBLE_SPEED_MODE
- #define USART0_DISABLE_DOUBLE_SPEED_MODE
- #define USART0_DISABLE_DOUBLE_SPEED_MODE UCSR0A &= ~(1 << U2X0)
- #define USART0_ENABLE_EVEN_PARITY_MODE UCSR0C = (1 << UPM01) | (UCSR0C & ~(1 << UPM00))
- #define USART0_ENABLE_ODD_PARITY_MODE UCSR0C |= ((1 << UPM01) | (1 << UPM00))
- #define USART0_DISABLE_PARITY_MODE UCSR0C &= ~((1 << UPM01) | (1 << UPM00))
- #define USART0_SET_ONE_STOP_BIT UCSR0C &= ~(1 << USBS0)
- #define USART0_SET_TWO_STOP_BITS UCSR0C |= (1 << USBS0)
- #define USART0_SET_9BIT_FRAME_SIZE
- #define USART0_SET_8BIT_FRAME_SIZE
- #define USART0_SET_7BIT_FRAME_SIZE
- #define USART0_SET_6BIT_FRAME_SIZE
- #define USART0_SET_5BIT_FRAME_SIZE
- #define USART0_ENABLE_TRANSMITTER UCSR0B |= 1 << TXEN0
- #define USART0_DISABLE_TRANSMITTER UCSR0B &= ~(1 << TXEN0)
- #define USART0_ENABLE_RECEIVER UCSR0B |= 1 << RXEN0
- #define USART0_DISABLE_RECEIVER UCSR0B &= ~(1 << RXEN0)
- #define USART0_CONTROL_STATUS_REGISTER UCSR0A
- #define USART0_DATA_REGISTER UDR0
- #define USART0_FRAME_ERROR FE0

- #define USART0_DATA_OVERRUN DOR0
- #define USART0_PARITY_ERROR UPE0
- #define USART0_ENABLE_DATA_REGISTER_EMPTY_INTERRUPT UCSR0B |= 1 << UDRIE0
- #define USART0_DISABLE_DATA_REGISTER_EMPTY_INTERRUPT UCSR0B &= ~(1 << UDRIE0)
- #define USART0_ENABLE_RECEIVE_COMPLETE_INTERRUPT UCSR0B |= 1 << RXCIE0
- #define USART0_DISABLE_RECEIVE_COMPLETE_INTERRUPT UCSR0B &= ~(1 << RXCIE0)
- #define USART0_ENABLE_TRANSMIT_COMPLETE_INTERRUPT UCSR0B |= 1 << TXCIE0
- #define USART0_DISABLE_TRANSMIT_COMPLETE_INTERRUPT UCSR0B &= ~(1 << TXCIE0)
- #define USART0_RECEIVE_COMPLETE_INTERRUPT USART_RX_vect
- #define USART0_TRANSMIT_COMPLETE_INTERRUPT USART_TX_vect
- #define USART0_DATA_REGISTER_EMPTY_INTERRUPT USART_UDRE_vect
- #define ADC_SELECT_REF_VOLTAGE(refVoltage) ADMUX &= 0x3F; ADMUX |= refVoltage << 6
- #define ADC_ADJUST_RESULT_LEFT ADMUX |= 1 << ADLAR
- #define ADC_ADJUST_RESULT_RIGHT ADMUX &= ~(1 << ADLAR)
- #define ADC_SELECT_ANALOG_INPUT(pinNumber) ADMUX &= 0xF0; ADMUX |= pinNumber
- #define ADC_DISABLE_DIGITAL_INPUT_REGISTER(pinNumber) DIDR0 &= 0xC0; DIDR0 |= pinNumber
- #define ADC_ENABLE ADCSRA |= 1 << ADEN
- #define ADC_DISABLE ADCSRA &= ~(1 << ADEN)
- #define ADC_START_CONVERSION ADCSRA |= 1 << ADSC
- #define ADC_STOP_CONVERSION ADCSRA &= ~(1 << ADSC)
- #define ADC_ENABLE_AUTOTRIGGER ADCSRA |= 1 << ADATE
- #define ADC_DISABLE_AUTOTRIGGER ADCSRA &= ~(1 << ADATE)
- #define ADC_ENABLE_CONVERSION_COMPLETE_INTERRUPT ADCSRA |= 1 << ADIE
- #define ADC_DISABLE_CONVERSION_COMPLETE_INTERRUPT ADCSRA &= ~(1 << ADIE)
- #define ADC_SELECT_CLOCK_PRESCALER(clockPrescaler) ADCSRA &= 0xF8; ADCSRA |= clock↩
  Prescaler
- #define ADC_SELECT_AUTO_TRIGGER_SOURCE(triggerSource) ADCSRB &= 0xF8; ADCSRB |=
  triggerSource
- #define ADC_CONVERSION_COMPLETE_INTERRUPT ADC_vect
- #define EXT_INT_SET_INT0_SENSE_CONTROL(senseControl) EICRA &= 0xFC; EICRA |= senseControl
- #define EXT_INT_SET_INT1_SENSE_CONTROL(senseControl) EICRA &= 0xF3; EICRA |= senseControl
- #define EXT_INT_ENABLE_INT0 EIMSK |= 1 << INT0
- #define EXT_INT_DISABLE_INT0 EIMSK &= ~(1 << INT0)
- #define EXT_INT_ENABLE_INT1 EIMSK |= 1 << INT1
- #define EXT_INT_DISABLE_INT1 EIMSK &= ~(1 << INT1)
- #define EXT_INT_ENABLE_PIN_CHANGE_INTERRUPT(pinChangePort) PCICR |= 1 << pinChangePort
- #define EXT_INT_DISABLE_PIN_CHANGE_INTERRUPT(pinChangePort) PCICR &= ~(1 << pinChange↩
  Port)
- #define EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTB(pinChangePin) PCMSK0 |= 1 << pinChange↩
  Pin
- #define EXT_INT_DISABLE_PIN_CHANGE_MASK_PORTB(pinChangePin) PCMSK0 &= ~(1 << pin↩
  ChangePin)
- #define EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTC(pinChangePin) PCMSK1 |= 1 << pinChange↩
  Pin
- #define EXT_INT_DISABLE_PIN_CHANGE_MASK_PORTC(pinChangePin) PCMSK1 &= ~(1 << pin↩
  ChangePin)
- #define EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTD(pinChangePin) PCMSK2 |= 1 << pinChange↩
  Pin
- #define EXT_INT_DISABLE_PIN_CHANGE_MASK_PORTD(pinChangePin) PCMSK2 &= ~(1 << pin↩
  ChangePin)
- #define EXT_INT_INT0_INTERRUPT INT0_vect
- #define EXT_INT_INT1_INTERRUPT INT1_vect
- #define EXT_INT_PIN_CHANGE_PORTB_INTERRUPT PCINT0_vect
- #define EXT_INT_PIN_CHANGE_PORTC_INTERRUPT PCINT1_vect
- #define EXT_INT_PIN_CHANGE_PORTD_INTERRUPT PCINT2_vect

- #define TIMER0_STOP TCCR0B &= 0xF8
- #define TIMER1_STOP TCCR1B &= 0xF8
- #define TIMER2_STOP TCCR2B &= 0xF8
- #define TIMER0_SELECT_CLOCK_SOURCE(clockSource) TCCR0B &= 0xF8; TCCR0B |= clockSource
- #define TIMER1_SELECT_CLOCK_SOURCE(clockSource) TCCR1B &= 0xF8; TCCR1B |= clockSource
- #define TIMER2_SELECT_CLOCK_SOURCE(clockSource) TCCR2B &= 0xF8; TCCR2B |= clockSource
- #define TIMER0_SELECT_OPERATION_MODE(operationMode) TCCR0A &= 0xFC; TCCR0A |= (operationMode & 3); TCCR0B &= 0xF7; TCCR0B |= (operationMode & 12) << 1
- #define TIMER1_SELECT_OPERATION_MODE(operationMode) TCCR1A &= 0xFC; TCCR1A |= (operationMode & 3); TCCR1B &= 0xE7; TCCR1B |= (operationMode & 12) << 1
- #define TIMER2_SELECT_OPERATION_MODE(operationMode) TCCR2A &= 0xFC; TCCR2A |= (operationMode & 3); TCCR2B &= 0xF7; TCCR2B |= (operationMode & 12) << 1
- #define TIMER0_SELECT_COM_CHANNEL_A(compareOutputMode) TCCR0A &= 0x3F; TCCR0A |= compareOutputMode << 6
- #define TIMER0_SELECT_COM_CHANNEL_B(compareOutputMode) TCCR0A &= 0xCF; TCCR0A |= compareOutputMode << 4
- #define TIMER1_SELECT_COM_CHANNEL_A(compareOutputMode) TCCR1A &= 0x3F; TCCR1A |= compareOutputMode << 6
- #define TIMER1_SELECT_COM_CHANNEL_B(compareOutputMode) TCCR1A &= 0xCF; TCCR1A |= compareOutputMode << 4
- #define TIMER2_SELECT_COM_CHANNEL_A(compareOutputMode) TCCR2A &= 0x3F; TCCR2A |= compareOutputMode << 6
- #define TIMER2_SELECT_COM_CHANNEL_B(compareOutputMode) TCCR2A &= 0xCF; TCCR2A |= compareOutputMode << 4
- #define TIMER0_ENABLE_COM_CHANNEL_A_INTERRUPT TIMSK0 |= 1 << OCIE0A
- #define TIMER0_DISABLE_COM_CHANNEL_A_INTERRUPT TIMSK0 &= ~(1 << OCIE0A)
- #define TIMER0_ENABLE_COM_CHANNEL_B_INTERRUPT TIMSK0 |= 1 << OCIE0B
- #define TIMER0_DISABLE_COM_CHANNEL_B_INTERRUPT TIMSK0 &= ~(1 << OCIE0B)
- #define TIMER0_ENABLE_OVERFLOW_INTERRUPT TIMSK0 |= 1 << TOIE0
- #define TIMER0_DISABLE_OVERFLOW_INTERRUPT TIMSK0 &= ~(1 << TOIE0)
- #define TIMER1_ENABLE_COM_CHANNEL_A_INTERRUPT TIMSK1 |= 1 << OCIE1A
- #define TIMER1_DISABLE_COM_CHANNEL_A_INTERRUPT TIMSK1 &= ~(1 << OCIE1A)
- #define TIMER1_ENABLE_COM_CHANNEL_B_INTERRUPT TIMSK1 |= 1 << OCIE1B
- #define TIMER1_DISABLE_COM_CHANNEL_B_INTERRUPT TIMSK1 &= ~(1 << OCIE1B)
- #define TIMER1_ENABLE_OVERFLOW_INTERRUPT TIMSK1 |= 1 << TOIE1
- #define TIMER1_DISABLE_OVERFLOW_INTERRUPT TIMSK1 &= ~(1 << TOIE1)
- #define TIMER1_ENABLE_INPUT_CAPTURE_INTERRUPT TIMSK1 |= 1 << ICIE1
- #define TIMER1_DISABLE_INPUT_CAPTURE_INTERRUPT TIMSK1 &= ~(1 << ICIE1)
- #define TIMER2_ENABLE_COM_CHANNEL_A_INTERRUPT TIMSK2 |= 1 << OCIE2A
- #define TIMER2_DISABLE_COM_CHANNEL_A_INTERRUPT TIMSK2 &= ~(1 << OCIE2A)
- #define TIMER2_ENABLE_COM_CHANNEL_B_INTERRUPT TIMSK2 |= 1 << OCIE2B
- #define TIMER2_DISABLE_COM_CHANNEL_B_INTERRUPT TIMSK2 &= ~(1 << OCIE2B)
- #define TIMER2_ENABLE_OVERFLOW_INTERRUPT TIMSK2 |= 1 << TOIE2
- #define TIMER2_DISABLE_OVERFLOW_INTERRUPT TIMSK2 &= ~(1 << TOIE2)
- #define TIMER0_COM_CHANNEL_A_INTERRUPT TIMER0_COMPA_vect
- #define TIMER0_COM_CHANNEL_B_INTERRUPT TIMER0_COMPB_vect
- #define TIMER0_OVERFLOW_INTERRUPT TIMER0_OVF_vect
- #define TIMER1_COM_CHANNEL_A_INTERRUPT TIMER1_COMPA_vect
- #define TIMER1_COM_CHANNEL_B_INTERRUPT TIMER1_COMPB_vect
- #define TIMER1_OVERFLOW_INTERRUPT TIMER1_OVF_vect
- #define TIMER1_INPUT_CAPTURE_INTERRUPT TIMER1_CAPT_vect
- #define TIMER2_COM_CHANNEL_A_INTERRUPT TIMER2_COMPA_vect
- #define TIMER2_COM_CHANNEL_B_INTERRUPT TIMER2_COMPB_vect
- #define TIMER2_OVERFLOW_INTERRUPT TIMER2_OVF_vect

- #define WATCHDOG_SELECT_TIMEOUT(timeOut) WDTCSR |= (1<<WDCE) | (1<<WDE); WDTCSR = (0<<WDIE) | (0<<WDE) | timeOut;
- #define WATCHDOG_START(operationMode, timeOut) MCUSR &= ∼(1<<WDRF); WDTCSR |= (1<<W↩
  DCE) | (1<<WDE); WDTCSR = operationMode | timeOut;
- #define WATCHDOG_STOP MCUSR &= ∼(1<<WDRF); WDTCSR |= (1<<WDCE) | (1<<WDE); WDT↩
  CSR = 0x00;
- #define WATCHDOG_TIMEOUT_INTERRUPT WDT_vect
- #define MCU_SELECT_SLEEP_MODE(sleepMode) SMCR &= 0xF1; SMCR |= sleepMode << 1
- #define MCU_SLEEP_ENABLE SMCR |= 1 << SE
- #define MCU_SLEEP_DISABLE SMCR &= ∼(1 << SE)
- #define MCU_TWI_ENABLE PRR &= ∼(1 << PRTWI)
- #define MCU_TWI_DISABLE PRR |= 1 << PRTWI
- #define MCU_TIMER2_ENABLE PRR &= ∼(1 << PRTIM2)
- #define MCU_TIMER2_DISABLE PRR |= 1 << PRTIM2
- #define MCU_TIMER1_ENABLE PRR &= ∼(1 << PRTIM1)
- #define MCU_TIMER1_DISABLE PRR |= 1 << PRTIM1
- #define MCU_TIMER0_ENABLE PRR &= ∼(1 << PRTIM0)
- #define MCU_TIMER0_DISABLE PRR |= 1 << PRTIM0
- #define MCU_SPI_ENABLE PRR &= ∼(1 << PRSPI)
- #define MCU_SPI_DISABLE PRR |= 1 << PRSPI
- #define MCU_USART0_ENABLE PRR &= ∼(1 << PRUSART0)
- #define MCU_USART0_DISABLE PRR |= 1 << PRUSART0
- #define MCU_ADC_ENABLE PRR &= ∼(1 << PRADC)
- #define MCU_ADC_DISABLE PRR |= 1 << PRADC
- #define MCU_BOD_DISABLE MCUCR |= (1<<BODSE) | (1<<BODS); MCUCR &= ∼(1<<BODSE);
- #define SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT(pulseWidth, clockPrescaler) ((F_CPU/1000000↩
  UL) ∗ (pulseWidth/ clockPrescaler))
- #define SERVOMOTOR_TIMER_ANGLE_COUNT(angle, out_min, out_mid, out_max) (((out_min∗(angle
  - 90L)∗(angle - 180L))/16200L + (angle∗out_max∗(angle - 90L))/16200L - (angle∗out_mid∗(angle -
  180L))/8100L))
- #define SPI_ENABLE SPCR |= 1 << SPE
- #define SPI_DISABLE SPCR &= ∼(1 << SPE)
- #define SPI_SELECT_MASTER_MODE SPCR |= 1 << MSTR
- #define SPI_SELECT_SLAVE_MODE SPCR &= ∼(1 << MSTR)
- #define SPI_SELECT_DATA_MODE(dataMode) SPCR &= 0xF3; SPCR |= dataMode << 2
- #define SPI_SELECT_CLOCK_PRESCALER(clockPrescaler) SPCR &= 0xFC; SPCR |= (clockPrescaler &
  3); SPSR &= 0xFE; SPSR |= (clockPrescaler & 4) >> 2
- #define SPI_SELECT_DATA_ORDER(dataOrder) SPCR &= 0xDF; SPCR |= dataOrder << 5
- #define SPI_WRITE_COLLISION WCOL
- #define SPI_TRANSFER_COMPLETE SPIF
- #define SPI_MASTER_MODE MSTR
- #define SPI_CONTROL_REGISTER SPCR
- #define SPI_DATA_REGISTER SPDR
- #define SPI_STATUS_REGISTER SPSR
- #define SPI_ENABLE_TRANSFER_COMPLETE_INTERRUPT SPCR |= 1 << SPIE
- #define SPI_DISABLE_TRANSFER_COMPLETE_INTERRUPT SPCR &= ∼(1 << SPIE)
- #define SPI_TRANSFER_COMPLETE_INTERRUPT SPI_STC_vect

7.29.1 Detailed Description

Header file for the hardware abstraction macros of the Atmega328p.

Author

Farid Oubbati (https://github.com/faroub)

Date

March 2020

Definition in file ha_m328p.h.

7.29.2 Macro Definition Documentation

7.29.2.1 ADC_ADJUST_RESULT_LEFT

```
#define ADC_ADJUST_RESULT_LEFT ADMUX |= 1 << ADLAR
```

Definition at line 126 of file ha_m328p.h.

7.29.2.2 ADC_ADJUST_RESULT_RIGHT

```
#define ADC_ADJUST_RESULT_RIGHT ADMUX &= ~(1 << ADLAR)
```

Definition at line 127 of file ha_m328p.h.

7.29.2.3 ADC_CONVERSION_COMPLETE_INTERRUPT

```
#define ADC_CONVERSION_COMPLETE_INTERRUPT ADC_vect
```

Definition at line 151 of file ha_m328p.h.

7.29.2.4 ADC_DISABLE

```
#define ADC_DISABLE ADCSRA &= ~(1 << ADEN)
```

Definition at line 134 of file ha_m328p.h.

7.29.2.5 ADC_DISABLE_AUTOTRIGGER

```
#define ADC_DISABLE_AUTOTRIGGER ADCSRA &= ~(1 << ADATE)
```

Definition at line 140 of file ha_m328p.h.

7.29.2.6 ADC_DISABLE_CONVERSION_COMPLETE_INTERRUPT

```
#define ADC_DISABLE_CONVERSION_COMPLETE_INTERRUPT ADCSRA &= ~(1 << ADIE)
```

Definition at line 143 of file ha_m328p.h.

7.29.2.7 ADC_DISABLE_DIGITAL_INPUT_REGISTER

```
#define ADC_DISABLE_DIGITAL_INPUT_REGISTER(
             pinNumber ) DIDR0 &= 0xC0; DIDR0 |= pinNumber
```

Definition at line 130 of file ha_m328p.h.

7.29.2.8 ADC_ENABLE

```
#define ADC_ENABLE ADCSRA |= 1 << ADEN
```

Definition at line 133 of file ha_m328p.h.

7.29.2.9 ADC_ENABLE_AUTOTRIGGER

```
#define ADC_ENABLE_AUTOTRIGGER ADCSRA |= 1 << ADATE
```

Definition at line 139 of file ha_m328p.h.

7.29.2.10 ADC_ENABLE_CONVERSION_COMPLETE_INTERRUPT

```
#define ADC_ENABLE_CONVERSION_COMPLETE_INTERRUPT ADCSRA |= 1 << ADIE
```

Definition at line 142 of file ha_m328p.h.

7.29.2.11 ADC_SELECT_ANALOG_INPUT

```
#define ADC_SELECT_ANALOG_INPUT(
             pinNumber ) ADMUX &= 0xF0; ADMUX |= pinNumber
```

Definition at line 129 of file ha_m328p.h.

7.29.2.12 ADC_SELECT_AUTO_TRIGGER_SOURCE

```
#define ADC_SELECT_AUTO_TRIGGER_SOURCE(
             triggerSource ) ADCSRB &= 0xF8; ADCSRB |= triggerSource
```

Definition at line 148 of file ha_m328p.h.

7.29.2.13 ADC_SELECT_CLOCK_PRESCALER

```
#define ADC_SELECT_CLOCK_PRESCALER(
             clockPrescaler ) ADCSRA &= 0xF8; ADCSRA |= clockPrescaler
```

Definition at line 145 of file ha_m328p.h.

7.29.2.14 ADC_SELECT_REF_VOLTAGE

```
#define ADC_SELECT_REF_VOLTAGE(
             refVoltage ) ADMUX &= 0x3F; ADMUX |= refVoltage << 6
```

Definition at line 124 of file ha_m328p.h.

7.29.2.15 ADC_START_CONVERSION

```
#define ADC_START_CONVERSION ADCSRA |= 1 << ADSC
```

Definition at line 136 of file ha_m328p.h.

7.29.2.16 ADC_STOP_CONVERSION

```
#define ADC_STOP_CONVERSION ADCSRA &= ∼(1 << ADSC)
```

Definition at line 137 of file ha_m328p.h.

7.29.2.17 EXT_INT_DISABLE_INT0

```
#define EXT_INT_DISABLE_INT0 EIMSK &= ~(1 << INT0)
```

Definition at line 159 of file ha_m328p.h.

7.29.2.18 EXT_INT_DISABLE_INT1

```
#define EXT_INT_DISABLE_INT1 EIMSK &= ~(1 << INT1)
```

Definition at line 162 of file ha_m328p.h.

7.29.2.19 EXT_INT_DISABLE_PIN_CHANGE_INTERRUPT

```
#define EXT_INT_DISABLE_PIN_CHANGE_INTERRUPT(
            pinChangePort ) PCICR &= ~(1 << pinChangePort)
```

Definition at line 166 of file ha_m328p.h.

7.29.2.20 EXT_INT_DISABLE_PIN_CHANGE_MASK_PORTB

```
#define EXT_INT_DISABLE_PIN_CHANGE_MASK_PORTB(
            pinChangePin ) PCMSK0 &= ~(1 << pinChangePin)
```

Definition at line 170 of file ha_m328p.h.

7.29.2.21 EXT_INT_DISABLE_PIN_CHANGE_MASK_PORTC

```
#define EXT_INT_DISABLE_PIN_CHANGE_MASK_PORTC(
            pinChangePin ) PCMSK1 &= ~(1 << pinChangePin)
```

Definition at line 173 of file ha_m328p.h.

7.29.2.22 EXT_INT_DISABLE_PIN_CHANGE_MASK_PORTD

```
#define EXT_INT_DISABLE_PIN_CHANGE_MASK_PORTD(
            pinChangePin ) PCMSK2 &= ~(1 << pinChangePin)
```

Definition at line 176 of file ha_m328p.h.

7.29.2.23 EXT_INT_ENABLE_INT0

```
#define EXT_INT_ENABLE_INT0 EIMSK |= 1 << INT0
```

Definition at line 158 of file ha_m328p.h.

7.29.2.24 EXT_INT_ENABLE_INT1

```
#define EXT_INT_ENABLE_INT1 EIMSK |= 1 << INT1
```

Definition at line 161 of file ha_m328p.h.

7.29.2.25 EXT_INT_ENABLE_PIN_CHANGE_INTERRUPT

```
#define EXT_INT_ENABLE_PIN_CHANGE_INTERRUPT(
            pinChangePort ) PCICR |= 1 << pinChangePort
```

Definition at line 165 of file ha_m328p.h.

7.29.2.26 EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTB

```
#define EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTB(
            pinChangePin ) PCMSK0 |= 1 << pinChangePin
```

Definition at line 169 of file ha_m328p.h.

7.29.2.27 EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTC

```
#define EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTC(
            pinChangePin ) PCMSK1 |= 1 << pinChangePin
```

Definition at line 172 of file ha_m328p.h.

7.29.2.28 EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTD

```
#define EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTD(
            pinChangePin ) PCMSK2 |= 1 << pinChangePin
```

Definition at line 175 of file ha_m328p.h.

7.29.2.29 EXT_INT_INT0_INTERRUPT

#define EXT_INT_INT0_INTERRUPT INT0_vect

Definition at line 179 of file ha_m328p.h.

7.29.2.30 EXT_INT_INT1_INTERRUPT

#define EXT_INT_INT1_INTERRUPT INT1_vect

Definition at line 180 of file ha_m328p.h.

7.29.2.31 EXT_INT_PIN_CHANGE_PORTB_INTERRUPT

#define EXT_INT_PIN_CHANGE_PORTB_INTERRUPT PCINT0_vect

Definition at line 182 of file ha_m328p.h.

7.29.2.32 EXT_INT_PIN_CHANGE_PORTC_INTERRUPT

#define EXT_INT_PIN_CHANGE_PORTC_INTERRUPT PCINT1_vect

Definition at line 183 of file ha_m328p.h.

7.29.2.33 EXT_INT_PIN_CHANGE_PORTD_INTERRUPT

#define EXT_INT_PIN_CHANGE_PORTD_INTERRUPT PCINT2_vect

Definition at line 184 of file ha_m328p.h.

7.29.2.34 EXT_INT_SET_INT0_SENSE_CONTROL

#define EXT_INT_SET_INT0_SENSE_CONTROL(
            senseControl) EICRA &= 0xFC; EICRA |= senseControl

Definition at line 155 of file ha_m328p.h.

7.29.2.35 EXT_INT_SET_INT1_SENSE_CONTROL

```
#define EXT_INT_SET_INT1_SENSE_CONTROL(
             senseControl ) EICRA &= 0xF3; EICRA |= senseControl
```

Definition at line 156 of file ha_m328p.h.

7.29.2.36 MCU_ADC_DISABLE

```
#define MCU_ADC_DISABLE PRR |= 1 << PRADC
```

Definition at line 286 of file ha_m328p.h.

7.29.2.37 MCU_ADC_ENABLE

```
#define MCU_ADC_ENABLE PRR &= ~(1 << PRADC)
```

Definition at line 285 of file ha_m328p.h.

7.29.2.38 MCU_BOD_DISABLE

```
#define MCU_BOD_DISABLE MCUCR |= (1<<BODSE) | (1<<BODS); MCUCR &= ~(1<<BODSE);
```

Definition at line 288 of file ha_m328p.h.

7.29.2.39 MCU_SELECT_SLEEP_MODE

```
#define MCU_SELECT_SLEEP_MODE(
             sleepMode ) SMCR &= 0xF1; SMCR |= sleepMode << 1
```

Definition at line 262 of file ha_m328p.h.

7.29.2.40 MCU_SLEEP_DISABLE

```
#define MCU_SLEEP_DISABLE SMCR &= ~(1 << SE)
```

Definition at line 265 of file ha_m328p.h.

7.29.2.41 MCU_SLEEP_ENABLE

`#define MCU_SLEEP_ENABLE SMCR |= 1 << SE`

Definition at line 264 of file ha_m328p.h.

7.29.2.42 MCU_SPI_DISABLE

`#define MCU_SPI_DISABLE PRR |= 1 << PRSPI`

Definition at line 280 of file ha_m328p.h.

7.29.2.43 MCU_SPI_ENABLE

`#define MCU_SPI_ENABLE PRR &= ∼(1 << PRSPI)`

Definition at line 279 of file ha_m328p.h.

7.29.2.44 MCU_TIMER0_DISABLE

`#define MCU_TIMER0_DISABLE PRR |= 1 << PRTIM0`

Definition at line 277 of file ha_m328p.h.

7.29.2.45 MCU_TIMER0_ENABLE

`#define MCU_TIMER0_ENABLE PRR &= ∼(1 << PRTIM0)`

Definition at line 276 of file ha_m328p.h.

7.29.2.46 MCU_TIMER1_DISABLE

`#define MCU_TIMER1_DISABLE PRR |= 1 << PRTIM1`

Definition at line 274 of file ha_m328p.h.

7.29.2.47 MCU_TIMER1_ENABLE

```
#define MCU_TIMER1_ENABLE PRR &= ~(1 << PRTIM1)
```

Definition at line 273 of file ha_m328p.h.

7.29.2.48 MCU_TIMER2_DISABLE

```
#define MCU_TIMER2_DISABLE PRR |= 1 << PRTIM2
```

Definition at line 271 of file ha_m328p.h.

7.29.2.49 MCU_TIMER2_ENABLE

```
#define MCU_TIMER2_ENABLE PRR &= ~(1 << PRTIM2)
```

Definition at line 270 of file ha_m328p.h.

7.29.2.50 MCU_TWI_DISABLE

```
#define MCU_TWI_DISABLE PRR |= 1 << PRTWI
```

Definition at line 268 of file ha_m328p.h.

7.29.2.51 MCU_TWI_ENABLE

```
#define MCU_TWI_ENABLE PRR &= ~(1 << PRTWI)
```

Definition at line 267 of file ha_m328p.h.

7.29.2.52 MCU_USART0_DISABLE

```
#define MCU_USART0_DISABLE PRR |= 1 << PRUSART0
```

Definition at line 283 of file ha_m328p.h.

7.29.2.53 MCU_USART0_ENABLE

```
#define MCU_USART0_ENABLE PRR &= ∼(1 << PRUSART0)
```

Definition at line 282 of file ha_m328p.h.

7.29.2.54 PUSHBUTTON_DEBOUNCE_TIME_US

```
#define PUSHBUTTON_DEBOUNCE_TIME_US 1000
```

Definition at line 16 of file ha_m328p.h.

7.29.2.55 PUSHBUTTON_SAMPLING

```
#define PUSHBUTTON_SAMPLING 12
```

Definition at line 17 of file ha_m328p.h.

7.29.2.56 SERVOMOTOR_TIMER_ANGLE_COUNT

```
#define SERVOMOTOR_TIMER_ANGLE_COUNT(
            angle,
            out_min,
            out_mid,
            out_max ) (((out_min*(angle - 90L)*(angle - 180L))/16200L + (angle*out_max*(angle
- 90L))/16200L - (angle*out_mid*(angle - 180L))/8100L))
```

Definition at line 295 of file ha_m328p.h.

7.29.2.57 SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT

```
#define SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT(
            pulseWidth,
            clockPrescaler ) ((F_CPU/1000000UL) * (pulseWidth/ clockPrescaler))
```

Definition at line 293 of file ha_m328p.h.

7.29.2.58   SPI_CONTROL_REGISTER

```
#define SPI_CONTROL_REGISTER SPCR
```

Definition at line 313 of file ha_m328p.h.

7.29.2.59   SPI_DATA_REGISTER

```
#define SPI_DATA_REGISTER SPDR
```

Definition at line 314 of file ha_m328p.h.

7.29.2.60   SPI_DISABLE

```
#define SPI_DISABLE SPCR &= ∼(1 << SPE)
```

Definition at line 300 of file ha_m328p.h.

7.29.2.61   SPI_DISABLE_TRANSFER_COMPLETE_INTERRUPT

```
#define SPI_DISABLE_TRANSFER_COMPLETE_INTERRUPT SPCR &= ∼(1 << SPIE)
```

Definition at line 318 of file ha_m328p.h.

7.29.2.62   SPI_ENABLE

```
#define SPI_ENABLE SPCR |= 1 << SPE
```

Definition at line 299 of file ha_m328p.h.

7.29.2.63   SPI_ENABLE_TRANSFER_COMPLETE_INTERRUPT

```
#define SPI_ENABLE_TRANSFER_COMPLETE_INTERRUPT SPCR |= 1 << SPIE
```

Definition at line 317 of file ha_m328p.h.

7.29.2.64 SPI_MASTER_MODE

```
#define SPI_MASTER_MODE MSTR
```

Definition at line 312 of file ha_m328p.h.

7.29.2.65 SPI_SELECT_CLOCK_PRESCALER

```
#define SPI_SELECT_CLOCK_PRESCALER(
            clockPrescaler ) SPCR &= 0xFC; SPCR |= (clockPrescaler & 3); SPSR &= 0xFE; SPSR |=
(clockPrescaler & 4) >> 2
```

Definition at line 306 of file ha_m328p.h.

7.29.2.66 SPI_SELECT_DATA_MODE

```
#define SPI_SELECT_DATA_MODE(
            dataMode ) SPCR &= 0xF3; SPCR |= dataMode << 2
```

Definition at line 305 of file ha_m328p.h.

7.29.2.67 SPI_SELECT_DATA_ORDER

```
#define SPI_SELECT_DATA_ORDER(
            dataOrder ) SPCR &= 0xDF; SPCR |= dataOrder << 5
```

Definition at line 307 of file ha_m328p.h.

7.29.2.68 SPI_SELECT_MASTER_MODE

```
#define SPI_SELECT_MASTER_MODE SPCR |= 1 << MSTR
```

Definition at line 301 of file ha_m328p.h.

7.29.2.69 SPI_SELECT_SLAVE_MODE

```
#define SPI_SELECT_SLAVE_MODE SPCR &= ~(1 << MSTR)
```

Definition at line 302 of file ha_m328p.h.

7.29.2.70 SPI_STATUS_REGISTER

```
#define SPI_STATUS_REGISTER SPSR
```

Definition at line 315 of file ha_m328p.h.

7.29.2.71 SPI_TRANSFER_COMPLETE

```
#define SPI_TRANSFER_COMPLETE SPIF
```

Definition at line 310 of file ha_m328p.h.

7.29.2.72 SPI_TRANSFER_COMPLETE_INTERRUPT

```
#define SPI_TRANSFER_COMPLETE_INTERRUPT SPI_STC_vect
```

Definition at line 321 of file ha_m328p.h.

7.29.2.73 SPI_WRITE_COLLISION

```
#define SPI_WRITE_COLLISION WCOL
```

Definition at line 309 of file ha_m328p.h.

7.29.2.74 TIMER0_COM_CHANNEL_A_INTERRUPT

```
#define TIMER0_COM_CHANNEL_A_INTERRUPT TIMER0_COMPA_vect
```

Definition at line 239 of file ha_m328p.h.

7.29.2.75 TIMER0_COM_CHANNEL_B_INTERRUPT

```
#define TIMER0_COM_CHANNEL_B_INTERRUPT TIMER0_COMPB_vect
```

Definition at line 240 of file ha_m328p.h.

7.29.2.76 TIMER0_DISABLE_COM_CHANNEL_A_INTERRUPT

`#define TIMER0_DISABLE_COM_CHANNEL_A_INTERRUPT TIMSK0 &= ~(1 << OCIE0A)`

Definition at line 210 of file ha_m328p.h.

7.29.2.77 TIMER0_DISABLE_COM_CHANNEL_B_INTERRUPT

`#define TIMER0_DISABLE_COM_CHANNEL_B_INTERRUPT TIMSK0 &= ~(1 << OCIE0B)`

Definition at line 213 of file ha_m328p.h.

7.29.2.78 TIMER0_DISABLE_OVERFLOW_INTERRUPT

`#define TIMER0_DISABLE_OVERFLOW_INTERRUPT TIMSK0 &= ~(1 << TOIE0)`

Definition at line 216 of file ha_m328p.h.

7.29.2.79 TIMER0_ENABLE_COM_CHANNEL_A_INTERRUPT

`#define TIMER0_ENABLE_COM_CHANNEL_A_INTERRUPT TIMSK0 |= 1 << OCIE0A`

Definition at line 209 of file ha_m328p.h.

7.29.2.80 TIMER0_ENABLE_COM_CHANNEL_B_INTERRUPT

`#define TIMER0_ENABLE_COM_CHANNEL_B_INTERRUPT TIMSK0 |= 1 << OCIE0B`

Definition at line 212 of file ha_m328p.h.

7.29.2.81 TIMER0_ENABLE_OVERFLOW_INTERRUPT

`#define TIMER0_ENABLE_OVERFLOW_INTERRUPT TIMSK0 |= 1 << TOIE0`

Definition at line 215 of file ha_m328p.h.

7.29.2.82 TIMER0_OVERFLOW_INTERRUPT

```
#define TIMER0_OVERFLOW_INTERRUPT TIMER0_OVF_vect
```

Definition at line 241 of file ha_m328p.h.

7.29.2.83 TIMER0_SELECT_CLOCK_SOURCE

```
#define TIMER0_SELECT_CLOCK_SOURCE(
            clockSource ) TCCR0B &= 0xF8; TCCR0B |= clockSource
```

Definition at line 192 of file ha_m328p.h.

7.29.2.84 TIMER0_SELECT_COM_CHANNEL_A

```
#define TIMER0_SELECT_COM_CHANNEL_A(
            compareOutputMode ) TCCR0A &= 0x3F; TCCR0A |= compareOutputMode << 6
```

Definition at line 200 of file ha_m328p.h.

7.29.2.85 TIMER0_SELECT_COM_CHANNEL_B

```
#define TIMER0_SELECT_COM_CHANNEL_B(
            compareOutputMode ) TCCR0A &= 0xCF; TCCR0A |= compareOutputMode << 4
```

Definition at line 201 of file ha_m328p.h.

7.29.2.86 TIMER0_SELECT_OPERATION_MODE

```
#define TIMER0_SELECT_OPERATION_MODE(
            operationMode ) TCCR0A &= 0xFC; TCCR0A |= (operationMode & 3); TCCR0B &= 0xF7;
TCCR0B |= (operationMode & 12) << 1
```

Definition at line 196 of file ha_m328p.h.

7.29.2.87 TIMER0_STOP

```
#define TIMER0_STOP TCCR0B &= 0xF8
```

Definition at line 188 of file ha_m328p.h.

7.29.2.88 TIMER1_COM_CHANNEL_A_INTERRUPT

`#define TIMER1_COM_CHANNEL_A_INTERRUPT TIMER1_COMPA_vect`

Definition at line 243 of file ha_m328p.h.

7.29.2.89 TIMER1_COM_CHANNEL_B_INTERRUPT

`#define TIMER1_COM_CHANNEL_B_INTERRUPT TIMER1_COMPB_vect`

Definition at line 244 of file ha_m328p.h.

7.29.2.90 TIMER1_DISABLE_COM_CHANNEL_A_INTERRUPT

`#define TIMER1_DISABLE_COM_CHANNEL_A_INTERRUPT TIMSK1 &= ∼(1 << OCIE1A)`

Definition at line 219 of file ha_m328p.h.

7.29.2.91 TIMER1_DISABLE_COM_CHANNEL_B_INTERRUPT

`#define TIMER1_DISABLE_COM_CHANNEL_B_INTERRUPT TIMSK1 &= ∼(1 << OCIE1B)`

Definition at line 222 of file ha_m328p.h.

7.29.2.92 TIMER1_DISABLE_INPUT_CAPTURE_INTERRUPT

`#define TIMER1_DISABLE_INPUT_CAPTURE_INTERRUPT TIMSK1 &= ∼(1 << ICIE1)`

Definition at line 228 of file ha_m328p.h.

7.29.2.93 TIMER1_DISABLE_OVERFLOW_INTERRUPT

`#define TIMER1_DISABLE_OVERFLOW_INTERRUPT TIMSK1 &= ∼(1 << TOIE1)`

Definition at line 225 of file ha_m328p.h.

7.29.2.94 TIMER1_ENABLE_COM_CHANNEL_A_INTERRUPT

`#define TIMER1_ENABLE_COM_CHANNEL_A_INTERRUPT TIMSK1 |= 1 << OCIE1A`

Definition at line 218 of file ha_m328p.h.

7.29.2.95 TIMER1_ENABLE_COM_CHANNEL_B_INTERRUPT

`#define TIMER1_ENABLE_COM_CHANNEL_B_INTERRUPT TIMSK1 |= 1 << OCIE1B`

Definition at line 221 of file ha_m328p.h.

7.29.2.96 TIMER1_ENABLE_INPUT_CAPTURE_INTERRUPT

`#define TIMER1_ENABLE_INPUT_CAPTURE_INTERRUPT TIMSK1 |= 1 << ICIE1`

Definition at line 227 of file ha_m328p.h.

7.29.2.97 TIMER1_ENABLE_OVERFLOW_INTERRUPT

`#define TIMER1_ENABLE_OVERFLOW_INTERRUPT TIMSK1 |= 1 << TOIE1`

Definition at line 224 of file ha_m328p.h.

7.29.2.98 TIMER1_INPUT_CAPTURE_INTERRUPT

`#define TIMER1_INPUT_CAPTURE_INTERRUPT TIMER1_CAPT_vect`

Definition at line 246 of file ha_m328p.h.

7.29.2.99 TIMER1_OVERFLOW_INTERRUPT

`#define TIMER1_OVERFLOW_INTERRUPT TIMER1_OVF_vect`

Definition at line 245 of file ha_m328p.h.

7.29.2.100 TIMER1_SELECT_CLOCK_SOURCE

```
#define TIMER1_SELECT_CLOCK_SOURCE(
                clockSource ) TCCR1B &= 0xF8; TCCR1B |= clockSource
```

Definition at line 193 of file ha_m328p.h.

7.29.2.101 TIMER1_SELECT_COM_CHANNEL_A

```
#define TIMER1_SELECT_COM_CHANNEL_A(
                compareOutputMode ) TCCR1A &= 0x3F; TCCR1A |= compareOutputMode << 6
```

Definition at line 203 of file ha_m328p.h.

7.29.2.102 TIMER1_SELECT_COM_CHANNEL_B

```
#define TIMER1_SELECT_COM_CHANNEL_B(
                compareOutputMode ) TCCR1A &= 0xCF; TCCR1A |= compareOutputMode << 4
```

Definition at line 204 of file ha_m328p.h.

7.29.2.103 TIMER1_SELECT_OPERATION_MODE

```
#define TIMER1_SELECT_OPERATION_MODE(
                operationMode ) TCCR1A &= 0xFC; TCCR1A |= (operationMode & 3); TCCR1B &= 0xE7;
TCCR1B |= (operationMode & 12) << 1
```

Definition at line 197 of file ha_m328p.h.

7.29.2.104 TIMER1_STOP

```
#define TIMER1_STOP TCCR1B &= 0xF8
```

Definition at line 189 of file ha_m328p.h.

7.29.2.105 TIMER2_COM_CHANNEL_A_INTERRUPT

```
#define TIMER2_COM_CHANNEL_A_INTERRUPT TIMER2_COMPA_vect
```

Definition at line 248 of file ha_m328p.h.

7.29.2.106 TIMER2_COM_CHANNEL_B_INTERRUPT

```
#define TIMER2_COM_CHANNEL_B_INTERRUPT TIMER2_COMPB_vect
```

Definition at line 249 of file ha_m328p.h.

7.29.2.107 TIMER2_DISABLE_COM_CHANNEL_A_INTERRUPT

```
#define TIMER2_DISABLE_COM_CHANNEL_A_INTERRUPT TIMSK2 &= ~(1 << OCIE2A)
```

Definition at line 231 of file ha_m328p.h.

7.29.2.108 TIMER2_DISABLE_COM_CHANNEL_B_INTERRUPT

```
#define TIMER2_DISABLE_COM_CHANNEL_B_INTERRUPT TIMSK2 &= ~(1 << OCIE2B)
```

Definition at line 234 of file ha_m328p.h.

7.29.2.109 TIMER2_DISABLE_OVERFLOW_INTERRUPT

```
#define TIMER2_DISABLE_OVERFLOW_INTERRUPT TIMSK2 &= ~(1 << TOIE2)
```

Definition at line 237 of file ha_m328p.h.

7.29.2.110 TIMER2_ENABLE_COM_CHANNEL_A_INTERRUPT

```
#define TIMER2_ENABLE_COM_CHANNEL_A_INTERRUPT TIMSK2 |= 1 << OCIE2A
```

Definition at line 230 of file ha_m328p.h.

7.29.2.111 TIMER2_ENABLE_COM_CHANNEL_B_INTERRUPT

```
#define TIMER2_ENABLE_COM_CHANNEL_B_INTERRUPT TIMSK2 |= 1 << OCIE2B
```

Definition at line 233 of file ha_m328p.h.

7.29.2.112 TIMER2_ENABLE_OVERFLOW_INTERRUPT

```
#define TIMER2_ENABLE_OVERFLOW_INTERRUPT TIMSK2 |= 1 << TOIE2
```

Definition at line 236 of file ha_m328p.h.

7.29.2.113 TIMER2_OVERFLOW_INTERRUPT

```
#define TIMER2_OVERFLOW_INTERRUPT TIMER2_OVF_vect
```

Definition at line 250 of file ha_m328p.h.

7.29.2.114 TIMER2_SELECT_CLOCK_SOURCE

```
#define TIMER2_SELECT_CLOCK_SOURCE(
             clockSource ) TCCR2B &= 0xF8; TCCR2B |= clockSource
```

Definition at line 194 of file ha_m328p.h.

7.29.2.115 TIMER2_SELECT_COM_CHANNEL_A

```
#define TIMER2_SELECT_COM_CHANNEL_A(
             compareOutputMode ) TCCR2A &= 0x3F; TCCR2A |= compareOutputMode << 6
```

Definition at line 206 of file ha_m328p.h.

7.29.2.116 TIMER2_SELECT_COM_CHANNEL_B

```
#define TIMER2_SELECT_COM_CHANNEL_B(
             compareOutputMode ) TCCR2A &= 0xCF; TCCR2A |= compareOutputMode << 4
```

Definition at line 207 of file ha_m328p.h.

7.29.2.117 TIMER2_SELECT_OPERATION_MODE

```
#define TIMER2_SELECT_OPERATION_MODE(
             operationMode ) TCCR2A &= 0xFC; TCCR2A |= (operationMode & 3); TCCR2B &= 0xF7;
TCCR2B |= (operationMode & 12) << 1
```

Definition at line 198 of file ha_m328p.h.

7.29.2.118 TIMER2_STOP

```
#define TIMER2_STOP TCCR2B &= 0xF8
```

Definition at line 190 of file ha_m328p.h.

7.29.2.119 USART0_CONTROL_STATUS_REGISTER

```
#define USART0_CONTROL_STATUS_REGISTER UCSR0A
```

Definition at line 91 of file ha_m328p.h.

7.29.2.120 USART0_DATA_OVERRUN

```
#define USART0_DATA_OVERRUN DOR0
```

Definition at line 99 of file ha_m328p.h.

7.29.2.121 USART0_DATA_REGISTER

```
#define USART0_DATA_REGISTER UDR0
```

Definition at line 92 of file ha_m328p.h.

7.29.2.122 USART0_DATA_REGISTER_EMPTY_INTERRUPT

```
#define USART0_DATA_REGISTER_EMPTY_INTERRUPT USART_UDRE_vect
```

Definition at line 119 of file ha_m328p.h.

7.29.2.123 USART0_DISABLE_DATA_REGISTER_EMPTY_INTERRUPT

```
#define USART0_DISABLE_DATA_REGISTER_EMPTY_INTERRUPT UCSR0B &= ~(1 << UDRIE0)
```

Definition at line 105 of file ha_m328p.h.

7.29.2.124 USART0_DISABLE_DOUBLE_SPEED_MODE [1/2]

```
#define USART0_DISABLE_DOUBLE_SPEED_MODE
```

Definition at line 40 of file ha_m328p.h.

7.29.2.125 USART0_DISABLE_DOUBLE_SPEED_MODE [2/2]

```
#define USART0_DISABLE_DOUBLE_SPEED_MODE UCSR0A &= ~(1 << U2X0)
```

Definition at line 40 of file ha_m328p.h.

7.29.2.126 USART0_DISABLE_PARITY_MODE

```
#define USART0_DISABLE_PARITY_MODE UCSR0C &= ~((1 << UPM01) | (1 << UPM00))
```

Definition at line 45 of file ha_m328p.h.

7.29.2.127 USART0_DISABLE_RECEIVE_COMPLETE_INTERRUPT

```
#define USART0_DISABLE_RECEIVE_COMPLETE_INTERRUPT UCSR0B &= ~(1 << RXCIE0)
```

Definition at line 108 of file ha_m328p.h.

7.29.2.128 USART0_DISABLE_RECEIVER

```
#define USART0_DISABLE_RECEIVER UCSR0B &= ~(1 << RXEN0)
```

Definition at line 87 of file ha_m328p.h.

7.29.2.129 USART0_DISABLE_TRANSMIT_COMPLETE_INTERRUPT

```
#define USART0_DISABLE_TRANSMIT_COMPLETE_INTERRUPT UCSR0B &= ~(1 << TXCIE0)
```

Definition at line 111 of file ha_m328p.h.

7.29.2.130 USART0_DISABLE_TRANSMITTER

```
#define USART0_DISABLE_TRANSMITTER UCSR0B &= ∼(1 << TXEN0)
```

Definition at line 82 of file ha_m328p.h.

7.29.2.131 USART0_ENABLE_ASYNC_TRANSMISSION_MODE

```
#define USART0_ENABLE_ASYNC_TRANSMISSION_MODE UCSR0C &= ∼((1 << UMSEL01) | (1 << UMSEL00))
```

Definition at line 26 of file ha_m328p.h.

7.29.2.132 USART0_ENABLE_DATA_REGISTER_EMPTY_INTERRUPT

```
#define USART0_ENABLE_DATA_REGISTER_EMPTY_INTERRUPT UCSR0B |= 1 << UDRIE0
```

Definition at line 104 of file ha_m328p.h.

7.29.2.133 USART0_ENABLE_DOUBLE_SPEED_MODE

```
#define USART0_ENABLE_DOUBLE_SPEED_MODE
```

Definition at line 31 of file ha_m328p.h.

7.29.2.134 USART0_ENABLE_EVEN_PARITY_MODE

```
#define USART0_ENABLE_EVEN_PARITY_MODE UCSR0C = (1 << UPM01) | (UCSR0C & ∼(1 << UPM00))
```

Definition at line 43 of file ha_m328p.h.

7.29.2.135 USART0_ENABLE_MASTER_SPI_MODE

```
#define USART0_ENABLE_MASTER_SPI_MODE UCSR0C |= (1 << UMSEL01) | (1 << UMSEL00)
```

Definition at line 28 of file ha_m328p.h.

7.29.2.136 USART0_ENABLE_ODD_PARITY_MODE

`#define USART0_ENABLE_ODD_PARITY_MODE UCSR0C |= ((1 << UPM01) | (1 << UPM00))`

Definition at line 44 of file ha_m328p.h.

7.29.2.137 USART0_ENABLE_RECEIVE_COMPLETE_INTERRUPT

`#define USART0_ENABLE_RECEIVE_COMPLETE_INTERRUPT UCSR0B |= 1 << RXCIE0`

Definition at line 107 of file ha_m328p.h.

7.29.2.138 USART0_ENABLE_RECEIVER

`#define USART0_ENABLE_RECEIVER UCSR0B |= 1 << RXEN0`

Definition at line 86 of file ha_m328p.h.

7.29.2.139 USART0_ENABLE_SYNC_TRANSMISSION_MODE

`#define USART0_ENABLE_SYNC_TRANSMISSION_MODE UCSR0C = (UCSR0C & ~(1 << UMSEL01)) | (1 << UM↩SEL00)`

Definition at line 27 of file ha_m328p.h.

7.29.2.140 USART0_ENABLE_TRANSMIT_COMPLETE_INTERRUPT

`#define USART0_ENABLE_TRANSMIT_COMPLETE_INTERRUPT UCSR0B |= 1 << TXCIE0`

Definition at line 110 of file ha_m328p.h.

7.29.2.141 USART0_ENABLE_TRANSMITTER

`#define USART0_ENABLE_TRANSMITTER UCSR0B |= 1 << TXEN0`

Definition at line 81 of file ha_m328p.h.

7.29.2.142 USART0_FRAME_ERROR

```
#define USART0_FRAME_ERROR FE0
```

Definition at line 97 of file ha_m328p.h.

7.29.2.143 USART0_PARITY_ERROR

```
#define USART0_PARITY_ERROR UPE0
```

Definition at line 101 of file ha_m328p.h.

7.29.2.144 USART0_RECEIVE_COMPLETE_INTERRUPT

```
#define USART0_RECEIVE_COMPLETE_INTERRUPT USART_RX_vect
```

Definition at line 115 of file ha_m328p.h.

7.29.2.145 USART0_SET_5BIT_FRAME_SIZE

```
#define USART0_SET_5BIT_FRAME_SIZE
```

Value:
```
do { \
    UCSR0C &= ~((1 « UCSZ01) | (1 « UCSZ00)); \
    UCSR0B &= ~(1 « UCSZ02); \
} while (0)
```

Definition at line 74 of file ha_m328p.h.

7.29.2.146 USART0_SET_6BIT_FRAME_SIZE

```
#define USART0_SET_6BIT_FRAME_SIZE
```

Value:
```
do { \
    UCSR0C = (UCSR0C & ~(1 « UCSZ01)) | (1 « UCSZ00); \
    UCSR0B &= ~(1 « UCSZ02); \
} while (0)
```

Definition at line 69 of file ha_m328p.h.

7.29.2.147 USART0_SET_7BIT_FRAME_SIZE

#define USART0_SET_7BIT_FRAME_SIZE

Value:
```
do { \
    UCSR0C = (1 << UCSZ01) | (UCSR0C & ~(1 << UCSZ00)); \
    UCSR0B &= ~(1 << UCSZ02); \
} while (0)
```

Definition at line 64 of file ha_m328p.h.

7.29.2.148 USART0_SET_8BIT_FRAME_SIZE

#define USART0_SET_8BIT_FRAME_SIZE

Value:
```
do { \
    UCSR0C |= ((1 << UCSZ01) | (1 << UCSZ00)); \
    UCSR0B &= ~(1 << UCSZ02); \
} while (0)
```

Definition at line 58 of file ha_m328p.h.

7.29.2.149 USART0_SET_9BIT_FRAME_SIZE

#define USART0_SET_9BIT_FRAME_SIZE

Value:
```
do { \
    UCSR0C |= ((1 << UCSZ01) | (1 << UCSZ00)); \
    UCSR0B |= (1 << UCSZ02); \
} while (0)
```

Definition at line 52 of file ha_m328p.h.

7.29.2.150 USART0_SET_BAUDRATE_HIGH_REGISTER

#define USART0_SET_BAUDRATE_HIGH_REGISTER UBRR0H = UBRRH_VALUE

Definition at line 23 of file ha_m328p.h.

7.29.2.151 USART0_SET_BAUDRATE_LOW_REGISTER

#define USART0_SET_BAUDRATE_LOW_REGISTER UBRR0L = UBRRL_VALUE

Definition at line 24 of file ha_m328p.h.

7.29.2.152 USART0_SET_ONE_STOP_BIT

```
#define USART0_SET_ONE_STOP_BIT UCSR0C &= ∼(1 << USBS0)
```

Definition at line 48 of file ha_m328p.h.

7.29.2.153 USART0_SET_TWO_STOP_BITS

```
#define USART0_SET_TWO_STOP_BITS UCSR0C |= (1 << USBS0)
```

Definition at line 49 of file ha_m328p.h.

7.29.2.154 USART0_TRANSMIT_COMPLETE_INTERRUPT

```
#define USART0_TRANSMIT_COMPLETE_INTERRUPT USART_TX_vect
```

Definition at line 117 of file ha_m328p.h.

7.29.2.155 WATCHDOG_SELECT_TIMEOUT

```
#define WATCHDOG_SELECT_TIMEOUT(
            timeOut ) WDTCSR |= (1<<WDCE) | (1<<WDE); WDTCSR = (0<<WDIE) | (0<<WDE) | time↩
Out;
```

Definition at line 254 of file ha_m328p.h.

7.29.2.156 WATCHDOG_START

```
#define WATCHDOG_START(
            operationMode,
            timeOut ) MCUSR &= ∼(1<<WDRF); WDTCSR |= (1<<WDCE) | (1<<WDE); WDTCSR = operation↩
Mode | timeOut;
```

Definition at line 255 of file ha_m328p.h.

7.29.2.157 WATCHDOG_STOP

```
#define WATCHDOG_STOP MCUSR &= ∼(1<<WDRF); WDTCSR |= (1<<WDCE) | (1<<WDE); WDTCSR = 0x00;
```

Definition at line 256 of file ha_m328p.h.

7.29.2.158 WATCHDOG_TIMEOUT_INTERRUPT

```
#define WATCHDOG_TIMEOUT_INTERRUPT WDT_vect
```

Definition at line 257 of file ha_m328p.h.

7.30   ha_m328p.h

```
00001
00008 #ifndef HAM329P_H
00009 #define HAM329P_H
00010
00011 #ifndef HABASE_H
00012     #error "don't use this file directly! Please include only ha_base.h!"
00013 #endif
00014
00015 // PushButton defines
00016 #define PUSHBUTTON_DEBOUNCE_TIME_US 1000 // microseconds to wait for next check
00017 #define PUSHBUTTON_SAMPLING    12          // number of times a push button must be pressed
00018
00019
00020 // USART defines
00021 #include <util/setbaud.h>
00022
00023 #define   USART0_SET_BAUDRATE_HIGH_REGISTER     UBRR0H = UBRRH_VALUE
00024 #define   USART0_SET_BAUDRATE_LOW_REGISTER      UBRR0L = UBRRL_VALUE
00025
00026 #define   USART0_ENABLE_ASYNC_TRANSMISSION_MODE    UCSR0C &= ~((1 « UMSEL01) | (1 « UMSEL00))
00027 #define   USART0_ENABLE_SYNC_TRANSMISSION_MODE     UCSR0C = (UCSR0C & ~(1 « UMSEL01)) | (1 « UMSEL00)
00028 #define   USART0_ENABLE_MASTER_SPI_MODE            UCSR0C |= (1 « UMSEL01) | (1 « UMSEL00)
00029
00030
00031 #define   USART0_ENABLE_DOUBLE_SPEED_MODE
00032 #define   USART0_DISABLE_DOUBLE_SPEED_MODE
00033
00034 #if USE_2X
00035     #undef  USART0_ENABLE_DOUBLE_SPEED_MODE
00036     #define USART0_ENABLE_DOUBLE_SPEED_MODE UCSR0A |= (1 « U2X0)
00037     #warning "double speed operation activated"
00038 #else
00039     #undef  USART0_DISABLE_DOUBLE_SPEED_MODE
00040     #define USART0_DISABLE_DOUBLE_SPEED_MODE UCSR0A &= ~(1 « U2X0)
00041 #endif
00042
00043 #define   USART0_ENABLE_EVEN_PARITY_MODE    UCSR0C = (1 « UPM01) | (UCSR0C & ~(1 « UPM00))
00044 #define   USART0_ENABLE_ODD_PARITY_MODE     UCSR0C |=  ((1 « UPM01) | (1 « UPM00))
00045 #define   USART0_DISABLE_PARITY_MODE        UCSR0C &= ~((1 « UPM01) | (1 « UPM00))
00046
00047
00048 #define   USART0_SET_ONE_STOP_BIT   UCSR0C &= ~(1 « USBS0)
00049 #define   USART0_SET_TWO_STOP_BITS  UCSR0C |= (1 « USBS0)
00050
00051
00052 #define   USART0_SET_9BIT_FRAME_SIZE   \
00053     do { \
00054         UCSR0C |= ((1 « UCSZ01) | (1 « UCSZ00)); \
00055         UCSR0B |= (1 « UCSZ02); \
00056     } while (0)
00057
00058 #define   USART0_SET_8BIT_FRAME_SIZE   \
00059     do { \
00060         UCSR0C |= ((1 « UCSZ01) | (1 « UCSZ00)); \
00061         UCSR0B &= ~(1 « UCSZ02); \
00062     } while (0)
00063
00064 #define   USART0_SET_7BIT_FRAME_SIZE  \
00065     do { \
00066         UCSR0C = (1 « UCSZ01) | (UCSR0C & ~(1 « UCSZ00)); \
00067         UCSR0B &= ~(1 « UCSZ02); \
00068     } while (0)
00069 #define   USART0_SET_6BIT_FRAME_SIZE \
00070     do { \
00071         UCSR0C = (UCSR0C & ~(1 « UCSZ01)) | (1 « UCSZ00); \
00072         UCSR0B &= ~(1 « UCSZ02); \
00073     } while (0)
00074 #define   USART0_SET_5BIT_FRAME_SIZE \
00075     do { \
00076         UCSR0C &= ~((1 « UCSZ01) | (1 « UCSZ00)); \
00077         UCSR0B &= ~(1 « UCSZ02); \
00078     } while (0)
```

```
00079
00080
00081 #define   USART0_ENABLE_TRANSMITTER       UCSR0B |=   1 « TXEN0
00082 #define   USART0_DISABLE_TRANSMITTER      UCSR0B &= ~(1 « TXEN0)
00083
00084
00085
00086 #define   USART0_ENABLE_RECEIVER          UCSR0B |=   1 « RXEN0
00087 #define   USART0_DISABLE_RECEIVER         UCSR0B &= ~(1 « RXEN0)
00088
00089
00090
00091 #define   USART0_CONTROL_STATUS_REGISTER UCSR0A
00092 #define   USART0_DATA_REGISTER           UDR0
00093
00094
00095
00096
00097 #define   USART0_FRAME_ERROR             FE0
00098
00099 #define   USART0_DATA_OVERRUN            DOR0
00100
00101 #define   USART0_PARITY_ERROR           UPE0
00102
00103
00104 #define   USART0_ENABLE_DATA_REGISTER_EMPTY_INTERRUPT   UCSR0B |=   1 « UDRIE0
00105 #define   USART0_DISABLE_DATA_REGISTER_EMPTY_INTERRUPT  UCSR0B &= ~(1 « UDRIE0)
00106
00107 #define   USART0_ENABLE_RECEIVE_COMPLETE_INTERRUPT   UCSR0B |=   1 « RXCIE0
00108 #define   USART0_DISABLE_RECEIVE_COMPLETE_INTERRUPT  UCSR0B &= ~(1 « RXCIE0)
00109
00110 #define   USART0_ENABLE_TRANSMIT_COMPLETE_INTERRUPT   UCSR0B |=   1 « TXCIE0
00111 #define   USART0_DISABLE_TRANSMIT_COMPLETE_INTERRUPT  UCSR0B &= ~(1 « TXCIE0)
00112
00113
00114
00115 #define   USART0_RECEIVE_COMPLETE_INTERRUPT     USART_RX_vect
00116
00117 #define   USART0_TRANSMIT_COMPLETE_INTERRUPT    USART_TX_vect
00118
00119 #define   USART0_DATA_REGISTER_EMPTY_INTERRUPT  USART_UDRE_vect
00120
00121
00122 // ADC defines
00123
00124 #define   ADC_SELECT_REF_VOLTAGE(refVoltage)       ADMUX &= 0x3F; ADMUX |= refVoltage « 6
00125
00126 #define   ADC_ADJUST_RESULT_LEFT           ADMUX |=   1 « ADLAR
00127 #define   ADC_ADJUST_RESULT_RIGHT          ADMUX &= ~(1 « ADLAR)
00128
00129 #define   ADC_SELECT_ANALOG_INPUT(pinNumber)       ADMUX &= 0xF0; ADMUX |= pinNumber
00130 #define   ADC_DISABLE_DIGITAL_INPUT_REGISTER(pinNumber)      DIDR0 &= 0xC0; DIDR0 |= pinNumber
00131
00132
00133 #define   ADC_ENABLE            ADCSRA |=   1 « ADEN
00134 #define   ADC_DISABLE          ADCSRA &= ~(1 « ADEN)
00135
00136 #define   ADC_START_CONVERSION            ADCSRA |=   1 « ADSC
00137 #define   ADC_STOP_CONVERSION           ADCSRA &= ~(1 « ADSC)
00138
00139 #define   ADC_ENABLE_AUTOTRIGGER          ADCSRA |=   1 « ADATE
00140 #define   ADC_DISABLE_AUTOTRIGGER         ADCSRA &= ~(1 « ADATE)
00141
00142 #define   ADC_ENABLE_CONVERSION_COMPLETE_INTERRUPT   ADCSRA |=   1 « ADIE
00143 #define   ADC_DISABLE_CONVERSION_COMPLETE_INTERRUPT  ADCSRA &= ~(1 « ADIE)
00144
00145 #define   ADC_SELECT_CLOCK_PRESCALER(clockPrescaler)       ADCSRA &= 0xF8; ADCSRA |= clockPrescaler
00146
00147
00148 #define   ADC_SELECT_AUTO_TRIGGER_SOURCE(triggerSource)       ADCSRB &= 0xF8; ADCSRB |=
     triggerSource
00149
00150
00151 #define   ADC_CONVERSION_COMPLETE_INTERRUPT  ADC_vect
00152
00153 // Externally Triggered Interrupts defines
00154
00155 #define EXT_INT_SET_INT0_SENSE_CONTROL(senseControl) EICRA &= 0xFC; EICRA |= senseControl
00156 #define EXT_INT_SET_INT1_SENSE_CONTROL(senseControl) EICRA &= 0xF3; EICRA |= senseControl
00157
00158 #define EXT_INT_ENABLE_INT0   EIMSK |= 1 « INT0
00159 #define EXT_INT_DISABLE_INT0   EIMSK &= ~(1 « INT0)
00160
00161 #define EXT_INT_ENABLE_INT1   EIMSK |= 1 « INT1
00162 #define EXT_INT_DISABLE_INT1   EIMSK &= ~(1 « INT1)
00163
00164
```

```
00165 #define EXT_INT_ENABLE_PIN_CHANGE_INTERRUPT(pinChangePort)     PCICR |= 1 « pinChangePort
00166 #define EXT_INT_DISABLE_PIN_CHANGE_INTERRUPT(pinChangePort)    PCICR &= ~(1 « pinChangePort)
00167
00168
00169 #define EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTB(pinChangePin)     PCMSK0 |= 1 « pinChangePin
00170 #define EXT_INT_DISABLE_PIN_CHANGE_MASK_PORTB(pinChangePin)    PCMSK0 &= ~(1 « pinChangePin)
00171
00172 #define EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTC(pinChangePin)     PCMSK1 |= 1 « pinChangePin
00173 #define EXT_INT_DISABLE_PIN_CHANGE_MASK_PORTC(pinChangePin)    PCMSK1 &= ~(1 « pinChangePin)
00174
00175 #define EXT_INT_ENABLE_PIN_CHANGE_MASK_PORTD(pinChangePin)     PCMSK2 |= 1 « pinChangePin
00176 #define EXT_INT_DISABLE_PIN_CHANGE_MASK_PORTD(pinChangePin)    PCMSK2 &= ~(1 « pinChangePin)
00177
00178
00179 #define  EXT_INT_INT0_INTERRUPT   INT0_vect
00180 #define  EXT_INT_INT1_INTERRUPT   INT1_vect
00181
00182 #define  EXT_INT_PIN_CHANGE_PORTB_INTERRUPT   PCINT0_vect
00183 #define  EXT_INT_PIN_CHANGE_PORTC_INTERRUPT   PCINT1_vect
00184 #define  EXT_INT_PIN_CHANGE_PORTD_INTERRUPT   PCINT2_vect
00185
00186 // Timers/Counters defines
00187
00188 #define TIMER0_STOP TCCR0B &= 0xF8
00189 #define TIMER1_STOP TCCR1B &= 0xF8
00190 #define TIMER2_STOP TCCR2B &= 0xF8
00191
00192 #define TIMER0_SELECT_CLOCK_SOURCE(clockSource) TCCR0B &= 0xF8; TCCR0B |= clockSource
00193 #define TIMER1_SELECT_CLOCK_SOURCE(clockSource) TCCR1B &= 0xF8; TCCR1B |= clockSource
00194 #define TIMER2_SELECT_CLOCK_SOURCE(clockSource) TCCR2B &= 0xF8; TCCR2B |= clockSource
00195
00196 #define TIMER0_SELECT_OPERATION_MODE(operationMode) TCCR0A &= 0xFC; TCCR0A |= (operationMode & 3);
      TCCR0B &= 0xF7; TCCR0B |= (operationMode & 12) « 1
00197 #define TIMER1_SELECT_OPERATION_MODE(operationMode) TCCR1A &= 0xFC; TCCR1A |= (operationMode & 3);
      TCCR1B &= 0xE7; TCCR1B |= (operationMode & 12) « 1
00198 #define TIMER2_SELECT_OPERATION_MODE(operationMode) TCCR2A &= 0xFC; TCCR2A |= (operationMode & 3);
      TCCR2B &= 0xF7; TCCR2B |= (operationMode & 12) « 1
00199
00200 #define TIMER0_SELECT_COM_CHANNEL_A(compareOutputMode) TCCR0A &= 0x3F; TCCR0A |= compareOutputMode « 6
00201 #define TIMER0_SELECT_COM_CHANNEL_B(compareOutputMode) TCCR0A &= 0xCF; TCCR0A |= compareOutputMode « 4
00202
00203 #define TIMER1_SELECT_COM_CHANNEL_A(compareOutputMode) TCCR1A &= 0x3F; TCCR1A |= compareOutputMode « 6
00204 #define TIMER1_SELECT_COM_CHANNEL_B(compareOutputMode) TCCR1A &= 0xCF; TCCR1A |= compareOutputMode « 4
00205
00206 #define TIMER2_SELECT_COM_CHANNEL_A(compareOutputMode) TCCR2A &= 0x3F; TCCR2A |= compareOutputMode « 6
00207 #define TIMER2_SELECT_COM_CHANNEL_B(compareOutputMode) TCCR2A &= 0xCF; TCCR2A |= compareOutputMode « 4
00208
00209 #define TIMER0_ENABLE_COM_CHANNEL_A_INTERRUPT TIMSK0 |=  1 « OCIE0A
00210 #define TIMER0_DISABLE_COM_CHANNEL_A_INTERRUPT TIMSK0 &= ~(1 « OCIE0A)
00211
00212 #define TIMER0_ENABLE_COM_CHANNEL_B_INTERRUPT TIMSK0 |=  1 « OCIE0B
00213 #define TIMER0_DISABLE_COM_CHANNEL_B_INTERRUPT TIMSK0 &= ~(1 « OCIE0B)
00214
00215 #define TIMER0_ENABLE_OVERFLOW_INTERRUPT TIMSK0 |=  1 « TOIE0
00216 #define TIMER0_DISABLE_OVERFLOW_INTERRUPT TIMSK0 &= ~(1 « TOIE0)
00217
00218 #define TIMER1_ENABLE_COM_CHANNEL_A_INTERRUPT TIMSK1 |=  1 « OCIE1A
00219 #define TIMER1_DISABLE_COM_CHANNEL_A_INTERRUPT TIMSK1 &= ~(1 « OCIE1A)
00220
00221 #define TIMER1_ENABLE_COM_CHANNEL_B_INTERRUPT TIMSK1 |=  1 « OCIE1B
00222 #define TIMER1_DISABLE_COM_CHANNEL_B_INTERRUPT TIMSK1 &= ~(1 « OCIE1B)
00223
00224 #define TIMER1_ENABLE_OVERFLOW_INTERRUPT TIMSK1 |=  1 « TOIE1
00225 #define TIMER1_DISABLE_OVERFLOW_INTERRUPT TIMSK1 &= ~(1 « TOIE1)
00226
00227 #define TIMER1_ENABLE_INPUT_CAPTURE_INTERRUPT TIMSK1 |=  1 « ICIE1
00228 #define TIMER1_DISABLE_INPUT_CAPTURE_INTERRUPT TIMSK1 &= ~(1 « ICIE1)
00229
00230 #define TIMER2_ENABLE_COM_CHANNEL_A_INTERRUPT TIMSK2 |=  1 « OCIE2A
00231 #define TIMER2_DISABLE_COM_CHANNEL_A_INTERRUPT TIMSK2 &= ~(1 « OCIE2A)
00232
00233 #define TIMER2_ENABLE_COM_CHANNEL_B_INTERRUPT TIMSK2 |=  1 « OCIE2B
00234 #define TIMER2_DISABLE_COM_CHANNEL_B_INTERRUPT TIMSK2 &= ~(1 « OCIE2B)
00235
00236 #define TIMER2_ENABLE_OVERFLOW_INTERRUPT TIMSK2 |=  1 « TOIE2
00237 #define TIMER2_DISABLE_OVERFLOW_INTERRUPT TIMSK2 &= ~(1 « TOIE2)
00238
00239 #define    TIMER0_COM_CHANNEL_A_INTERRUPT  TIMER0_COMPA_vect
00240 #define    TIMER0_COM_CHANNEL_B_INTERRUPT  TIMER0_COMPB_vect
00241 #define    TIMER0_OVERFLOW_INTERRUPT  TIMER0_OVF_vect
00242
00243 #define    TIMER1_COM_CHANNEL_A_INTERRUPT  TIMER1_COMPA_vect
00244 #define    TIMER1_COM_CHANNEL_B_INTERRUPT  TIMER1_COMPB_vect
00245 #define    TIMER1_OVERFLOW_INTERRUPT  TIMER1_OVF_vect
00246 #define    TIMER1_INPUT_CAPTURE_INTERRUPT  TIMER1_CAPT_vect
00247
00248 #define    TIMER2_COM_CHANNEL_A_INTERRUPT  TIMER2_COMPA_vect
```

```
00249 #define   TIMER2_COM_CHANNEL_B_INTERRUPT  TIMER2_COMPB_vect
00250 #define   TIMER2_OVERFLOW_INTERRUPT  TIMER2_OVF_vect
00251
00252 // Watchdog Timer defines
00253
00254 #define WATCHDOG_SELECT_TIMEOUT(timeOut) WDTCSR |= (1«WDCE) | (1«WDE);  WDTCSR = (0«WDIE) | (0«WDE) |
      timeOut;
00255 #define WATCHDOG_START(operationMode,timeOut) MCUSR &= ~(1«WDRF); WDTCSR |= (1«WDCE) | (1«WDE); WDTCSR
      = operationMode | timeOut;
00256 #define WATCHDOG_STOP MCUSR &= ~(1«WDRF); WDTCSR |= (1«WDCE) | (1«WDE); WDTCSR = 0x00;
00257 #define WATCHDOG_TIMEOUT_INTERRUPT  WDT_vect
00258
00259 // MCU defines
00260
00261
00262 #define MCU_SELECT_SLEEP_MODE(sleepMode) SMCR &= 0xF1; SMCR |= sleepMode « 1
00263
00264 #define MCU_SLEEP_ENABLE SMCR |=  1 « SE
00265 #define MCU_SLEEP_DISABLE SMCR &= ~(1 « SE)
00266
00267 #define MCU_TWI_ENABLE PRR &= ~(1 « PRTWI)
00268 #define MCU_TWI_DISABLE PRR |=  1 « PRTWI
00269
00270 #define MCU_TIMER2_ENABLE PRR &= ~(1 « PRTIM2)
00271 #define MCU_TIMER2_DISABLE PRR |=  1 « PRTIM2
00272
00273 #define MCU_TIMER1_ENABLE PRR &= ~(1 « PRTIM1)
00274 #define MCU_TIMER1_DISABLE PRR |=  1 « PRTIM1
00275
00276 #define MCU_TIMER0_ENABLE PRR &= ~(1 « PRTIM0)
00277 #define MCU_TIMER0_DISABLE PRR |=  1 « PRTIM0
00278
00279 #define MCU_SPI_ENABLE PRR &= ~(1 « PRSPI)
00280 #define MCU_SPI_DISABLE PRR |=  1 « PRSPI
00281
00282 #define MCU_USART0_ENABLE PRR &= ~(1 « PRUSART0)
00283 #define MCU_USART0_DISABLE PRR |=  1 « PRUSART0
00284
00285 #define MCU_ADC_ENABLE PRR &= ~(1 « PRADC)
00286 #define MCU_ADC_DISABLE PRR |=  1 « PRADC
00287
00288 #define MCU_BOD_DISABLE MCUCR |= (1«BODSE) | (1«BODS); MCUCR &= ~(1«BODSE);
00289
00290
00291 // ServoMotor defines
00292
00293 #define SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT(pulseWidth,clockPrescaler) ((F_CPU/1000000UL) *
      (pulseWidth/ clockPrescaler))
00294
00295 #define SERVOMOTOR_TIMER_ANGLE_COUNT(angle,out_min,out_mid,out_max) (((out_min*(angle - 90L)*(angle -
      180L))/16200L + (angle*out_max*(angle - 90L))/16200L - (angle*out_mid*(angle - 180L))/8100L))
00296
00297 // SPI defines
00298
00299 #define   SPI_ENABLE            SPCR |=  1 « SPE
00300 #define   SPI_DISABLE           SPCR &= ~(1 « SPE)
00301 #define   SPI_SELECT_MASTER_MODE SPCR |=  1 « MSTR
00302 #define   SPI_SELECT_SLAVE_MODE SPCR &= ~(1 « MSTR)
00303
00304
00305 #define   SPI_SELECT_DATA_MODE(dataMode) SPCR &= 0xF3; SPCR |= dataMode « 2
00306 #define   SPI_SELECT_CLOCK_PRESCALER(clockPrescaler) SPCR &= 0xFC; SPCR |= (clockPrescaler & 3); SPSR
      &= 0xFE; SPSR |= (clockPrescaler & 4) » 2
00307 #define   SPI_SELECT_DATA_ORDER(dataOrder) SPCR &= 0xDF; SPCR |= dataOrder « 5
00308
00309 #define   SPI_WRITE_COLLISION WCOL
00310 #define   SPI_TRANSFER_COMPLETE SPIF
00311
00312 #define   SPI_MASTER_MODE MSTR
00313 #define   SPI_CONTROL_REGISTER SPCR
00314 #define   SPI_DATA_REGISTER SPDR
00315 #define   SPI_STATUS_REGISTER SPSR
00316
00317 #define   SPI_ENABLE_TRANSFER_COMPLETE_INTERRUPT SPCR |= 1 « SPIE
00318 #define   SPI_DISABLE_TRANSFER_COMPLETE_INTERRUPT SPCR &= ~(1 « SPIE)
00319
00320
00321 #define   SPI_TRANSFER_COMPLETE_INTERRUPT SPI_STC_vect
00322
00323 // StepperMotor defines
00324
00325
00326
00327
00328
00329
00330 #endif
```

00331

7.31 LCD.cpp File Reference

7.32 LCD.cpp

7.33 LCD.h File Reference

7.34 LCD.h

7.35 Led.cpp File Reference

```
#include "Led.h"
```
Include dependency graph for Led.cpp:

7.36 Led.cpp

```cpp
00001 #include "Led.h"
00002
00003 component::Led::Led(const io::Pin &ar_pin)
00004          : m_pin(ar_pin)
00005 {
00006     m_pin.toOutput();
00007 }
00008
00009 component::Led::~Led()
00010 {
00011
00012 }
00013
00014
00015 void component::Led::on()
00016 {
00017     m_pin.setHigh();
00018
00019 }
00020
00021 void component::Led::off()
```

```
00022 {
00023     m_pin.setLow();
00024
00025 }
00026
00027
00028 void component::Led::toggle()
00029 {
00030     m_pin.toggle();
00031
00032 }
00033
00034 uint8_t component::Led::isOn()
00035 {
00036     return m_pin.isHigh();
00037
00038 }
00039
00040
00041 uint8_t component::Led::isOff()
00042 {
00043     return m_pin.isLow();
00044
00045 }
00046
```

7.37   Led.h File Reference

Header file of the Led class.

```
#include "Pin.h"
```
Include dependency graph for Led.h:

This graph shows which files directly or indirectly include this file:

Classes

- class component::Led

Namespaces

- component

7.37.1 Detailed Description

Header file of the Led class.

class to control a Led.

Usage example (simple on/off example):

Author

Farid Oubbati (`https://github.com/faroub`)

Date

March 2020

Definition in file Led.h.

7.38 Led.h

```
00001 #ifndef LED_H
00002 #define LED_H
00003 #include "Pin.h"
00004
00017 namespace component
00018 {
00019
00032 class Led
00033 {
00034
00035 public:
00042     Led(const io::Pin &ar_pin);
00046     ~Led();
00049     void on();
00052     void off();
00055     void toggle();
00058     uint8_t isOn();
00061     uint8_t isOff();
00062
00063 protected:
00064
00065 private:
00066
00067     io::Pin m_pin;
00071 };
00072
00073 }
00074
00075
00076 #endif
```

7.39 main.cpp File Reference

Demo example: Blink a Led.

```
#include "Led.h"
#include <util/delay.h>
```
Include dependency graph for main.cpp:

Macros

- #define PIN_NUMBER 0

    Led pin number.
- #define TIMEDELAY 500

    Time delay.

Functions

- int main (void)

7.39.1 Detailed Description

Demo example: Blink a Led.

Usage demonstration of the TahakomAVRLib in a simple blink a Led example. This example demonstrates the use of the Led and Pin abstraction objects.

- Compiler: gcc-avr

- Supported devices: The example compiles on the ATmega48P/88P/168P/328P AVR family

Author

    Farid Oubbati (https://github.com/faroub)

Date

    March 2018

Definition in file main.cpp.

7.39.2 Macro Definition Documentation

7.39.2.1 PIN_NUMBER

```
#define PIN_NUMBER 0
```

Led pin number.

Definition at line 19 of file main.cpp.

7.39.2.2 TIMEDELAY

```
#define TIMEDELAY 500
```

Time delay.

Definition at line 20 of file main.cpp.

7.39.3 Function Documentation

7.39.3.1 main()

```
int main (
            void )
```

Definition at line 22 of file main.cpp.

```
00022              {
00023
00024    // Init
00025
00026    // Instantiate a Led object
00027    component::Led Led(io::Pin(PIN_NUMBER,io::PortB));
00028
00029    // Mainloop
00030    while (1) {
00031
00032        Led.on();
00033        _delay_ms(TIMEDELAY);
00034
00035        Led.off();
00036        _delay_ms(TIMEDELAY);
00037    }
00038    return 0;
00039 }
```

7.40 main.cpp

```
00001
00016 #include "Led.h"
00017 #include <util/delay.h>
00018
00019 #define PIN_NUMBER 0
00020 #define TIMEDELAY 500
00022 int main(void) {
00023
00024     // Init
00025
00026     // Instantiate a Led object
00027     component::Led Led(io::Pin(PIN_NUMBER,io::PortB));
00028
00029     // Mainloop
00030     while (1) {
00031
00032         Led.on();
00033         _delay_ms(TIMEDELAY);
00034
00035         Led.off();
00036         _delay_ms(TIMEDELAY);
00037     }
00038     return 0;
00039 }
```

7.41 MCU.cpp File Reference

```
#include "MCU.h"
```
Include dependency graph for MCU.cpp:

7.42 MCU.cpp

```
00001 #include "MCU.h"
00002
00003 void core::MCU::init()
00004 {
00005     enableUSART0(0);
00006     enableTimerCounter0(0);
00007     enableTimerCounter1(0);
00008     enableTimerCounter2(0);
00009     enableTWI(0);
00010     enableSPI(0);
00011     enableADC(0);
00012
00013 }
00014
00015 void core::MCU::selectSleepMode(const sleepMode &a_sleepMode)
00016 {
00017     MCU_SELECT_SLEEP_MODE(static_cast<uint8_t>(a_sleepMode));
00018
00019 }
00020
```

```
00021 void core::MCU::goToSleep(const BODMode &a_BODMode)
00022 {
00023     cli();
00024     switch (a_BODMode)
00025     {
00026         case core::BODMode::enabled:
00027         {
00028             sleepEnable(1);
00029             sei();
00030             sleep_cpu();
00031             sleepEnable(0);
00032             break;
00033         }
00034         case core::BODMode::disabled:
00035         {
00036             sleepEnable(1);
00037             disableBOD();
00038             sei();
00039             sleep_cpu();
00040             sleepEnable(0);
00041             break;
00042         }
00043     }
00044
00045 }
00046
00047 void core::MCU::sleepEnable(const uint8_t a_enable)
00048 {
00049     if (a_enable) {
00050         MCU_SLEEP_ENABLE;
00051     } else {
00052         MCU_SLEEP_DISABLE;
00053     }
00054
00055 }
00056
00057 void core::MCU::enableUSART0(const uint8_t a_enable)
00058 {
00059     if (a_enable) {
00060         MCU_USART0_ENABLE;
00061     } else {
00062         MCU_USART0_DISABLE;
00063     }
00064
00065 }
00066
00067 void core::MCU::enableTimerCounter0(const uint8_t a_enable)
00068 {
00069     if (a_enable) {
00070         MCU_TIMER0_ENABLE;
00071     } else {
00072         MCU_TIMER0_DISABLE;
00073     }
00074
00075 }
00076
00077 void core::MCU::enableTimerCounter1(const uint8_t a_enable)
00078 {
00079     if (a_enable) {
00080         MCU_TIMER1_ENABLE;
00081     } else {
00082         MCU_TIMER1_DISABLE;
00083     }
00084
00085 }
00086
00087 void core::MCU::enableTimerCounter2(const uint8_t a_enable)
00088 {
00089     if (a_enable) {
00090         MCU_TIMER2_ENABLE;
00091     } else {
00092         MCU_TIMER2_DISABLE;
00093     }
00094
00095 }
00096
00097 void core::MCU::enableTWI(const uint8_t a_enable)
00098 {
00099     if (a_enable) {
00100         MCU_TWI_ENABLE;
00101     } else {
00102         MCU_TWI_DISABLE;
00103     }
00104
00105 }
00106
00107 void core::MCU::enableSPI(const uint8_t a_enable)
```

```
00108 {
00109     if (a_enable) {
00110         MCU_SPI_ENABLE;
00111     } else {
00112         MCU_SPI_DISABLE;
00113     }
00114
00115 }
00116
00117 void core::MCU::enableADC(const uint8_t a_enable)
00118 {
00119     if (a_enable) {
00120         MCU_ADC_ENABLE;
00121     } else {
00122         MCU_ADC_DISABLE;
00123     }
00124 }
00125
00126 void core::MCU::disableBOD()
00127 {
00128     MCU_BOD_DISABLE;
00129 }
```

7.43 MCU.h File Reference

Header file of the MCU class.

```
#include "ha_base.h"
```
Include dependency graph for MCU.h:

This graph shows which files directly or indirectly include this file:

Classes

• class core::MCU

Namespaces

• core

Enumerations

- enum core::BODMode : uint8_t { core::BODMode::enabled =0, core::BODMode::disabled }
- enum core::sleepMode : uint8_t {
  core::sleepMode::Idle =0, core::sleepMode::ADC_NoiseReduction, core::sleepMode::powerDown, core::sleepMode::powerSav
  core::sleepMode::standby =6, core::sleepMode::extendedStandby }

7.43.1 Detailed Description

Header file of the MCU class.

Basic class abstraction of the MCU.

Usage example (test):

#include "PushButton.h" #include "Led.h" #include "ExternInterrupt.h" #include "MCU.h"

#define PUSHBUTTON_NUMBER 2 #define LED_NUMBER 0

int main(void) {

Init initialize MCU core::MCU::init();

instantiate a Led object component::Led Led(io::Pin(LED_NUMBER,io::PortB));

instantiate a Led object component::PushButton PushButton(io::Pin(PUSHBUTTON_NUMBER,io::PortD));

instantiate the external interrupt manager core::ExternInterrupt &myExternInterrupt = core::ExternInterrupt::getInstance();
myExternInterrupt.enableInt0(1); myExternInterrupt.setInt0SenseControl(core::senseControl::logicalChange);

set sleep mode core::MCU::selectSleepMode(core::sleepMode::powerDown);

Mainloop while (1) {

flash the LED for (uint8_t i=0;i<10;i++) { Led.on(); _delay_ms(100); Led.off(); _delay_ms(100); } _delay_ms(5000);
Led.on(); _delay_ms(100); Led.off(); core::MCU::goToSleep(core::BODMode::enabled);

} return 0; }

void core::ExternInterrupt::Int0ServiceRoutine() {

}

Author

> Farid Oubbati (https://github.com/faroub)

Date

> March 2020

Definition in file MCU.h.

7.44 MCU.h

```
00001
00069 #ifndef MCU_H
00070 #define MCU_H
00071 #include "ha_base.h"
00072
00073
00074 namespace core
00075 {
00076
00077 enum class BODMode : uint8_t {
00078     enabled=0,
00079     disabled,
00080 };
00081
00082 enum class sleepMode : uint8_t {
00083     Idle=0,
00084     ADC_NoiseReduction,
00085     powerDown,
00086     powerSave,
00087     standby=6,
00088     extendedStandby,
00089 };
00090
00091 class MCU
00092 {
00093 public:
00094
00095     static void init();
00096
00097     static void selectSleepMode(const sleepMode &a_sleepMode);
00098
00099     static void goToSleep(const BODMode &a_BODMode);
00100
00101     static void sleepEnable(const uint8_t ar_enable);
00102
00103     static void enableUSART0(const uint8_t a_enable);
00104
00105     static void enableTimerCounter0(const uint8_t a_enable);
00106
00107     static void enableTimerCounter1(const uint8_t a_enable);
00108
00109     static void enableTimerCounter2(const uint8_t a_enable);
00110
00111     static void enableTWI(const uint8_t a_enable);
00112
00113     static void enableSPI(const uint8_t a_enable);
00114
00115     static void enableADC(const uint8_t a_enable);
00116
00117     static void disableBOD();
00118
00119
00120
00121
00122
00123 protected:
00124
00125
00126
00127 private:
00128
00129
00130
00131
00132
00133
00134
00135 };
00136
00137
00138
00139
00140
00141 }
00142 #endif
```

7.45 Pin.cpp File Reference

```
#include "Pin.h"
```

Include dependency graph for Pin.cpp:

7.46   Pin.cpp

```
00001 #include "Pin.h"
00002
00003
00004 io::Pin::Pin(const uint8_t a_pinNumber, const Port &mr_portName)
00005         : mr_portName(mr_portName), m_pinNumber(a_pinNumber)
00006 {
00007
00008 }
00009
00010
00011 io::Pin::~Pin()
00012
00013 {
00014
00015 }
00016
00017 void io::Pin::toOutput()
00018 {
00019     *mr_portName.mp_ddrReg  |=  (1 << m_pinNumber);
00020 }
00021
00022 void io::Pin::toInput(const uint8_t &ar_useInternalPullUp)
00023 {
00024     if (ar_useInternalPullUp)
00025     {
00026         *mr_portName.mp_portReg |= (1 << m_pinNumber);
00027         *mr_portName.mp_ddrReg  &= ~(1 << m_pinNumber);
00028
00029
00030     }
00031     else
00032     {
00033         *mr_portName.mp_portReg &= ~(1 << m_pinNumber);
00034         *mr_portName.mp_ddrReg  &= ~(1 << m_pinNumber);
00035     }
00036
00037 }
00038
00039 void io::Pin::setLow()
00040 {
00041     if (*mr_portName.mp_ddrReg & (1 << m_pinNumber))
00042     {
00043         *mr_portName.mp_portReg &= ~(1 << m_pinNumber);
00044     }
00045 }
00046
00047 void io::Pin::setHigh()
00048 {
00049     if (*mr_portName.mp_ddrReg & (1 << m_pinNumber))
00050     {
00051         *mr_portName.mp_portReg |=  (1 << m_pinNumber);
00052     }
00053 }
00054
00055 void io::Pin::toggle()
00056 {
00057     if (*mr_portName.mp_ddrReg & (1 << m_pinNumber))
```

```
00058    {
00059         *mr_portName.mp_portReg ^=   1 « m_pinNumber;
00060    }
00061 }
00062
00063 uint8_t io::Pin::isHigh()
00064 {
00065     return  *mr_portName.mp_pinReg & (1 « m_pinNumber);
00066 }
00067
00068 uint8_t io::Pin::isLow()
00069 {
00070     return  !(*mr_portName.mp_pinReg & (1 « m_pinNumber));
00071 }
00072
00073 uint8_t io::Pin::getPinNumber()
00074 {
00075     return m_pinNumber;
00076 }
```

7.47 Pin.h File Reference

```
#include "ha_base.h"
```
Include dependency graph for Pin.h:

This graph shows which files directly or indirectly include this file:

Classes

- struct io::Port

     Structure.
- class io::Pin

Namespaces

- io

Variables

- static io::Port io::PortB = { &DDRB, &PORTB, &PINB }

    global static Port B object

- static io::Port io::PortC = { &DDRC, &PORTC, &PINC }

    global static Port C object

- static io::Port io::PortD = { &DDRD, &PORTD, &PIND }

    global static Port D object

7.48   Pin.h

```
00001 #ifndef PIN_H
00002 #define PIN_H
00003 #include "ha_base.h"
00004
00005 namespace io
00006 {
00007
00011 struct Port
00012 {
00013    volatile uint8_t* mp_ddrReg;
00015    volatile uint8_t* mp_portReg;
00017    volatile uint8_t* mp_pinReg;
00018 };
00019
00020 class Pin
00021 {
00022
00023 public:
00029     Pin(const uint8_t a_pinNumber, const Port &ar_portName);
00032     ~Pin();
00035     void toOutput();
00040     void toInput(const uint8_t &ar_useInternalPullUp);
00043     void setLow();
00046     void setHigh();
00049     void toggle();
00052     uint8_t isHigh();
00055     uint8_t isLow();
00058     uint8_t getPinNumber();
00059
00060 protected:
00061
00062
00063 private:
00064
00065      const Port &mr_portName;
00066      const uint8_t m_pinNumber;
00070 };
00071
00072 static io::Port PortB = { &DDRB, &PORTB, &PINB };
00073 static io::Port PortC = { &DDRC, &PORTC, &PINC };
00074 static io::Port PortD = { &DDRD, &PORTD, &PIND };
00076 }
00077
00078
00079 #endif
```

7.49   PushButton.cpp File Reference

```
#include "PushButton.h"
```

Include dependency graph for PushButton.cpp:

7.50 PushButton.cpp

```
00001 #include "PushButton.h"
00002
00003 component::PushButton::PushButton(const io::Pin& ar_pin, const uint8_t &ar_useInternalPullUp, const
      uint8_t &ar_isActiveLow)
00004                                     : m_pin(ar_pin),
00005                                       mr_isActiveLow(ar_isActiveLow),
00006                                       mr_useInternalPullUp(ar_useInternalPullUp)
00007
00008
00009 {
00010     m_pin.toInput(mr_useInternalPullUp);
00011     m_buttonPressed = 0;
00012 }
00013
00014 component::PushButton::~PushButton()
00015 {
00016
00017 }
00018
00019
00020 uint8_t component::PushButton::isPressed()
00021 {
00022     if (mr_isActiveLow || mr_useInternalPullUp) {
00023         if (m_pin.isLow()) {
00024             _delay_us(PUSHBUTTON_DEBOUNCE_TIME_US);
00025             if (m_pin.isLow()) {
00026                 ++m_buttonPressed;
00027                 return 1;
00028             }
00029         }
00030     } else {
00031
00032         if (m_pin.isHigh()) {
00033             _delay_us(PUSHBUTTON_DEBOUNCE_TIME_US);
00034             if (m_pin.isHigh()) {
00035                 ++m_buttonPressed;
00036                 return 1;
00037             }
00038         }
00039
00040     }
00041     m_buttonPressed = 0;
00042     return 0;
00043
00044 }
00045
00046 uint8_t component::PushButton::getPressedCount() const
00047 {
00048
00049     return m_buttonPressed;
00050
00051 }
00052
```

```
00053 void component::PushButton::resetPressedCount()
00054 {
00055     m_buttonPressed = 0;
00056
00057 }
```

7.51 PushButton.h File Reference

Header file of the Push Button class.

```
#include "Pin.h"
#include <math.h>
```
Include dependency graph for PushButton.h:

This graph shows which files directly or indirectly include this file:

Classes

- class component::PushButton

Namespaces

- component

7.51.1 Detailed Description

Header file of the Push Button class.

class to monitor a Push Button

Usage example (current state):

#include "PushButton.h" #include "Led.h"

#define PUSHBUTTON_NUMBER 1 #define LED_NUMBER 0

int main(void) {

Init

instantiate a Led object component::Led Led(io::Pin(LED_NUMBER,io::PortB));

instantiate a Led object component::PushButton PushButton(io::Pin(PUSHBUTTON_NUMBER,io::PortB));

Mainloop while (1) {

if (PushButton.isPressed()) { Led.on(); } else { Led.off(); }

} return 0; }

Usage example (changing state):

#include "PushButton.h" #include "Led.h"

#define PUSHBUTTON_NUMBER 1 #define LED_NUMBER 0

int main(void) {

Init

uint8_t l_statePushButton = 0;

instantiate a Led object component::Led Led(io::Pin(LED_NUMBER,io::PortB));

instantiate a Led object component::PushButton PushButton(io::Pin(PUSHBUTTON_NUMBER,io::PortB));

Mainloop while (1) {

if (PushButton.isPressed()) { if (l_statePushButton == 0) {

```
Led.toggle();
l_statePushButton = 1;
```

} } else { l_statePushButton = 0; }

} return 0; }

Author

> Farid Oubbati (https://github.com/faroub)

Date

> March 2020

Definition in file PushButton.h.

7.52 PushButton.h

```
00001
00085 #ifndef PUSHBUTTON_H
00086 #define PUSHBUTTON_H
00087 #include "Pin.h"
00088 #include <math.h>
00089
00090 // TODO: check the use PUSHBUTTON_SAMPLING in ha_m328p.h
00091
00092
00093 namespace component
00094 {
00095 class PushButton
00096 {
00097 public:
00104     PushButton(const io::Pin &ar_pin, const uint8_t &ar_useInternalPullUp=1, const uint8_t
      &ar_isActiveLow=1);
00107     ~PushButton();
00110     uint8_t isPressed();
00113     uint8_t getPressedCount() const;
00116     void resetPressedCount();
00117
00118
00119 protected:
00120
00121 private:
00122     io::Pin m_pin;
00123     const uint8_t &mr_isActiveLow;
00124     const uint8_t &mr_useInternalPullUp;
00125     uint8_t m_buttonPressed;
00129 };
00130 }
00131
00132
00133
00134
00135 #endif
```

7.53 ServoMotor.cpp File Reference

```
#include "ServoMotor.h"
```
Include dependency graph for ServoMotor.cpp:

7.54 ServoMotor.cpp

```
00001 #include "ServoMotor.h"
```

```
00002
00003
00004
00005 component::ServoMotor::ServoMotor(const io::Pin &ar_pin,
00006                                   const uint16_t &ar_pulseCycle,
00007                                   const uint16_t &ar_pulseWidthMin,
00008                                   const uint16_t &ar_pulseWidthMid,
00009                                   const uint16_t &ar_pulseWidthMax)
00010                     : m_pin(ar_pin),
00011                       m_pulseCycle(ar_pulseCycle),
00012                       m_pulseWidthMin(ar_pulseWidthMin),
00013                       m_pulseWidthMid(ar_pulseWidthMid),
00014                       m_pulseWidthMax(ar_pulseWidthMax)
00015 {
00016     m_pin.toOutput();
00017
00018 }
00019
00020 component::ServoMotor::~ServoMotor()
00021 {
00022
00023 }
00024
00025
00026
00027
00028 void component::ServoMotor::on()
00029 {
00030     m_pin.setHigh();
00031 }
00032
00033 void component::ServoMotor::off()
00034 {
00035     m_pin.setLow();
00036 }
00037
00038 void component::ServoMotor::toggle()
00039 {
00040     m_pin.toggle();
00041
00042 }
00043
00044 uint16_t component::ServoMotor::computePulseCycleCount(const uint16_t &ar_clockPrescaler)
00045 {
00046     return SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT(m_pulseCycle,ar_clockPrescaler);
00047 }
00048
00049 uint16_t component::ServoMotor::computePulseWidthMinCount(const uint16_t &ar_clockPrescaler)
00050 {
00051     return SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT(m_pulseWidthMin,ar_clockPrescaler);
00052 }
00053
00054 uint16_t component::ServoMotor::computePulseWidthMaxCount(const uint16_t &ar_clockPrescaler)
00055 {
00056     return SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT(m_pulseWidthMax,ar_clockPrescaler);
00057 }
00058
00059 uint16_t component::ServoMotor::computePulseWidthMidCount(const uint16_t &ar_clockPrescaler)
00060 {
00061     return SERVOMOTOR_TIMER_PULSE_WIDTH_COUNT(m_pulseWidthMid,ar_clockPrescaler);
00062 }
00063
00064 uint16_t component::ServoMotor::computeRotationAngleCount(const uint8_t &ar_angle_deg,const uint16_t
      &ar_clockPrescaler)
00065 {
00066     return
      static_cast<uint16_t>(SERVOMOTOR_TIMER_ANGLE_COUNT(ar_angle_deg,static_cast<long>(computePulseWidthMinCount(ar_clockPr
00067 }
00068
00069
00070
00071 void component::ServoMotor::rotate(core::TimerCounter1 &ar_timerCounter1,
00072                                    const uint8_t &ar_angle_deg,
00073                                    const core::channel &ar_channel)
00074 {
00075
00076     ar_timerCounter1.setOutputCompareRegister(ar_channel,
      computeRotationAngleCount(ar_angle_deg,ar_timerCounter1.getClockPrescaler()));
00077
00078     // start timer
00079     ar_timerCounter1.start();
00080
00081
00082 }
00083
00084
00085 void component::ServoMotor::connect(core::TimerCounter1 &ar_timerCounter1,
```

```
00086                const core::channel &ar_channel)
00087 {
00088
00089
00090
    ar_timerCounter1.setInputCaptureRegister(computePulseCycleCount(ar_timerCounter1.getClockPrescaler()));
00091     ar_timerCounter1.selectOperationMode(core::operationMode::fast_PWM_ICR);
00092     ar_timerCounter1.selectCompareOutputMode(ar_channel, core::compareOutputMode::clear);
00093     ar_timerCounter1.setCounter(0);
00094
00095 }
00096
00097 void component::ServoMotor::disconnect(core::TimerCounter1 &ar_timerCounter1,
00098                const core::channel &ar_channel)
00099 {
00100     ar_timerCounter1.selectCompareOutputMode(ar_channel, core::compareOutputMode::normal);
00101     // stop timer
00102     ar_timerCounter1.stop();
00103 }
```

7.55 ServoMotor.h File Reference

Header file of the ServoMotor class.

```
#include "ha_base.h"
#include "Pin.h"
#include "TimerCounter1.h"
```
Include dependency graph for ServoMotor.h:

This graph shows which files directly or indirectly include this file:

Classes

- class component::ServoMotor

Namespaces

- component

7.55.1 Detailed Description

Header file of the ServoMotor class.

Header file of the StepperMotor class.

Usage example (separate): #include "MCU.h" #include "ServoMotor.h" #include "TimerCounter1.h"

#define SERVOMOTOR_NUMBER 1 #define SERVOMOTOR_PULSE_CYCLE 30000 // pulse cycle [us] #define SERVOMOTOR_PULSE_WIDTH_MIN 500// pulse width min [us] #define SERVOMOTOR_PULSE_WIDTH_MID 1520 // pulse width mid [us] #define SERVOMOTOR_PULSE_WIDTH_MAX 3000 // pulse width max [us]

int main(void) {

Init initialize MCU core::MCU::init();

instantiate the TimerCounter0 object core::TimerCounter1 &myTimerCounter1 = core::TimerCounter1::getInstance(); myTimerCounter1.selectClockSource(core::clockSource::PS_8); myTimerCounter1.selectOperationMode(core←↩ ::operationMode::fast_PWM_ICR); myTimerCounter1.selectCompareOutputMode(core::channel::A, core←↩ ::compareOutputMode::clear);

instantiate the Buzzer object component::ServoMotor myServoMotor(io::Pin(SERVOMOTOR_NUMBER,io::PortB), SERVOMOTOR_PULSE_CYCLE, SERVOMOTOR_PULSE_WIDTH_MIN, SERVOMOTOR_PULSE_WIDTH_M←↩ ID, SERVOMOTOR_PULSE_WIDTH_MAX);

myTimerCounter1.setInputCaptureRegister(myServoMotor.computePulseCycleCount(myTimerCounter1.get←↩ ClockPrescaler())); myTimerCounter1.setOutputCompareRegister(core::channel::A, myServoMotor.compute←↩ RotationAngleCount(0,myTimerCounter1.getClockPrescaler())); myTimerCounter1.start(); _delay_ms(2000); my←↩ TimerCounter1.setOutputCompareRegister(core::channel::A, myServoMotor.computeRotationAngleCount(45,my←↩ TimerCounter1.getClockPrescaler())); myTimerCounter1.start(); _delay_ms(2000); myTimerCounter1.set←↩ OutputCompareRegister(core::channel::A, myServoMotor.computeRotationAngleCount(90,myTimerCounter1.←↩ getClockPrescaler())); myTimerCounter1.start(); _delay_ms(2000); myTimerCounter1.setOutputCompare←↩ Register(core::channel::A, myServoMotor.computeRotationAngleCount(135,myTimerCounter1.getClockPrescaler())); myTimerCounter1.start(); _delay_ms(2000); myTimerCounter1.setOutputCompareRegister(core::channel::A, my←↩ ServoMotor.computeRotationAngleCount(180,myTimerCounter1.getClockPrescaler())); myTimerCounter1.start(); _delay_ms(2000); myTimerCounter1.setOutputCompareRegister(core::channel::A, myServoMotor.compute←↩ RotationAngleCount(0,myTimerCounter1.getClockPrescaler())); myTimerCounter1.start(); _delay_ms(2000);

Mainloop while (1) {

} return 0; } Usage example (TimerCounter1): #include "MCU.h" #include "ServoMotor.h" #include "Timer←↩ Counter1.h"

#define SERVOMOTOR_NUMBER 1 #define SERVOMOTOR_PULSE_CYCLE 30000 // pulse cycle [us] #define SERVOMOTOR_PULSE_WIDTH_MIN 500// pulse width min [us] #define SERVOMOTOR_PULSE_WIDTH_MID 1520 // pulse width mid [us] #define SERVOMOTOR_PULSE_WIDTH_MAX 3000 // pulse width max [us]

int main(void) {

Init initialize MCU core::MCU::init();

instantiate the TimerCounter1 object core::TimerCounter1 &myTimerCounter1 = core::TimerCounter1::getInstance(); myTimerCounter1.selectClockSource(core::clockSource::PS_8);

instantiate the Buzzer object component::ServoMotor myServoMotor(io::Pin(SERVOMOTOR_NUMBER,io::PortB), SERVOMOTOR_PULSE_CYCLE, SERVOMOTOR_PULSE_WIDTH_MIN, SERVOMOTOR_PULSE_WIDTH_M←ID, SERVOMOTOR_PULSE_WIDTH_MAX);

myServoMotor.connect(myTimerCounter1);

myServoMotor.rotate(myTimerCounter1,0); _delay_ms(2000); myServoMotor.rotate(myTimerCounter1,45); _←delay_ms(2000); myServoMotor.rotate(myTimerCounter1,90); _delay_ms(2000); myServoMotor.rotate(myTimer←Counter1,135); _delay_ms(2000); myServoMotor.rotate(myTimerCounter1,180); _delay_ms(2000); myServo←Motor.rotate(myTimerCounter1,0); _delay_ms(2000);

myServoMotor.disconnect(myTimerCounter1);

Mainloop while (1) {

```
}
return 0;
```

}

class to control a servo motor

Author

> Farid Oubbati (https://github.com/faroub)

Date

> March 2020

The StepperMotor class is implemented and tested for the 28BYJ-48 Stepper Motor Usage example (basic):

#include "StepperMotor.h"

#define StepperMotor_Pin_1 0 #define StepperMotor_Pin_2 1 #define StepperMotor_Pin_3 2 #define Stepper←Motor_Pin_4 3

#define STEP_ANGLE_FULL_STEP 0.176 #define STEP_ANGLE_HALF_STEP 0.0879

int main(void) {

instantiate the StepperMotor object component::StepperMotor myStepperMotor(component::mode::halfStep, io::Pin(StepperMotor_Pin_1,io::PortB), io::Pin(StepperMotor_Pin_2,io::PortB), io::Pin(StepperMotor_Pin_3,io::PortB), io::Pin(StepperMotor_Pin_4,io::PortB));

int16_t l_angle = -180; int16_t l_step = static_cast<int16_t>(l_angle / STEP_ANGLE_HALF_STEP);

set speed [steps/s] full step: max speed: 500p/s half step: max speed: 1000p/s

set speed [%/s] full step: max speed: 40%/s half step: max speed: 80%/s

Mainloop while (1) {

```
 while (!myStepperMotor.goalReached())
 {
```

set motor steps myStepperMotor.step(l_step,1000); myStepperMotor.step(l_step,80,STEP_ANGLE_HALF_STEP);

```
 }
```

} return 0; }

class to control a servo motor

Author

Farid Oubbati (https://github.com/faroub)

Date

March 2020

Definition in file ServoMotor.h.

7.56 ServoMotor.h

```
00001
00126 #ifndef SERVOMOTOR_H
00127 #define SERVOMOTOR_H
00128 #include "ha_base.h"
00129 #include "Pin.h"
00130 #include "TimerCounter1.h"
00131
00132
00133
00134 namespace component
00135 {
00136
00137
00138 class ServoMotor
00139 {
00140 public:
00141
00142     ServoMotor(const io::Pin &ar_pin,
00143               const uint16_t &ar_pulseCycle=0,
00144               const uint16_t &ar_pulseWidthMin=0,
00145               const uint16_t &ar_pulseWidthMid=0,
00146              const uint16_t &ar_pulseWidthMax=0);
00147
00148     ~ServoMotor();
00149
00152     void on();
00155     void off();
00158     void toggle();
00159
00160     uint16_t computePulseCycleCount(const uint16_t &ar_clockPrescaler);
00161
00162     uint16_t computePulseWidthMinCount(const uint16_t &ar_clockPrescaler);
00163
00164     uint16_t computePulseWidthMidCount(const uint16_t &ar_clockPrescaler);
00165
00166     uint16_t computePulseWidthMaxCount(const uint16_t &ar_clockPrescaler);
00167
00168     uint16_t computeRotationAngleCount(const uint8_t &ar_angle_deg, const uint16_t
00169     &ar_clockPrescaler);
00170
00171     void rotate(core::TimerCounter1 &ar_timerCounter1,
00172                 const uint8_t &ar_angle_deg,
00173                 const core::channel &ar_channel=core::channel::A);
00174
00175     void connect(core::TimerCounter1 &ar_timerCounter1,
00176                  const core::channel &ar_channel=core::channel::A);
00177
00178     void disconnect(core::TimerCounter1 &ar_timerCounter1,
00179                     const core::channel &ar_channel=core::channel::A);
00180
00181
00182
00183 protected:
00184
00185 private:
00186
00187
00188     io::Pin m_pin;
00190     uint16_t m_pulseCycle;
00192     uint16_t m_pulseWidthMin;
00194     uint16_t m_pulseWidthMid;
00196     uint16_t m_pulseWidthMax;
00205 };
00206
00207
```

```
00208 }
00209
00210
00211
00212 #endif
```

7.57 SPI.cpp File Reference

```
#include "SPI.h"
#include "MCU.h"
```
Include dependency graph for SPI.cpp:

7.58 SPI.cpp

```
00001 #include "SPI.h"
00002 #include "MCU.h"
00003
00004 volatile uint8_t io::SPI::m_data = 0;
00005
00006
00007
00008 io::SPI& io::SPI::getInstance(const Pin &ar_pinSCK,
00009                              const Pin &ar_pinMISO,
00010                              const Pin &ar_pinMOSI,
00011                              const Pin &ar_pinSS)
00012 {
00013     static SPI l_instance(ar_pinSCK,
00014                           ar_pinMISO,
00015                           ar_pinMOSI,
00016                           ar_pinSS);
00017
00018     return l_instance;
00019
00020 }
00021
00022 io::SPI::SPI(const Pin &ar_pinSCK,
00023             const Pin &ar_pinMISO,
00024             const Pin &ar_pinMOSI,
00025             const Pin &ar_pinSS)
00026         : m_pinSCK(ar_pinSCK),
00027           m_pinMISO(ar_pinMISO),
00028           m_pinMOSI(ar_pinMOSI),
00029           m_pinSS(ar_pinSS)
00030 {
00031     core::MCU::enableSPI(1);
00032     sei();
00033     enableTransferCompleteInterrupt(1);
00034
00035 }
00036
```

```
00037 io::SPI::~SPI()
00038 {
00039
00040 }
00041
00042 uint8_t io::SPI::writeCollision()
00043 {
00044     return (SPI_STATUS_REGISTER & (1 « SPI_WRITE_COLLISION));
00045 }
00046
00047
00048 uint8_t io::SPI::transferComplete()
00049 {
00050     return (SPI_STATUS_REGISTER & (1 « SPI_TRANSFER_COMPLETE));
00051 }
00052
00053 void io::SPI::selectClockPrescaler(const clockPrescaler& ar_clockPrescaler)
00054 {
00055     SPI_SELECT_CLOCK_PRESCALER(static_cast<uint8_t>(ar_clockPrescaler));
00056
00057 }
00058
00059 void io::SPI::selectOperationMode(const operationMode& ar_operationMode)
00060 {
00061     switch (ar_operationMode)
00062     {
00063         case operationMode::master:
00064         {
00065             m_pinMOSI.toOutput();
00066             m_pinSCK.toOutput();
00067             m_pinMISO.toInput(1);
00068             m_pinSS.toOutput();
00069             m_pinSS.setHigh();
00070             SPI_SELECT_MASTER_MODE;
00071             SPI_ENABLE;
00072             break;
00073         }
00074         case operationMode::slave:
00075         {
00076             m_pinMISO.toOutput();
00077             SPI_SELECT_SLAVE_MODE;
00078             SPI_ENABLE;
00079             break;
00080         }
00081         case operationMode::submaster:
00082         {
00083             m_pinMOSI.toOutput();
00084             m_pinSCK.toOutput();
00085             m_pinMISO.toInput(1);
00086             m_pinSS.toInput(1);
00087             SPI_SELECT_MASTER_MODE;
00088             SPI_ENABLE;
00089             break;
00090         }
00091         case operationMode::disable:
00092         {
00093             SPI_DISABLE;
00094             break;
00095         }
00096     }
00097 }
00098
00099 void io::SPI::selectDataMode(const dataMode& ar_dataMode)
00100 {
00101     SPI_SELECT_DATA_MODE(static_cast<uint8_t>(ar_dataMode));
00102 }
00103
00104 void io::SPI::selectDataOrder(const dataOrder& ar_dataOrder)
00105 {
00106     SPI_SELECT_DATA_ORDER(static_cast<uint8_t>(ar_dataOrder));
00107
00108 }
00109
00110 void io::SPI::enableTransferCompleteInterrupt(const uint8_t a_enable)
00111 {
00112     if (a_enable) {
00113         SPI_ENABLE_TRANSFER_COMPLETE_INTERRUPT;
00114     } else {
00115         SPI_DISABLE_TRANSFER_COMPLETE_INTERRUPT;
00116     }
00117 }
00118
00119 void io::SPI::selectSlave(const uint8_t a_select)
00120 {
00121     if (a_select) {
00122         m_pinSS.setLow();
00123
```

```
00124        } else {
00125            m_pinSS.setHigh();
00126        }
00127
00128 }
00129 void io::SPI::transferCompleteServiceRoutine()
00130 {
00131
00132        m_data = SPI_DATA_REGISTER;
00133 }
00134
00135 void io::SPI::masterSendByte(const uint8_t &ar_byte)
00136 {
00137
00138        SPI_DATA_REGISTER = ar_byte;
00139        selectSlave(1);
00140        while(!transferComplete()){};
00141        selectSlave(0);
00142
00143
00144
00145 }
00146
00147 void io::SPI::masterReceiveByte(uint8_t &ar_byte)
00148 {
00149        masterSendByte(0);
00150        ar_byte = m_data;
00151
00152 }
00153
00154 void io::SPI::slaveReceiveByte(uint8_t &ar_byte)
00155 {
00156        ar_byte = m_data;
00157
00158 }
```

7.59 SPI.h File Reference

Header file of the SPI class.

```
#include "ha_base.h"
#include "Pin.h"
```
Include dependency graph for SPI.h:

This graph shows which files directly or indirectly include this file:

Classes

- class io::SPI

Namespaces

- io

Enumerations

- enum io::operationMode : uint8_t { io::operationMode::master =0, io::operationMode:slave, io::operationMode::submaster, io::operationMode::disable }
- enum io::clockPrescaler : uint8_t { io::clockPrescaler::PS_4 = 0, io::clockPrescaler::PS_16, io::clockPrescaler::PS_64, io::clockPrescaler::PS_128, io::clockPrescaler::PS_2, io::clockPrescaler::PS_8, io::clockPrescaler::PS_32 }
- enum io::dataMode : uint8_t { io::dataMode::mode_0 = 0, io::dataMode::mode_1, io::dataMode::mode_2, io::dataMode::mode_3 }
- enum io::dataOrder : uint8_t { io::dataOrder::first_MSB = 0, io::dataOrder::first_LSB }

7.59.1 Detailed Description

Header file of the SPI class.

Usage example (test): #include "MCU.h" #include "SPI.h"

#define SPI_SCK 5 #define SPI_MISO 4 #define SPI_MOSI 3 #define SPI_SS 2

int main(void) {

Init initialize MCU core::MCU::init(); instantiate a SPI object io::SPI &myISP = io::SPI::getInstance(io::Pin(SPI_SCK,io::PortB), io::Pin(SPI_MISO,io::PortB), io::Pin(SPI_MOSI,io::PortB), io::Pin(SPI_SS,io::PortB));

myISP.selectClockPrescaler(io::clockPrescaler::PS_128); myISP.selectDataMode(io::dataMode::mode_0); myIS←
P.selectDataOrder(io::dataOrder::first_LSB); myISP.selectOperationMode(io::operationMode::master);

myISP.masterSendByte(0x03);

Mainloop while (1) {

} return 0; }

Basic class for IO abstraction of Pin and Port

Author

Farid Oubbati (https://github.com/faroub)

Date

March 2020

Definition in file SPI.h.

7.60   SPI.h

```
00001
00048 #ifndef SPI_H
00049 #define SPI_H
00050 #include "ha_base.h"
00051 #include "Pin.h"
00052
00053 namespace io
00054 {
00055
00056 enum class operationMode : uint8_t {
00057     master=0,
00058     slave,
00059     submaster,
00060     disable,
00061 };
00062
00063 enum class clockPrescaler : uint8_t  {
00064     PS_4 = 0,
00065     PS_16,
00066     PS_64,
00067     PS_128,
00068     PS_2,
00069     PS_8,
00070     PS_32
00071 };
00072
00073 enum class dataMode : uint8_t  {
00074     mode_0 = 0,
00075     mode_1,
00076     mode_2,
00077     mode_3,
00078 };
00079
00080 enum class dataOrder : uint8_t  {
00081     first_MSB = 0,
00082     first_LSB
00083 };
00084
00085
00086 class SPI
00087 {
00088
00089 public:
00090     static SPI& getInstance(const io::Pin &ar_pinSCK,
00091                             const io::Pin &ar_pinMISO,
00092                             const io::Pin &ar_pinMOSI,
00093                             const io::Pin &ar_pinSS);
00094
00095     void selectDataMode(const dataMode& ar_dataMode);
00096
00097     void selectDataOrder(const dataOrder& ar_dataOrder);
00098
00099     void selectOperationMode(const operationMode& ar_operationMode);
00100
00101     void selectClockPrescaler(const clockPrescaler& ar_clockPrescaler);
00102
00103     void selectSlave(const uint8_t a_select);
00104
00107     uint8_t writeCollision();
00108
00111     uint8_t transferComplete();
00112
00113
00114     static void enableTransferCompleteInterrupt(const uint8_t a_enable);
00115
00116     void masterSendByte(const uint8_t &ar_byte);
```

```
00117
00118     void masterReceiveByte(uint8_t &ar_byte);
00119
00120     void slaveReceiveByte(uint8_t &ar_byte);
00121
00124     static void transferCompleteServiceRoutine() __asm__(STR(SPI_TRANSFER_COMPLETE_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
00125
00126
00127
00128 private:
00137     SPI(const io::Pin &ar_pinSCK,
00138         const io::Pin &ar_pinMISO,
00139         const io::Pin &ar_pinMOSI,
00140         const io::Pin &ar_pinSS);
00141
00144     ~SPI();
00145
00148     SPI(const SPI&);
00149
00152     const SPI& operator=(const SPI&);
00153
00154     static volatile uint8_t m_data;
00155
00156     io::Pin m_pinSCK;
00157     io::Pin m_pinMISO;
00158     io::Pin m_pinMOSI;
00159     io::Pin m_pinSS;
00167 };
00168
00169 }
00170 #endif // SPI_H
```

7.61 StepperMotor.cpp File Reference

```
#include "StepperMotor.h"
#include <math.h>
```
Include dependency graph for StepperMotor.cpp:

7.62 StepperMotor.cpp

```
00001 #include "StepperMotor.h"
00002 #include <math.h>
00003
00004 // TODO: steps to angle
00005 // TODO: maximum speed
00006 // TODO: speed and accelleration profiles
00007
00008 component::StepperMotor::StepperMotor(const mode &ar_mode,
00009                                       const io::Pin &ar_pinCoil1,
```

```
00010                                                 const io::Pin &ar_pinCoil2,
00011                                                 const io::Pin &ar_pinCoil3,
00012                                                 const io::Pin &ar_pinCoil4)
00013     : m_pinCoil1(ar_pinCoil1),
00014       m_pinCoil2(ar_pinCoil2),
00015       m_pinCoil3(ar_pinCoil3),
00016       m_pinCoil4(ar_pinCoil4),
00017       stepMode(ar_mode)
00018 {
00019
00020     m_pinCoil1.toOutput();
00021     m_pinCoil2.toOutput();
00022     m_pinCoil3.toOutput();
00023     m_pinCoil4.toOutput();
00024     m_goalReached = 0;
00025     m_currentPos = 0;
00026
00027
00028 }
00029
00030 component::StepperMotor::~StepperMotor()
00031 {
00032
00033 }
00034
00035 void component::StepperMotor::setCurrentPos(uint16_t a_currentPos)
00036 {
00037     m_currentPos = a_currentPos;
00038 }
00039
00040 uint16_t component::StepperMotor::currentPos()
00041 {
00042     return m_currentPos;
00043 }
00044
00045
00046
00047 void component::StepperMotor::step(const int16_t a_step,
00048         const uint16_t a_speed,
00049         const uint16_t a_accel,
00050         const uint16_t a_decel)
00051 {
00052     static int16_t l_stepNumber = 0;
00053     uint8_t l_stepDelay_ms = 0;
00054     uint16_t l_step=0;
00055
00056     if (a_step<=0)
00057     {
00058        l_step = -a_step;
00059     } else
00060     {
00061         l_step = a_step;
00062     }
00063
00064     l_stepDelay_ms = computeStepDelay(l_step,
00065                                       a_speed,
00066                                       a_accel,
00067                                       a_decel);
00068
00069 if (l_stepDelay_ms>0)
00070 {
00071
00072     if (a_step<=0)
00073     {
00074         if (l_stepNumber== -a_step)
00075         {
00076             m_goalReached = 1;
00077
00078         } else {
00079             l_stepNumber++;
00080             m_currentPos++;
00081         }
00082
00083
00084     } else {
00085
00086         if (l_stepNumber == -a_step)
00087         {
00088             m_goalReached = 1;
00089
00090         } else {
00091             l_stepNumber--;
00092             m_currentPos--;
00093
00094         }
00095     }
00096
```

```
00097
00098    if (m_goalReached == 0)
00099    {
00100
00101        switch (stepMode)
00102        {
00103            case mode::fullStep:
00104            {
00105                // equivalent to l_stepNumber % 4
00106                // 1 3 5 7 <->
00107                stepPulse(2*(l_stepNumber & 3)+1);
00108                break;
00109            }
00110
00111            case mode::halfStep:
00112            {
00113                // equivalent to l_stepNumber % 8
00114                // 0 1 2 3 4 5 6 7 <->
00115                stepPulse(l_stepNumber & 7);
00116                break;
00117            }
00118        }
00119
00120        stepDelay(l_stepDelay_ms);
00121
00122    }
00123 }
00124
00125 }
00126
00127 uint8_t component::StepperMotor::computeStepDelay(uint16_t a_step,
00128                          uint16_t a_speed,
00129                          uint16_t a_accel,
00130                          uint16_t a_decel)
00131 {
00132
00133
00134    uint32_t l_accelTime= (1000UL*a_speed/a_accel);
00135    uint16_t l_decelTime = (1000UL*a_speed/a_decel);
00136    int16_t l_constSpeedTime=((1000UL*a_step/a_speed)-(l_accelTime/2)-(l_decelTime/2));
00137    static uint32_t l_time=0;
00138    static uint32_t l_speed=0;
00139    static uint64_t l_speed_time_product=0;
00140    static uint64_t l_current_position=0;
00141
00142
00143
00144
00145
00146
00147
00148    if (l_constSpeedTime<0)
00149    {
00150        l_constSpeedTime=0;
00151        l_accelTime = static_cast<uint32_t>(1000UL*sqrtf(a_step/a_accel));
00152        a_speed=l_accelTime*a_accel/1000UL;
00153        l_decelTime = 1000UL*a_speed/a_decel;
00154
00155    }
00156
00157
00158
00159
00160    if (l_time<=l_accelTime)
00161    {
00162        l_speed=a_accel*l_time;
00163
00164    }
00165    else if ((l_time>l_accelTime) && (l_time<=(l_accelTime+l_constSpeedTime)))
00166    {
00167        l_speed=1000UL*a_speed;
00168
00169    }
00170    else if
      ((l_time>(l_accelTime+l_constSpeedTime))&&(l_time<=l_accelTime+l_constSpeedTime+l_decelTime))
00171    {
00172        l_speed= (1000UL*a_speed)-a_decel*(l_time-l_accelTime-l_constSpeedTime);
00173
00174
00175    }
00176
00177
00178    l_time=l_time+1;
00179
00180
00181    l_speed_time_product = l_speed_time_product+l_speed;
00182
```

```
00183     if (l_speed_time_product - l_current_position >= 1000000UL)
00184     {
00185         l_current_position=l_current_position+1000000UL;
00186         return 1;
00187     }
00188     else
00189     {
00190         stepDelay(1);
00191         return 0;
00192     }
00193
00194
00195
00196
00197
00198 }
00199
00200
00201 void component::StepperMotor::step(const int16_t a_step, const uint16_t a_speed)
00202 {
00203     static int16_t l_stepNumber = 0;
00204     static uint8_t l_stepDelay_ms = static_cast<uint8_t>(1000UL/a_speed);
00205
00206     if (a_step<=0)
00207     {
00208         if (l_stepNumber== -a_step)
00209         {
00210             m_goalReached = 1;
00211
00212         } else {
00213             l_stepNumber++;
00214             m_currentPos++;
00215         }
00216
00217
00218     } else {
00219
00220         if (l_stepNumber == -a_step)
00221         {
00222             m_goalReached = 1;
00223
00224         } else {
00225             l_stepNumber--;
00226             m_currentPos--;
00227
00228         }
00229     }
00230
00231
00232     if (m_goalReached == 0)
00233     {
00234
00235         switch (stepMode)
00236         {
00237             case mode::fullStep:
00238             {
00239                 // equivalent to l_stepNumber % 4
00240                 // 1 3 5 7 <->
00241                 stepPulse(2*(l_stepNumber & 3)+1);
00242                 break;
00243             }
00244
00245             case mode::halfStep:
00246             {
00247                 // equivalent to l_stepNumber % 8
00248                 // 0 1 2 3 4 5 6 7 <->
00249                 stepPulse(l_stepNumber & 7);
00250                 break;
00251             }
00252         }
00253
00254         stepDelay(l_stepDelay_ms);
00255
00256     }
00257 }
00258
00259 void component::StepperMotor::step(const int16_t a_step, const uint16_t a_speed, const float
    a_stepAngle)
00260 {
00261     static int16_t l_stepNumber = 0;
00262     static uint8_t l_stepDelay_ms = static_cast<uint8_t>(1000UL*a_stepAngle/a_speed);
00263
00264     if (a_step<=0)
00265     {
00266         if (l_stepNumber== -a_step)
00267         {
00268             m_goalReached = 1;
```

```
00269
00270            } else {
00271                l_stepNumber++;
00272                m_currentPos++;
00273            }
00274
00275
00276        } else {
00277
00278            if (l_stepNumber == -a_step)
00279            {
00280                m_goalReached = 1;
00281
00282            } else {
00283                l_stepNumber--;
00284                m_currentPos--;
00285
00286            }
00287        }
00288
00289
00290        if (m_goalReached == 0)
00291        {
00292
00293            switch (stepMode)
00294            {
00295                case mode::fullStep:
00296                {
00297                    // equivalent to l_stepNumber % 4
00298                    // 1 3 5 7 <->
00299                    stepPulse(2*(l_stepNumber & 3)+1);
00300                    break;
00301                }
00302
00303                case mode::halfStep:
00304                {
00305                    // equivalent to l_stepNumber % 8
00306                    // 0 1 2 3 4 5 6 7 <->
00307                    stepPulse(l_stepNumber & 7);
00308                    break;
00309                }
00310            }
00311
00312            stepDelay(l_stepDelay_ms);
00313
00314        }
00315
00316
00317 }
00318
00319
00320 void component::StepperMotor::stepPulse(const uint8_t a_stepPulse)
00321 {
00322
00323        switch (a_stepPulse) {
00324          case 0:     // 1000
00325          {
00326            m_pinCoil1.setHigh();
00327            m_pinCoil2.setLow();
00328            m_pinCoil3.setLow();
00329            m_pinCoil4.setLow();
00330            break;
00331          }
00332          case 1:     // 1100
00333          {
00334            m_pinCoil1.setHigh();
00335            m_pinCoil2.setHigh();
00336            m_pinCoil3.setLow();
00337            m_pinCoil4.setLow();
00338            break;
00339          }
00340          case 2:     //0100
00341          {
00342            m_pinCoil1.setLow();
00343            m_pinCoil2.setHigh();
00344            m_pinCoil3.setLow();
00345            m_pinCoil4.setLow();
00346            break;
00347          }
00348          case 3:     //0110
00349          {
00350            m_pinCoil1.setLow();
00351            m_pinCoil2.setHigh();
00352            m_pinCoil3.setHigh();
00353            m_pinCoil4.setLow();
00354            break;
00355          }
```

```
00356        case 4:    //0010
00357        {
00358          m_pinCoil1.setLow();
00359          m_pinCoil2.setLow();
00360          m_pinCoil3.setHigh();
00361          m_pinCoil4.setLow();
00362          break;
00363        }
00364        case 5:    //0011
00365        {
00366          m_pinCoil1.setLow();
00367          m_pinCoil2.setLow();
00368          m_pinCoil3.setHigh();
00369          m_pinCoil4.setHigh();
00370          break;
00371        }
00372        case 6:    //0001
00373        {
00374          m_pinCoil1.setLow();
00375          m_pinCoil2.setLow();
00376          m_pinCoil3.setLow();
00377          m_pinCoil4.setHigh();
00378          break;
00379        }
00380        case 7:    //1001
00381        {
00382          m_pinCoil1.setHigh();
00383          m_pinCoil2.setLow();
00384          m_pinCoil3.setLow();
00385          m_pinCoil4.setHigh();
00386          break;
00387        }
00388      }
00389
00390
00391 }
00392
00393
00394
00395 void component::StepperMotor::stepDelay(uint8_t a_stepDelay)
00396 {
00397      while(a_stepDelay--)
00398      {
00399          _delay_ms(1);
00400      }
00401 }
00402
00403 uint8_t component::StepperMotor::goalReached()
00404 {
00405      return m_goalReached;
00406
00407 }
```

7.63 StepperMotor.h File Reference

```
#include "ha_base.h"
#include "Pin.h"
```
Include dependency graph for StepperMotor.h:

This graph shows which files directly or indirectly include this file:

Classes

- class component::StepperMotor

Namespaces

- component

Enumerations

- enum component::mode : uint8_t { component::mode::fullStep =0, component::mode::halfStep }

7.64 StepperMotor.h

```
00001
00062 #ifndef STEPPERMOTOR_H
00063 #define STEPPERMOTOR_H
00064 #include "ha_base.h"
00065 #include "Pin.h"
00066
00067 namespace component
00068 {
00069
00070 enum class mode : uint8_t {
00071     fullStep=0,
00072     halfStep,
00073 };
00074
00075 class StepperMotor
00076 {
00077 public:
00078
00079     StepperMotor(const mode &ar_mode,
00080                  const io::Pin &ar_pinCoil1,
00081                  const io::Pin &ar_pinCoil2,
00082                  const io::Pin &ar_pinCoil3,
00083                  const io::Pin &ar_pinCoil4);
00084
00085     ~StepperMotor();
00086
00090     void step(const int16_t a_step,
00091               const uint16_t a_speed);
00092
00093     void step(const int16_t a_step,
00094               const uint16_t a_speed,
00095              const float a_stepAngle);
```

```
00096
00097      void step(const int16_t a_step,
00098                const uint16_t a_speed,
00099                const uint16_t a_accel,
00100                const uint16_t a_decel);
00101
00102      void stepPulse(const uint8_t a_stepPulse);
00103
00104      void stepDelay(uint8_t a_stepDelay);
00105
00106      uint8_t goalReached();
00107
00108      void setCurrentPos(uint16_t a_currentPos);
00109
00110      uint16_t currentPos();
00111
00112
00113      uint8_t computeStepDelay(uint16_t a_step,
00114                               const uint16_t a_speed,
00115                               const uint16_t a_accel,
00116                               const uint16_t a_decel);
00117
00118      uint16_t m_accelTime;
00119      uint16_t m_decelTime;
00120      uint16_t m_constSpeedTime;
00124 private:
00125
00126 //    uint8_t computeStepDelay(int16_t a_step,
00127 //                             const uint16_t a_speed,
00128 //                             const uint16_t a_accel,
00129 //                             const uint16_t a_decel);
00130
00131
00132      io::Pin m_pinCoil1;
00133      io::Pin m_pinCoil2;
00134      io::Pin m_pinCoil3;
00135      io::Pin m_pinCoil4;
00137      mode stepMode;
00138      uint8_t m_goalReached;
00139      uint16_t m_currentPos;
00144 };
00145
00146 }
00147 #endif // STEPPERMOTOR_H
```

7.65 TimerCounter.h File Reference

Header file of the TimerCounter class.

```
#include "ha_base.h"
```
Include dependency graph for TimerCounter.h:

This graph shows which files directly or indirectly include this file:

Classes

- class core::TimerCounter

Namespaces

- core

Enumerations

- enum core::channel : uint8_t { core::channel::A =0, core::channel::B }
- enum core::compareOutputMode : uint8_t { core::compareOutputMode::normal =0, core::compareOutputMode::toggle, core::compareOutputMode::clear, core::compareOutputMode::set }
- enum core::operationMode : uint8_t {
  core::operationMode::normal =0, core::operationMode::PWM_PC, core::operationMode::PWM_PC_8bit, core::operationMode::PWM_PC_9bit,
  core::operationMode::PWM_PC_10bit, core::operationMode::PWM_PFC_ICR, core::operationMode::PWM_PFC_OCR, core::operationMode::PWM_PC_ICR,
  core::operationMode::PWM_PC_OCR, core::operationMode::fast_PWM, core::operationMode::fast_PWM_8bit, core::operationMode::fast_PWM_9bit,
  core::operationMode::fast_PWM_10bit, core::operationMode::fast_PWM_ICR, core::operationMode::fast_PWM_OCR, core::operationMode::CTC_OCR,
  core::operationMode::CTC_ICR, core::operationMode::interrupt =1, core::operationMode::reset, core::operationMode::interrupt
  }
- enum core::clockSource : uint16_t {
  core::clockSource::noClock =0, core::clockSource::PS_1, core::clockSource::PS_8, core::clockSource::PS_32,
  core::clockSource::PS_64, core::clockSource::PS_128, core::clockSource::PS_256, core::clockSource::PS_1024,
  core::clockSource::extern_Clock_T0_Falling_Edge, core::clockSource::extern_Clock_T0_Rising_Edge }

7.65.1 Detailed Description

Header file of the TimerCounter class.

Basic class for abstraction of the TimerCounter peripherals.

Author

Farid Oubbati (https://github.com/faroub)

Date

March 2020

Basic class for abstraction of the TimerCounter peripherals.

Usage example (Reaction Timer): #include "TimerCounter.h" #include "USART0.h" #include "PushButton.h" #include "Led.h"

void randomDelay(void); void printWord(uint16_t word);

instantiate the Counter object extern core::TimerCounter core::TimerCounter &myCounter = core::TimerCounter↩
::getInstanceTimerCounter0();

instantiate the USART0 object extern io::USART0 io::USART0 &myUSART0 = io::USART0::getInstance();

#define BUFFER_SIZE 1 #define LED_NUMBER 0 #define PUSHBUTTON_NUMBER 2

int main(void) {

Init uint16_t timerValue;

char l_receiverBuffer[BUFFER_SIZE];

```
myCounter.selectClockSource(core::timerCounter::timerCounter1, core::clockSource::PS_1024);
```

/ instantiate a Led object component::Led Led(io::Pin(LED_NUMBER,io::PortB));

instantiate a Led object component::PushButton PushButton(io::Pin(PUSHBUTTON_NUMBER,io::PortD));

ready to send flag uint8_t l_ready2Send = 1;

if (myUSART0.ready2Send()) { myUSART0.sendString("Reaction Timer:\r\n"); }

wait to send next string while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send()) { myUSART0.sendString("--------------\r\n"); }

wait to send next string while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send()) { myUSART0.sendString("Press any key to start.\r\n"); }

Mainloop while (1) {

myUSART0.receiveFrame(reinterpret_cast<uint8_t∗>(l_receiverBuffer),BUFFER_SIZE);

wait for a key press while (!myUSART0.getNumberBytesReceived()) {

}

reset number of bytes after extracting the received data myUSART0.resetNumberBytesReceived();

wait to send next string while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send()) { myUSART0.sendString("\r\nGet ready..."); }

randomDelay();

wait to send next string while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send()) { myUSART0.sendString("\r\nGo!\r\n"); }

Led.on();

myCounter.setCounter(core::timerCounter::timerCounter1,0);

if (PushButton.isPressed()) { wait to send next string while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send()) { myUSART0.sendString("You're only cheating yourself.\r\n"); }

} else {

wait for a button press while (!PushButton.isPressed()) {

} get counter value myCounter.getCounter(core::timerCounter::timerCounter1, &timerValue); bit shift divide by 16 = 2^4 to convert from micro to millseconds timerValue = timerValue $>>$ 4; print response time printWord(timerValue); }

Led.off();

while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send()) { myUSART0.sendString("\r\nPress any key to try again.\r\n"); }

} return 0; }

void randomDelay(void) {

Waits for a "random" delay from 1 - 3.5 sec Requires timer 1 initialized and running It's not really random, but very hard to control –like coin-flipping.

```
uint16_t counter;
_delay_ms(1000);

myCounter.getCounter(core::timerCounter::timerCounter1, &counter);
uint8_t randomTime = static_cast<uint8_t>(counter);
```

type-casting the 16-bit TCNT1 as an 8-bit number keeps only the 8 least-significant (fastest-changing) bits

```
while (--randomTime) {
_delay_ms(10);
}
}

void printWord(uint16_t word) {

while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send())
{
    myUSART0.sendByte('0' + (word / 10000));

}

while (!myUSART0.ready2Send()){};
```

```
if (myUSART0.ready2Send())
{
    myUSART0.sendByte('0' + ((word / 1000) % 10));
}

while (!myUSART0.ready2Send()){};


if (myUSART0.ready2Send())
{
    myUSART0.sendByte('0' + ((word / 100) % 10));
}


while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send())
{
    myUSART0.sendByte('0' + ((word / 10) % 10));
}



while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send())
{
    myUSART0.sendByte('0' + (word % 10));
}

}
void printWord(uint16_t word) {

char timerValue = '0' + (word / 10000);

while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send())
{
   myUSART0.sendFrame(reinterpret_cast<uint8_t*>(&timerValue),BUFFER_SIZE);

}

timerValue = '0' + ((word / 1000) % 10);

while (!myUSART0.ready2Send()){};


if (myUSART0.ready2Send())
{
   myUSART0.sendFrame(reinterpret_cast<uint8_t*>(&timerValue),BUFFER_SIZE);

}

timerValue = '0' + ((word / 100) % 10);

while (!myUSART0.ready2Send()){};


if (myUSART0.ready2Send())
{
   myUSART0.sendFrame(reinterpret_cast<uint8_t*>(&timerValue),BUFFER_SIZE);

}
timerValue = '0' + ((word / 10) % 10);

while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send())
{
   myUSART0.sendFrame(reinterpret_cast<uint8_t*>(&timerValue),BUFFER_SIZE);

}
```

```
timerValue = '0' + (word % 10);

while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send())
{
    myUSART0.sendFrame(reinterpret_cast<uint8_t*>(&timerValue),BUFFER_SIZE);

}

}
```

Usage example (PWM):

#include "Led.h" #include "USART0.h" #include "TimerCounter1.h" #include "TimerCounter2.h"

uint8_t getNumber(const char ∗ap_receive);

#define LED_1 1 #define LED_2 2 #define LED_3 3 #define BUFFER_SIZE 4

int main(void) {

Init receiver buffer char l_receiverBuffer[BUFFER_SIZE];

instantiate Led objects component::Led Led1(io::Pin(LED_1,io::PortB)); component::Led Led2(io::Pin(LED_2,io::← PortB)); component::Led Led3(io::Pin(LED_3,io::PortB));

instantiate USART0 object io::USART0 &myUSART0 = io::USART0::getInstance();

instantiate Timer1 object core::TimerCounter1 &myTimerCounter1 = core::TimerCounter1::getInstance(); my← TimerCounter1.selectOperationMode(core::operationMode::Fast_PWM_8bit); myTimerCounter1.selectCompare← OutputMode(core::channel::A,core::compareOutputMode::Clear); myTimerCounter1.selectCompareOutput← Mode(core::channel::B,core::compareOutputMode::Clear); instantiate Timer2 object core::TimerCounter2 &my← TimerCounter2 = core::TimerCounter2::getInstance(); myTimerCounter2.selectOperationMode(core::operation← Mode::Fast_PWM); myTimerCounter2.selectCompareOutputMode(core::channel::A,core::compareOutputMode← ::Clear);

if (myUSART0.ready2Send()) { myUSART0.sendString("-- LED PWM Demo --\r\n"); } wait to send next string while (!myUSART0.ready2Send()){}

myTimerCounter1.start(core::clockSource::PS_64); myTimerCounter2.start(core::clockSource::PS_64);

--·—— Event loop --·—— // while (1) {

```
if (myUSART0.ready2Send())
{
    myUSART0.sendString("\r\nEnter (0-255) for PWM duty cycle: ");
}

myUSART0.receiveFrame(reinterpret_cast<uint8_t*>(l_receiverBuffer),BUFFER_SIZE);
```

wait for a key press while (myUSART0.getNumberBytesReceived()<4){}

reset number of bytes after extracting the received data myUSART0.resetNumberBytesReceived();

send back the received character if (myUSART0.ready2Send()) { myUSART0.sendFrame(reinterpret_cast<uint8← _t∗>(l_receiverBuffer),BUFFER_SIZE); }

while (!myUSART0.ready2Send()){} myTimerCounter2.setOutputCompareRegister(core::channel::A,myTimer← Counter1.getOutputCompareRegister(core::channel::B)); myTimerCounter1.setOutputCompareRegister(core::channel::B,my← TimerCounter1.getOutputCompareRegister(core::channel::A)); myTimerCounter1.setOutputCompareRegister(core← ::channel::A,getNumber(l_receiverBuffer));

```
}
return 0;
```

```
}
```

uint8_t getNumber(const char ∗ap_receive) { Gets a numerical 0-255 from the serial port. Converts from string to number. char hundreds = '0'; char tens = '0'; char ones = '0'; char thisChar = '0'; do { hundreds = tens; tens = ones; ones = thisChar; thisChar = ∗ap_receive; ap_receive++;

} while (∗ap_receive != '\r'); return (100 ∗ (hundreds - '0') + 10 ∗ (tens - '0') + ones - '0'); }

Usage example (PWM on Any Pin):

#include "TimerCounter0.h" #include "Led.h"

#define LED_0 0 #define LED_1 1 #define LED_2 2 #define LED_3 3

instantiate Timer0 object extern core::TimerCounter0 core::TimerCounter0 &myTimerCounter0 = core::TimerCounter0::getInstance();

instantiate Led objects extern component::Led Led0; component::Led Led0(io::Pin(LED_0,io::PortB)); extern component::Led Led1; component::Led Led1(io::Pin(LED_1,io::PortB)); extern component::Led Led2; component::Led Led2(io::Pin(LED_2,io::PortB)); extern component::Led Led3; component::Led Led3(io::Pin(↩ LED_3,io::PortB));

#define DELAYTIME 3

volatile uint8_t l_brightnessA; volatile uint8_t l_brightnessB;

int main(void) {

Init uint8_t i;

sei();

myTimerCounter0.enableOutputCompareMatchInterrupt(core::channel::A,1); myTimerCounter0.enableOutput↩ CompareMatchInterrupt(core::channel::B,1); myTimerCounter0.enableOverflowInterrupt(1); myTimerCounter0.↩ start(core::clockSource::PS_1024);

---— Event loop ---— // while (1) {

```
for (i = 0; i < 255; i++) {
    _delay_ms(DELAYTIME);
    l_brightnessA = i;
    l_brightnessB = 255 - i;
}
for (i = 254; i > 0; i--) {
    _delay_ms(DELAYTIME);
    l_brightnessA = i;
    l_brightnessB = 255 - i;
}
```

} return 0; }

```
void core::TimerCounter0::overflowServiceRoutine()
{
    Led0.on();
    Led1.on();
    Led2.on();
    Led3.on();
    myTimerCounter0.setOutputCompareRegister(core::channel::A,l_brightnessA);
    myTimerCounter0.setOutputCompareRegister(core::channel::B,l_brightnessB);
}

void core::TimerCounter0::outputCompareMatchAServiceRoutine()
{
    Led0.off();
    Led1.off();
    Led2.on();
    Led3.on();
}
void core::TimerCounter0::outputCompareMatchBServiceRoutine()
{
    Led0.on();
    Led1.on();
    Led2.off();
    Led3.off();
}
```

Author

Farid Oubbati (https://github.com/faroub)

Date

March 2020

Basic class for abstraction of the TimerCounter peripherals.

Usage example (Reaction Timer): #include "TimerCounter.h" #include "USART0.h" #include "PushButton.h" #include "Led.h"

void randomDelay(void); void printWord(uint16_t word);

instantiate the Counter object extern core::TimerCounter core::TimerCounter &myCounter = core::TimerCounter←┘ ::getInstanceTimerCounter0();

instantiate the USART0 object extern io::USART0 io::USART0 &myUSART0 = io::USART0::getInstance();

#define BUFFER_SIZE 1 #define LED_NUMBER 0 #define PUSHBUTTON_NUMBER 2

int main(void) {

Init uint16_t timerValue;

char l_receiverBuffer[BUFFER_SIZE];

myCounter.selectClockSource(core::timerCounter::timerCounter1, core::clockSource::PS_1024);

/ instantiate a Led object component::Led Led(io::Pin(LED_NUMBER,io::PortB));

instantiate a Led object component::PushButton PushButton(io::Pin(PUSHBUTTON_NUMBER,io::PortD));

ready to send flag uint8_t l_ready2Send = 1;

if (myUSART0.ready2Send()) { myUSART0.sendString("Reaction Timer:\r\n"); }

wait to send next string while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send()) { myUSART0.sendString("--------------\r\n"); }

wait to send next string while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send()) { myUSART0.sendString("Press any key to start.\r\n"); }

Mainloop while (1) {

myUSART0.receiveFrame(reinterpret_cast<uint8_t∗>(l_receiverBuffer),BUFFER_SIZE);

wait for a key press while (!myUSART0.getNumberBytesReceived()) {

}

reset number of bytes after extracting the received data myUSART0.resetNumberBytesReceived();

wait to send next string while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send()) { myUSART0.sendString("\r\nGet ready..."); }

randomDelay();

wait to send next string while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send()) { myUSART0.sendString("\r\nGo!\r\n"); }

Led.on();

myCounter.setCounter(core::timerCounter::timerCounter1,0);

if (PushButton.isPressed()) { wait to send next string while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send()) { myUSART0.sendString("You're only cheating yourself.\r\n"); }

} else {

wait for a button press while (!PushButton.isPressed()) {

} get counter value myCounter.getCounter(core::timerCounter::timerCounter1, &timerValue); bit shift divide by 16 = 2^4 to convert from micro to millseconds timerValue = timerValue $>>$ 4; print response time printWord(timerValue); }

Led.off();

while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send()) { myUSART0.sendString("\r\nPress any key to try again.\r\n"); }

} return 0; }

void randomDelay(void) {

Waits for a "random" delay from 1 - 3.5 sec Requires timer 1 initialized and running It's not really random, but very hard to control –like coin-flipping.

```
uint16_t counter;
_delay_ms(1000);

myCounter.getCounter(core::timerCounter::timerCounter1, &counter);
uint8_t randomTime = static_cast<uint8_t>(counter);
```

type-casting the 16-bit TCNT1 as an 8-bit number keeps only the 8 least-significant (fastest-changing) bits

```
while (--randomTime) {
_delay_ms(10);
}
}

void printWord(uint16_t word) {

while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send())
{
    myUSART0.sendByte('0' + (word / 10000));

}

while (!myUSART0.ready2Send()){};


if (myUSART0.ready2Send())
{
    myUSART0.sendByte('0' + ((word / 1000) % 10));
}

while (!myUSART0.ready2Send()){};


if (myUSART0.ready2Send())
{
    myUSART0.sendByte('0' + ((word / 100) % 10));
}


while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send())
{
    myUSART0.sendByte('0' + ((word / 10) % 10));
}


while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send())
{
    myUSART0.sendByte('0' + (word % 10));
}

}
void printWord(uint16_t word) {

char timerValue = '0' + (word / 10000);

while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send())
{
    myUSART0.sendFrame(reinterpret_cast<uint8_t*>(&timerValue),BUFFER_SIZE);

}

timerValue = '0' + ((word / 1000) % 10);

while (!myUSART0.ready2Send()){};
```

```
if (myUSART0.ready2Send())
{
    myUSART0.sendFrame(reinterpret_cast<uint8_t*>(&timerValue),BUFFER_SIZE);

}

timerValue = '0' + ((word / 100) % 10);

while (!myUSART0.ready2Send()){};


if (myUSART0.ready2Send())
{
    myUSART0.sendFrame(reinterpret_cast<uint8_t*>(&timerValue),BUFFER_SIZE);

}
timerValue = '0' + ((word / 10) % 10);

while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send())
{
    myUSART0.sendFrame(reinterpret_cast<uint8_t*>(&timerValue),BUFFER_SIZE);

}

timerValue = '0' + (word % 10);

while (!myUSART0.ready2Send()){};

if (myUSART0.ready2Send())
{
    myUSART0.sendFrame(reinterpret_cast<uint8_t*>(&timerValue),BUFFER_SIZE);

}

}
```

Usage example (Reaction Timer):

Author

Farid Oubbati (https://github.com/faroub)

Date

March 2020

Definition in file TimerCounter.h.

7.66 TimerCounter.h

```
00001
00039
00461 #ifndef TIMER_COUNTER_H
00462 #define TIMER_COUNTER_H
00463 #include "ha_base.h"
00464
00465
00466
00467 namespace core
00468 {
00469
00470 enum class channel : uint8_t {
00471     A=0,
```

```
00472        B,
00473 };
00474
00475
00476 enum class compareOutputMode : uint8_t {
00477        normal=0,
00478        toggle,
00479        clear,
00480        set,
00481 };
00482
00483
00484
00485 enum class operationMode : uint8_t {
00486        normal=0,
00487        PWM_PC,
00488        PWM_PC_8bit,
00489        PWM_PC_9bit,
00490        PWM_PC_10bit,
00491        PWM_PFC_ICR,
00492        PWM_PFC_OCR,
00493        PWM_PC_ICR,
00494        PWM_PC_OCR,
00495        fast_PWM,
00496        fast_PWM_8bit,
00497        fast_PWM_9bit,
00498        fast_PWM_10bit,
00499        fast_PWM_ICR,
00500        fast_PWM_OCR,
00501        CTC_OCR,
00502        CTC_ICR,
00503 };
00504 enum class clockSource : uint16_t {
00505         noClock=0,
00506        PS_1,
00507        PS_8,
00508        PS_32,
00509        PS_64,
00510        PS_128,
00511        PS_256,
00512        PS_1024,
00513        extern_Clock_T0_Falling_Edge,
00514        extern_Clock_T0_Rising_Edge,
00515 };
00516
00517 class TimerCounter
00518 {
00519
00520 public:
00521
00522
00523        virtual void selectOperationMode(const operationMode &ar_operationMode) = 0;
00524
00525        virtual void start() = 0;
00526
00527        virtual void stop() = 0;
00528
00529        virtual void selectClockSource(const clockSource &ar_clockSource) = 0;
00530
00531        virtual void selectCompareOutputMode(const channel &ar_channel, const compareOutputMode
      &ar_compareOutputMode) = 0;
00532
00533        virtual void setCounter(const uint16_t &ar_dataBuffer) = 0;
00534
00535        virtual uint16_t getCounter() const = 0;
00536
00537        virtual void setOutputCompareRegister(const channel &ar_channel, const uint16_t &ar_dataBuffer) =
      0;
00538
00539        virtual uint16_t getOutputCompareRegister(const channel &ar_channel) const = 0;
00540
00541        virtual void enableOutputCompareMatchInterrupt(const channel &ar_channel, const uint8_t a_enable)
      = 0;
00542
00543        virtual void enableOverflowInterrupt(const uint8_t a_enable) = 0;
00544
00545        virtual uint16_t getClockPrescaler() = 0;
00546
00547 protected:
00548
00549 private:
00550
00551
00552
00553
00554 };
00555
```

```
00556 }
00557
00558
00559 #endif
```

7.67   TimerCounter0.cpp File Reference

```
#include "TimerCounter0.h"
#include "MCU.h"
```
Include dependency graph for TimerCounter0.cpp:

7.68   TimerCounter0.cpp

```
00001 #include "TimerCounter0.h"
00002 #include "MCU.h"
00003
00004
00005 core::TimerCounter0& core::TimerCounter0::getInstance(const channel &ar_channel,
00006                                                       const operationMode &ar_operationMode,
00007                                                       const clockSource &ar_clockSource,
00008                                                       const compareOutputMode &ar_compareOutputMode)
00009 {
00010     static TimerCounter0 l_instance(ar_channel,
00011                                     ar_operationMode,
00012                                     ar_clockSource,
00013                                     ar_compareOutputMode);
00014
00015     return l_instance;
00016
00017
00018 }
00019
00020 core::TimerCounter0::TimerCounter0(const channel &ar_channel,
00021                                    const operationMode &ar_operationMode,
00022                                    const clockSource &ar_clockSource,
00023                                    const compareOutputMode& ar_compareOutputMode)
00024 {
00025     core::MCU::enableTimerCounter0(1);
00026     stop();
00027     selectOperationMode(ar_operationMode);
00028     selectClockSource(ar_clockSource);
00029     selectCompareOutputMode(ar_channel,ar_compareOutputMode);
00030
00031
00032
00033 }
00034 core::TimerCounter0::~TimerCounter0()
00035 {
00036
00037 }
```

```
00038
00039 void core::TimerCounter0::selectClockSource(const clockSource &ar_clockSource)
00040 {
00041     switch (ar_clockSource)
00042     {
00043         case core::clockSource::noClock:
00044         {
00045             m_clockPrescaler=0;
00046             m_clockSource=0;
00047             break;
00048         }
00049         case core::clockSource::PS_1:
00050         {
00051             m_clockPrescaler=1;
00052             m_clockSource=1;
00053             break;
00054         }
00055         case core::clockSource::PS_8:
00056         {
00057             m_clockPrescaler=8;
00058             m_clockSource=2;
00059             break;
00060         }
00061         case core::clockSource::PS_64:
00062         {
00063             m_clockPrescaler=64;
00064             m_clockSource=3;
00065             break;
00066         }
00067         case core::clockSource::PS_256:
00068         {
00069             m_clockPrescaler=256;
00070             m_clockSource=4;
00071             break;
00072         }
00073         case core::clockSource::PS_1024:
00074         {
00075             m_clockPrescaler=1024;
00076             m_clockSource=5;
00077             break;
00078         }
00079         case core::clockSource::extern_Clock_T0_Falling_Edge:
00080         {
00081             m_clockPrescaler=0;
00082             m_clockSource=6;
00083             break;
00084         }
00085         case core::clockSource::extern_Clock_T0_Rising_Edge:
00086         {
00087             m_clockPrescaler=0;
00088             m_clockSource=7;
00089             break;
00090         }
00091     }
00092
00093
00094 }
00095
00096 void core::TimerCounter0::selectOperationMode(const operationMode &ar_operationMode)
00097 {
00098     switch (ar_operationMode)
00099     {
00100         case core::operationMode::normal:
00101         {
00102             TIMER0_SELECT_OPERATION_MODE(0);
00103             break;
00104         }
00105         case core::operationMode::PWM_PC:
00106         {
00107             TIMER0_SELECT_OPERATION_MODE(1);
00108             break;
00109         }
00110         case core::operationMode::CTC_OCR:
00111         {
00112             TIMER0_SELECT_OPERATION_MODE(2);
00113             break;
00114         }
00115         case core::operationMode::fast_PWM:
00116         {
00117             TIMER0_SELECT_OPERATION_MODE(3);
00118             break;
00119         }
00120         case core::operationMode::PWM_PC_OCR:
00121         {
00122             TIMER0_SELECT_OPERATION_MODE(5);
00123             break;
00124         }
```

```
00125            case core::operationMode::fast_PWM_OCR:
00126            {
00127                TIMER0_SELECT_OPERATION_MODE(7);
00128                break;
00129            }
00130
00131        }
00132
00133  }
00134
00135
00136  void core::TimerCounter0::start()
00137  {
00138        TIMER0_SELECT_CLOCK_SOURCE(m_clockSource);
00139  }
00140
00141  uint16_t core::TimerCounter0::getClockPrescaler()
00142  {
00143        return m_clockPrescaler;
00144  }
00145
00146  void core::TimerCounter0::stop()
00147  {
00148        TIMER0_STOP;
00149  }
00150
00151
00152  void core::TimerCounter0::selectCompareOutputMode(const channel &ar_channel, const compareOutputMode
        &ar_compareOutputMode)
00153  {
00154        switch (ar_channel)
00155        {
00156            case core::channel::A:
00157            {
00158                TIMER0_SELECT_COM_CHANNEL_A(static_cast<uint8_t>(ar_compareOutputMode));
00159                break;
00160            }
00161            case core::channel::B:
00162            {
00163                TIMER0_SELECT_COM_CHANNEL_B(static_cast<uint8_t>(ar_compareOutputMode));
00164                break;
00165            }
00166        }
00167  }
00168
00169
00170
00171  void core::TimerCounter0::setCounter(const uint16_t &ar_dataBuffer)
00172  {
00173        TCNT0 = static_cast<uint8_t>(ar_dataBuffer);
00174  }
00175
00176  uint16_t core::TimerCounter0::getCounter() const
00177  {
00178        return TCNT0;
00179  }
00180
00181  void core::TimerCounter0::setOutputCompareRegister(const channel &ar_channel, const uint16_t
        &ar_dataBuffer)
00182  {
00183        switch (ar_channel)
00184        {
00185            case core::channel::A:
00186            {
00187                OCR0A = static_cast<uint8_t>(ar_dataBuffer);
00188                break;
00189            }
00190            case core::channel::B:
00191            {
00192                OCR0B = static_cast<uint8_t>(ar_dataBuffer);
00193                break;
00194            }
00195
00196        }
00197  }
00198
00199
00200
00201  uint16_t core::TimerCounter0::getOutputCompareRegister(const channel &ar_channel) const
00202  {
00203        switch (ar_channel)
00204        {
00205            case core::channel::A:
00206            {
00207                return OCR0A;
00208            }
00209            case core::channel::B:
```

```
00210            {
00211                return OCR0B;
00212            }
00213        }
00214 }
00215
00216 void core::TimerCounter0::enableOutputCompareMatchInterrupt(const channel &ar_channel, const uint8_t
      a_enable)
00217 {
00218      switch (ar_channel)
00219      {
00220          case core::channel::A:
00221          {
00222              if (a_enable) {
00223
00224                  TIMER0_ENABLE_COM_CHANNEL_A_INTERRUPT;
00225
00226              } else {
00227
00228                  TIMER0_DISABLE_COM_CHANNEL_A_INTERRUPT;
00229              }
00230              break;
00231          }
00232          case core::channel::B:
00233          {
00234              if (a_enable) {
00235
00236                  TIMER0_ENABLE_COM_CHANNEL_B_INTERRUPT;
00237
00238              } else {
00239
00240                  TIMER0_DISABLE_COM_CHANNEL_B_INTERRUPT;
00241
00242              }
00243              break;
00244          }
00245      }
00246
00247 }
00248
00249
00250
00251 void core::TimerCounter0::enableOverflowInterrupt(const uint8_t a_enable)
00252 {
00253
00254      if (a_enable) {
00255
00256          TIMER0_ENABLE_OVERFLOW_INTERRUPT;
00257
00258      } else {
00259
00260          TIMER0_DISABLE_OVERFLOW_INTERRUPT;
00261      }
00262
00263 }
```

7.69 TimerCounter0.h File Reference

```
#include "TimerCounter.h"
#include "ha_base.h"
```

Include dependency graph for TimerCounter0.h:

This graph shows which files directly or indirectly include this file:

Classes

- class core::TimerCounter0

Namespaces

- core

7.70 TimerCounter0.h

```
00001
00039
00268 #ifndef TIMER_COUNTER0_H
00269 #define TIMER_COUNTER0_H
00270 #include "TimerCounter.h"
00271 #include "ha_base.h"
00272
00273
00274
00275 namespace core
00276 {
00277
00278
00279 class TimerCounter0 : public TimerCounter
```

```
00280 {
00281
00282 public:
00283
00284     static TimerCounter0& getInstance(const channel &ar_channel = channel::A,
00285                                       const operationMode &ar_operationMode = operationMode::normal,
00286                                       const clockSource &ar_clockSource= clockSource::noClock,
00287                                       const compareOutputMode& ar_compareOutputMode =
      compareOutputMode::normal);
00288
00289     void selectOperationMode(const operationMode &ar_operationMode) override;
00290
00291     void start() override;
00292
00293     void stop() override;
00294
00295     void selectClockSource(const clockSource &ar_clockSource) override;
00296
00297     void selectCompareOutputMode(const channel &ar_channel, const compareOutputMode
      &ar_compareOutputMode) override;
00298
00299     void setCounter(const uint16_t &ar_dataBuffer) override;
00300
00301     uint16_t getCounter() const override;
00302
00303     void setOutputCompareRegister(const channel &ar_channel, const uint16_t &ar_dataBuffer) override;
00304
00305     uint16_t getOutputCompareRegister(const channel &ar_channel) const override;
00306
00307     void enableOutputCompareMatchInterrupt(const channel &ar_channel, const uint8_t a_enable)
      override;
00308
00309     void enableOverflowInterrupt(const uint8_t a_enable) override;
00310
00311     uint16_t getClockPrescaler() override;
00312
00313     static void outputCompareMatchAServiceRoutine() __asm__(STR(TIMER0_COM_CHANNEL_A_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
00314
00315     static void outputCompareMatchBServiceRoutine() __asm__(STR(TIMER0_COM_CHANNEL_B_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
00316
00317     static void overflowServiceRoutine() __asm__(STR(TIMER0_OVERFLOW_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
00318
00319
00320
00321 protected:
00322
00323 private:
00324
00325     TimerCounter0(const channel &ar_channel,
00326                   const operationMode &ar_operationMode,
00327                   const clockSource &ar_clockSource,
00328                   const compareOutputMode& ar_compareOutputMode);
00329
00330     ~TimerCounter0();
00331
00334     TimerCounter0(const TimerCounter0&);
00335
00338     const TimerCounter0& operator=(const TimerCounter0&);
00339
00340     uint16_t m_clockPrescaler;
00341
00342     uint8_t m_clockSource;
00343
00344
00345
00346 };
00347
00348 }
00349
00350
00351 #endif
```

7.71 TimerCounter1.cpp File Reference

```
#include "TimerCounter1.h"
#include "MCU.h"
```

Include dependency graph for TimerCounter1.cpp:

7.72 TimerCounter1.cpp

```
00001 #include "TimerCounter1.h"
00002 #include "MCU.h"
00003
00004
00005 core::TimerCounter1& core::TimerCounter1::getInstance(const channel &ar_channel,
00006                                                        const operationMode &ar_operationMode,
00007                                                        const clockSource &ar_clockSource,
00008                                                        const compareOutputMode& ar_compareOutputMode)
00009 {
00010     static TimerCounter1 l_instance(ar_channel,
00011                                     ar_operationMode,
00012                                     ar_clockSource,
00013                                     ar_compareOutputMode);
00014
00015     return l_instance;
00016
00017
00018 }
00019
00020 core::TimerCounter1::TimerCounter1(const channel &ar_channel,
00021                                    const operationMode &ar_operationMode,
00022                                    const clockSource &ar_clockSource,
00023                                    const compareOutputMode& ar_compareOutputMode)
00024 {
00025     core::MCU::enableTimerCounter1(1);
00026     stop();
00027     selectOperationMode(ar_operationMode);
00028     selectClockSource(ar_clockSource);
00029     selectCompareOutputMode(ar_channel,ar_compareOutputMode);
00030
00031
00032 }
00033 core::TimerCounter1::~TimerCounter1()
00034 {
00035
00036 }
00037
00038 void core::TimerCounter1::selectClockSource(const clockSource &ar_clockSource)
00039 {
00040     switch (ar_clockSource)
00041     {
00042         case core::clockSource::noClock:
00043         {
00044             m_clockPrescaler=0;
00045             m_clockSource=0;
00046             break;
00047         }
00048         case core::clockSource::PS_1:
00049         {
00050             m_clockPrescaler=1;
00051             m_clockSource=1;
00052             break;
00053         }
```

```
00054            case core::clockSource::PS_8:
00055            {
00056                m_clockPrescaler=8;
00057                m_clockSource=2;
00058                break;
00059            }
00060            case core::clockSource::PS_64:
00061            {
00062                m_clockPrescaler=64;
00063                m_clockSource=3;
00064                break;
00065            }
00066            case core::clockSource::PS_256:
00067            {
00068                m_clockPrescaler=256;
00069                m_clockSource=4;
00070                break;
00071            }
00072            case core::clockSource::PS_1024:
00073            {
00074                m_clockPrescaler=1024;
00075                m_clockSource=5;
00076                break;
00077            }
00078            case core::clockSource::extern_Clock_T0_Falling_Edge:
00079            {
00080                m_clockPrescaler=0;
00081                m_clockSource=6;
00082                break;
00083            }
00084            case core::clockSource::extern_Clock_T0_Rising_Edge:
00085            {
00086                m_clockPrescaler=0;
00087                m_clockSource=7;
00088                break;
00089            }
00090        }
00091
00092
00093 }
00094
00095 void core::TimerCounter1::selectOperationMode(const operationMode &ar_operationMode)
00096 {
00097     switch (ar_operationMode)
00098     {
00099         case core::operationMode::normal:
00100         {
00101             TIMER1_SELECT_OPERATION_MODE(0);
00102             break;
00103         }
00104         case core::operationMode::PWM_PC_8bit:
00105         {
00106             TIMER1_SELECT_OPERATION_MODE(1);
00107             break;
00108         }
00109         case core::operationMode::PWM_PC_9bit:
00110         {
00111             TIMER1_SELECT_OPERATION_MODE(2);
00112             break;
00113         }
00114         case core::operationMode::PWM_PC_10bit:
00115         {
00116             TIMER1_SELECT_OPERATION_MODE(3);
00117             break;
00118         }
00119         case core::operationMode::CTC_OCR:
00120         {
00121             TIMER1_SELECT_OPERATION_MODE(4);
00122             break;
00123         }
00124         case core::operationMode::fast_PWM_8bit:
00125         {
00126             TIMER1_SELECT_OPERATION_MODE(5);
00127             break;
00128         }
00129         case core::operationMode::fast_PWM_9bit:
00130         {
00131             TIMER1_SELECT_OPERATION_MODE(6);
00132             break;
00133         }
00134         case core::operationMode::fast_PWM_10bit:
00135         {
00136             TIMER1_SELECT_OPERATION_MODE(7);
00137             break;
00138         }
00139         case core::operationMode::PWM_PFC_ICR:
00140         {
```

```
00141                 TIMER1_SELECT_OPERATION_MODE(8);
00142             break;
00143         }
00144         case core::operationMode::PWM_PFC_OCR:
00145         {
00146             TIMER1_SELECT_OPERATION_MODE(9);
00147             break;
00148         }
00149         case core::operationMode::PWM_PC_ICR:
00150         {
00151             TIMER1_SELECT_OPERATION_MODE(10);
00152             break;
00153         }
00154         case core::operationMode::PWM_PC_OCR:
00155         {
00156             TIMER1_SELECT_OPERATION_MODE(11);
00157             break;
00158         }
00159         case core::operationMode::CTC_ICR:
00160         {
00161             TIMER1_SELECT_OPERATION_MODE(12);
00162             break;
00163         }
00164         case core::operationMode::fast_PWM_ICR:
00165         {
00166             TIMER1_SELECT_OPERATION_MODE(14);
00167             break;
00168         }
00169         case core::operationMode::fast_PWM_OCR:
00170         {
00171             TIMER1_SELECT_OPERATION_MODE(15);
00172             break;
00173         }
00174
00175     }
00176
00177
00178 }
00179
00180
00181 void core::TimerCounter1::start()
00182 {
00183     TIMER1_SELECT_CLOCK_SOURCE(m_clockSource);
00184 }
00185
00186 uint16_t core::TimerCounter1::getClockPrescaler()
00187 {
00188     return m_clockPrescaler;
00189 }
00190
00191 void core::TimerCounter1::stop()
00192 {
00193     TIMER1_STOP;
00194 }
00195
00196
00197 void core::TimerCounter1::selectCompareOutputMode(const channel &ar_channel, const compareOutputMode
     &ar_compareOutputMode)
00198 {
00199     switch (ar_channel)
00200     {
00201         case core::channel::A:
00202         {
00203             TIMER1_SELECT_COM_CHANNEL_A(static_cast<uint8_t>(ar_compareOutputMode));
00204             break;
00205         }
00206         case core::channel::B:
00207         {
00208             TIMER1_SELECT_COM_CHANNEL_B(static_cast<uint8_t>(ar_compareOutputMode));
00209             break;
00210         }
00211     }
00212
00213 }
00214
00215
00216 void core::TimerCounter1::setCounter(const uint16_t &ar_dataBuffer)
00217 {
00218     TCNT1 = ar_dataBuffer;
00219 }
00220
00221 uint16_t core::TimerCounter1::getCounter() const
00222 {
00223     return TCNT1;
00224 }
00225
00226 void core::TimerCounter1::setOutputCompareRegister(const channel &ar_channel, const uint16_t
```

```
       &ar_dataBuffer)
00227 {
00228     switch (ar_channel)
00229     {
00230         case core::channel::A:
00231         {
00232             OCR1A = ar_dataBuffer;
00233             break;
00234         }
00235         case core::channel::B:
00236         {
00237             OCR1B = ar_dataBuffer;
00238             break;
00239         }
00240     }
00241 }
00242
00243
00244
00245 uint16_t core::TimerCounter1::getOutputCompareRegister(const channel &ar_channel) const
00246 {
00247     switch (ar_channel)
00248     {
00249         case core::channel::A:
00250         {
00251             return OCR1A;
00252         }
00253         case core::channel::B:
00254         {
00255             return OCR1B;
00256         }
00257     }
00258 }
00259
00260 void core::TimerCounter1::enableOutputCompareMatchInterrupt(const channel &ar_channel, const uint8_t
       a_enable)
00261 {
00262     switch (ar_channel)
00263     {
00264         case core::channel::A:
00265         {
00266             if (a_enable) {
00267
00268                 TIMER1_ENABLE_COM_CHANNEL_A_INTERRUPT;
00269
00270             } else {
00271
00272                 TIMER1_DISABLE_COM_CHANNEL_A_INTERRUPT;
00273             }
00274             break;
00275         }
00276         case core::channel::B:
00277         {
00278             if (a_enable) {
00279
00280                 TIMER1_ENABLE_COM_CHANNEL_B_INTERRUPT;
00281
00282             } else {
00283
00284                 TIMER1_DISABLE_COM_CHANNEL_B_INTERRUPT;
00285
00286             }
00287             break;
00288         }
00289     }
00290
00291 }
00292
00293
00294
00295 void core::TimerCounter1::enableOverflowInterrupt(const uint8_t a_enable)
00296 {
00297
00298     if (a_enable) {
00299
00300         TIMER1_ENABLE_OVERFLOW_INTERRUPT;
00301
00302     } else {
00303
00304         TIMER1_DISABLE_OVERFLOW_INTERRUPT;
00305     }
00306
00307 }
00308
00309 void core::TimerCounter1::enableInputCaptureInterrupt(const uint8_t a_enable)
00310 {
00311     if (a_enable) {
```

```
00312
00313          TIMER1_ENABLE_INPUT_CAPTURE_INTERRUPT;
00314
00315      } else {
00316
00317          TIMER1_DISABLE_INPUT_CAPTURE_INTERRUPT;
00318      }
00319 }
00320
00321 void core::TimerCounter1::setInputCaptureRegister(const uint16_t &ar_dataBuffer)
00322 {
00323      ICR1 = ar_dataBuffer;
00324 }
00325
00326
00327 uint16_t core::TimerCounter1::getInputCaptureRegister() const
00328 {
00329      return ICR1;
00330 }
```

7.73   TimerCounter1.h File Reference

```
#include "TimerCounter.h"
#include "ha_base.h"
```
Include dependency graph for TimerCounter1.h:

This graph shows which files directly or indirectly include this file:

Classes

- class core::TimerCounter1

Namespaces

- core

7.74 TimerCounter1.h

```
00001
00039
00268 #ifndef TIMER_COUNTER1_H
00269 #define TIMER_COUNTER1_H
00270 #include "TimerCounter.h"
00271 #include "ha_base.h"
00272
00273
00274
00275 namespace core
00276 {
00277
00278
00279 class TimerCounter1 : public TimerCounter
00280 {
00281
00282 public:
00283
00284     static TimerCounter1& getInstance(const channel &ar_channel = channel::A,
00285                                 const operationMode &ar_operationMode = operationMode::normal,
00286                                 const clockSource &ar_clockSource= clockSource::noClock,
00287                                 const compareOutputMode& ar_compareOutputMode =
      compareOutputMode::normal);
00288
00289     void selectOperationMode(const operationMode &ar_operationMode) override;
00290
00291     void start() override;
00292
00293     void stop() override;
00294
00295     void selectClockSource(const clockSource &ar_clockSource) override;
00296
00297
00298     void selectCompareOutputMode(const channel &ar_channel, const compareOutputMode
      &ar_compareOutputMode) override;
00299
00300     void setCounter(const uint16_t &ar_dataBuffer) override;
00301
00302     uint16_t getCounter() const override;
00303
00304     void setOutputCompareRegister(const channel &ar_channel, const uint16_t &ar_dataBuffer) override;
00305
00306     uint16_t getOutputCompareRegister(const channel &ar_channel) const override;
00307
00308     void setInputCaptureRegister(const uint16_t &ar_dataBuffer);
00309
00310     uint16_t getInputCaptureRegister() const;
00311
00312     void enableOutputCompareMatchInterrupt(const channel &ar_channel, const uint8_t a_enable)
      override;
00313
00314     void enableOverflowInterrupt(const uint8_t a_enable) override;
00315
00316     void enableInputCaptureInterrupt(const uint8_t a_enable);
00317
00318     uint16_t getClockPrescaler() override;
00319
00320     static void outputCompareMatchAServiceRoutine() __asm__(STR(TIMER1_COM_CHANNEL_A_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
00321
00322     static void outputCompareMatchBServiceRoutine() __asm__(STR(TIMER1_COM_CHANNEL_B_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
00323
00324     static void overflowServiceRoutine() __asm__(STR(TIMER1_OVERFLOW_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
00325
00326     static void inputCaptureServiceRoutine() __asm__(STR(TIMER1_INPUT_CAPTURE_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
```

```
00327
00328
00329
00330 protected:
00331
00332 private:
00333
00334     TimerCounter1(const channel &ar_channel,
00335                   const operationMode &ar_operationMode,
00336                   const clockSource &ar_clockSource,
00337                   const compareOutputMode& ar_compareOutputMode);
00338
00339     ~TimerCounter1();
00340
00343     TimerCounter1(const TimerCounter1&);
00344
00347     const TimerCounter1& operator=(const TimerCounter1&);
00348
00349     uint16_t m_clockPrescaler;
00350
00351     uint8_t m_clockSource;
00352
00353 };
00354
00355 }
00356
00357
00358 #endif
```

7.75 TimerCounter2.cpp File Reference

```
#include "TimerCounter2.h"
#include "MCU.h"
```
Include dependency graph for TimerCounter2.cpp:

7.76 TimerCounter2.cpp

```
00001 #include "TimerCounter2.h"
00002 #include "MCU.h"
00003
00004
00005 core::TimerCounter2& core::TimerCounter2::getInstance(const channel &ar_channel,
00006                                                       const operationMode &ar_operationMode,
00007                                                       const clockSource &ar_clockSource,
00008                                                       const compareOutputMode& ar_compareOutputMode)
00009 {
00010     static TimerCounter2 l_instance(ar_channel,
00011                                     ar_operationMode,
00012                                     ar_clockSource,
00013                                     ar_compareOutputMode);
```

```
00014
00015     return l_instance;
00016
00017
00018 }
00019
00020 core::TimerCounter2::TimerCounter2(const channel &ar_channel,
00021                                    const operationMode &ar_operationMode,
00022                                    const clockSource &ar_clockSource,
00023                                    const compareOutputMode& ar_compareOutputMode)
00024 {
00025     core::MCU::enableTimerCounter2(1);
00026     stop();
00027     selectOperationMode(ar_operationMode);
00028     selectClockSource(ar_clockSource);
00029     selectCompareOutputMode(ar_channel, ar_compareOutputMode);
00030
00031 }
00032 core::TimerCounter2::~TimerCounter2()
00033 {
00034
00035 }
00036
00037 void core::TimerCounter2::selectClockSource(const clockSource &ar_clockSource)
00038 {
00039     switch (ar_clockSource)
00040     {
00041         case core::clockSource::noClock:
00042         {
00043             m_clockPrescaler=0;
00044             m_clockSource=0;
00045             break;
00046         }
00047         case core::clockSource::PS_1:
00048         {
00049             m_clockPrescaler=1;
00050             m_clockSource=1;
00051             break;
00052         }
00053         case core::clockSource::PS_8:
00054         {
00055             m_clockPrescaler=8;
00056             m_clockSource=2;
00057             break;
00058         }
00059         case core::clockSource::PS_32:
00060         {
00061             m_clockPrescaler=32;
00062             m_clockSource=3;
00063             break;
00064         }
00065         case core::clockSource::PS_64:
00066         {
00067             m_clockPrescaler=64;
00068             m_clockSource=4;
00069             break;
00070         }
00071         case core::clockSource::PS_128:
00072         {
00073             m_clockPrescaler=128;
00074             m_clockSource=5;
00075             break;
00076         }
00077         case core::clockSource::PS_256:
00078         {
00079             m_clockPrescaler=256;
00080             m_clockSource=6;
00081             break;
00082         }
00083         case core::clockSource::PS_1024:
00084         {
00085             m_clockPrescaler=1024;
00086             m_clockSource=7;
00087             break;
00088         }
00089     }
00090
00091 }
00092
00093 void core::TimerCounter2::selectOperationMode(const operationMode &ar_operationMode)
00094 {
00095     switch (ar_operationMode)
00096     {
00097         case core::operationMode::normal:
00098         {
00099             TIMER2_SELECT_OPERATION_MODE(0);
00100             break;
```

```
00101             }
00102         case core::operationMode::PWM_PC:
00103         {
00104             TIMER2_SELECT_OPERATION_MODE(1);
00105             break;
00106         }
00107         case core::operationMode::CTC_OCR:
00108         {
00109             TIMER2_SELECT_OPERATION_MODE(2);
00110             break;
00111         }
00112         case core::operationMode::fast_PWM:
00113         {
00114             TIMER2_SELECT_OPERATION_MODE(3);
00115             break;
00116         }
00117         case core::operationMode::PWM_PC_OCR:
00118         {
00119             TIMER2_SELECT_OPERATION_MODE(5);
00120             break;
00121         }
00122         case core::operationMode::fast_PWM_OCR:
00123         {
00124             TIMER2_SELECT_OPERATION_MODE(7);
00125             break;
00126         }
00127
00128     }
00129
00130 }
00131
00132
00133 void core::TimerCounter2::start()
00134 {
00135     TIMER2_SELECT_CLOCK_SOURCE(m_clockSource);
00136 }
00137
00138 uint16_t core::TimerCounter2::getClockPrescaler()
00139 {
00140     return m_clockPrescaler;
00141 }
00142
00143
00144 void core::TimerCounter2::stop()
00145 {
00146     TIMER2_STOP;
00147 }
00148
00149
00150 void core::TimerCounter2::selectCompareOutputMode(const channel &ar_channel, const compareOutputMode
     &ar_compareOutputMode)
00151 {
00152     switch (ar_channel)
00153     {
00154         case core::channel::A:
00155         {
00156             TIMER2_SELECT_COM_CHANNEL_A(static_cast<uint8_t>(ar_compareOutputMode));
00157             break;
00158         }
00159         case core::channel::B:
00160         {
00161             TIMER2_SELECT_COM_CHANNEL_B(static_cast<uint8_t>(ar_compareOutputMode));
00162             break;
00163         }
00164     }
00165
00166
00167 }
00168
00169
00170
00171 void core::TimerCounter2::setCounter(const uint16_t &ar_dataBuffer)
00172 {
00173     TCNT2 = static_cast<uint8_t>(ar_dataBuffer);
00174 }
00175
00176 uint16_t core::TimerCounter2::getCounter() const
00177 {
00178     return TCNT2;
00179 }
00180
00181 void core::TimerCounter2::setOutputCompareRegister(const channel &ar_channel, const uint16_t
     &ar_dataBuffer)
00182 {
00183     switch (ar_channel)
00184     {
00185         case core::channel::A:
```

```
00186            {
00187                OCR2A = static_cast<uint8_t>(ar_dataBuffer);
00188                break;
00189            }
00190        case core::channel::B:
00191            {
00192                OCR2B = static_cast<uint8_t>(ar_dataBuffer);
00193                break;
00194            }
00195        }
00196 }
00197
00198
00199 uint16_t core::TimerCounter2::getOutputCompareRegister(const channel &ar_channel) const
00200 {
00201     switch (ar_channel)
00202     {
00203         case core::channel::A:
00204            {
00205                return OCR2A;
00206            }
00207        case core::channel::B:
00208            {
00209                return OCR2B;
00210            }
00211        }
00212
00213 }
00214
00215 void core::TimerCounter2::enableOutputCompareMatchInterrupt(const channel &ar_channel, const uint8_t
      a_enable)
00216 {
00217     switch (ar_channel)
00218     {
00219         case core::channel::A:
00220            {
00221                if (a_enable) {
00222
00223                    TIMER2_ENABLE_COM_CHANNEL_A_INTERRUPT;
00224
00225                } else {
00226
00227                    TIMER2_DISABLE_COM_CHANNEL_A_INTERRUPT;
00228                }
00229                break;
00230            }
00231        case core::channel::B:
00232            {
00233                if (a_enable) {
00234
00235                    TIMER2_ENABLE_COM_CHANNEL_B_INTERRUPT;
00236
00237                } else {
00238
00239                    TIMER2_DISABLE_COM_CHANNEL_B_INTERRUPT;
00240
00241                }
00242                break;
00243            }
00244        }
00245
00246 }
00247
00248
00249
00250 void core::TimerCounter2::enableOverflowInterrupt(const uint8_t a_enable)
00251 {
00252
00253     if (a_enable) {
00254
00255         TIMER2_ENABLE_OVERFLOW_INTERRUPT;
00256
00257     } else {
00258
00259         TIMER2_DISABLE_OVERFLOW_INTERRUPT;
00260     }
00261
00262 }
```

7.77 TimerCounter2.h File Reference

```
#include "TimerCounter.h"
```

```
#include "ha_base.h"
```
Include dependency graph for TimerCounter2.h:

This graph shows which files directly or indirectly include this file:

Classes

- class core::TimerCounter2

Namespaces

- core

7.78 TimerCounter2.h

```
00001
00039
00268 #ifndef TIMER_COUNTER2_H
00269 #define TIMER_COUNTER2_H
00270 #include "TimerCounter.h"
00271 #include "ha_base.h"
00272
00273
00274
00275 namespace core
00276 {
00277
```

```
00278
00279 class TimerCounter2 : public TimerCounter
00280 {
00281
00282 public:
00283
00284     static TimerCounter2& getInstance(const channel &ar_channel = channel::A,
00285                                       const operationMode &ar_operationMode = operationMode::normal,
00286                                       const clockSource &ar_clockSource= clockSource::noClock,
00287                                       const compareOutputMode& ar_compareOutputMode =
      compareOutputMode::normal);
00288
00289     void selectOperationMode(const operationMode &ar_operationMode) override;
00290
00291     void start() override;
00292
00293     void stop() override;
00294
00295     void selectClockSource(const clockSource &ar_clockSource) override;
00296
00297     void selectCompareOutputMode(const channel &ar_channel, const compareOutputMode
      &ar_compareOutputMode) override;
00298
00299     void setCounter(const uint16_t &ar_dataBuffer) override;
00300
00301     uint16_t getCounter() const override;
00302
00303     void setOutputCompareRegister(const channel &ar_channel, const uint16_t &ar_dataBuffer) override;
00304
00305     uint16_t getOutputCompareRegister(const channel &ar_channel) const override;
00306
00307     void enableOutputCompareMatchInterrupt(const channel &ar_channel, const uint8_t a_enable)
      override;
00308
00309     void enableOverflowInterrupt(const uint8_t a_enable) override;
00310
00311     uint16_t getClockPrescaler() override;
00312
00313     static void outputCompareMatchAServiceRoutine() __asm__(STR(TIMER2_COM_CHANNEL_A_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
00314
00315     static void outputCompareMatchBServiceRoutine() __asm__(STR(TIMER2_COM_CHANNEL_B_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
00316
00317     static void overflowServiceRoutine() __asm__(STR(TIMER2_OVERFLOW_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
00318
00319 protected:
00320
00321 private:
00322
00323     TimerCounter2(const channel &ar_channel,
00324                   const operationMode &ar_operationMode,
00325                   const clockSource &ar_clockSource,
00326                   const compareOutputMode& ar_compareOutputMode);
00327
00328     ~TimerCounter2();
00329
00332     TimerCounter2(const TimerCounter2&);
00333
00336     const TimerCounter2& operator=(const TimerCounter2&);
00337
00338     uint16_t m_clockPrescaler;
00339
00340     uint8_t m_clockSource;
00341
00342 };
00343
00344 }
00345
00346
00347 #endif
```

7.79 USART0.cpp File Reference

```
#include "USART0.h"
#include "MCU.h"
#include <string.h>
```

Include dependency graph for USART0.cpp:

7.80 USART0.cpp

```
00001 #include "USART0.h"
00002 #include "MCU.h"
00003 #include <string.h>
00004
00005 volatile uint8_t io::USART0::m_status = 0;
00006 const uint8_t* io::USART0::mp_data2Send = nullptr;
00007 uint8_t* io::USART0::mp_data2Receive = nullptr;
00008 uint16_t io::USART0::m_sizeData2Send = 0;
00009 uint16_t io::USART0::m_sizeData2Receive = 0;
00010 volatile uint16_t io::USART0::m_numberBytesReceived = 0;
00011 volatile uint16_t io::USART0::m_numberBytesSent = 0;
00012 volatile uint8_t io::USART0::m_ready2Send = 1;
00013
00014
00015
00016
00017 io::USART0& io::USART0::getInstance(const transmissionMode& ar_transMode,
00018                               const communicationMode& ar_comMode,
00019                               const frameSize& ar_frameSize,
00020                               const stopBit& ar_stopBit,
00021                               const parityMode& ar_parityMode)
00022 {
00023     static USART0 l_instance(ar_transMode,
00024                              ar_comMode,
00025                              ar_frameSize,
00026                              ar_stopBit,
00027                              ar_parityMode);
00028
00029     return l_instance;
00030 }
00031
00032
00033
00034 io::USART0::USART0(const transmissionMode& ar_transMode,
00035                    const communicationMode& ar_comMode,
00036                    const frameSize& ar_frameSize,
00037                    const stopBit& ar_stopBit,
00038                    const parityMode& ar_parityMode)
00039
00040 {
00041     core::MCU::enableUSART0(1);
00042     setBaudRate();
00043     setTransmissionMode(ar_transMode);
00044     setCommunicationMode(ar_comMode);
00045     setParityMode(ar_parityMode);
00046     setFrameSize(ar_frameSize);
00047     setStopBit(ar_stopBit);
00048     sei();
00049     enableReceiveCompleteInterrupt(1);
00050 }
00051
00052 io::USART0::~USART0()
00053 {
00054
00055 }
00056
00057 void io::USART0::setBaudRate()
```

```
00058 {
00059     USART0_SET_BAUDRATE_HIGH_REGISTER;
00060     USART0_SET_BAUDRATE_LOW_REGISTER;
00061
00062 }
00063
00064 void io::USART0::setTransmissionMode(const transmissionMode& ar_transMode)
00065 {
00066     switch (ar_transMode)
00067     {
00068         case transmissionMode::async:
00069         {
00070             USART0_ENABLE_ASYNC_TRANSMISSION_MODE;
00071             break;
00072         }
00073         case transmissionMode::sync:
00074         {
00075             USART0_DISABLE_DOUBLE_SPEED_MODE;
00076             USART0_ENABLE_SYNC_TRANSMISSION_MODE;
00077             break;
00078         }
00079     case transmissionMode::masterSPI:
00080         {
00081             USART0_ENABLE_MASTER_SPI_MODE;
00082             break;
00083         }
00084     }
00085
00086
00087 }
00088
00089 void io::USART0::setCommunicationMode(const communicationMode &ar_comMode)
00090 {
00091     switch (ar_comMode)
00092     {
00093         case communicationMode::duplex:
00094         {
00095             USART0_ENABLE_TRANSMITTER;
00096             USART0_ENABLE_RECEIVER;
00097             break;
00098         }
00099         case communicationMode::receive:
00100         {
00101             USART0_ENABLE_RECEIVER;
00102             USART0_DISABLE_TRANSMITTER;
00103             break;
00104         }
00105         case communicationMode::transmit:
00106         {
00107             USART0_ENABLE_TRANSMITTER;
00108             USART0_DISABLE_RECEIVER;
00109             break;
00110         }
00111     }
00112
00113 }
00114
00115 void io::USART0::setParityMode(const parityMode& ar_parityMode)
00116 {
00117     switch (ar_parityMode)
00118     {
00119         case parityMode::noParity:
00120         {
00121             USART0_DISABLE_PARITY_MODE;
00122             break;
00123         }
00124         case parityMode::evenParity:
00125         {
00126             USART0_ENABLE_EVEN_PARITY_MODE;
00127             break;
00128         }
00129         case parityMode::oddParity:
00130         {
00131             USART0_ENABLE_ODD_PARITY_MODE;
00132             break;
00133         }
00134     }
00135
00136 }
00137
00138 void io::USART0::setFrameSize(const frameSize& ar_frameSize)
00139 {
00140     switch (ar_frameSize)
00141     {
00142         case frameSize::eightBits:
00143         {
00144             USART0_SET_8BIT_FRAME_SIZE;
```

```
00145                break;
00146            }
00147        case frameSize::sevenBits:
00148        {
00149            USART0_SET_7BIT_FRAME_SIZE;
00150            break;
00151        }
00152        case frameSize::sixBits:
00153        {
00154            USART0_SET_6BIT_FRAME_SIZE;
00155            break;
00156        }
00157        case frameSize::fiveBits:
00158        {
00159            USART0_SET_5BIT_FRAME_SIZE;
00160            break;
00161        }
00162        case frameSize::neineBits:
00163        {
00164            USART0_SET_9BIT_FRAME_SIZE;
00165            break;
00166        }
00167    }
00168
00169 }
00170 void io::USART0::setStopBit(const stopBit& ar_stopBit)
00171 {
00172    switch (ar_stopBit)
00173    {
00174        case stopBit::oneStopBit:
00175        {
00176            USART0_SET_ONE_STOP_BIT;
00177            break;
00178        }
00179        case stopBit::twoStopBits:
00180        {
00181            USART0_SET_TWO_STOP_BITS;
00182            break;
00183        }
00184    }
00185
00186 }
00187
00188
00189 uint8_t io::USART0::frameError()
00190 {
00191    return (m_status & (1 << USART0_FRAME_ERROR));
00192
00193 }
00194
00195 uint8_t io::USART0::dataOverrun()
00196 {
00197    return (m_status & (1 << USART0_DATA_OVERRUN));
00198
00199 }
00200
00201 uint8_t io::USART0::parityError()
00202 {
00203    return (m_status & (1 << USART0_PARITY_ERROR));
00204
00205 }
00206
00207 void io::USART0::sendFrames(const uint8_t* ap_dataBuffer, const uint8_t a_size)
00208 {
00209    while (!ready2Send()){};
00210    m_sizeData2Send = a_size;
00211    mp_data2Send = ap_dataBuffer;
00212    enableDataRegisterEmptyInterrupt(1);
00213 }
00214
00215
00216 void io::USART0::sendString(const char* ap_string)
00217 {
00218    while (!ready2Send()){};
00219    m_sizeData2Send = strlen(ap_string);
00220    mp_data2Send = reinterpret_cast<const uint8_t*>(ap_string);
00221    enableDataRegisterEmptyInterrupt(1);
00222
00223 }
00224
00225
00226 void io::USART0::sendByte(const uint8_t &ar_byte)
00227 {
00228    static uint8_t l_byte2Send[3];
00229    l_byte2Send[0] = '0' + (ar_byte / 100);
00230    l_byte2Send[1] = '0' + ((ar_byte / 10) % 10);
00231    l_byte2Send[2] = '0' + (ar_byte % 10);
```

```
00232
00233      while (!ready2Send()){};
00234      m_sizeData2Send = 3;
00235      mp_data2Send = l_byte2Send;
00236      enableDataRegisterEmptyInterrupt(1);
00237
00238 }
00239 void io::USART0::sendLong(const uint32_t &ar_long)
00240 {
00241      static uint8_t l_word2Send[10];
00242      l_word2Send[0] = '0' + (ar_long / 1000000000);
00243      l_word2Send[1] = '0' + ((ar_long / 100000000) % 10);
00244      l_word2Send[2] = '0' + ((ar_long /  10000000) % 10);
00245      l_word2Send[3] = '0' + ((ar_long /   1000000) % 10);
00246      l_word2Send[4] = '0' + ((ar_long /    100000) % 10);
00247      l_word2Send[5] = '0' + ((ar_long /     10000) % 10);
00248      l_word2Send[6] = '0' + ((ar_long /      1000) % 10);
00249      l_word2Send[7] = '0' + ((ar_long /       100) % 10);
00250      l_word2Send[8] = '0' + ((ar_long /        10) % 10);
00251      l_word2Send[9] = '0' + (ar_long % 10);
00252
00253      while (!ready2Send()){};
00254      m_sizeData2Send = 10;
00255      mp_data2Send = l_word2Send;
00256      enableDataRegisterEmptyInterrupt(1);
00257
00258 }
00259 void io::USART0::sendWord(const uint16_t &ar_word)
00260 {
00261      static uint8_t l_word2Send[5];
00262      l_word2Send[0] = '0' + (ar_word / 10000);
00263      l_word2Send[1] = '0' + ((ar_word / 1000) % 10);
00264      l_word2Send[2] = '0' + ((ar_word /  100) % 10);
00265      l_word2Send[3] = '0' + ((ar_word /   10) % 10);
00266      l_word2Send[4] = '0' + (ar_word %    10);
00267
00268      while (!ready2Send()){};
00269      m_sizeData2Send = 5;
00270      mp_data2Send = l_word2Send;
00271      enableDataRegisterEmptyInterrupt(1);
00272
00273 }
00274
00275 void io::USART0::sendChar(const uint8_t &ar_char)
00276 {
00277      while (!ready2Send()){};
00278      m_sizeData2Send = 1;
00279      mp_data2Send = &ar_char;
00280      enableDataRegisterEmptyInterrupt(1);
00281
00282 }
00283
00284 void io::USART0::receiveChar(uint8_t &ar_char)
00285 {
00286      m_sizeData2Receive = 1;
00287      mp_data2Receive = &ar_char;
00288 }
00289
00290
00291 void io::USART0::receiveFrames(uint8_t *ap_dataBuffer, const uint8_t a_size)
00292 {
00293      m_sizeData2Receive = a_size;
00294      mp_data2Receive = ap_dataBuffer;
00295
00296
00297
00298 }
00299
00300 void io::USART0::receiveString(const char *ap_string)
00301 {
00302
00303 }
00304
00305
00306 void io::USART0::receiveCompleteServiceRoutine()
00307 {
00308      static volatile uint8_t *lp_dataReceived = mp_data2Receive;
00309      static uint16_t l_dataSize = m_sizeData2Receive;
00310
00311      m_status = USART0_CONTROL_STATUS_REGISTER;
00312
00313
00314
00315          if (l_dataSize)
00316          {
00317
00318              *lp_dataReceived++ = USART0_DATA_REGISTER;
```

```
00319                l_dataSize--;
00320                m_numberBytesReceived++;
00321
00322            }
00323          else
00324          {
00325                l_dataSize = m_sizeData2Receive;
00326                lp_dataReceived = mp_data2Receive;
00327          }
00328
00329 }
00330
00331 void io::USART0::dataRegisterEmptyServiceRoutine()
00332 {
00333
00334      if (m_sizeData2Send)
00335      {
00336          m_ready2Send = 0;
00337          USART0_DATA_REGISTER = *mp_data2Send++;
00338          m_sizeData2Send--;
00339          m_numberBytesSent++;
00340
00341      }
00342      else
00343      {
00344          enableDataRegisterEmptyInterrupt(0);
00345          m_numberBytesSent = 0;
00346          m_ready2Send = 1;
00347
00348      }
00349
00350 }
00351
00352
00353 void io::USART0::enableTransmitCompleteInterrupt(const uint8_t ar_enable)
00354 {
00355      if (ar_enable) {
00356          USART0_ENABLE_TRANSMIT_COMPLETE_INTERRUPT;
00357      } else {
00358          USART0_DISABLE_TRANSMIT_COMPLETE_INTERRUPT;
00359      }
00360
00361 }
00362
00363 void io::USART0::enableReceiveCompleteInterrupt(const uint8_t ar_enable)
00364 {
00365      if (ar_enable) {
00366          USART0_ENABLE_RECEIVE_COMPLETE_INTERRUPT;
00367
00368      } else {
00369          USART0_DISABLE_RECEIVE_COMPLETE_INTERRUPT;
00370      }
00371
00372 }
00373
00374 void io::USART0::enableDataRegisterEmptyInterrupt(const uint8_t ar_enable)
00375 {
00376      if (ar_enable) {
00377          USART0_ENABLE_DATA_REGISTER_EMPTY_INTERRUPT;
00378
00379      } else {
00380          USART0_DISABLE_DATA_REGISTER_EMPTY_INTERRUPT;
00381      }
00382
00383 }
00384
00385 void io::USART0::transmitCompleteServiceRoutine()
00386 {
00387
00388 }
00389
00390 uint16_t io::USART0::getNumberBytesSent()
00391 {
00392      return m_numberBytesSent;
00393 }
00394
00395 uint16_t io::USART0::getNumberBytesReceived()
00396 {
00397      return m_numberBytesReceived;
00398 }
00399
00400 void io::USART0::resetNumberBytesReceived()
00401 {
00402      m_numberBytesReceived = 0;
00403 }
00404
00405 uint8_t io::USART0::ready2Send()
```

```
00406 {
00407     return m_ready2Send;
00408
00409 }
00410
```

7.81 USART0.h File Reference

Header file of the USART0 class.

```
#include "ha_base.h"
```
Include dependency graph for USART0.h:

This graph shows which files directly or indirectly include this file:

Classes

- class io::USART0

Namespaces

- io

Enumerations

- enum io::transmissionMode : uint8_t { io::transmissionMode::async =0, io::transmissionMode::sync, io::transmissionMode::masterSPI }
- enum io::communicationMode : uint8_t { io::communicationMode::duplex =0, io::communicationMode::transmit, io::communicationMode::receive }
- enum io::parityMode : uint8_t { io::parityMode::noParity =0, io::parityMode::evenParity, io::parityMode::oddParity }
- enum io::frameSize : uint8_t { io::frameSize::eightBits =0, io::frameSize::fiveBits, io::frameSize::sixBits, io::frameSize::sevenBits, io::frameSize::neineBits }
- enum io::stopBit : uint8_t { io::stopBit::oneStopBit =0, io::stopBit::twoStopBits }

7.81.1 Detailed Description

Header file of the USART0 class.

Basic class for IO abstraction of the Universal Synchronous and Asynchronous serial Receiver and Transmitter serial communication device.

Usage example (loopback v1):

#include "USART0.h"

#define BUFFER_SIZE 1

int main(void) {

Init uint8_t l_data[BUFFER_SIZE];

io::USART0 &myUSART0 = io::USART0::getInstance();

myUSART0.sendString("Hello World!\r\n");

---— Event loop ---— // while (1) {

```
myUSART0.receiveFrames(l_data,BUFFER_SIZE);
if (myUSART0.getNumberBytesReceived()==BUFFER_SIZE)
{
        myUSART0.sendFrames(l_data,BUFFER_SIZE);
        myUSART0.resetNumberBytesReceived();
}
```

} return 0; }

Usage example (loopback v2):

#include "USART0.h"

int main(void) {

Init uint8_t l_data;

io::USART0 &myUSART0 = io::USART0::getInstance();

myUSART0.sendString("Hello World!\r\n");

---— Event loop ---— // while (1) {

```
myUSART0.receiveChar(l_data);
if (myUSART0.getNumberBytesReceived()==1)
{
    myUSART0.sendChar(l_data);
    myUSART0.resetNumberBytesReceived();
}
```

} return 0; }

Author

> Farid Oubbati (https://github.com/faroub)

Date

> March 2020

Definition in file USART0.h.

7.82 USART0.h

```
00001
00071 #ifndef USART_H
00072 #define USART_H
00073 #include "ha_base.h"
00074
00075 // TODO: add aditional function to send data
00076 // TODO: add a fuse programmer
00077 namespace io
00078 {
00079 enum class transmissionMode : uint8_t {
00080     async=0,
00081     sync,
00082     masterSPI
00083 };
00084
00085 enum class communicationMode : uint8_t {
00086     duplex=0,
00087     transmit,
00088     receive,
00090 };
00091
00092 enum class parityMode : uint8_t {
00093     noParity=0,
00094     evenParity,
00095     oddParity
00096 };
00097
00098 enum class frameSize : uint8_t {
00099     eightBits=0,
00100     fiveBits,
00101     sixBits,
00102     sevenBits,
00103     neineBits
00104 };
00105
00106 enum class stopBit : uint8_t{
00107     oneStopBit=0,
00108     twoStopBits
00109 };
00110
00111
00112 class USART0
00113 {
00114
00115 public:
00116
00117
00126     static USART0& getInstance(const transmissionMode& ar_transMode = transmissionMode::async,
00127                                const communicationMode& ar_comMode = communicationMode::duplex,
00128                                const frameSize& ar_frameSize = frameSize::eightBits,
00129                                const stopBit& ar_stopBit = stopBit::oneStopBit,
00130                                const parityMode& ar_parityMode = parityMode::noParity);
00134     void setBaudRate();
00139     void setTransmissionMode(const transmissionMode& ar_transMode);
00144     void setCommunicationMode(const communicationMode& ar_comMode);
00149     void setParityMode(const parityMode& ar_parityMode);
00154     void setFrameSize(const frameSize& ar_frameSize);
00159     void setStopBit(const stopBit& ar_stopBit);
00165     void sendFrames(const uint8_t *ap_dataBuffer, const uint8_t a_size);
00170     void sendString(const char *ap_string);
00175     void receiveString(const char *ap_string);
00180     void sendChar(const uint8_t &ar_char);
00185     void sendByte(const uint8_t &ar_byte);
00186
00191     void sendWord(const uint16_t &ar_word);
00196     void sendLong(const uint32_t &ar_long);
```

```
00197
00202     void receiveChar(uint8_t &ar_char);
00203
00210     void receiveFrames(uint8_t *ap_dataBuffer, const uint8_t a_size);
00215     void enableTransmitCompleteInterrupt(const uint8_t ar_enable);
00220     void enableReceiveCompleteInterrupt(const uint8_t ar_enable);
00225     static void enableDataRegisterEmptyInterrupt(const uint8_t ar_enable);
00228     uint8_t frameError();
00231     uint8_t dataOverrun();
00234     uint8_t parityError();
00237     uint16_t getNumberBytesReceived();
00240     uint16_t getNumberBytesSent();
00243     uint8_t ready2Send();
00246     void resetNumberBytesReceived();
00249     static void receiveCompleteServiceRoutine() __asm__(STR(USART0_RECEIVE_COMPLETE_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
00252     static void dataRegisterEmptyServiceRoutine() __asm__(STR(USART0_DATA_REGISTER_EMPTY_INTERRUPT))
      __attribute__((__signal__,__used__, __externally_visible__));
00255     static void transmitCompleteServiceRoutine() __asm__(STR(USART0_TRANSMIT_COMPLETE_INTERRUPT))
      __attribute__((__signal__, __used__, __externally_visible__));
00256
00257
00258 protected:
00259
00260
00261
00262
00263 private:
00272     USART0(const transmissionMode& ar_transMode,
00273            const communicationMode& ar_comMode,
00274            const frameSize& ar_frameSize,
00275            const stopBit& ar_stopBit,
00276            const parityMode& ar_parityMode);
00277
00280     ~USART0();
00281
00284     USART0(const USART0&);
00285
00288     const USART0& operator=(const USART0&);
00289
00290     static volatile uint8_t m_status;
00292     static const uint8_t *mp_data2Send;
00294     static uint8_t *mp_data2Receive;
00296     static uint16_t m_sizeData2Send;
00298     static uint16_t m_sizeData2Receive;
00300     static volatile uint16_t m_numberBytesReceived;
00302     static volatile uint16_t m_numberBytesSent;
00304     static volatile uint8_t m_ready2Send;
00307 };
00308
00309
00310
00311 }
00312
00313
00314
00315
00316
00317
00318
00319
00320
00321
00322
00323 #endif
```

7.83 utils_m328p.cpp File Reference

```
#include "utils_m328p.h"
```

Include dependency graph for utils_m328p.cpp:

7.84   utils_m328p.cpp

```
00001 #include "utils_m328p.h"
00002
00003 long utils::map(long x, long in_min, long in_max, long out_min, long out_max)
00004 {
00005   return (x - in_min) * (out_max - out_min) / (in_max - in_min) + out_min;
00006 }
```

7.85   utils_m328p.h File Reference

This graph shows which files directly or indirectly include this file:

Namespaces

- utils

Functions

- long utils::map (long x, long in_min, long in_max, long out_min, long out_max)

7.86 utils_m328p.h

```
00001 #ifndef UTILSM329P_H
00002 #define UTILSM329P_H
00003 namespace utils
00004 {
00005
00006
00007 // delay functions
00008
00009
00010
00011 // multiplication / division operations bit-shift devide multiply
00012
00013
00014 // clock division (set prescaler)
00015
00016 // clock power saving through macros
00017
00018
00019 // mapping values
00020
00021 long map(long x, long in_min, long in_max, long out_min, long out_max);
00022
00023
00024 }
00025 #endif
```

7.87 WatchdogTimer.cpp File Reference

```
#include "WatchdogTimer.h"
```
Include dependency graph for WatchdogTimer.cpp:

7.88 WatchdogTimer.cpp

```
00001 #include "WatchdogTimer.h"
00002
00003
00004 core::WatchdogTimer& core::WatchdogTimer::getInstance()
00005 {
00006     static WatchdogTimer l_instance;
00007     return l_instance;
00008
00009 }
00010
00011 core::WatchdogTimer::WatchdogTimer()
00012 {
00013     sei();
00014     stop();
00015 }
00016
00017 core::WatchdogTimer::~WatchdogTimer()
00018 {
00019
```

```
00020 }
00021
00022 void core::WatchdogTimer::selectTimeOut(const timeOut &ar_timeOut)
00023 {
00024     m_timeOut = static_cast<uint8_t>(ar_timeOut);
00025     m_timeOut = static_cast<uint8_t>((m_timeOut & 7) | ((m_timeOut & 8) << 2 ));
00026     cli();
00027     wdt_reset();
00028     WATCHDOG_SELECT_TIMEOUT(m_timeOut);
00029     sei();
00030
00031 }
00032
00033 void core::WatchdogTimer::reset()
00034 {
00035     wdt_reset();
00036
00037 }
00038
00039 void core::WatchdogTimer::start(const operationMode &ar_operationMode)
00040 {
00041     m_operationMode = static_cast<uint8_t>(ar_operationMode);
00042     m_operationMode = static_cast<uint8_t>(((m_operationMode & 1) << 6) | ((m_operationMode & 2) << 3
     ));
00043     cli();
00044     wdt_reset();
00045     WATCHDOG_START(m_operationMode,m_timeOut);
00046     sei();
00047
00048 }
00049
00050 void core::WatchdogTimer::start(const operationMode &ar_operationMode, const timeOut &ar_timeOut)
00051 {
00052     m_timeOut = static_cast<uint8_t>(ar_timeOut);
00053     m_timeOut = static_cast<uint8_t>((m_timeOut & 7) | ((m_timeOut & 8) << 2 ));
00054     m_operationMode = static_cast<uint8_t>(ar_operationMode);
00055     m_operationMode = static_cast<uint8_t>(((m_operationMode & 1) << 6) | ((m_operationMode & 2) << 3
     ));
00056     cli();
00057     wdt_reset();
00058     WATCHDOG_START(m_operationMode,m_timeOut);
00059     sei();
00060
00061 }
00062
00063 void core::WatchdogTimer::stop()
00064 {
00065     cli();
00066     wdt_reset();
00067     WATCHDOG_STOP;
00068     sei();
00069
00070 }
00071
```

7.89 WatchdogTimer.h File Reference

Header file of the WatchdogTimer class.

```
#include "ha_base.h"
```
Include dependency graph for WatchdogTimer.h:

This graph shows which files directly or indirectly include this file:

Classes

- class core::WatchdogTimer

Namespaces

- core

Enumerations

- enum core::timeOut : uint8_t {
  core::timeOut::to_16ms =0, core::timeOut::to_32ms, core::timeOut::to_64ms, core::timeOut::to_125ms,
  core::timeOut::to_250ms, core::timeOut::to_500ms, core::timeOut::to_1s, core::timeOut::to_2s,
  core::timeOut::to_4s, core::timeOut::to_8s }
- enum core::operationMode : uint8_t {
  core::operationMode::normal =0, core::operationMode::PWM_PC, core::operationMode::PWM_PC_8bit,
  core::operationMode::PWM_PC_9bit,
  core::operationMode::PWM_PC_10bit, core::operationMode::PWM_PFC_ICR, core::operationMode::PWM_PFC_OCR,
  core::operationMode::PWM_PC_ICR,
  core::operationMode::PWM_PC_OCR, core::operationMode::fast_PWM, core::operationMode::fast_PWM_8bit,
  core::operationMode::fast_PWM_9bit,
  core::operationMode::fast_PWM_10bit, core::operationMode::fast_PWM_ICR, core::operationMode::fast_PWM_OCR,
  core::operationMode::CTC_OCR,
  core::operationMode::CTC_ICR, core::operationMode::interrupt =1, core::operationMode::reset, core::operationMode::interrupt_
  }

7.89.1 Detailed Description

Header file of the WatchdogTimer class.

Basic class abstraction of the WatchdogTimer peripheral

Usage example (test):

#include "WatchdogTimer.h" #include "Led.h" instantiate a Led object extern component::Led Led; component::Led
Led(io::Pin(1,io::PortB)); extern component::Led LedStart; component::Led LedStart(io::Pin(2,io::PortB));

int main(void) {

Init instantiate a Watchdog object core::WatchdogTimer &myWatchdog = core::WatchdogTimer::getInstance(); my↵
Watchdog.selectTimeOut(core::timeOut::to_8s); LedStart.on(); _delay_ms(5000); LedStart.off(); myWatchdog.↵
start(core::operationMode::reset); --——— Event loop --——— // while (1) {

```
Led.on();
_delay_ms(1000);
Led.off();
_delay_ms(1000);
```

} return 0; }

void [core::WatchdogTimer::timeOutServiceRoutine()](#) { for (uint8_t i=0;i<10;i++) { Led.on(); _delay_ms(100); Led.↩
off(); _delay_ms(100);

}

}

Author

    Farid Oubbati (https://github.com/faroub)

Date

    March 2020

Definition in file [WatchdogTimer.h](#).

7.90 WatchdogTimer.h

```
00001
00057 #ifndef WATCHDOG_TIMER_H
00058 #define WATCHDOG_TIMER_H
00059 #include "ha_base.h"
00060
00061
00062
00063 namespace core
00064 {
00065 enum class timeOut : uint8_t {
00066     to_16ms=0,
00067     to_32ms,
00068     to_64ms,
00069     to_125ms,
00070     to_250ms,
00071     to_500ms,
00072     to_1s,
00073     to_2s,
00074     to_4s,
00075     to_8s,
00076 };
00077
00078 enum class operationMode : uint8_t {
00079     interrupt=1,
00080     reset,
00081     interrupt_reset,
00082 };
00083
00084 class WatchdogTimer
00085 {
00086
00087 public:
00088
00089     static WatchdogTimer& getInstance();
00090
00091     void selectTimeOut(const timeOut &ar_timeOut);
00092
00093     void reset();
00094
00095     void start(const operationMode &ar_operationMode);
00096
00097     void start(const operationMode &ar_operationMode, const timeOut &ar_timeOut);
00098
00099
```

```
00100     void stop();
00101
00102     static void timeOutServiceRoutine() __asm__(STR(WATCHDOG_TIMEOUT_INTERRUPT))
       __attribute__((__signal__, __used__, __externally_visible__));
00103
00104
00105 protected:
00106
00107 private:
00108
00109     WatchdogTimer();
00110
00113     ~WatchdogTimer();
00114
00117     WatchdogTimer(const WatchdogTimer&);
00118
00121     const WatchdogTimer& operator=(const WatchdogTimer&);
00122
00123     uint8_t m_timeOut;
00124
00125     uint8_t m_operationMode;
00126
00127 };
00128
00129 }
00130
00131
00132 #endif
```

Index