


Rod Cutting Problem

Given a rod of length n inches and a table of prices p_i for $i = 1, 2, \dots, n$, determine the maximum revenue r_n obtainable by cutting up the rod and selling the pieces.

length i	1	2	3	4	5	6	7	8	9	10
price p_i	1	5	8	9	10	17	17	20	24	30

Rod Cutting Problem


Given a rod of length n inches and a table of prices p_i for $i = 1, 2, \dots, n$, determine the maximum revenue r_n obtainable by cutting up the rod and selling the pieces.



Brute Force: How many different ways to cut the rod?

Rod Cutting Problem

The 8 possible ways of cutting up a rod of length 4. Above each piece is the value of that piece.



Brute Force: 2^{n-1} different ways to cut the rod.

Rod Cutting example

CUT-ROD(p, n)

1 **if** $n == 0$

2 **return** 0

3 $q = -\infty$

4 **for** $i = 1$ **to** n

5 $q = \max(q, p[i] + \text{CUT-ROD}(p, n - i))$

6 **return** q

Rod Cutting example

MEMOIZED-CUT-ROD-AUX(p, n, r)

```
1  if  $r[n] \geq 0$ 
2      return  $r[n]$ 
3  if  $n == 0$ 
4       $q = 0$ 
5  else  $q = -\infty$ 
6      for  $i = 1$  to  $n$ 
7           $q = \max(q, p[i] + \text{MEMOIZED-CUT-ROD-AUX}(p, n - i, r))$ 
8   $r[n] = q$ 
9  return  $q$ 
```

Rod Cutting example

BOTTOM-UP-CUT-ROD(p, n)

```
1  let  $r[0..n]$  be a new array
2   $r[0] = 0$ 
3  for  $j = 1$  to  $n$ 
4       $q = -\infty$ 
5      for  $i = 1$  to  $j$ 
6           $q = \max(q, p[i] + r[j - i])$ 
7       $r[j] = q$ 
8  return  $r[n]$ 
```

Reference Reading

Algorithm Design by Tardos et. al. 2006

Chapter 6: §6.1 - §6.2 Weighted Interval Scheduling

Introductions to Algorithms, 3rd Edition, by Cormen, et. al.

Chapter 5: §5.1 Rod cutting problem

Algorithms by Dasgupta, Papadimitriou, and Vazirani

Chapter 6: §6.3 Edit distance