1.
2. [tech](#)
3. archlinux chrome　—

archlinux 上用 **chrome** 实现 ~~透明计算~~ 远程登录

2015 02 13 ( )

- [_](#)
- [_](#)

[linux](#) [archlinux](#) [arch](#) [chrome](#) [remote](#) [desktop](#) 🔄 Loading...

- [Chrome Remote Desktop　　](#)
- [Archlinux　　　](#)
- [Linux　　Chrome　　Windows/ OS X　　](#)
- [Bonus　　　](#)

[__](#)　　　　　　　　[____](#)

Xorg　　　　　　VNC　　NX　　RDP　　　　　　ssh X forwarding
不太易用　　　　ip　　　　NAT

　　　　　　chrome-remote-desktop archlinux　　　　　　　　Google
　　XMPP　　　　NAT　　　　　　　　　　　　Chrome Remote
Desktop

Chrome Remote Desktop

Chrome Remote Desktop 的客户端

Chrome   Google   remote-desktop
        Windows/OS X   Linux

Archlinux 上设置远程登录的服务器

Windows   OS X   Chrome   Linux
    _   debian   Ubuntu 12.10

chrome-remote-desktop   Windows/OS X   Remote
Desktop Host Controller archlinux   [archlinuxcn]   AUR

$ pacman -Ss chrome-remote-desktop
archlinuxcn/**chrome-remote-desktop** 40.0.2214.44-1
Allows you to securely access your computer over the Internet through Chrome.

groupadd   ID "chrome-remote-desktop"

Please create ~/.config/chrome-remote-desktop folder
manually, if it doesn't exist, or else you can't use CRD. The
needed files are created by the Chrome app, inside the
chrome-remote-desktop folder, after Enabling Remote
Connections. To {enable,start} the service use systemctl --
user {enable,start} chrome-remote-desktop

You may need to create a ~/.chrome-remote-desktop-
session file with commands to start your session

Go to https://support.google.com/chrome/answer/1649523
for more information.

AUR   Google   chrome-remote-desktop
chrome remote desktop

```
$ /opt/google/chrome-remote-desktop/chrome-remote-desktop --add-user
```

~/.config/chrome-remote-desktop   chrome   host#.json

```
$ mkdir ~/.config/chrome-remote-desktop
```

shell   ~/.chrome-remote-desktop-session   .xinitrc
WM/DE   xfce4

```
$ cat ~/.chrome-remote-desktop-session
#!/bin/bash
startxfce4
$ chmod 755 .chrome-remote-desktop-session
```

Chrome   Chrome Remote Desktop

Chrome Remote Desktop

Archlinux   chromium   aur/google-chrome
40.0.2214.111   Chrome Web Store   Chrome Remote Desktop
41.0.2272.41   Chrome   Remoting   API
Chrome   google-chrome-dev   chrome

32   Linux   Chrome Remote Desktop   Host   <u>bug</u>

PIN   Google   hostname

~/.config/chrome-remote-desktop

```
$ ls .config/chrome-remote-desktop
chrome-profile host#8cfe7ecfd6bb17955c1ea22f77d0d800.json pulseaudio#8cfe7ecfd6
```

systemd   systemctl --user enable

$ systemctl --user start chrome-remote-desktop.service

chrome-remote-desktop   Xorg

htop   chrome-remote-desktop   Xorg

Remote Desktop   Xorg

XFCE4

Linux 版本的 Chrome远程桌面 和 Windows/ OS X 上的区别

Linux   X   X

Chrome   Linux Host Controller   beta   Ubuntu 12.04 12.10 14.04   [Bug](#)

Bonus： 手机远程登录

Chrome   App

Chrome   Chrome   Windows / OS X / Linux

Chrome   Android   [Chrome   App](#)   App

[换到 farseerfc.me 域名](#)

Loading...

[从天气预报谈谈日本的学术氛围](#)

[关于 farseerfc](#)

[标签云](#)

- [termcap](#) [1]
- [tty](#) [1]
- [ugh](#) [1]
- [pelican](#) [4]
- [domain](#) [1]
- [icse](#) [2]
- [travis](#) [1]
- [unix](#) [1]
- [paper](#) [1]
- [gnome3](#) [1]
- [zz](#) [1]
- [linux](#) [4]
- [japan](#) [1]

- [remote](#) [1]
- [stdio](#) [1]
- [bootstrap](#) [1]
- [will](#) [1]
- [travis-ci](#) [1]
- [terminfo](#) [1]
- [subsite](#) [1]
- [microsoft](#) [2]
- [software](#) [2]

GitHub仓库

Status updating...

[@farseerfc](#) on GitHub

最新微博

眞愛//@某亞瑟: 眞愛无误//@艾魯夫: 眞愛 //@S電音狂人兔基神:眞愛无误//@月刊少女Ku Ma君: 如果這都不算愛 //@发菜:印象里兩千多吧[思考] //@J岛AC妹子:如果這都不算愛

烂醉绅士 ：480的SSD啊。。。

今天 10:41 　　　　　　　　　　　　　　　　　　　　　　　　　転发 ｜ 评论

最新推文

目录