- _

archlinux 上用 chrome 实现 透明计算 远程登录

2015 02 13 ( )

- [_](#)
- [_](#)

[linux](#) [archlinux](#) [arch](#) [chrome](#) [remote](#) [desktop](#) Loading...

- [Chrome Remote Desktop](#)
- [Archlinux](#)
- [Linux   Chrome   Windows/ OS X](#)
- [Bonus](#)

[__](#)   [____](#)

Xorg   VNC   NX   RDP   ssh X forwarding
不太易用   ip   NAT

              chrome-remote-desktop   archlinux   Google
     XMPP   NAT   Chrome Remote
Desktop

Chrome Remote Desktop

Chrome Remote Desktop 的客户端

Chrome   Google   remote-desktop

Windows/OS X   Linux

Archlinux 上设置远程登录的服务器

Windows OS X Chrome   Linux

_   debian   Ubuntu 12.10

chrome-remote-desktop   Windows/OS X   Remote
Desktop Host Controller archlinux   [archlinuxcn]   AUR

$ pacman -Ss chrome-remote-desktop
archlinuxcn/**chrome-remote-desktop** 40.0.2214.44-1
Allows you to securely access your computer over the Internet through Chrome.

groupadd   ID "chrome-remote-desktop"

Please create ~/.config/chrome-remote-desktop folder
manually, if it doesn't exist, or else you can't use CRD. The
needed files are created by the Chrome app, inside the
chrome-remote-desktop folder, after Enabling Remote
Connections. To {enable,start} the service use systemctl --
user {enable,start} chrome-remote-desktop

You may need to create a ~/.chrome-remote-desktop-
session file with commands to start your session

Go to https://support.google.com/chrome/answer/1649523
for more information.

AUR   Google   chrome-remote-desktop
chrome remote desktop

```
$ /opt/google/chrome-remote-desktop/chrome-remote-desktop --add-user
```

~/.config/chrome-remote-desktop   chrome   host#.json

```
$ mkdir ~/.config/chrome-remote-desktop
```

shell   ~/.chrome-remote-desktop-session   .xinitrc
WM/DE   xfce4

```
$ cat ~/.chrome-remote-desktop-session
#!/bin/bash
startxfce4
$ chmod 755 .chrome-remote-desktop-session
```

Chrome   Chrome Remote Desktop

```

```

Chrome Remote Desktop

Archlinux   chromium   aur/google-chrome
40.0.2214.111   Chrome Web Store   Chrome Remote Desktop
41.0.2272.41   Chrome   Remoting   API
Chrome   google-chrome-dev   chrome

32   Linux   Chrome Remote Desktop   Host   bug

PIN   Google   hostname

```

```

~/.config/chrome-remote-desktop

```
$ ls .config/chrome-remote-desktop
chrome-profile host#8cfe7ecfd6bb17955c1ea22f77d0d800.json pulseaudio#8cfe7ecfd6
```

systemd   systemctl --user enable

$ systemctl --user start chrome-remote-desktop.service

chrome-remote-desktop   Xorg

```

```

htop   chrome-remote-desktop   Xorg

Remote Desktop   Xorg

```

```

XFCE4

Linux 版本的 Chrome远程桌面和 Windows/ OS X 上的区别

Linux   X   X

Chrome   Linux Host Controller   beta   Ubuntu 12.04
12.10 14.04   Bug

Bonus：手机远程登录

Chrome   App

```

```

Chrome   Chrome   Windows / OS X / Linux

Chrome   Android   Chrome   App   App

换到 farseerfc.me 域名

Loading...

从天气预报谈谈日本的学术氛围

关于 farseerfc

标签云

- [termcap](#) [1]
- [tty](#) [1]
- [ugh](#) [1]
- [pelican](#) [4]
- [domain](#) [1]
- [icse](#) [2]
- [travis](#) [1]
- [unix](#) [1]
- [paper](#) [1]
- [gnome3](#) [1]
- [zz](#) [1]
- [linux](#) [4]
- [japan](#) [1]

- kde5 [1]
- creationism [1]
- Java [2]
- academic [1]
- chrome [1]
- ruby [1]
- msr [1]
- desktop [1]
- python [4]
- archlinux [1]
- marry [1]
- template [1]
- you [1]
- cloudflare [1]
- plasma [1]
- acpi [1]
- css [1]
- mining [1]
- sjtu [1]
- repository [1]
- ncurses [1]
- material [2]
- yssy [1]
- oop [1]
- ubuntu [1]
- arch [1]
- pages [1]
- me [1]
- C++ [14]
- github [2]

- [remote](#) [1]
- [stdio](#) [1]
- [bootstrap](#) [1]
- [will](#) [1]
- [travis-ci](#) [1]
- [terminfo](#) [1]
- [subsite](#) [1]
- [microsoft](#) [2]
- [software](#) [2]

GitHub仓库

Status updating...

[@farseerfc](#) on GitHub

最新微博

farseerfc 海外 日本

➕ 加关注

崔永元加入了ETO降臨派綠色和平組織，柴静加入了ETO拯救派[doge]//@比尔盖子V：→_→//@飞雪之灵："……就像当时我的纪录片一出来，他们最后没得说了，就说你采访的不是主流科学家"崔永元你敢把数据来源明白放出来？敢把采访的单位和人跟柴静片尾放出的比比么？这样给自己贴金不嫌害臊？[挖鼻屎]

> 澎湃新闻 🔽 ：【崔永元谈柴静纪录片：《穹顶之下》唯一的作用就是启蒙作用】这部片子对于国家雾霾治理可以忽略不计。假如柴静拍了一个纪录片，让所有人都明白了雾霾的原因是什么，从而导致雾霾被彻底治理，那你说我们要那些部门干嘛用啊？崔永元直言，这部纪录片比自己的转基因纪录片拍得好。http://t.cn/RwYhBDB

最新推文

[Tweets by farseerfc]

目录