

# Appendix: CIS Controls v8 IG 3 Mapped Recommendations

| Recommendation |                                                                             | Set Correctly            |                                     |
|----------------|-----------------------------------------------------------------------------|--------------------------|-------------------------------------|
|                |                                                                             | Yes                      | No                                  |
| 1.1.1          | Enable 'aaa new-model'                                                      | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.1.2          | Enable 'aaa authentication login'                                           | <input type="checkbox"/> | <input checked="" type="checkbox"/> |
| 1.1.3          | Enable 'aaa authentication enable default'                                  | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.1.4          | Set 'login authentication for 'line con 0''                                 | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.1.5          | Set 'login authentication for 'line tty''                                   | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.1.6          | Set 'login authentication for 'line vty''                                   | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.1.7          | Set 'aaa accounting' to log all privileged use commands using 'commands 15' | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.1.8          | Set 'aaa accounting connection'                                             | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.1.9          | Set 'aaa accounting exec'                                                   | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.1.10         | Set 'aaa accounting network'                                                | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.1.11         | Set 'aaa accounting system'                                                 | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.2.1          | Set 'privilege 1' for local users                                           | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.2.2          | Set 'transport input ssh' for 'line vty' connections                        | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.2.4          | Create 'access-list' for use with 'line vty'                                | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.2.5          | Set 'access-class' for 'line vty'                                           | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.3.1          | Set the 'banner-text' for 'banner exec'                                     | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.3.2          | Set the 'banner-text' for 'banner login'                                    | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.3.3          | Set the 'banner-text' for 'banner motd'                                     | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.4.1          | Set 'password' for 'enable secret'                                          | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.4.2          | Enable 'service password-encryption'                                        | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.4.3          | Set 'username secret' for all local users                                   | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.5.1          | Set 'no snmp-server' to disable SNMP when unused                            | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.5.2          | Unset 'private' for 'snmp-server community'                                 | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.5.3          | Unset 'public' for 'snmp-server community'                                  | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.5.4          | Do not set 'RW' for any 'snmp-server community'                             | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.5.5          | Set the ACL for each 'snmp-server community'                                | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.5.6          | Create an 'access-list' for use with SNMP                                   | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.5.7          | Set 'snmp-server host' when using SNMP                                      | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.5.8          | Set 'snmp-server enable traps snmp'                                         | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.5.9          | Set 'priv' for each 'snmp-server group' using SNMPv3                        | <input type="checkbox"/> | <input type="checkbox"/>            |
| 1.5.10         | Require 'aes 128' as minimum for 'snmp-server user' when using SNMPv3       | <input type="checkbox"/> | <input type="checkbox"/>            |
| 2.1.1.1.1      | Set the 'hostname'                                                          | <input type="checkbox"/> | <input type="checkbox"/>            |

|           |                                                                                         |                          |                          |
|-----------|-----------------------------------------------------------------------------------------|--------------------------|--------------------------|
| 2.1.1.1.2 | Set the 'ip domain-name'                                                                | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.1.1.1.3 | Set 'modulus' to greater than or equal to 2048 for 'crypto key generate rsa'            | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.1.1.1.4 | Set 'seconds' for 'ip ssh timeout'                                                      | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.1.1.1.5 | Set maximum value for 'ip ssh authentication-retries'                                   | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.1.1.2   | Set version 2 for 'ip ssh version'                                                      | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.1.2     | Set 'no cdp run'                                                                        | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.1.3     | Set 'no ip bootp server'                                                                | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.1.4     | Set 'no service dhcp'                                                                   | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.1.5     | Set 'no ip identd'                                                                      | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.1.6     | Set 'service tcp-keepalives-in'                                                         | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.1.8     | Set 'no service pad'                                                                    | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.2.1     | Set 'logging on'                                                                        | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.2.2     | Set 'buffer size' for 'logging buffered'                                                | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.2.3     | Set 'logging console critical'                                                          | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.2.4     | Set IP address for 'logging host'                                                       | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.2.5     | Set 'logging trap informational'                                                        | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.2.6     | Set 'service timestamps debug datetime'                                                 | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.2.7     | Set 'logging source interface'                                                          | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.3.1.1   | Set 'ntp authenticate'                                                                  | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.3.1.2   | Set 'ntp authentication-key'                                                            | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.3.1.3   | Set the 'ntp trusted-key'                                                               | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.3.1.4   | Set 'key' for each 'ntp server'                                                         | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.3.2     | Set 'ip address' for 'ntp server'                                                       | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.4.1     | Create a single 'interface loopback'                                                    | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.4.2     | Set AAA 'source-interface'                                                              | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.4.3     | Set 'ntp source' to Loopback Interface                                                  | <input type="checkbox"/> | <input type="checkbox"/> |
| 2.4.4     | Set 'ip tftp source-interface' to the Loopback Interface                                | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.1.1     | Set 'no ip source-route'                                                                | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.1.2     | Set 'no ip proxy-arp'                                                                   | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.1.3     | Set 'no interface tunnel'                                                               | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.1.4     | Set 'ip verify unicast source reachable-via'                                            | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.2.1     | Set 'ip access-list extended' to Forbid Private Source Addresses from External Networks | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.2.2     | Set inbound 'ip access-group' on the External Interface                                 | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.1.1   | Set 'key chain'                                                                         | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.1.2   | Set 'key'                                                                               | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.1.3   | Set 'key-string'                                                                        | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.1.4   | Set 'address-family ipv4 autonomous-system'                                             | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.1.5   | Set 'af-interface default'                                                              | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.1.6   | Set 'authentication key-chain'                                                          | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.1.7   | Set 'authentication mode md5'                                                           | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.1.8   | Set 'ip authentication key-chain eigrp'                                                 | <input type="checkbox"/> | <input type="checkbox"/> |

|         |                                                   |                          |                          |
|---------|---------------------------------------------------|--------------------------|--------------------------|
| 3.3.1.9 | Set 'ip authentication mode eigrp'                | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.2.1 | Set 'authentication message-digest' for OSPF area | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.2.2 | Set 'ip ospf message-digest-key md5'              | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.3.1 | Set 'key chain'                                   | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.3.2 | Set 'key'                                         | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.3.3 | Set 'key-string'                                  | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.3.4 | Set 'ip rip authentication key-chain'             | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.3.5 | Set 'ip rip authentication mode' to 'md5'         | <input type="checkbox"/> | <input type="checkbox"/> |
| 3.3.4.1 | Set 'neighbor password'                           | <input type="checkbox"/> | <input type="checkbox"/> |