

## UML Class Structure Outline

This system consists of multiple components, categorized as follows.

### Visibility Modifiers:

- **+ Public** → Accessible by all classes.
  - **- Private** → Accessible only within the class.
  - **# Protected** → Accessible within the class and subclasses.
  - **~ Package-Private** → Accessible within the same package.
- 

## 1. Core Classes

### 1.1 GeneralStats (Abstract Parent Class)

#### Responsibilities:

- Acts as a **base class** for all game statistics.
- Contains **universal statistics** applicable to all board games.
- Provides generic methods (**win()**, **lose()**, **tie()**) that child classes override.
- Handles **MMR updates** and **rank updates** dynamically.

#### Attributes (Instance Variables):

- **# playerId: String**
- **# wins: int**
- **# losses: int**
- **# ties: int**
- **# gamesPlayed: int**
- **# mmr: int**
- **# rank: Rank (NEW: Stores player's current rank)**

#### Methods:

- **+ win(): void**
- **+ lose(): void**
- **+ tie(): void**
- **+ get\_mmr(): int**
- **+ get\_wins(): int**
- **+ get\_losses(): int**
- **+ get\_ties(): int**

- # updateMMR(win: boolean): void (abstract) (Calls **updateRank()**)
  - # updateRank(): void (NEW: Adjusts rank after MMR change)
- 

## 1.2 Game-Specific Stats (Child Classes)

Each game (**Connect4**, **Tic Tac Toe**, **Checkers**) extends **GeneralStats**, adding game-specific attributes and logic.

### 1.2.1 Connect4Stats

#### Attributes:

- - piecesDropped: int

#### Methods:

- + recordMove(column: int): void
  - + getMoves(): int
  - # updateMMR(win: boolean): void
- 

### 1.2.2 TicTacToeStats

#### Attributes:

- - movesMade: int

#### Methods:

- + recordMove(): void
  - + getMoves(): int
  - # updateMMR(win: boolean): void
- 

### 1.2.3 CheckersStats

#### Attributes:

- - piecesCaptured: int
- - movesMade: int

#### Methods:

- + recordMove(): void

- + getMoves(): int
  - # updateMMR(win: boolean): void
- 

## 2. Ranking System

### 2.1 Rank (Enum)

#### Responsibilities:

- Stores **universal ranking tiers**.
- Ensures **consistent ranking levels across all games**.

#### Values (Enum Constants):

- + BRONZE
- + SILVER
- + GOLD
- + PLATINUM
- + DIAMOND
- + MASTER
- + GRANDMASTER

#### Methods:

- + getRank(mmr: int, minMMR: int, maxMMR: int): Rank
    - Takes **mmr**, **minMMR**, and **maxMMR** to compute the **player's rank dynamically**.
- 

## 3. Player Profile

### 3.1 Player

#### Responsibilities:

- Represents a **player profile** storing statistics for multiple games.

#### Attributes:

- + playerId: String
- + connect4Stats: Connect4Stats
- + ticTacToeStats: TicTacToeStats

- + checkersStats: CheckersStats

#### Methods:

- + getStats(gameType: String): GeneralStats
- 

## 4. Matchmaking System

### 4.1 MatchmakingSystem

#### Responsibilities:

- Handles **rank-based queue system** for matchmaking.
- Moves players **down to lower-ranked queues** after a wait time.

#### Attributes:

- - queues: Map<int, List<Player>> (14 ranks, 2 queue pairs each)

#### Methods:

- + addPlayerToQueue(player: Player): void
  - + matchPlayers(): List<Pair<Player, Player>>
  - + waitAndMoveDown(player: Player): void
  - + removePlayer(player: Player): void
- 

## 5. Leaderboard System

### 5.1 LeaderboardManager

#### Responsibilities:

- Tracks and sorts **player statistics**.
- Stores data in **CSV or simulated database**.

#### Attributes:

- - leaderboardData: List<Player>

#### Methods:

- + updatePlayer(player: Player): void
  - + getTopPlayers(by: String, topN: int): List<Player>
- 

## 6. UML Relationship Types

Using **UML standards** and referencing the **provided images**, the relationships between classes will follow:

### 1. Inheritance (Generalization)

- **GeneralStats** (Abstract Parent Class) → **Connect4Stats**, **TicTacToeStats**, **CheckersStats** (Concrete Subclasses).
- **MatchmakingSystem** and **LeaderboardManager** **operate separately** but interact with **Player**.

### 2. Aggregation

- **Player** **aggregates** multiple **GameStats** objects.
- **LeaderboardManager** **aggregates** multiple **Players**, to collect info on each of their stats.

### 3. Dependency

- **GeneralStats** **depends** on **Rank** for the updateRank()
- **MatchmakingSystem** also depends on **Player**, as it needs to move around, players, and match them up using their stats information.