

N.F.A. (%)	REQ NUM OF VALVES	ACT NUM OF VALVES	TOLERANCE (±)	ROW SPACING	TIER SPACING
7.81	565	566	11	117.4	81.4

SUPPORTING WIDTH						SUPPORTING THICKNESS	
							8
7.81	565	566	11	117.4	81.4		

NO.OF SVG VALVES-520
NO.OF PUSH VALVES-88
TOTAL NO.OF VALVES-566

ITEM	MATERIAL			
	180	182	183	184
089-092	×			
093a/095				×
096A/097	×			
098a/099				×
098a/092	×			
091				×
8439A/A3	×			
8439A/A2	×			
071	×			
072		×		
085-085			×	
086-089	×			

Спецификация								
Поз.	Обозн.	Кол.	Ед.	Масса ед. кг	Примечание	Описание	Документ-основание	Материал
001	1	1	PC	2139334-001-092		Сборка тарелка №2 2-поточная тарелка #2		
041	2	1	PC	300012114		Вал труб		
042	3	1	PC	300012115		Пружина		
043,061	4	1	PC	300012116		Пружина		
061	2	1	PC	300012117		Пружина		
062	4	1	PC	300012118		Пружина		
071	5	1	PC	300012119		Пружина		
072	2	1	PC	300012120		Пружина		
081	10	1	PC	300012121		Пластина		
082	10	1	PC	300012122		Пластина		
083	4	1	PC	300012123		Пластина		
084	10	1	PC	300012124		Пластина		
085	4	1	PC	300012125		Пластина		
086-088	3	1	PC	300012126		Болт двухсторонний		
089	12	1	PC	300012127		Болт двухсторонний		
090-091	12	1	PC	300012128		Болт двухсторонний		
092	2	1	PC	300012129		Вал		
100	105	8	KG	1000A284		Лист	316SS/4305	-
101	5	1	KG	1000A284		Лист	316SS/4305	-
104	5	1	KG	1000A284		Лист	316SS/4305	-
105	103	8	KG	1000A284		Лист	316SS/4305	-
301	82	8	PC	1000A284		Шайба плоская	316SS/4305	A2-70
328	32	3	PC	1000A284		Шайба плоская	316SS/4305	A2-70
401	64	12	PC	1000A284		Шайба плоская	316SS/4305	A2-70
402	304	32	PC	1000A284		Шайба плоская	316SS/4305	A2-70
412	6	6	PC	1000A284		Шайба плоская	316SS/4305	A2-70
413	2	2	PC	1000A284		Шайба плоская	316SS/4305	A2-70
414	2	2	PC	1000A284		Шайба плоская	316SS/4305	A2-70
421	2	2	PC	1000A284		Шайба плоская	316SS/4305	A2-70
439	2	2	PC	1000A284		Шайба плоская	316SS/4305	A2-70
482	2	2	PC	1000A284		Шайба плоская	316SS/4305	A2-70
484	2	2	PC	1000A284		Шайба плоская	316SS/4305	A2-70
485	2	2	PC	1000A284		Шайба плоская	316SS/4305	A2-70

TOP VIEW OF 2 PASS TRAY #2
2-поточная тарелка #2, вид сверху

SECTION A-A
СЕЧЕНИЕ

DETAIL 'A' УЗЕЛ 'A'
DETAIL 'B' УЗЕЛ 'B'
DETAIL 'C' УЗЕЛ 'C'
DETAIL 'D' УЗЕЛ 'D'
DETAIL 'E' УЗЕЛ 'E'
DETAIL 'F' УЗЕЛ 'F'
DETAIL 'X' УЗЕЛ 'X'

DETAIL OF ANTI JUMP BAFFLE (FOR TRAY #2)
узел предотвращения (для тарелки #2)

SECTION B-B СЕЧЕНИЕ

(42xREQ'D)

TOLERANCE NOTES :
1. MAXIMUM ALL ROUND LEVEL DEVIATION OF TRAY SUPPORT RING IS 0.15 % OF INSIDE DIAMETER OF COLUMN WITH A MAX. OF 5 mm
2. DIMENSION TOLERANCE OF OUTLETWEIR HEIGHT ±1.5 mm
3. DIMENSION TOLERANCE OF CLEARANCE IS ± 3 mm

TOLERANCES UNLESS OTHERWISE STATED :

1	м/l	150	mm ± 1.0 mm
301	м/l	300	mm ± 2.0 mm
301	м/l	600	mm ± 3.0 mm
601	м/l	1000	mm ± 5.0 mm
1001	м/l	2000	mm ± 10.0 mm
2001	м/l		mm ± 15.0 mm

TOLERANCES FOR HOLES : ± 0.1 mm

ДОПУСК ПРИЗНАКОВ							