

Lecture 6

Inheritance

1

Topics

- Reusability
- Base class and derived class
- Function Overriding
- Access Control and Inheritance
- Public Inheritance
- Constructors and Destructors in Inheritance
- Assignment Operator and Inheritance
- Multiple Inheritance
- Virtual Base Classes

Reusability in Object-Oriented Programming

- Reusability is the process of taking an existing class, and using it in a new program.
- By reusing the classes, the time and effort needed to develop a program can be reduced.
- The simplest way to reuse a class is to use an object of that class directly.
 - Standard library of the C++ provides many built-in classes.
 - Example: The `std::string` class.
- The second way to reuse a class is to place an object of that class inside a new class.
 - The new class contains objects of existing classes.
 - It is referred to as **composition (has-a)**.

3

Reusability in Object-Oriented Programming

The third way to reuse a class is **inheritance**.

- Inheritance is one of the ways in object-oriented programming that makes reusability possible.
- By the help of inheritance, programmer can write more special classes from general classes.
- Inheritance is referred to as **(is-a)** or **(a-kind-of)**.

4

Example : Using built-in **string** class

- To use built-in C++ strings, the C++ header file **<string>** is included.
- Built-in overloaded operators such as +, +=, etc can be used with strings.

```
#include <string>           // String class header file is included
#include <iostream>
using namespace std;

int main()
{
    string s1 = "ABC";      // Initialized by assignment
    string s2 ("DEF");      // Initialized by constructor
    string s3;              // Empty string

    s3 = s1 + " , " + s2;   // Combining strings (overloaded +)
    s3 += "XYZ";            // Appending a string (overloaded +=)

    cout << s3 << endl;    // Screen output : ABC , DEFXYZ
}
```

5


Inheritance

- OOP provides a way to modify a class without changing its code.
- It is achieved by using **inheritance** to derive a new class from the old one.
- The old class (**base class**) is not modified, but the new class (**derived class**) can use all the features of the old one, and additional features of its own.

6

Generalization and Specialization

- With inheritance, special classes can be written from general classes.
- Special classes (derived) may have more members (data and functions) than general classes (base).
- Example:
University is base class (general)
StateUniversity is-a-kind of University (special)
FoundationUniversity is-a-kind of University (special)




7

Topics

- Reusability
- Base class and derived class
- Function Overriding
- Access Control and Inheritance
- Public Inheritance
- Constructors and Destructors in Inheritance
- Assignment Operator and Inheritance
- Multiple Inheritance
- Virtual Base Classes

Example: Class Diagrams for Inheritance



Member access specifiers

is protected

+ is public

- is private

9

Example : Base class

- Defining the classes **Teacher** and **Principal** (director) in a school.
- First, the **Teacher** class should be defined as the base class.
- Then, the **Principal** class can be defined, which is derived from **Teacher** class.
- Protected members of base class will be public in derived class members.

```
class Teacher // Base class
{
    protected:
        string name;
        int    numOfStudents;

    public:
        void setName (string tname)
        {
            name = tname;
        }
        void print ();
};
```

10

Example : Derived class

- Principal is a special type of Teacher.
- It has more member data and functions.

```
class Principal : public Teacher // Derived class
{
    string schoolName; // Additional data members
    int    numOfTeachers;

    public:
        void setSchool (string  sname)
            { schoolName = sname; }
        void print ();
};
```

```
int main() {
    Teacher  t1;
    Principal p1;

    t1 . setName ("Louis");
    p1 . setName ("Richard");
    p1 . setSchool ("College of Science");
}
```

11

Base and Derived Classes

- An object of a **derived class** inherits all the member data and functions of the **base class**.
- **Private, Protected, and Public** members of the base class are inherited by the derived class.
- But Private members are not visible in the derived class, only others are visible in derived class.
- The member functions of the derived class can not access private members of the base class directly.
- The derived class may access them only through the public interface functions of the base class.

12

Redefining the Members (**Overriding**)

- Sometimes member data and functions should be redefined in the derived class.
- Example : The **print** function must be redefined in Principal class, because principals have more properties to print.

```
class Teacher    // Base class
{
    protected:
        string name;
        int    numOfStudents;

    public:
        void setName (string tname) { name = tname; }
        void print ();
};
```

```
void Teacher :: print () // Print function of Teacher class
{
    cout << "Name: " << name << endl;
    cout << "Number of Students: " << numOfStudents << endl;
}
```

13

- The **print()** function of the derived Principal class **overrides** (hides) the **print()** function of the base Teacher class.
- The Principal class has actually two **print()** functions. (Inherited print function and also its own print function.)

```
class Principal : public Teacher // Derived class
{
    string schoolName;
    int    numOfTeachers;

    public:
        void setSchool (string sname) { schoolName = sname; }
        void print() ; // Print function of Principal class (Overridden)
};
```

```
void Principal :: print() // Print function of Principal class (Overridden)
{
    cout << "Name: " << name << endl;
    cout << "Number of Students: " << numOfStudents << endl;
    cout << "Name of the school: " << schoolName << endl;
}
```

14

Alternative method :

(Calling the print function of base class Teacher)

- Members (data and function) of the base class can be accessed by using the scope operator (::) .
- The print function of base class can be called, from the print function of derived class.

```
void Principal :: print()    // Print function of Principal class (Overridden)
{
    Teacher :: print();    // Calls print function of Teacher class (base)

    cout << "Name of the school: " << schoolName << endl;
}
```

15

Topics

- Reusability
- Base class and derived class
- Function Overriding
- Access Control and Inheritance
- Public Inheritance
- Constructors and Destructors in Inheritance
- Assignment Operator and Inheritance
- Multiple Inheritance
- Virtual Base Classes

Overriding the member functions

- If the programmer of the **derived class** redefines a member function, it means he changes the interface of the **base class**.
- In this case the member function of the base class is hidden (**overridden**).
- The hidden members in base class are still accessible through the scope `::` operator.
- The derived class will have **two member functions** with the same name.

17

Example: Overriding of member data and functions

```
class A
{
public:
    int i1;
    int i2;
    void f1 ();
    int f2 (int);
};
```

```
class B: public A
{
public:
    float i1;           // overrides i1
    float f1 (float);   // overrides f1
};
```

```
int main() {
    B b;
    int j = b.f2 (10);    // A :: f2
    b.i1 = 40;            // B :: i1
    b.i2 = 30;            // A :: i2, because i2 is public in A
    float y = b.f1 (3.14); // B :: f1
    b.f1 ();              // Compiler error f1(float) in B hides the f1(void) of A
    b.A::f1 ();           // OK, because f1(void) is public in A
    b.A::i1 = 20;         // OK, because i1 is public in A
}
```

18

Topics

- Reusability
- Base class and derived class
- Function Overriding
- Access Control and Inheritance
- Public Inheritance
- Constructors and Destructors in Inheritance
- Assignment Operator and Inheritance
- Multiple Inheritance
- Virtual Base Classes

Access Control and Inheritance

- When inheritance is not involved, class member functions have access to anything in the class, whether public or private. But objects of that class have access only to public members.
- Member functions of a derived class can access **public** and **protected** members of base class, but not **private** members.
- Objects of a derived class can access only public members of base class.

Access specifier	Accessible from own class	Accessible from derived class	Accessible from other objects or from main
public	Yes	Yes	Yes
protected	Yes	Yes	No
private	Yes	No	No

Example : Access Specifiers

```
class Teacher // Base class
{
    private :
        string name;

    protected :
        int numOfStudents;

    public :
        void setName (string tname)
            { name = tname; }

        void print() ;
};
```

Only member functions of Teacher class can access.

Also member functions of derived classes can access.

Can be accessed from everywhere.

21

```
class Principal : public Teacher // Derived class
{
    private: // Default access specifier
        string schoolName;
        int    numOfTeachers;

    public:
        void setSchool (string sname) { schoolName = sname; }
        void print();
        int getNumOfStudents() { return numOfStudents; } // Protected
        string get_name() { return name; } //Error (name is private)
};
```

```
int main() {
    Teacher T1;
    Principal P1;
    T1 . numOfStudents = 100;
    //Error (numOfStudents is protected)

    T1 . setName ("John");
    P1 . setSchool ("College of Science");
}
```

22

Topics

- Reusability
- Base class and derived class
- Function Overriding
- Access Control and Inheritance
- Public Inheritance
- Constructors and Destructors in Inheritance
- Assignment Operator and Inheritance
- Multiple Inheritance
- Virtual Base Classes

Public Inheritance

- The access specifier of derivation is usually written as public.
- In **public inheritance**, the objects of derived class can access public members of base class.
- Public members of base class are also public members of derived class.

```
class Base { ..... };
```

```
class Derived : public Base { ..... };
```

Private Inheritance


- In **private inheritance**, the public members of base class are private members of derived class.
- Objects of derived class can not access any members of base class.
- Member functions of derived class can still access public and protected members of base class.

```
class Base { ..... };
```

```
class Derived : private Base { ..... };
```

25

Inheritance Example



26

Special Member Functions and Inheritance

- Some special functions will need to do different things in the base class and in the derived class.
- Overloaded assignment operator:
The = operator in the derived class must assign values to derived class data, and the = operator in the base class must assign values to base class data.
- Constructors :
Because the derived class and base class constructors initialize different data, one constructor cannot be used in place of another.

27

Topics

- Reusability
- Base class and derived class
- Function Overriding
- Access Control and Inheritance
- Public Inheritance
- Constructors and Destructors in Inheritance
- Assignment Operator and Inheritance
- Multiple Inheritance
- Virtual Base Classes

Constructors and Inheritance

- When an object of a derived class is defined, the base class constructor will be automatically invoked (called) before the derived class constructor.

```
class Teacher //Base class
{
    string name;
    int numOfStudents;
public:

    // Constructor of base class
    Teacher (string tname) : name (tname) { }
};
```

```
class Principal : public Teacher // Derived class
{
    int numOfTeachers;
public:
    // Constructor of derived class
    Principal (string , int );
};
```

29

Correct method to invoke base class constructor:

- If the base class has a constructor, which must take some arguments, then the derived class must also have a constructor that calls the constructor of the base with proper arguments.
- The definition below uses an initializer list to invoke the base class constructor.

```
// Constructor of derived class
Principal :: Principal (string tname, int numOT) : Teacher (tname)
{
    numOfTeachers = numOT;
}
```

Base class constructor

30

Wrong method to invoke base class constructor:

- The following definition gives a compiler error.
- Because the base class constructor can not be called directly like a function call.

```
Principal : : Principal (string tname, int numOT)
{
    numOfTeachers = numOT;
    Teacher (tname) ; // Compiler error.
                     // Base class constructor
                     // can not be called directly.
}
```

31

Destructors and Inheritance

- When an object of derived class goes out of scope, the destructors are called in reverse order.
- **The derived object is automatically destroyed first, then the base class object is destroyed.**

```
class B // Base class
{
    public:
        B() { cout << "Base constructor called \n"; }
        ~B() { cout << "Base destructor called \n"; }
};
```

```
class D : public B // Derived class
{
    public:
        D() { cout << "Derived constructor called \n"; }
        ~D() { cout << "Derived destructor called \n"; }
};
```

32


```
int main ()
{
    cout << "Program started \n";

    D x;    // Object of derived class

    cout << " Program ended \n";
}
```

Screen
output

```
Program started
Base constructor called
Derived constructor called

Program ended
Derived destructor called
Base destructor called
```

33

Topics

- Reusability
- Base class and derived class
- Function Overriding
- Access Control and Inheritance
- Public Inheritance
- Constructors and Destructors in Inheritance
- Assignment Operator and Inheritance
- Multiple Inheritance
- Virtual Base Classes

Overloaded Assignment Operator and Inheritance

In inheritance, assignment operator of derived class should be different than assignment operator of base class.

```
class String //Base class
{
    protected:
        int size;
        char *contents;
    public:
        const String & operator= (const String &);
        // Overloaded assignment operator
};
```

```
const String & String :: operator= (const String & in_object)
{
    delete [ ] contents;    // Delete old contents
    size = in_object.size;
    contents = new char[size+1];
    strcpy (contents, in_object . contents);
    return *this;
}
```

35


- String2 class is derived from String class.
- It has two contents.
- First is inherited from base class, second is declared as an extra.

```
class String2 : public String // Derived class
{
    int size2;
    char *contents2;

    public:
        String2 ();
        String2 (const char *, const char *);
        String2 (const String2 &);


        const String2 & operator= (const String2 &);

        void print() const;
        ~String2 ();
};
```



36

Members of derived class String2



37

Overloaded assignment operator of String2 class

- Data members of `String` class (base) must be protected.
- Otherwise functions of `String2` class (derived) can not access them.

```
const String2 & String2 :: operator= (const String2 &in_object)
{
    // Copy the inherited data members (base class)
    size = in_object.size;
    delete [ ] contents;
    contents = new char[size + 1];
    strcpy (contents, in_object.contents);

    // Copy the additional data members (derived class)
    size2 = in_object . size2;
    delete [ ] contents2;
    contents2 = new char[size2 + 1];
    strcpy (contents2, in_object . contents2);

    return *this;
}
```

38

Inheritance and Composition

- **Inheritance** represents the **is-a** relation.
Example: Class B is-a kind of class A.
- **Composition** represents the **has-a** relation.
Example: Class C has-a class A object.

```
class A { };
```

```
class B : public A { };
```

B is-a A
(Inheritance)

```
class C  
{  
    A a;  
};
```

C has-a A
(Composition)

32

Example : Inheritance and Composition

Inheritance and composition can be used together.

```
class A  
{  
    public:  
    void f () {cout << "A is called \n" ;}  
};
```

```
class B  
{  
    public:  
    void f () {cout << "B is called \n";}  
};
```

```
class C : public B // Inheritance, C is-a B  
{  
    A a; // Composition, C has-a A  
    public:  
    void f () // Redefinition (function override)  
    {  
        a.f (); // Call function f of a  
        B::f (); // Call function f of base class B  
    }  
};
```

```
int main()  
{  
    C c;  
    c.f ();  
}
```

Screen output

```
A is called  
B is called
```

40

Topics

- Reusability
- Base class and derived class
- Function Overriding
- Access Control and Inheritance
- Public Inheritance
- Constructors and Destructors in Inheritance
- Assignment Operator and Inheritance
- Multiple Inheritance
- Virtual Base Classes

Multiple Inheritance

Multiple inheritance occurs when a class inherits from two or more base classes.

```
class Base1
{
    public:
    void f1 ()
    char* f2 (int);
};
```

```
class Derived : public Base1 , public Base2
{
    public:
    float f1 (float); // override Base1
    void f4 ();       // override Base2
    int f5 (int);
};
```

```
class Base2
{
    public:
    char* f2 (int, char);
    int f3 ();
    void f4 ();
};
```


```
int main()
{
    Derived d;
    float y = d . f1 (0.8); // Derived :: f1
    d . f3 ();              // Base2 :: f3
    d . f4 ();              // Derived :: f4
    d . Base2 :: f4 ();     // Base2 :: f4
}
```

The Derived class contains the following 8 member functions.

Base1 :: f1
Base1 :: f2

Base2 :: f2
Base2 :: f3
Base2 :: f4

Derived :: f1
Derived :: f4
Derived :: f5




43

Repeated Base Classes

- In example below, **D object** will contain **two A subobjects**, one inherited via B and one inherited via C.
- It is a repeated (duplicated) inheritance.
- There are two subobjects when really there should be only one.

```
class A { };  
class B : public A { };  
class C : public A { };  
class D : public B, public C { };
```



44

Topics

- Reusability
- Base class and derived class
- Function Overriding
- Access Control and Inheritance
- Public Inheritance
- Constructors and Destructors in Inheritance
- Assignment Operator and Inheritance
- Multiple Inheritance
- Virtual Base Classes

Virtual Base Classes

- To fix repeated inheritance, the **virtual** keyword can be used, when deriving B and C from A.
- The **virtual** keyword tells the compiler to inherit only one A subobject from base class A.

```
class A { };  
class B : virtual public A { };  
class C : virtual public A { };  
class D : public B, public C { };
```

