# DATA 260 Homework 7 — Farzaan Dalwai

Repository: https://github.com/farzaandalwai/data260-0686

SID4 0686 | PORT_BASE 8686 | PREFIX s0686 | SEED 686 | VERIFY_SEED 260686 | DOMAIN_ID 6

Rental-housing domain; MySQL s0686_rel; FastAPI 8686; React 5173; Python 3.11.14; macOS 26.6.2 arm64; local model llama3.2:latest.

Implementation commit 0f36332004971170feeed26280faa25871a0e544; real hook commit 2f266c9ee441d0514cf839f0565df6b0cc972c51. The final report commit/tag hash cannot be printed inside the PDF that is itself committed; the submission handoff gives that hash.

I kept the prior HW6 report and unrelated working-tree changes out of the HW7 commits. Raw evidence and source snapshots are in reports/hw07/raw/.

## Part 1 — JWT, roles, and Ruff

The existing rental routes now require one JWT bearer scheme. MySQL users have unique username, password_hash, and reader/writer/moderator role; old session routing is not active on these routes. The pre-migration MySQL backup was kept privately outside Git.

### JWT HTTP cases

Real requests show successful login and role actions plus 401/403 failures. The JWT is masked.


```
POST /auth/login; GET /auth/me
GET /api/listings; POST /api/listings; DELETE /api/listings/{id}
```

```
(.venv-hw7) farzu@Farzaans-MacBook-Air data260-0686 % printf 'Farzaan Dalwai — DATA 260 HW7\n'
Farzaan Dalwai — DATA 260 HW7
(.venv-hw7) farzu@Farzaans-MacBook-Air data260-0686 % date '+%Y-%m-%d %H:%M:%S %Z'
2026-10-24 22:28:58 PDT
(.venv-hw7) farzu@Farzaans-MacBook-Air data260-0686 % /opt/homebrew/bin/python3.11 run_hw7_auth_evidence.py
login valid: HTTP 200 {'jwt': 'eyJhbG...[redacted]', 'token_type': 'bearer'}
login wrong password: HTTP 401
me missing token: HTTP 401
me invalid token: HTTP 401
me expired token: HTTP 401
list reader: HTTP 200
create reader: HTTP 403
delete writer: HTTP 403
create writer: HTTP 201
delete moderator: HTTP 200
(.venv-hw7) farzu@Farzaans-MacBook-Air data260-0686 %
```

## Ruff failure

Ruff caught two unused imports before the fix.

```
ruff check hw7_bike_agent.py
```



### Ruff fixed

After removing those unused imports, the same check passed.


```
ruff check hw7_bike_agent.py
```




### Commit hook

The configured Ruff hook passed during a real VS Code terminal commit.

```
git commit -m 'Record HW7 missing-ID run log'
```





## Part 2 — Hand-written tool agent

The agent uses the existing local-model adapter and rental tools, appends tool observations, and bounds steps, tools, and tokens. The three fixed cases all make multiple real calls. One limited-search count claim was rejected by the verifier rather than reported as a success.

### A, B, C and missing ID

A searches then inspects, B aggregates then inspects, C compares two details; an unknown ID returns not found.


```
run_agent(TASKS[task], task=task)
run_agent('Inspect listing ID 9999999')
```



### Twenty attempts

Under the same model settings, 13/20 were verified; the five required tool-call failure categories were all zero.

```
python3 show_hw7_evidence.py reliability
```





## Part 3 — Reflexion

The deterministic verifier checks the exact observed listing facts. Reflexion permits at most two retries with cumulative 12-tool and 12,000-token budgets. It finished 3/3 tasks versus the baseline's 13/20 trials; one task used two retries. The controlled tight-step probe shows a failed then successful retry. No final verifier false rejection was observed.

### Failed then retried

The trace shows the rejected unsupported count, scoped reflection, retries, and the probe's budget-exhausted first attempt.

```
run_reflexion(task)  # at most two retries
python3 show_hw7_evidence.py reflexion
```





## Part 4 — Divvy ReAct agent

This is a separate LangGraph StateGraph ReAct loop with csv_sql, policy_retriever, and calculator. Both CSVs contain 500 genuine anonymized January 2026 Divvy trip rows; scenario_selected marks a modeled rider subset. Tool JSON schemas and the common envelope are in hw7_bike_tools.py. Pricing snapshot URL, UTC access time, and SHA-256 are saved in raw/divvy_sources.json.

## Official prices

The real Divvy page provides the classic-bike single-ride and annual membership terms used below.

```
PRICE_URL = 'https://divvybikes.com/pricing'
# $1 + $0.20/min; $143.90/year billed upfront
```



Compare the options


They're all good ones

| | Single Ride | Day Pass | Divvy Annual | Lyft Pink All Access |
|---|---|---|---|---|
| | $1 + $0.20/min | $19.90/day | $143.90/year* ($99/year limited time offer available for new members) | $199/year |
| | Get the app → | Get a day pass → | Join → | Join → |
| **Classic bike prices** | $1 unlock + $0.20/min | 3 hours free, then $0.20/min | 45 min free, then $0.20/min | 45 min free, then $0.20/min |
| **Scooter prices** | $1 unlock + $0.44/min | Free unlocks /+ $0.44/min | Free unlocks /+ $0.34/min | Free unlocks /+ $0.34/min |
| **Ebike prices** | $1 unlock + $0.44/min | Free unlocks + $0.44/min | Free unlocks + $0.20/min (Capped at $6.00 for minutes 31 to 45) | Free unlocks + $0.20/min |

### Frequent rider

The browser's 48 selected rides favor membership: $1,571.88 projected pay/use year versus $143.90 annual upfront. Monthly $11.99 is a comparison equivalent, not a bill.

```
analyze_bike(divvy_member_csv, PRICE_URL)
```



## Tool timeline

The live UI shows two read-only CSV queries, sourced pricing retrieval, calculator, and observations.

```
csv_sql -> csv_sql -> policy_retriever -> calculator
```

Steps: 6; time: 13314.78 ms; stop: success

### Tool timeline

1. **csv_sql**

   Input: {"sql":"SELECT COUNT(*) AS total_rows, SUM(scenario_selected) AS scenario_rides FROM uploaded"}

   Observation: 1 row(s): [{"total_rows":500,"scenario_rides":48}]; source: uploaded.csv

   ▶ Full observation
2. **csv_sql**

   Input: {"sql":"SELECT week, SUM(scenario_selected) AS rides, ROUND(AVG(CASE WHEN scenario_selected=1 THEN duration_minutes END),2) AS avg_minutes, ROUND(SUM(CASE WHEN scenario_selected=1 THEN 1+0.2*duration_minutes ELSE 0 END),2) AS pay_cost FROM uploaded GROUP BY week ORDER BY week"}

   Observation: 4 row(s): [{"week":1,"rides":12,"avg_minutes":9.36,"pay_cost":34.46}, {"week":2,"rides":12,"avg_minutes":8.89,"pay_cost":33.34},{"week":3,"rides":12,"avg_minutes":8.49,"pay_cost":32.37}, {"week":4,"rides":12,"avg_minutes":7.84,"pay_cost":30.82}]; source: uploaded.csv

   ▶ Full observation
3. **policy_retriever**

   Input: {"url":"https://divvybikes.com/pricing","query":"single ride annual classic pricing","k":3}

   Observation: $1 + $0.20/min (https://divvybikes.com/pricing) | $143.90/year* ($99/year limited time offer available for new members) (https://divvybikes.com/pricing) | 45 min free, then $0.20/min (https://divvybikes.com/pricing); source: https://divvybikes.com/pricing

   ▶ Full observation
4. **calculator**

   Input: {"expression":"143.90/12","units":"USD/month"}


   Observation: 11.9917 USD/month; source: calculator

   ▶ Full observation

### Sparse rider

The distinct 500-row sample selects three rides; $78.12 projected annual pay/use beats $143.90 upfront.

```
analyze_bike(divvy_sparse_csv, PRICE_URL)
```




## Part 5 — Prompt injection

I wrote three goals and preconditions in THREAT_MODEL.md before testing. A hostile local pricing fixture was tested in a 3-by-3 matrix. Recommendation override caused one wrong answer before defenses and one with prompt defense alone; prompt plus deterministic cost/tool checks corrected it. The model did not attempt non-SELECT SQL or repeat the contaminating phrase in these trials. The independent read-only SQL gate rejected the hostile DELETE probe.

### Nine isolated tests

The terminal shows actual outcomes for override, SQL and contamination across all three defense conditions.

```
python3 show_hw7_evidence.py injection
```





## Part 6 — Sandbox tools

Six file tools use sandbox-relative paths. confirm_bash reports a reason, SAFE_PREFIXES limits commands, and pure-Python is_destructive blocks risky operations even with auto_approve=True. The temporary sandbox found two DEBUG matches in three Python files; five safe cases ran and five risky cases were refused.

### File search and gate

This is the real combined sandbox run, not reconstructed output.

```
python3 run_hw7_sandbox.py
```





## Final checks

### Live smoke test

The final live test passed 31/31 objective checks, including HTTP roles and the bike endpoint.

```
python3 verify_hw07.py --stdout-only --brief
```



## AI use

1. I used AI to draft and revise Python, React, tests, and this report, then checked the real local outputs.

2. An unsuitable output chose pay/use despite $2,160/year versus $143.90 membership. Another called a limited three-row listing search a total.

3. I found these by checking the costs and tool observations, then ran the live smoke, lint, UI, and gate tests.

4. I added a deterministic cost boundary and a verifier rule for unsupported count claims. The read-only SQL gate is independent of the prompt. Full answers are in AI_USE.md.

## Repository and access

Repository URL: https://github.com/farzaandalwai/data260-0686. I did not add collaborator permissions. The installed GitHub CLI credentials were invalid, so existing access for Sbnikitha and supriyaselvanganesan could not be independently verified here; the owner should check the exact accounts in repository settings before submission.