

Squirrel 1.0 Reference Manual

Alberto Demichelis

Squirrel 1.0 Reference Manual

Alberto Demichelis

Extensive review: Wouter Van Oortmersern

Copyright © 2003 Alberto Demichelis

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
 2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
 3. This notice may not be removed or altered from any source distribution.
-

Table of Contents

1. Introduction	1
2. The language	2
Lexical structure	2
Identifiers	2
Keywords	2
Operators	2
Other tokens	2
Literals	2
Values and Data types	3
Integer	3
Float	3
String	3
Null	3
Table	3
Array	4
Function	4
Generator	4
Userdata	4
Execution Context	4
Variables	4
Statements	6
Block	6
Control Flow Statements	6
Loops	7
break	8
continue	8
return	8
yield	9
Local variables declaration	9
Function declaration	9
try/catch	9
throw	9
expression statement	9
Expressions	10
Assignment(=) & new slot(<-)	10
Operators	10
Table constructor	12
delegate	13
clone	14
Array constructor	14
Tables	14
Construction	14
Slot creation	14
Slot deletion	15
Arrays	15
Functions	15
Function declaration	15
Function calls	16
Free variables	17
Tail recursion	17
Generators	17
Delegation	18
Metamethods	18

_set	19
_get	19
_newslot	19
_add	19
_sub	19
_mul	20
_div	20
_modulo	20
_unm	20
_typeof	20
_cmp	20
_call	20
_clone	20
_nexti	21
Built-in functions	21
Global functions	21
Default delegates	21
3. Embedding Squirrel	25
Memory management	25
Unicode	25
Error conventions	25
Initializing Squirrel	26
The Stack	26
Stack indexes	26
Stack manipulation	26
Runtime error handling	28
Compiling a script	28
Calling a function	29
Create a C function	29
Tables and arrays manipulation	31
Userdata and UserPointers	32
Keeping object references from C	33
Debug Interface	33
4. API Reference	35
Virtual Machine	35
Compiler	38
Stack Operations	39
Object creation and handling	41
Calls	46
Objects manipulation	48
Bytecode serialization	53
Raw object handling	54
Debug interface	55
Index	57

Chapter 1. Introduction

Squirrel is a high level imperative-OO programming language, designed to be a powerful scripting tool that fits in the size, memory bandwidth, and real-time requirements of applications like games. Although Squirrel offers a wide range of features like dynamic typing, delegation, higher order functions, generators, tail recursion, exception handling, automatic memory management, both compiler and virtual machine fit together in about 6k lines of C++ code.

Chapter 2. The language

This part of the document describes the syntax and semantics of the language.

Lexical structure

Identifiers

Identifiers start with a alphabetic character or '_' followed by any number of alphabetic characters, '_' or digits ([0-9]). Squirrel is a case sensitive language, this means that the lowercase and uppercase representation of the same alphabetic character are considered different characters. For instance "foo", "Foo" and "fOo" will be treated as 3 distinct identifiers.

$id := [a-zA-Z_][a-zA-Z_0-9]^*$

Keywords

The following words are reserved words by the language and cannot be used as identifiers:

break	case	catch	clone	continue	default	delegate	delete
else	for	if	in	local	null	resume	return
switch	this	throw	try	typeof	while	yield	

Keywords are covered in detail later in this document.

Operators

Squirrel recognizes the following operators:

!	!=	<-	%	&	&&	+	*
+	+=	--	-	<=	==	=>	>
^			~	<<	>>	++	--

Other tokens

Other used tokens are:

{ } [] . : :: ' ; "

Literals

Squirrel accepts integer numbers, floating point numbers and stings literals.

34	Integer number
0xFF00A120	Integer number
'a' or 'FORM'	Integer number

1.52	Floating point number
"I'm a string"	String

```
IntegerLiteral := [0-9]+ | '0x' [0-9A-Fa-f]+ | ''' [.]+ '''  
FloatLiteral := [0-9]+ '.' [0-9]+  
StringLiteral := '''[.]*'''
```

Values and Data types

Squirrel is a dynamically typed language so variables do not have a type, although they refer to a value that does have a type. Squirrel basic types are integer, float, string, null, table, array, function, generator and userdata.

Integer

An Integer represents a 32 bits (or better) signed number.

```
local a = 123 //decimal  
local b = 0x0012 //hexadecimal
```

Float

A float represents a 32 bits (or better) floating point number.

```
local a=1.0  
local b=0.234
```

String

Strings are an immutable sequence of characters to modify a string is necessary create a new one.

```
local a="I'm a wonderful string"
```

Null

The null value is a primitive value that represents the null, empty, or non-existent reference. The type Null has exactly one value, called null. In squirrel it is also used to represent a false Boolean value.

```
local a=null
```

Table

Tables are associative containers implemented as pairs of key/value (called a slot).

```
local t={}
local test=
{
    a=10
    b=function(a) { return a+1; }
}
```

Array

Arrays are simple sequence of objects, their size is dynamic and their index starts always from 0.

```
local a=["I'm", "an", "array"]
local b=[null]
b[0]=a[2];
```

Function

Functions are similar to those in other C-like languages and to most programming languages in general, however there are a few key differences (see below).

Generator

Generators are functions that can be suspended with the statement 'yield' and resumed later (see Generators).

Userdata

Userdata objects are blobs of memory(or pointers) defined by the host application but stored into Squirrel variables (See Userdata and UserPointers).

Execution Context

The execution context is the union of the function stack frame and the function environment object(this). The stack frame is the portion of stack where the local variables declared in its body are stored. The environment object is an implicit parameter that is automatically passed by the function caller (see Functions). During the execution, the body of a function can only transparently refer to its execution context. This means that a single identifier can refer either to a local variable or to an environment object slot; Global variables require a special syntax (see Variables). The environment object can be explicitly accessed by the keyword `this`.

Variables

There are two types of variables in Squirrel, local variables and tables/arrays slots. Because global variables are stored in a table, they are table slots.

A single identifier refers to a local variable or a slot in the environment object.

```
derefexp := id;
```

```
_table["foo"]  
_array[10]
```

with tables we can also use the '.' syntax

```
derefexp := exp '.' id
```

```
_table.foo
```

Squirrel first checks if an identifier is a local variable (function arguments are local variables) if not it checks if it is a member of the environment object (this).

For instance:

```
function testy(arg)  
{  
    local a=10;  
    print(a);  
    return arg;  
}
```

will access to local variable 'a' and prints 10.

```
function testy(arg)  
{  
    local a=10;  
    return arg+foo;  
}
```

in this case 'foo' will be equivalent to 'this.foo' or this["foo"].

Global variables are stored in a table called the root table. Usually in the global scope the environment object is the root table, but to explicitly access the global table from another scope, the slot name must be prefixed with '::' (::foo).

```
exp:= '::' id
```

For instance:

```
function testy(arg)  
{  
    local a=10;  
    return arg+::foo;  
}
```

accesses the global variable 'foo'.

Statements

A squirrel program is a simple sequence of statements.

```
stats := stat [';' | '\n'] stats
```

Statements in squirrel are comparable to the C-Family languages (C/C++, Java, C# etc...): assignment, function calls, program flow control structures etc.. plus some custom statement like yield, table and array constructors (All those will be covered in detail later in this document). Statements can be separated with a new line or ';' (or with the keywords case or default if inside a switch/case statement), both symbols are not required if the statement is followed by '}'.

Block

```
stat := '{' stats '}'
```

A sequence of statements delimited by curly brackets ({ }) is called block; a block is a statement itself.

Control Flow Statements

if/else

```
stat:= 'if' '(' exp ')' stat ['else' stat]
```

Conditionally execute a statement depending on the result of an expression. exp is considered 'false' when its value is null and true for any other value.

Warning

In Squirrel also the number 0 is considered 'true'.

```
if(a>b)
    a=b;
else
    b=a;
////
if(a==10)
{
    b=a+b;
    return a;
}
```

while

```
stat:= 'while' '(' exp ')' stat
```

Executes a statement until the condition is false(null).

```
function testy(n)
```

```
{
    local a=0;
    while(a<n) a+=1;

        while(1)
        {
            if(a<0) break;
            a-=1;
        }
}
```

do/while

stat := 'do' stat 'while' '(' expression ')'

Executes a statement once, and then repeats execution of the statement until a condition expression evaluates to null.

```
local a=0;
do
{
    print(a+"\n");
    a+=1;
} while(a>100)
```

switch

stat := 'switch' '(' exp ')' '{'
'case' case_exp ':'
stats
['default' ':'
stats]
'}'

Is a control statement allows multiple selections of code by passing control to one of the case statements within its body. The control is transferred to the case label whose *case_exp* matches with *exp* if none of the case match will jump to the default label (if present). A switch statement can contain any number of case instances, if 2 case have the same expression result the first one will be taken in account first. The default label is only allowed once and must be the last one. A break statement will jump outside the switch block.

Loops

for

stat := 'for' '(' [initexp] ';' [condexp] ';' [incexp] ')' *statement*

Executes a statement as long as a condition is different than null.

```
for(local a=0;a<10;a+=1)
    print(a+"\n");
//or
glob <- null
for(glob=0;glob<10;glob+=1){
    print(glob+"\n");
}
//or
for(;;){
    print(loops forever+"\n");
}
```

foreach

'foreach' '(' [index_id','] value_id 'in' exp ')' stat

Executes a statement for every element contained in an array, table or generator. If exp is a generator it will be resumed every iteration as long as it is alive; the value will be the result of 'resume' and the index the sequence number of the iteration starting from 0.

```
local a=[10,23,33,41,589,56]
foreach(idx,val in a)
    print("index="+idx+" value="+val+"\n");
//or
foreach(val in a)
    print("value="+val+"\n");
```

break

stat := 'break'

The break statement terminates the execution of a loop (for, foreach, while or do/while) or jumps out of switch statement;

continue

stat := 'continue'

The continue operator jumps to the next iteration of the loop skipping the execution of the following statements.

return

stat:= return [exp]

The return statement terminates the execution of the current function/generator and optionally returns

the result of an expression. If the expression is omitted the function will return null. If the return statement is used inside a generator, the generator will not be resumable anymore.

yield

```
stat := yield [exp]
```

(see Generators).

Local variables declaration

```
initz := id [= exp][', ' initz]  
stat := 'local' initz
```

Local variables can be declared at any point in the program; they exist between their declaration to the end of the block where they have been declared. EXCEPTION: a local declaration statement is allowed as first expression in a for loop.

```
for(local a=0;a<10;a+=1)  
  print(a);
```

Function declaration

```
funcname := id ['::' id]  
stat := 'function' id ['::' id] + '(' args ')' ['::' '(' args ')'] stat
```

creates a new function.

try/catch

```
stat := 'try' stat 'catch' '(' id ')' stat
```

The try statement encloses a block of code in which an exceptional condition can occur, such as a runtime error or a throw statement. The catch clause provides the exceptionhandling code. When a catch clause catches an exception, its id is bound to that exception.

throw

```
stat := 'throw' exp
```

Throws an exception. Any value can be thrown.

expression statement

```
stat := exp
```

In Squirrel every expression is also allowed as statement, if so, the result of the expression is thrown away.

Expressions

Assignment(=) & new slot(<-)

```
exp := derefexp '=' exp
exp := derefexp '<-' exp
```

squirrel implements 2 kind of assignment: the normal assignment(=)

```
a=10;
```

and the "new slot" assignment.

```
a <- 10;
```

The new slot expression allows to add a new slot into a table(see Tables). If the slot already exists in the table it behaves like a normal assignment.

Operators

?: Operator

```
exp := exp_cond '?' exp1 ':' exp2
```

conditionally evaluate an expression depending on the result of an expression.

Arithmetic

```
exp := 'exp' op 'exp'
```

Squirrel supports the standard arithmetic operators +, -, * and /. Other than that is also supports 2 compact operators (+= and -=) and increment and decrement operators(++ and --);

```
a+=2;
//is the same as write
a=a+2;
x++
//is the same as write
x=x+1
```

All operators work normally with integers and floats; if one operand is an integer and one is a float the result of the expression will be float. The + operator has a special behavior with strings; if one of the operands is a string the operator + will try to convert the other operand to string as well and concatenate both together.

Relational

```
exp := 'exp' op 'exp'
```

Relational operators in Squirrel are : == < <= > >= !=

These operators return null if the expression is false and a value different than null if the expression is true. Internally the VM uses the integer 1 as true but this could change in the future.

Logical

```
exp := exp op exp  
exp := '!' exp
```

Logical operators in Squirrel are : && || !

The operator && (logical and) returns null if its first argument is null, otherwise returns its second argument. The operator || (logical or) returns its first argument if it is different than null, otherwise returns the second argument.

The '!' operator will return null if the given value to negate was different than null, or a value different than null if the given value was null.

in operator

```
exp := keyexp 'in' tableexp
```

Tests the existence of a slot in a table. Returns a value different than null if keyexp is a valid key in tableexp

```
local t=  
{  
    foo="I'm foo",  
    [123]="I'm not foo"  
}  
  
if("foo" in t) dostuff("yep");  
if(123 in t) dostuff();
```

typeof operator

```
exp := 'typeof' exp
```

returns the type name of a value as string.

```
local a={},b="squirrel"  
print(typeof a); //will print "table"  
print(typeof b); //will print "string"
```

comma operator

exp := *exp* ' , ' *exp*

The comma operator evaluates two expression left to right, the result of the operator is the result of the expression on the right; the result of the left expression is discarded.

```
local j=0,k=0;
for(local i=0; i<10; i++ , j++)
{
    k = i + j;
}
local a,k;
a = (k=1,k+2); //a becomes 3
```

Bitwise Operators

exp := ' *exp* ' *op* ' *exp* '
exp := ' ~ ' *exp*

Squirrel supports the standard c-like bit wise operators & , | , ^ , ~ , << , >> . Those operators only work on integers values, passing of any other operand type to these operators will cause an exception.

Operators precedence

- , ~ , ! , typeof , ++ , --	highest
/ , * , %	...
+ , -	
<< , >>	
< , <= , > , >=	
== , !=	
&	
^	
&& , in	
?:	
+= , -= , *= , /=	...
, (comma operator)	lowest

Table constructor

tslots := (' *id* ' '=' *exp* | '[' *exp* ']' '=' *exp*) [' , ']
exp := '{' [*tslots*] '}'

Creates a new table.

```
local a={} //create an empty table
```

A table constructor can also contain slots declaration; With the syntax:

```
id = exp [',' ]
```

a new slot with *id* as key and *exp* as value is created

```
local a=
{
  slot1="I'm the slot value"
}
```

An alternative syntax can be

```
'[ ' exp1 ' ]' = exp2 [',' ]
```

A new slot with *exp1* as key and *exp2* as value is created

```
local a=
{
  [1]="I'm the value"
}
```

both syntaxes can be mixed

```
local table=
{
  a=10,
  b="string",
  [10]={},
  bau=function(a,b)
  {
    return a+b;
  }
}
```

The comma between slots is optional.

delegate

```
exp := 'delegate' parentexp : exp
```

Sets the parent of a table. The result of *parentexp* is set as parent of the result of *exp*, the result of the expression is *exp* (see Delegation).

clone

```
exp := 'clone' exp
```

Clone performs shallow copy of a table, (copies all slots in the new table without recursion). If the source table has a delegate, the same delegate will be assigned as delegate (not copied) to the new table (see Delegation).

After the new table is ready the “_clone” meta method is called (see Metamethods).

Array constructor

```
exp := '[' [explist] ']
```

Creates a new array.

```
a <- [] //creates an empty array
```

arrays can be initialized with values during the construction

```
a <- [1,"string!",[],{}] //creates an array with 4 elements
```

Tables

Tables are associative containers implemented as pairs of key/value (called slot); values can be any possible type and keys any type except 'null'. Tables are squirrel's skeleton, delegation and many other features are all implemented through this type; even the environment, where global variables are stored, is a table (known as root table).

Construction

Tables are created through the table constructor (see Table constructor)

Slot creation

Adding a new slot in a existing table is done through the "new slot" operator '<-'; this operator behaves like a normal assignment except that if the slot does not exists it will be created.

```
local a={}
```

The following line will cause an exception because the slot named 'newslet' does not exist in the table 'a'

```
a.newslet = 1234
```

this will succeed:

```
a.news1ot <- 1234;
```

or

```
a[1] <- "I'm the value of the new slot";
```

Slot deletion

exp := delete derefexp

Deletion of a slot is done through the keyword `delete`; the result of this expression will be the value of the deleted slot.

```
a <- {
  test1=1234
  deleteme="now"
}

delete a.test1
print(delete a.deleteme); //this will print the string "now"
```

Arrays

An array is a sequence of values indexed by a integer number from 0 to the size of the array minus 1. Arrays elements can be obtained through their index.

```
local a=["I'm a string", 123]
print(typeof a[1]) //prints "string"
print(typeof a[0]) //prints "integer"
```

Resizing, insertion, deletion of arrays and arrays elements is done through a set of standard functions (see built-in functions).

Functions

Functions are first class values like integer or strings and can be stored in table slots, local variables, arrays and passed as function parameters. Functions can be implemented in Squirrel or in a native language with calling conventions compatible with ANSI C.

Function declaration

Functions are declared through the function expression

```
local a= function(a,b,c) {return a+b-c;}
```

or with the syntactic sugar

```
function ciao(a,b,c)
{
  return a+b-c;
}
```

that is equivalent to

```
this.ciao=function(a,b)
{
  return a+b-c;
}
```

is also possible to declare something like

```
T <- {}
function T::ciao(a,b,c)
{
  return a+b-c;
}
```

that is equivalent to write

```
T.ciao <- function(a,b,c)
{
  return a+b-c;
}
```

Function calls

exp := derefexp '(' explist ')'

The expression is evaluated in this order: derefexp after the explist (arguments) and at the end the call.

Every function call in Squirrel passes the environment object 'this' as hidden parameter to the called function. The 'this' parameter is the object where the function was indexed from.

If we call a function with this syntax

```
table.foo(a)
```

the environment object passed to foo will be 'table'

```
foo(x,y) // equivalent to this.foo(x,y)
```

The environment object will be 'this' (the same of the caller function).

Free variables

Free variables are variables referenced by a function that are not visible in the function scope. In the following example the function foo() declares x, y and testy as free variables.

```
local x=10,y=20
testy <- "I'm testy"

function foo(a,b):(x,y,testy)
{
  ::print(testy);
  return a+b+x+y;
}
```

The value of a free variable is frozen and bound to the function when the function is created; the value is passed to the function as implicit parameter every time is called.

Tail recursion

Tail recursion is a method for partially transforming a recursion in a program into an iteration: it applies when the recursive calls in a function are the last executed statements in that function (just before the return). If this happens the squirrel interpreter collapses the caller stack frame before the recursive call; because of that very deep recursions are possible without risk of a stack overflow.

```
function loopy(n)
{
  if(n>0){
    ::print("n="+n+"\n");
    return loopy(n-1);
  }
}

loopy(1000);
```

Generators

A function that contains a yield statement is called 'generator function'. When a generator function is called, it does not execute the function body, instead it returns a new suspended generator. The returned generator can be resumed through the resume statement while it is alive. The yield keyword, suspends the execution of a generator and optionally returns the result of an expression to the function that resumed the generator. The generator dies when it returns, this can happen through an explicit return statement or by exiting the function body; If an unhandled exception (or runtime error) occurs while a generator is running, the generator will automatically die. A dead generator cannot be resumed anymore.

```
function geny(n)
{
  for(local i=0;i<n;i+=1)
    yield i;
  return null;
}

local gtor=geny(10);
local x;
while(x=resume gtor) print(x+"\n");
```

the output of this program will be

```
0
1
2
3
4
5
6
7
8
9
```

Delegation

Squirrel supports implicit delegation. Every table or userdata can have a parent table (delegate). A parent table is a normal table that allows the definition of special behaviors for his child. When a table (or userdata) is indexed with a key that doesn't correspond to one of its slots, the interpreter automatically delegates the get (or set) operation to its parent.

```
Entity <- {
}

function Entity::DoStuff()
{
  ::print(_name);
}

local newentity=delegate Entity : {
  _name="I'm the new entity"
}

newentity.DoStuff(); //prints "I'm the new entity"
```

Metamethods

Metamethods are a mechanism that allows the customization of certain aspects of the language semantics. Those methods are normal functions placed in a table parent(delegate); Is possible to change many aspect of a table behavior by just defining a metamethod for this parent. For instance when we use relational operators other than '==' on 2 tables, the VM will check if the table has a method in his parent

called ‘_cmp’ if so it will call it to determine the relation between the tables.

```
local comparable={
  _cmp = function (other)
  {
    if(name<other.name)return -1;
    if(name>other.name)return 1;
    return 0;
  }
}

local a=delegate comparable : { name="Alberto" };
local b=delegate comparable : { name="Wouter" };

if(a>b)
  print("a>b")
else
  print("b<=a");
```

_set

invoked when the index idx is not present in the table or in its delegate chain

```
function _set(idx,val) //returns val
```

_get

invoked when the index idx is not present in the table or in its delegate chain

```
function _get(idx) //return the fetched values
```

_newslot

invoked when a script tries to add a new slot in a table.

```
function _newslot(key,value) //returns val
```

if the slot already exists in the target table the method will not be invoked also if the “new slot” operator is used.

_add

the + operator

```
function _add(op) //returns this+op
```

_sub

the – operator (like _add)

`_mul`

the `*` operator (like `_add`)

`_div`

the `/` operator (like `_add`)

`_modulo`

the `%` operator (like `_add`)

`_unm`

the unary minus operator

```
function _unm()
```

`_typeof`

invoked by the `typeof` operator on tables and userdata

```
function _typeof() //returns the type of this as string
```

`_cmp`

invoked to emulate the `<` `>` `<=` `>=` operators

```
function _cmp(other)
```

returns an integer:

<code>>0</code>	if this <code>></code> other
<code>0</code>	if this <code>==</code> other
<code><0</code>	if this <code><</code> other

`_call`

invoked when a tables or userdatas are called

```
function call(original_this,params...)
```

`_clone`

invoked when a table is cloned(in the cloned table)

```
function clone()
```

`_nexti`

invoked when a userdata is iterated by a foreach loop

```
function nexti(previdx)
```

if `previdx==null` it means that it is the first iteration. The function has to return the index of the ‘next’ value.

Built-in functions

The squirrel virtual machine has a set of built utility functions.

Global functions

```
seterrorhandler(func)
```

sets the runtime error handler

```
setdebughook(hook_func)
```

sets the debug hook

```
getroottable()
```

returns the root table of the VM.

```
assert(exp)
```

throws an exception if `exp` is null

```
print(x)
```

prints `x` in the standard output

```
chcode2string(code)
```

converts an integer representing a character code to a string

```
collect_garbage()
```

calls the garbage collector and returns the number of reference cycles found(and deleted)

Default delegates

Except null and userdata every squirrel object has a default delegate containing a set of functions to manipulate and retrieve information from the object itself.

Integer

`tofloat()`

convert the number to float and returns it

`tostring()`

converts the number to string and returns it

Float

`tointeger()`

converts the number to integer and returns it

`tostring()`

converts the number to string and returns it

String

`len()`

returns the string length

`tointeger()`

converts the string to integer and returns it

`tofloat()`

converts the string to float and returns it

`slice(start, [end])`

returns a section of the string as new string. Copies from start to the end (not included). If start is negative the index is calculated as length + start, if end is negative the index is calculated as length + start. If end is omitted end is equal to the string length.

`find(substr, [startidx])`

search a sub string(substr) starting from the index startidx and returns the index of its first occurrence. If startidx is omitted the search operation starts from the beginning of the string. The function returns null if substr is not found.

Table

`len()`

returns the number of slots contained in a table

`rawget(key)`

tries to get a value from the slot 'key' without employ delegation

`rawset(key, val)`

sets the slot 'key' with the value 'val' without employing delegation. If the slot do not exists , it will be created.

`getdelegate()`

returns the table delegate or null if no delegate is assigned.

Array

`len()`

returns the length of the array

`append(val)`

appends the value 'val' at the end of the array

`extend(array)`

Extends the array by appending all the items in the given array.

`pop()`

removes a value from the back of the array and returns it.

`top()`

returns the value of the array with the higher index

`insert(idx, val)`

inserst the value 'val' at the position 'idx' in the array

`remove(idx)`

removes the value at the position 'idx' in the array

`rresize(size)`

resizes the array

`sort()`

sorts the array

`reverse()`

reverse the elements of the array in place

`slice(start, [end])`

returns a section of the array as new array. Copies from start to the end (not included). If start is negative the index is calculated as length + start, if end is negative the index is calculated as length + start. If end is omitted end is equal to the array length.

Function

`call(_this, args...)`

calls the function with the specified environment object('this') and parameters

`acall(array_args)`

calls the function with the specified environment object('this') and parameters. The function accepts an array containing the parameters that will be passed to the called function.

Generator

`getStatus()`

returns the status of the generator as string : "running", "dead" or "suspended".

Chapter 3. Embedding Squirrel

This section describes how to embed Squirrel in a host application, C language knowledge is required to understand this part of the manual.

Because of his nature of extension language, Squirrel's compiler and virtual machine are implemented as C library. The library exposes a set of functions to compile scripts, call functions, manipulate data and extend the virtual machine. All declarations needed for embedding the language in an application are in the header file 'squirrel.h'.

Memory management

Squirrel uses reference counting (RC) as primary system for memory management; however, is possible to conditionally compile the virtual machine (VM) with an auxiliary mark and sweep garbage collector.

There are 3 possible compile time options:

- First a situation where Squirrel is compiled with RC only; in this case it is impossible for the VM to detect reference cycles, so is the programmer that has to remove the links to avoid memory leaks (no special define is needed).
- The second option is compiling with 'CYCLIC_REF_SAFE' defined; in this situation the VM keeps a linked list of all objects that can cause a reference cycle (tables, arrays etc..) and ensures that, when the VM is deleted, all cycles are detected and removed.
- The third configuration consists in a mark and sweep garbage collector (option 'GARBAGE_COLLECTOR'). This option behaves like CYCLIC_REF_SAFE but in addition the host program can call the function `sq_collectgarbage()` and perform a garbage collection during the program execution. The garbage collector isn't invoked by the VM and has to be explicitly called by the host program.

The only disadvantage introduced by the second and third option is that 2 additional pointers have to be stored for each object (8 bytes for 32 bits systems). The types involved are: tables, arrays, functions, userdata and generators; all other types are untouched. These options do not affect execution speed.

Unicode

By default Squirrel strings are plain 8-bits ASCII characters; however if the symbol '_UNICODE' is defined the VM, compiler and API will use 16-bits characters.

Error conventions

Most of the functions in the API return a `SQRESULT` value; `SQRESULT` indicates if a function completed successfully or not. The macros `SQ_SUCCEEDED()` and `SQ_FAILED()` are used to test the result of a function.

```
if(SQ_FAILED(sq_getstring(v,-1,&s)))  
    printf("getstring failed");
```

Initializing Squirrel

The first thing that a host application has to do, is create a virtual machine. The host application can create any number of virtual machines through the function `sq_newvm()`.

Every single VM has to be released with the function `sq_releasevm()` when it is not needed anymore.

```
int main(int argc, char* argv[])
{
    HSQUIRRELVM v;
    v=sq_newvm(NULL,1024); //creates a VM with initial stack size 1024

    //do some stuff with squirrel here

    sq_releasevm(v);
}
```

The Stack

Squirrel exchanges values with the virtual machine through a stack. This mechanism has been inherited from the language LUA. For instance to call a Squirrel function from C it is necessary to push the function and the arguments in the stack and then invoke the function; also when Squirrel calls a C function the parameters will be in the stack as well.

Stack indexes

Many API functions can arbitrarily refer to any element in the stack through an index. The stack indexes follow those conventions:

- 1 is the stack base
- Negative indexes are considered an offset from top of the stack. For instance -1 is the top of the stack.
- 0 is an invalid index

Here an example (let's pretend that this table is the VM stack)

<i>STACK</i>	<i>positive index</i>	<i>negative index</i>
"test"	4	-1(top)
1	3	-2
0.5	2	-3
"foo"	1(base)	-4

In this case, the function `sq_gettop` would return 4;

Stack manipulation

The API offers several functions to push and retrieve data from the Squirrel stack.

To push a value that is already present in the stack in the top position

```
void sq_push(HSQUIRRELV v,int idx);
```

To pop an arbitrary number of elements

```
void sq_pop(HSQUIRRELV v,int nelemstopop);
```

To remove an element from the stack

```
void sq_remove(HSQUIRRELV v,int idx);
```

To retrieve the top index (and size) of the current virtual stack you must call `sq_gettop`

```
int sq_gettop(HSQUIRRELV v);
```

To force the stack to a certain size you can call `sq_settop`

```
void sq_settop(HSQUIRRELV v,int newtop);
```

If the newtop is bigger than the previous one, the new positions in the stack will be filled with null values.

The following function pushes a C value into the stack

```
void sq_pushstring(HSQUIRRELV v,const SQChar *s,int len);  
void sq_pushfloat(HSQUIRRELV v,SQFloat f);  
void sq_pushinteger(HSQUIRRELV v,SQInteger n);  
void sq_pushuserpointer(HSQUIRRELV v,SQUserPointer p);
```

this function pushes a null into the stack

```
void sq_pushnull(HSQUIRRELV v);
```

returns the type of the value in a arbitrary position in the stack

```
SQObjectType sq_gettype(HSQUIRRELV v,int idx);
```

the result can be one of the following values:

```
OT_NULL,OT_INTEGER,OT_FLOAT,OT_STRING,OT_TABLE,OT_ARRAY,OT_USERDATA,  
OT_CLOSURE,OT_NATIVECLOSURE,OT_GENERATOR,OT_USERPOINTER
```

The following functions convert a squirrel value in the stack to a C value

```
SQRESULT sq_getstring(HSQUIRRELV v,int idx,const SQChar **c);
```

```
SQRESULT sq_getinteger(HSQIRRELM v,int idx,SQInteger *i);
SQRESULT sq_getfloat(HSQIRRELM v,int idx,SQFloat *f);
SQRESULT sq_getuserpointer(HSQIRRELM v,int idx,SQUserPointer *p);
SQRESULT sq_getuserdata(HSQIRRELM v,int idx,SQUserPointer *p);
```

The function `sq_cmp` pops 2 values from the stack and returns their relation (like `strcmp()` in ANSI C).

```
int sq_cmp(HSQIRRELM v);
```

Runtime error handling

When an exception is not handled by Squirrel code with a try/catch statement, a runtime error is raised and the execution of the current program is interrupted. It is possible to set a call back function to intercept the runtime error from the host program; this is useful to show meaningful errors to the script writer and for implementing visual debuggers. The following API call pops a Squirrel function from the stack and sets it as error handler.

```
SQUIRREL_API void sq_seterrorhandler(HSQIRRELM v);
```

The error handler is called with 2 parameters, an environment object (this) and a object. The object can be any squirrel type.

Compiling a script

You can compile a Squirrel script with the function `sq_compile`.

```
typedef SQChar (*SQLEXREADFUNC)(SQUserPointer userdata);

SQRESULT sq_compile(HSQIRRELM v,SQLEXREADFUNC read,SQUserPointer p,
    const SQChar *sourcename,int raiseerror,int lineinfo);
```

In order to compile a script is necessary for the host application to implement a reader function (`SQLEXREADFUNC`); this function is used to feed the compiler with the script data. The function is called every time the compiler needs a character; It has to return a character code if succeed or 0 if the source is finished.

If `sq_compile` succeeds, the compiled script will be pushed as Squirrel function in the stack.

Here an example of a 'read' function that read from a file:

```
SQChar file_lexfeedASCII(SQUserPointer file)
{
    int ret;
    char c;
    if( ( ret=fread(&c,sizeof(c),1,(FILE *)file )>0) )
        return c;
    return 0;
}

int compile_file(HSQIRRELM v,const char *filename)
{
```

```
FILE *f=fopen(filename, "rb");
if(f)
{
    sq_compile(v, file_lexfeedASCII, file, filename, 1, 0);
    fclose(f);
    return 1;
}
return 0;
}
```

When the compiler fails for a syntax error it will try to call the ‘compiler error handler’; this function is must be declared as follow

```
typedef void (*SQCOMPILERERROR)(const SQChar * /*desc*/, const SQChar *
/*source*/, int /*line*/, int /*column*/);
```

and can be set with the following API call

```
void sq_setcompilererrorhandler(HSQUIRRELVm v, SQCOMPILERERROR f);
```

Calling a function

To call a squirrel function it is necessary to push the function in the stack followed by the parameters and then call the function `sq_call`. The function will pop the parameters and push the return value if the last `sq_call` parameter is `>0`.

```
sq_pushroottable(v);
sq_pushstring(v, "foo", -1);
sq_get(v, -2); //get the function from the root table
sq_pushroottable(v); // 'this' (function environment object)
sq_pushinteger(v, 1);
sq_pushfloat(v, 2.0);
sq_pushstring(v, "three", -1);
sq_call(v, 4, 0);
sq_pop(v, 2); //pops the roottable and the function
```

this is equivalent to the following Squirrel code

```
foo(1, 2.0, "three");
```

If a runtime error occurs (or a exception is thrown) during the squirrel code execution the `sq_call` will fail.

Create a C function

A native C function must have the following prototype:

```
typedef int (*SQFUNCTION)(HSQUIRRELVm);
```

The parameters is an handle to the calling VM and the return value is an integer respecting the following rules:

- Bigger than 0 if the function returns a value
- 0 if the function does not return a value
- Less than 0 to a runtime error is thrown

In order to obtain a new callable squirrel function from a C function pointer, is necessary to call `sq_newclosure()` passing the C function to it; the new Squirrel function will be pushed in the stack.

When the function is called, the stackbase is the first parameter of the function and the top is the last. In order to return a value the function has to push it in the stack and return a value bigger than 0.

Here an example, the following function print the value of each argument and return the number of arguments.

```
int print_args(HSQUIRRELVm v)
{
    int nargs = sq_gettop(v); //number of arguments
    for(int n=1;n<=nargs;n++)
    {
        printf("arg %d is ",n);
        switch(sq_gettype(v,n))
        {
            case OT_NULL:
                printf("null");
                break;
            case OT_INTEGER:
                printf("integer");
                break;
            case OT_FLOAT:
                printf("float");
                break;
            case OT_STRING:
                printf("string");
                break;
            case OT_TABLE:
                printf("table");
                break;
            case OT_ARRAY:
                printf("array");
                break;
            case OT_USERDATA:
                printf("userdata");
                break;
            case OT_CLOSURE:
                printf("closure(function)");
                break;
            case OT_NATIVECLOSURE:
                printf("native closure(C function)");
                break;
            case OT_GENERATOR:
                printf("generator");
                break;
            case OT_USERPOINTER:
                printf("userpointer");
                break;
            default:
                ;
        }
    }
}
```

```

        return sq_throwerror(v,"invalid param"); //throw an exception
    }
}
printf("\n");
sq_pushinteger(v,nargs); //push the number of arguments as return value
return 1; //1 because 1 value is returned
}

```

Here an example of how to register a function

```

int register_global_func(HSQUIRRELV v,SQFUNCTION f,const char *fname)
{
    sq_pushroottable(v);
    sq_pushstring(v,fname,-1);
    sq_newclosure(v,f,0); //create a new function
    sq_createslot(v,-3);
    sq_pop(v,1); //pops the root table
}

```

Tables and arrays manipulation

A new table is created calling `sq_newtable`, this function pushes a new table in the stack.

```
void sq_newtable (HSQUIRRELV v);
```

To create a new slot

```
SQRESULT sq_createslot(HSQUIRRELV v,int idx);
```

To set or get the table delegate

```
SQRESULT sq_setdelegate(HSQUIRRELV v,int idx);
SQRESULT sq_getdelegate(HSQUIRRELV v,int idx);
```

A new array is created calling `sq_newarray`, the function pushes a new array in the stack; if the parameters size is bigger than 0 the elements are initialized to null.

```
void sq_newarray (HSQUIRRELV v,int size);
```

To append a value to the back of the array

```
SQRESULT sq_arrayappend(HSQUIRRELV v,int idx);
```

To remove a value from the back of the array

```
SQRESULT sq_arraypop(HSQUIRRELV v,int idx,int pushval);
```

To resize the array

```
SQRESULT sq_arrayresize(HSQIRRELV v,int idx,int newsize);
```

To retrieve the size of a table or an array you must use `sq_getsize()`

```
SQInteger sq_getsize(HSQIRRELV v,int idx);
```

To set a value in an array or table

```
SQRESULT sq_set(HSQIRRELV v,int idx);
```

To get a value from an array or table

```
SQRESULT sq_get(HSQIRRELV v,int idx);
```

To get or set a value from a table without employ delegation

```
SQRESULT sq_rawget(HSQIRRELV v,int idx);
SQRESULT sq_rawset(HSQIRRELV v,int idx);
```

To iterate a table or an array

```
SQRESULT sq_next(HSQIRRELV v,int idx);
```

Here an example of how to perform an iteration:

```
//push your table/array here
sq_pushnull(v) //null iterator
while(SQ_SUCCEEDED(sq_next(v,-2)))
{
    //here -1 is the value and -2 is the key

    sq_pop(v,2); //pops key and val before the nex iteration
}
sq_pop(v,1); //pops the null iterator
```

Userdata and UserPointers

Squirrel allows the host application put arbitrary data chunks into a Squirrel value, this is possible through the data type userdata.

```
SQUserPointer sq_newuserdata (HSQIRRELV v,unsigned int size);
```

When the function `sq_newuserdata` is called, Squirrel allocates a new userdata with the specified size, returns a pointer to his payload buffer and push the object in the stack; at this point the application can do whatever it want with this memory chunk, the VM will automatically take care of the memory deallocation like for every other built-in type. A userdata can be passed to a function or stored in a table slot. By default Squirrel cannot manipulate directly userdata; however is possible to assign a delegate to it and define a behavior like it would be a table. Because the application would want to do something

with the data stored in a userdata object when it get deleted, is possible to assign a callback that will be called by the VM just before deleting a certain userdata. This is done through the API call `sq_setreleasehook`.

```
typedef int (*SQUSERDATARELEASE)(SQUserPointer);

void sq_setreleasehook(HSQUIRRELV v,int idx,SQUSERDATARELEASE hook);
```

Another kind of userdata is the userpointer; this type is not a memory chunk like the normal userdata, but just a 'void*' pointer. It cannot have a delegate and is passed by value, so pushing a userpointer doesn't cause any memory allocation.

```
void sq_pushuserpointer(HSQUIRRELV v,SQUserPointer p);
```

Keeping object references from C

Squirrel allows to keep objects references from C; the function `sq_getstackobject()` gets a handle to a squirrel object(any type), this object can be pushed later in the stack.

```
HSQOBJECT obj;

sq_resetobject(v,&obj) //initialize the handle
sq_geststackobject(v,-2,&obj); //retrieve an object handle from the pos -2
sq_addrref(v,&obj); //adds a reference to the object

... //do stuff

sq_pushobject(v,&obj); //push the object in the stack
sq_release(v,&obj); //release the object
```

Debug Interface

The squirrel VM exposes a very simple debug interface that allows to easily built a full featured debugger. Through the function `sq_setdebughook` is possible in fact to set a callback function that will be called every time the VM executes an new line of a script or if a function get called. The callback will pass as argument the current line the current source and the current function name (if any).

```
SQUIRREL_API void sq_setdebughook(HSQUIRRELV v);
```

The following code shows how a debug hook could look like(Obviously is possible to implement this function in C as well).

```
function debughook(event_type,sourcefile,line,funcname)
{
    local fname=funcname?funcname:"unknown";
    local srcfile=sourcefile?sourcefile:"unknown"
    switch(event_type){
    case 'l':
        ::print("LINE line ["++line+"] func ["+fname+"]");
        ::print("file ["+srcfile+"]\n");
        break;
    }
```

```
        case 'c':  
            ::print("LINE line [" + line + "] func [" + fname + "]");  
            ::print("file [" + srcfile + "]\n");  
        }  
    }
```

The parameter `event_type` can be 'l' or 'c'; the first if a new line was executed the second if a function call occurred.

A full-featured debugger always allows displaying local variables and calls stack. The call stack information are retrieved through `sq_getstackinfos()`

```
int sq_stackinfos(HSQUIRRELVm v, int level, SQStackInfos *si);
```

While the local variables info through `sq_getlocal()`

```
int sq_getlocal(HSQUIRRELVm v, unsigned int level, unsigned int nseq);
```

Chapter 4. API Reference

Virtual Machine

`sq_newvm`

```
HSQUIRRELVM sq_newvm(HSQUIRRELVM friendvm, int initialstacksize);
```

creates a new instance of a squirrel VM that consists in a new stack, new root table etc..

parameters:

HSQUIRRELVM friendvm A vm that can share objects with the newone, this parameter can be NULL.

int initialstacksize the size of the stack in slots(number of objects)

return: an handle to a squirrel vm

remarks: the returned VM has to be released with `sq_releasevm`

`sq_releasevm`

```
void sq_releasevm(HSQUIRRELVM v);
```

release a squirrel VM

parameters:

HSQUIRRELVM v the target VM

`sq_suspendvm`

```
HRESULT sq_suspendvm(HSQUIRRELVM v);
```

Suspends the execution of the specified vm.

parameters:

HSQUIRRELVM v the target VM

return: an HRESULT(that has to be returned by a C function)

remarks: `sq_result` can only be called as return expression of a C function. The function will fail if the suspension is done through more C calls or in a metamethod.

eg.

```
int suspend_vm_example(HSQUIRRELVm v)
{
    return sq_suspendvm(v);
}
```

`sq_wakeupvm`

HRESULT **sq_wakeupvm**(HSQUIRRELVm v, int resumedret, int retval);

Wake up the execution a previously suspended virtual machine.

parameters:

<i>HSQUIRRELVm v</i>	the target VM
<i>int resumedret</i>	if > 1 the function will pop a value from the stack and use it as return value for the function that has previously suspended the virtual machine.
<i>int retval</i>	if >0 the function will push the return value in the stack

return: an HRESULT.

`sq_getvmstate`

int **sq_getvmstate**(HSQUIRRELVm v);

returns the execution state of a virtual machine

parameters:

<i>HSQUIRRELVm v</i>	the target VM
----------------------	---------------

return: the state of the vm encoded as integer value. The following constants are defined:
SQ_VMSTATE_IDLE, SQ_VMSTATE_RUNNING, SQ_VMSTATE_SUSPENDED
.

`sq_seterrorhandler`

void **sq_seterrorhandler**(HSQUIRRELVm v);

pops from the stack a closure or native closure and sets it as runtime-error handler.

parameters:

HSQUIRRELVm v the target VM

`sq_setforeignptr`

```
void sq_setforeignptr(HSQUIRRELVm v, SQUserPointer p);
```

Sets the foreign pointer of a certain VM instance. The foreign pointer is an arbitrary user defined pointer associated to a VM (by default is value id 0). This pointer is ignored by the VM.

parameters:

HSQUIRRELVm v the target VM

SQUserPointer p The pointer that has to be set

`sq_getforeignptr`

```
SQUserPointer sq_getforeignptr(HSQUIRRELVm v);
```

Returns the foreign pointer of a VM instance.

parameters:

HSQUIRRELVm v the target VM

return: the current VM's foreign pointer.

`sq_pushroottable`

```
SQRESULT sq_pushroottable(HSQUIRRELVm v);
```

pushes the current root table in the stack

parameters:

HSQUIRRELVm v the target VM

`sq_setroottable`

```
void sq_setroottable(HSQUIRRELVm v);
```

pops a table from the stack and set it as root table

parameters:

HSQUIRRELVM v the target VM

Compiler

<code>sq_setcompilererrorhandler</code>

void **sq_setcompilererrorhandler**(*HSQUIRRELVM v*, *SQCOMPILERERROR f*);

sets the compiler error handler function

parameters:

HSQUIRRELVM v the target VM

SQCOMPILERERROR f A pointer to the error handler function

remarks: if the parameter *f* is NULL no function will be called when a compiler error occurs

<code>sq_compile</code>

SQRESULT **sq_compile**(*HSQUIRRELVM v*, *HSQLEXREADFUNC read*, *SQUserPointer p*, const *SQChar * sourcename*, int *raiseerror*, int *lineinfo*);

compiles a squirrel program; if it succeeds, push the compiled script as function in the stack.

parameters:

HSQUIRRELVM v the target VM

HSQLEXREADFUNC read a pointer to a read function that will feed the compiler with the program.

SQUserPointer p a user defined pointer that will be passed by the compiler to the read function at each invocation.

const *SQChar * sourcename* the symbolic name of the program (used only for more meaningful runtime errors)

int *raiseerror* if this value is different than 0 the compiler error handler will be called in case of an error

int *lineinfo* if this value is different than 0 the compiled code will contain debug information (to use with the runtime debug interface)

return: a *SQRESULT*. If the `sq_compile` fails nothing is pushed in the stack.

remarks: in case of an error the function will call the function set by `sq_setcompilererrorhandler()`.

Stack Operations

`sq_push`

```
void sq_push(HSQUIRRELVM v, int idx);
```

pushes in the stack the value at the index `idx`

parameters:

HSQUIRRELVM v the target VM

int idx the index in the stack of the value that has to be pushed

`sq_pop`

```
void sq_pop(HSQUIRRELVM v, int nelementstopop);
```

pops `n` elements from the stack

parameters:

HSQUIRRELVM v the target VM

int nelementstopop the number of elements to pop

`sq_reservestack`

```
void sq_reservestack(HSQUIRRELVM v, int nsize);
```

ensure that the stack is at least of a specified size.If the stack is smaller it will automatically grow.

parameters:

HSQUIRRELVM v the target VM

int nsize required stack size

`sq_remove`

```
void sq_remove(HSQUIRRELVM v, int idx);
```

removes an element from an arbitrary position in the stack

parameters:

HSQUIRRELM *v* the target VM
int *idx* index of the element that has to be removed

<code>sq_gettop</code>

```
int sq_gettop(HSQUIRRELM v);
```

returns the index of the top of the stack

parameters:

HSQUIRRELM *v* the target VM

return: an integer representing the index of the top of the stack

<code>sq_settop</code>

```
void sq_settop(HSQUIRRELM v, int v);
```

resize the stack, if new top is bigger then the current top the function will push nulls.

parameters:

HSQUIRRELM *v* the target VM
int *v* the new top index

<code>sq_cmp</code>

```
int sq_cmp(HSQUIRRELM v);
```

pops 2 object from the stack and compares them.

parameters:

HSQUIRRELM *v* the target VM

return: > 0 if obj1>obj2
 == 0 if obj1==obj2
 < 0 if obj1<obj2

Object creation and handling

`sq_newuserdata`

```
SQUserPointer sq_newuserdata(HSQUIRRELVM v, unsigned int size);
```

creates a new userdata and pushes it in the stack

parameters:

<i>HSQUIRRELVM v</i>	the target VM
<i>unsigned int size</i>	the size of the userdata that as to be created in bytes

`sq_newtable`

```
void sq_newtable(HSQUIRRELVM v);
```

creates a new table and pushes it in the stack

parameters:

<i>HSQUIRRELVM v</i>	the target VM
----------------------	---------------

`sq_newarray`

```
void sq_newarray(HSQUIRRELVM v, int size);
```

creates a new array and pushes it in the stack

parameters:

<i>HSQUIRRELVM v</i>	the target VM
<i>int size</i>	the size of the array that as to be created

`sq_newclosure`

```
void sq_newclosure(HSQUIRRELVM v, HSQFUNCTION func, int nfreevars);
```

create a new native closure, pops n values set those as free variables of the new closure, and push the new closure in the stack

parameters:

<i>HSQUIRRELVM v</i>	the target VM
<i>HSQFUNCTION func</i>	a pointer to a native-function
<i>int nfreevars</i>	number of free variables(can be 0)

`sq_pushstring`

```
void sq_pushstring(HSQUIRRELVM v, const SQChar * s, int len);
```

pushes a string in the stack

parameters:

<i>HSQUIRRELVM v</i>	the target VM
<i>const SQChar * s</i>	pointer to the string that has to be pushed
<i>int len</i>	length of the string pointed by s

remarks: if the parameter len is less than 0 the VM will calculate the length using strlen(s)

`sq_pushfloat`

```
void sq_pushfloat(HSQUIRRELVM v, SQFloat f);
```

pushes a float into the stack

parameters:

<i>HSQUIRRELVM v</i>	the target VM
<i>SQFloat f</i>	the float that has to be pushed

`sq_pushinteger`

```
void sq_pushinteger(HSQUIRRELVM v, SQInteger n);
```

pushes a integer into the stack

parameters:

<i>HSQUIRRELVM v</i>	the target VM
<i>SQInteger n</i>	the integer that has to be pushed

`sq_pushuserpointer`

```
void sq_pushuserpointer(HSQUIRRELVM v, SQUserPointer p);
```

pushes a userpointer into the stack

parameters:

HSQUIRRELVM v the target VM
SQUserPointer p the pointer that as to be pushed

`sq_pushnull`

```
void sq_pushnull(HSQUIRRELVM v);
```

pushes a null value into the stack

parameters:

HSQUIRRELVM v the target VM

`sq_gettype`

```
SQObjectType sq_gettype(HSQUIRRELVM v, int idx);
```

the type of the value at the position idx in the stack

parameters:

HSQUIRRELVM v the target VM
int idx an index in the stack

return: the type of the value at the position idx in the stack

`sq_getsize`

```
SQObjectType sq_getsize(HSQUIRRELVM v, int idx);
```

returns the size of a value at the idx position in the stack

parameters:

HSQUIRRELVM v the target VM

int idx an index in the stack

return: the size of the value at the position *idx* in the stack

remarks: this function only works with strings, arrays and tables if the value is not one of those types the function will return -1

`sq_getstring`

```
SQRESULT sq_getstring(HSQUIRRELVM v, int idx, const SQChar ** c);
```

gets a pointer to the string at the *idx* position in the stack.

parameters:

HSQUIRRELVM v the target VM

int idx an index in the stack

*const SQChar ** c* a pointer to the pointer that will point to the string

return: a SQRESULT

`sq_getinteger`

```
SQRESULT sq_getinteger(HSQUIRRELVM v, int idx, SQInteger * i);
```

gets the value of the integer at the *idx* position in the stack.

parameters:

HSQUIRRELVM v the target VM

int idx an index in the stack

*SQInteger * i* A pointer to the integer that will store the value

return: a SQRESULT

`sq_getfloat`

```
SQRESULT sq_getfloat(HSQUIRRELVM v, int idx, SQFloat * f);
```

gets the value of the float at the *idx* position in the stack.

parameters:

HSQUIRRELVM v the target VM
int idx an index in the stack
*SQFloat * f* A pointer to the float that will store the value

return: a SQRESULT

`sq_getuserpointer`

SQRESULT **sq_getuserpointer**(HSQUIRRELVM v, int idx, SQUserPointer * p);

gets the value of the userpointer at the idx position in the stack.

parameters:

HSQUIRRELVM v the target VM
int idx an index in the stack
*SQUserPointer * p* A pointer to the userpointer that will store the value

return: a SQRESULT

`sq_getuserdata`

SQRESULT **sq_getuserdata**(HSQUIRRELVM v, int idx, SQUserPointer * p);

gets a pointer to the value of the userdata at the idx position in the stack.

parameters:

HSQUIRRELVM v the target VM
int idx an index in the stack
*SQUserPointer * p* A pointer to the userpointer that will point to the userdata buffer

return: a SQRESULT

`sq_setreleasehook`

void **sq_setreleasehook**(HSQUIRRELVM v, int idx, HSQUERDATARELEASE hook);

sets the release hook of the userdata at position idx in the stack.

parameters:

<i>HSQUIRRELVm v</i>	the target VM
<i>int idx</i>	an index in the stack
<i>HSQUUSERDATARELEASE hook</i>	a function pointer(see HSQUUSERDATARELEASE)

remarks: the function hook is called by the VM before the userdata memory is deleted.

`sq_getscratchpad`

```
SQChar * sq_getscratchpad(HSQUIRRELVm v, int minsize);
```

returns a pointer to a memory buffer that is at least as big as minsize.

parameters:

<i>HSQUIRRELVm v</i>	the target VM
<i>int minsize</i>	the requested size for the scratchpad buffer

remarks: the buffer is valid until the next call to sq_getscratchpad

Calls

`sq_call`

```
SQRESULT sq_call(HSQUIRRELVm v, int params, int retval);
```

calls a closure or a native closure.

parameters:

<i>HSQUIRRELVm v</i>	the target VM
<i>int params</i>	number of parameters of the function
<i>int retval</i>	if >0 the function will push the return value in the stack

return: a SQRESULT

remarks: the function pops all the parameters and leave the closure in the stack; if retval != 0 the return value of the closure is pushed. If the execution of the function is suspended through sq_suspendvm(), the closure and the arguments will not be automatically popped from the stack.

sq_resume

```
SQRESULT sq_resume(HSQUIRRELVM v, int retval);
```

resumes the generator at the top position of the stack.

parameters:

<i>HSQUIRRELVM v</i>	the target VM
<i>int retval</i>	if >0 the function will push the return value in the stack

return: a SQRESULT

remarks: if `retval != 0` the return value of the generator is pushed.

sq_getlocal

```
const SQChar * sq_getlocal(HSQUIRRELVM v, unsigned int level, unsigned int nseq);
```

returns the name of a local variable given stackframe and sequence in the stack and pushes its current value.

parameters:

<i>HSQUIRRELVM v</i>	the target VM
<i>unsigned int level</i>	the function index in the calls stack, 0 is the current function
<i>unsigned int nseq</i>	the index of the local variable in the stack frame (0 is 'this')

return: the name of the local variable if a variable exists at the given level/seq otherwise NULL.

sq_throwerror

```
SQRESULT sq_throwerror(HSQUIRRELVM v, const SQChar * err);
```

sets the last error in the virtual machine and returns the value that has to be returned by a native closure in order to trigger an exception in the virtual machine.

parameters:

<i>HSQUIRRELVM v</i>	the target VM
<i>const SQChar * err</i>	the description of the error that has to be thrown

return: the value that has to be returned by a native closure in order to throw an exception in the virtual machine.

`sq_getlasterror`

`SQRESULT sq_getlasterror(HSQIRRELVM v);`

pushes the last error in the stack.

parameters:

HSQIRRELVM v the target VM

return: a `SQRESULT`

remarks: the pushed error descriptor can be any valid squirrel type.

Objects manipulation

`sq_createslot`

`SQRESULT sq_createslot(HSQIRRELVM v, int idx);`

pops a key and a value from the stack and performs a set operation on the table that is at position `idx` in the stack, if the slot does not exists it will be created.

parameters:

HSQIRRELVM v the target VM

int idx index of the target object in the stack

return: a `SQRESULT`

remarks: invoke the `_newslot` metamethod in the table delegate. it only works on tables.

`sq_set`

`SQRESULT sq_set(HSQIRRELVM v, int idx);`

pops a key and a value from the stack and performs a set operation on the object at position `idx` in the stack.

parameters:

HSQIRRELVM v the target VM

int idx index of the target object in the stack

return: a SQRESULT

remarks: this call will invoke the delegation system like a normal assignment, it only works on tables, arrays and userdata.

sq_get

```
SQRESULT sq_get(HSQUIRRELM v, int idx);
```

pops a key from the stack and performs a get operation on the object at the position idx in the stack, and pushes the result in the stack.

parameters:

HSQUIRRELM v the target VM

int idx index of the target object in the stack

return: a SQRESULT

remarks: this call will invokes the delegation system like a normal dereference it only works on tables, arrays and userdata. if the function fails nothing will be pushed in the stack.

sq_rawset

```
SQRESULT sq_rawset(HSQUIRRELM v, int idx);
```

pops a key and a value from the stack and performs a set operation on the object at position idx in the stack, without employing delegation or metamethods.

parameters:

HSQUIRRELM v the target VM

int idx index of the target object in the stack

return: a SQRESULT

remarks: it only works on tables, arrays. if the function fails nothing will be pushed in the stack.

sq_rawget

```
SQRESULT sq_rawget(HSQUIRRELM v, int idx);
```

pops a key from the stack and performs a get operation on the object at position idx in the stack, without employing delegation or metamethods.

parameters:

HSQUIRRELM *v* the target VM
int *idx* index of the target object in the stack

return: a SQRRESULT

remarks: Only works on tables, arrays and userdata.

`sq_arrayappend`

SQRRESULT **sq_arrayappend**(HSQUIRRELM *v*, int *idx*);

pops a value from the stack and pushes it in the back of the array at the position *idx* in the stack.

parameters:

HSQUIRRELM *v* the target VM
int *idx* index of the target array in the stack

return: a SQRRESULT

remarks: Only works on arrays.

`sq_arraypop`

SQRRESULT **sq_arraypop**(HSQUIRRELM *v*, int *idx*);

pops a value from the back of the array at the position *idx* in the stack.

parameters:

HSQUIRRELM *v* the target VM
int *idx* index of the target array in the stack

return: a SQRRESULT

remarks: Only works on arrays.

`sq_arrayreverse`

SQRRESULT **sq_arrayreverse**(HSQUIRRELM *v*, int *idx*);

reverse an array in place.

parameters:

HSQUIRRELVm v the target VM
int idx index of the target array in the stack

return: a SQRRESULT

remarks: Only works on arrays.

`sq_arrayresize`

SQRRESULT **sq_arrayresize**(HSQUIRRELVm v, int idx, int newsize);

resizes the array at the position idx in the stack.

parameters:

HSQUIRRELVm v the target VM
int idx index of the target array in the stack
int newsize requested size of the array

return: a SQRRESULT

remarks: Only works on arrays. if newsize is greater than the current size the new array slots will be filled with nulls.

`sq_setdelegate`

SQRRESULT **sq_setdelegate**(HSQUIRRELVm v, int idx);

pops a table from the stack and sets it as delegate of the object at the position idx in the stack.

parameters:

HSQUIRRELVm v the target VM
int idx index of the target object in the stack

return: a SQRRESULT

remarks: to remove the delegate from an object is necessary to use null as delegate instead of a table.

`sq_getdelegate`

SQRRESULT **sq_getdelegate**(HSQUIRRELVm v, int idx);

pushes the current delegate of the object at the position `idx` in the stack.

parameters:

HSQUIRRELM *v* the target VM
int *idx* index of the target object in the stack

return: a SQRRESULT

sq_clone

SQRRESULT **sq_clone**(HSQUIRRELM *v*, int *idx*);

Clones the table or array at the position `idx`, clones it and pushes the new object in the stack.

parameters:

HSQUIRRELM *v* the target VM
int *idx* index of the target object in the stack

return: a SQRRESULT

sq_setfreevariable

SQRRESULT **sq_setfreevariable**(HSQUIRRELM *v*, int *idx*, int *nval*);

pops a value from the stack and sets it as free variable of the closure at the position `idx` in the stack.

parameters:

HSQUIRRELM *v* the target VM
int *idx* index of the target object in the stack
int *nval* 0 based index of the free variable(relative to the closure).

return: a SQRRESULT

sq_next

SQRRESULT **sq_next**(HSQUIRRELM *v*, int *idx*);

Pushes in the stack the next key and value of an array or table slot. To start the iteration this function expects a null value on top of the stack; at every call the function will substitute the null value with an iterator and push key and value of the container slot. Every iteration the application has to pop the previous key and value but leave the iterator(that is used as reference point for the next iteration). The function

will fail when all slots have been iterated(see Tables and arrays manipulation).

parameters:

HSQUIRRELVm v the target VM
int idx index of the target object in the stack

return: a SQRRESULT

Bytecode serialization

`sq_writeclosure`

```
SQRRESULT sq_writeclosure(HSQUIRRELVm v, SQWRITEFUNC writef, SQUserPointer up);
```

serialize(write) the closure on top of the stack, the desination is user defined through a write callback.

parameters:

HSQUIRRELVm v the target VM
SQWRITEFUNC writef pointer to a write function that will be invoked by the vm during the serialization.
SQUserPointer up pointer that will be passed to each call to the write function

return: a SQRRESULT

remarks: closures with free variables cannot be serialized

`sq_readclosure`

```
SQRRESULT sq_readclosure(HSQUIRRELVm v, SQREADFUNC readf, SQUserPointer up);
```

serialize(read) the closure on top of the stack, the source is user defined through a write callback.

parameters:

HSQUIRRELVm v the target VM
SQREADFUNC readf pointer to a read function that will be invoked by the vm during the serialization.
SQUserPointer up pointer that will be passed to each call to the read function

return: a SQRESULT

Raw object handling

`sq_getstackobj`

SQRESULT **sq_getstackobj**(HSQUIRRELVM *v*, int *idx*, HSQOBJECT * *po*);

gets an object from the stack and stores it in a object handler.

parameters:

<i>HSQUIRRELVM v</i>	the target VM
<i>int idx</i>	index of the target object in the stack
<i>HSQOBJECT * po</i>	pointer to an object handler

return: a SQRESULT

`sq_pushobject`

void **sq_pushobject**(HSQUIRRELVM *v*, HSQOBJECT *obj*);

push an object referenced by an object handler into the stack.

parameters:

<i>HSQUIRRELVM v</i>	the target VM
<i>HSQOBJECT obj</i>	object handler

`sq_addref`

void **sq_addref**(HSQUIRRELVM *v*, HSQOBJECT * *po*);

adds a reference to an object handler.

parameters:

<i>HSQUIRRELVM v</i>	the target VM
<i>HSQOBJECT * po</i>	pointer to an object handler

`sq_release`

```
void sq_release(HSQUIRRELM v, HSQOBJECT * po);
```

remove a reference from an object handler.

parameters:

HSQUIRRELM v the target VM

*HSQOBJECT * po* pointer to an object handler

`sq_resetobject`

```
void sq_resetobject(HSQUIRRELM v, HSQOBJECT * po);
```

resets(initialize) an object handler.

parameters:

HSQUIRRELM v the target VM

*HSQOBJECT * po* pointer to an object handler

remarks: Every object handler has to be initialized with this function.

Debug interface

`sq_setdebughook`

```
void sq_setdebughook(HSQUIRRELM v);
```

pops a closure from the stack and sets it as debug hook. on.

parameters:

HSQUIRRELM v the target VM

remarks: In order to receive a 'per line' callback, it is necessary to compile the scripts with the line informations. Without line informations activated, only the 'per call' callback will be invoked.

`sq_stackinfos`

```
SQRESULT sq_stackinfos(HSQUIRRELM v, int level, SQStackInfos * si);
```

retrieve the calls stack informations of a certain level in the calls stack.

parameters:

<i>HSQUIRRELV</i> <i>v</i>	the target VM
<i>int level</i>	calls stack level
<i>SQStackInfos</i> * <i>si</i>	pointer to the <i>SQStackInfos</i> structure that will store the stack informations

return: a *SQRESULT*.

Index

Symbols

?: operator, 10

A

API

- sq_addrf, 54
- sq_arrayappend, 50
- sq_arraypop, 50
- sq_arrayresize, 51
- sq_arrayreverse, 50
- sq_call, 46
- sq_clone, 52
- sq_cmp, 40
- sq_compile, 38
- sq_createslot, 48
- sq_get, 49
- sq_getdelegate, 51
- sq_getfloat, 44
- sq_getforeignptr, 37
- sq_getinteger, 44
- sq_getlasterror, 48
- sq_getlocal, 47
- sq_getscratchpad, 46
- sq_getsize, 43
- sq_getstackobj, 54
- sq_getstring, 44
- sq_gettop, 40
- sq_gettype, 43
- sq_getuserdata, 45
- sq_getuserpointer, 45
- sq_getvmstate, 36
- sq_newarray, 41
- sq_newclosure, 41
- sq_newtable, 41
- sq_newuserdata, 41
- sq_newvm, 35
- sq_next, 52
- sq_pop, 39
- sq_push, 39
- sq_pushfloat, 42
- sq_pushinteger, 42
- sq_pushnull, 43
- sq_pushobject, 54
- sq_pushroottable, 37
- sq_pushstring, 42
- sq_pushuserpointer, 43
- sq_rawget, 49
- sq_rawset, 49
- sq_readclosure, 53
- sq_release, 54
- sq_releasevm, 35
- sq_remove, 39
- sq_reservestack, 39

- sq_resetobject, 55
- sq_resume, 47
- sq_set, 48
- sq_setcompilererrorhandler, 38
- sq_setdebughook, 55
- sq_setdelegate, 51
- sq_seterrorhandler, 36
- sq_setforeignptr, 37
- sq_setfreevariable, 52
- sq_setreleasehook, 45
- sq_setroottable, 37
- sq_settop, 40
- sq_stackinfos, 55
- sq_suspendvm, 35
- sq_throwerror, 47
- sq_wakeupvm, 36
- sq_writeclosure, 53
- arithmetic operators, 10
- array constructor, 14
- arrays, 15
- assert, 21
- assignment(=), 10

B

- bitwise Operators, 12
- block statement, 6
- break statement, 8

C

- chcode2string, 21
- clone, 14
- collect_garbage, 21
- comma operator, 12
- continue statement, 8

D

- data types, 3
- delegate, 13
- delegation, 18
- do/while statement, 7

E

- execution context, 4
- expression statement, 9
- expressions, 10

F

- for loop, 7
- foreach loop, 8
- free variables, 17
- function declaration, 9
- functions, 15
 - calls, 16
 - declaration, 15

G

- I**
- generators, 17
 - getroottable, 21
- K**
- keywords, 2
- L**
- literals, 2
 - local variables declaration, 9
 - logical operators, 11
- M**
- metamethods, 18
 - _add, 19
 - _call, 20
 - _clone, 20
 - _cmp, 20
 - _div, 20
 - _get, 19
 - _modulo, 20
 - _mul, 20
 - _newslot, 19
 - _nexti, 21
 - _set, 19
 - _sub, 19
 - _typeof, 20
 - _unm, 20
- N**
- new slot(<-), 10
- O**
- operators, 2, 10
 - operators precedence, 12
- P**
- print, 21
- R**
- relational operators, 11
 - return statement, 8
- S**
- setdebughook, 21
 - seterrorhandler, 21
 - statements, 6
 - switch statement, 7
- T**
- table constructor, 12
 - tables, 14
 - slot creation, 14
 - slot deletion, 15
 - tail recursion, 17
 - throw statement, 9
 - try/catch statement, 9
 - typeof operator, 11
- V**
- variables, 4
- W**
- while statement, 6
- Y**
- yield statement, 9