

Project Documentation

Overview

This project is a solution that integrates the pumped oil orders from the OilMat system with workshop ERP solutions in order to free the workshop manager from the work of ensuring that the corresponding orderline is added to the customer invoice. Components:

- A flask api to handle the incoming orders.
- A worker that consumes the orders and send them to workshop ERP solution.
- Queues that handles communication between api and worker

In addition there will be a number of changes in both the workshop and ILX management apis to allow users to configure and handle each integration. Philip will specify these changes in a separate doc referenced from here.

Workshop integration configuration and handling:

- Type of ERP system
- User credentials
- Active indicator
- Activate/deactivate integration

Management api:

- Get health overview for integrations
- Start/Stop integration api
- Start/Stop integration worker
- Kill integration api.

The solution is build using the selenium package for python and the chrome webdriver.

Currently its planed to start a separate flask server/api and consumer pr workshop ERP integration. This ensures that problems concerning one workshop wont affect others and allow for easy scalability.

The application provides the below endpoints to interact with the workshop ERP system:

GET /alive

Checks if the API is alive and if the worker is running.

Response:

- **200 OK** with a JSON object indicating the status of API + worker and the workshop that the api instance is serving.

PUT /kill

Kills an api instance.

Response:

- **200 OK** with a JSON object indicating whether the API instance was running or not.

GET /queue?type={type}

The type parameter can have the value **task** and **error**. Retrieves the current tasks in the specified queue type.

Response:

- **200 OK** with a JSON object containing the list of tasks in the queue and the length of the queue.
- **400** wrong queue type

PUT /clear_queue

The type parameter can have the value **task** and **error**. Clears all in the specified queue type.

Response:

- **200 OK** with a JSON object indicating the queue has been cleared.
- **400** wrong queue type

PUT /start_worker

Starts the worker thread to process tasks in the queue.

Response:

- **200 OK** with a JSON object indicating the worker has started.

PUT /stop_worker

Stops the worker thread.

Response:

- **200 OK** with a JSON object indicating the worker has stopped.

POST /create

Adds a task to create an order line to the queue.

Request Body:

```
{
  "workshop": "Bennys Auto",
  "worksheet": "558",
  "product_nr": "10",
  "product_amount": "5",
  "unique_id": "xxx",
  "username": "admin",
```

```
    "password": "gygag",
  }
```

Response:

- **200 OK** with a JSON object indicating the task has been added to the queue.
- **400 Bad Request** if any required parameters are missing.

GET /get_order_status?unique_id={id}

Get the current status of a placed order, a successful order will go through the following states:

- preceived
- processing
- completed

There are 2 error states:

- bad request. Set in case the body of a create request contains wrong or missing parameters.
- failed. All other error scenarios.

Response:

- **200 OK** with a JSON object indicating the task has been added to the queue.
- **400** order_id missing.
- **404** order_id not found

Files and Directories

requirements.txt -- all necessary dependencies

Readme.md -- This doc

erp_integrations/ -- contains all selenium code

au2office/

create_erp_orderline.py

admanager/

create_erp_orderline.py

workshops/ -- One subdirectory for each integrated workshop containing queues and status db

workshop1/

order_status.db

create_orderline.log

api.log

_task_queue/

_error_queue/

workshop2/

workshopN/

flask_api/ -- api code

app.py

order_status_db.py

chromedriver/

Install

Test

The test setup is located under the ilx-admin user in C:\Users\ilx-admin\LHP\python_selenium>.

The dependencies are installed in a venv virtual environment activated by:

```
python_selenium> .\virtualenv\Scripts\activate
```

Dependencies

Install the dependencies using pip:

```
pip install -r requirements.txt
```

Start Integration

During normal operation an ERP integration needs to be started/restarted in the following situations:

1. A new integration is configured in gui
2. An existing integration is reconfigured in gui
3. Its specifically requested in the ILX Systems admin gui
4. The backend server is restarted. All configured active ERP integrations must be started automatically at server startup

Shell command to start an api instances

```
python api.py port workshop integration-type
```

Example

```
python3 app.py 5000 'hosses' 'admanager'
```