



Search millions of products, datasheets, and more $\boldsymbol{\epsilon}$



 $\stackrel{\circ}{=}$

Ultrasonic Sensors: How They Work (and How to Use Them with Arduino)

4 Apr 2018



LATEST NEWS

Application of UWB

This article ex...

We've updated our privacy policy. Please take a moment to review these changes. By clicking I Agree to Arrow Electronics Terms Of Use and have read and understand the Privacy Policy and Cookie Policy.

READ MORE

ACCEPT TERMS



SEE SHORT POLICY ▶



• LIUITE UELECTION AND ALEA SENSOIS. HAITE

Search millions of products, datasheets, and more a

Jeremy S. Cook Sensors based on magnetic fields

has a

Ultrasonic sensors

BSME from

Clemson University.

How Does an Ultrasonic Sensor Work?

worked for 10 years in

Ultrasonic sensors work by emitting sound waves at a frequency too high for humans to hear. They then wait for the manufacturing do be reflected back, calculating

automation distance based on the time required. This is similar to how radar measures the time He now writes it takes a radio wave to return after

for a variet...

hitting an object.

Read more

While some sensors use a separate sound emitter and receiver, it's also possible to combine these into one package device, having an ultrasonic element alternate between emitting and receiving signals. This type of sensor can be manufactured in a smaller package than with separate elements, which is convenient for applications where size is at a premium.

While radar and ultrasonic sensors can be used for some of the same purposes, sound-based sensors are readily

In-depth comparison

This article wil...

9 days ago

We've updated our privacy policy. Please take a moment to review these changes. By clicking I Agree to Arrow Electronics Terms Of Use and have read and understand the Privacy Policy and Cookie Policy.

READ MORE

ACCEPT TERMS





Search millions of products, datasheets, and more a

distance from your sensor, this can be calculated based on this formula:

Distance = ½ T x C

(T = Time and C = the speed of sound)

At 20°C (68°F), the speed of sound is 343 meters/second (1125 feet/second), but this varies depending on temperature and humidity.

Specially adapted ultrasonic sensors can also be used underwater. The speed of sound, however, is 4.3 times as fast in water as in air, so this calculation must be adjusted significantly.

What are Ultrasonic Sensors Used For?

So where can we use these sensors? Robot navigation comes to mind, as well as factory automation. Water-level sensing is another good use, and can be accomplished by positioning one sensor above a water surface. Another aquatic application is to use these sensors to "see" the bottom of a body of water

We've updated our privacy policy. Please take a moment to review these changes. By clicking I Agree to Arrow Electronics Terms Of Use and have read and understand the Privacy Policy and Cookie Policy.

READ MORE

ACCEPT TERMS






Search millions of products, datasheets, and more a

retations between the two.

Flowrate accuracy can be increased by using data from multiple ultrasonic elements, giving results accurate to within a fraction of a percent.

Incorporating Ultrasonic Sensors into <u>Arduino</u> Projects



We've updated our privacy policy. Please take a moment to review these changes. By clicking I Agree to Arrow Electronics Terms Of Use and have read and understand the Privacy Policy and Cookie Policy.

READ MORE

ACCEPT TERMS





Search millions of products, datasheets, and more a

Gather the components (Arduino, HC-SR04, wires, and breadboard) and go into the Arduino IDE and install the "NewPing" sensor library.

SEE RELATED PRODUCT

Arduino Nano | A000005

Arduino S.r.l. Embedded System

Development Boards and Kits

Once installed, there will be a number of new example sketches you can choose from.

Open up the "NewPing3Sensors" sketch.

Attach pins from your Arduino to the HC-SR04, as defined in the program, adding ground and 5V from the Arduino.

Send the program to your dev board, and then open up a serial monitor at 115200 baud. You'll see a distance reading when you put something in front of it. Note that it reads "0" when it doesn't properly read a distance.

Try experimenting with different shapes and materials to see what works and

We've updated our privacy policy. Please take a moment to review these changes. By clicking I Agree to Arrow Electronics Terms Of Use and have read and understand the Privacy Policy and Cookie Policy.

READ MORE

ACCEPT TERMS



Search millions of products, datasheets, and more a

Arrow Newsletters: Subscribe Now and Save 10%

Sign Up

Connect with Electronic Components









Contact Us

Contact and Support

Programs and Partners

Contact Arrow

ArrowSphere

FAOs

MyArrow™

We've updated our privacy policy. Please take a moment to review these changes. By clicking I Agree to Arrow Electronics Terms Of Use and have read and understand the Privacy Policy and Cookie Policy.

READ MORE

ACCEPT TERMS





Search millions of products, datasheets, and more $\boldsymbol{\epsilon}$

Development Nits and Tools Infilieon Technologies Ad

Sensors Molex

Relays onsemi

Memory Silicon Labs

Resistors STMicroelectronics

Wire and Cable TE Connectivity

All Categories Verticals & Trends

Aerospace & Defense

Automotive/Transportation

Energy Storage Systems

EV Charging

Green Infrastructure

Medical & Healthcare

Renewable Energy

We've updated our privacy policy. Please take a moment to review these changes. By clicking I Agree to Arrow Electronics Terms Of Use and have read and understand the Privacy Policy and Cookie Policy.

READ MORE

ACCEPT TERMS

Search millions of products, datasheets, and more a

140 77 31 00111

Connect with Arrow







© 2025 Arrow Electronics, Inc. All rights reserved

Privacy Center

Terms and Conditions

Cookie Policy

We've updated our privacy policy. Please take a moment to review these changes. By clicking I Agree to Arrow Electronics Terms Of Use and have read and understand the Privacy Policy and Cookie Policy.

READ MORE

ACCEPT TERMS