



SOVEREIGN AI WORKFORCE

Design System v1.0

"Mission Control for a Digital Workforce"

Boukhalifa Fateh Abderrahim

Sovereign AI Engineer · USTHB · Algeria dz

USAII Global AI Hackathon 2026

CONFIDENTIAL — DESIGN SYSTEM DOCUMENTATION

1. Brand Identity

Brand Name & Mark

Sovereign AI Workforce is a compound name that signals both governance and capability. 'Sovereign' communicates authority, autonomy, and national-scale ambition. 'AI Workforce' is literal and direct — this platform deploys workers, not features.

Logomark — The Octagram (◆)

The primary mark is the ◆ character (Unicode U+25C8, White Diamond Containing Black Small Diamond). It is chosen for five reasons:

- **Precision:** The nested geometric form communicates layered intelligence — an outer structure containing an inner core, mirroring the architecture of an orchestrated multi-agent system.
- **Scalability:** The vector form renders cleanly from 12px favicons to full-bleed print.
- **Distinctiveness:** No major competitor uses this mark. It is immediately ownable.
- **Meaning:** The diamond's four compass points map to the four pillars of the platform: Memory, Execution, Oversight, and Intelligence.
- **Character:** Used in combination with the wordmark or standalone as an icon, app icon, or watermark.

Wordmark

SOVEREIGN AI WORKFORCE — set in all caps, Arial Bold. The full wordmark is used in documents and formal communications. The short-form mark 'SAW' or '◆ SAW' is used in product UI, headers, and compact contexts.

Brand Taglines

- **Primary:** "Your workforce. Amplified."
- **Technical:** "Orchestrated AI agents. Human-approved outcomes."
- **Government/Enterprise:** "Sovereign intelligence for sovereign organizations."
- **Hackathon/Demo:** "13 hours reclaimed. Every week. Automatically."

2. Brand Personality

The Sovereign AI Workforce brand occupies a deliberate position: not a consumer AI product (warm, chatty, approachable) and not a legacy enterprise platform (cold, institutional, feature-list-driven). It is what a mission-critical operations room would feel like if it were designed by engineers who also cared about beauty.

Trait	Expression	Where Applied
Authoritative	Confident in its capabilities without arrogance. Speaks in facts and outcomes, not hype.	Primary voice in all communications
Precise	Every element — label, measurement, data point — is exact. No vague language.	UI copy, error messages, system feedback
Trustworthy	Human-in-the-loop by design. Transparent about what agents can and cannot do.	Approval workflows, status indicators
Ambitious	Positioned for national-scale impact. References sovereign infrastructure, not departmental tools.	Marketing, investor materials
Calm under load	The UI remains quiet and organized even when 6 agents are running in parallel.	Dashboard, workflow views
Culturally grounded	Built from and for the MENA region. Arabic-ready, data-sovereign, globally competitive.	All localized content

3. Visual Principles

Principle 1 — Signal Over Noise

Every pixel on screen must earn its presence. The UI is built on a dark foundation that recedes, allowing data, status, and agent outputs to command attention. No decorative elements that don't carry meaning. No colors without semantic purpose.

Principle 2 — Trust Through Transparency

The system communicates its state at all times. Which agents are running, which are idle, which have flagged a concern — these are not hidden in logs. They surface in the UI as first-class information. The monitoring layer is visible, not buried.

Principle 3 — Hierarchy of Urgency

The color system is built around a hierarchy of attention. Amber for action-required. Blue for information. Green for success. Red for critical. Neutral for context. A user who glances at the dashboard for three seconds should know what needs their attention.

Principle 4 — Density Without Clutter

Enterprise users need information density. The grid system and component library are designed for maximum information per viewport without triggering cognitive overload. White space is used to separate semantic groups, not to fill emptiness.

Principle 5 — Consistency as Confidence

A system that looks consistent feels reliable. Every spacing value, every border radius, every shadow level derives from a shared token system. No one-off values. No magic numbers. The consistency of the UI is a proxy for the consistency of the platform's behavior.

Principle 6 — Motion with Purpose

Animation is used only where it communicates system state: agent streaming (typing animation), pipeline progression (sequential activation), approval gate (attention-drawing pulse). No animation for aesthetics alone.

4. Color System

The color system is semantic first. Every color has a job. The dark foundation (Deep Navy) recedes. The Sovereign Amber activates. The Signal Blue informs. Status colors — green, red, yellow, purple, cyan — each own a single meaning and never deviate from it.

4.1 Foundation — Deep Navy Scale

The primary background palette. 900 is the deepest background. 800/700 are surface layers. 500/400/300 are borders and dividers. 200/100/050 are text on dark surfaces.

	Hex	Token Name	Usage
	#04060F	navy-900	Deepest background — body, app shell, hero sections
	#080D1A	navy-800	Primary panels, sidebar, card backgrounds
	#0C1220	navy-700	Secondary panels, elevated surfaces
	#0F1628	navy-600	Input backgrounds, subtle surface variation
	#1A2540	navy-500	Primary borders, dividers, separator lines
	#243050	navy-400	Secondary borders, inactive elements
	#2D3D65	navy-300	Subtle borders, skeleton loading states
	#4A5E8A	navy-200	Disabled text on dark surfaces
	#7A90B8	navy-100	Secondary text on dark surfaces
	#C7D4EC	navy-050	Primary text on dark surfaces

4.2 Sovereign Amber — Primary Accent




Used exclusively for: primary calls to action, the logomark, active navigation states, 'action required' prompts, the approval gate, and data highlight values. Never used decoratively.

	Hex	Token Name	Usage
	#B45309	amber-600	Pressed state for primary buttons, strong emphasis
	#D97706	amber-500	Primary CTA buttons, the logomark, active nav

	#F59E0B	amber-400	Hover state, icon fills, KPI values on dark bg
	#FBB935	amber-300	Data highlight on dark, secondary accent
	#FDE68A	amber-200	Light background tint for amber contexts
	#FEF3C7	amber-100	Very subtle amber wash on light surfaces

4.3 Signal Blue — Information & Links


Used for: informational UI, agent identifiers, hyperlinks, focus rings, non-urgent notifications, and the primary 'in progress' state. Distinct from amber (action) — blue means 'here is information'.

Hex	Token Name	Usage
	#1D4ED8 blue-600	Pressed links, strong blue emphasis
	#2563EB blue-500	Links, info badges, agent color (Email, Research)
	#3B82F6 blue-400	Hover blue, secondary agent indicators
	#60A5FA blue-300	Light blue text on dark, streaming dots
	#BFDDBFE blue-200	Blue tint backgrounds on light surfaces
	#EFF6FF blue-100	Very subtle blue wash, focus ring fill

4.4 Status Colors

Each status color owns exactly one semantic meaning. Do not use green for branding. Do not use red for emphasis. These are reserved exclusively for system state communication.

Hex	Token Name	Usage
	#10B981 green-500	SUCCESS — task completed, agent done, system healthy
	#34D399 green-400	Active pulse, running indicator, positive trend
	#D1FAE5 green-100	Success background tint, light mode success
	#EF4444 red-500	ERROR / CRITICAL — agent failed, system error, block
	#F87171 red-400	Error text, warning border, destructive hover
	#FEE2E2 red-100	Error background tint, critical alert fill

	#EAB308	yellow-500	WARNING — compliance flag, needs review, caution
	#FEF9C3	yellow-100	Warning background tint
	#8B5CF6	purple-500	AGENT — Calendar Agent, Compliance Agent color
	#06B6D4	cyan-500	AGENT — Meeting Notes Agent, special workflow color

4.5 Neutral Scale

Used in light-mode contexts, document surfaces, data tables, and any elements where the dark navy foundation is not appropriate. The complete neutral scale allows the design to operate across both dark and light contexts.

Hex	Token Name	Usage
#FFFFFF	white	Pure white — modal backgrounds, card surfaces (light)
#F8FAFC	gray-50	Page background in light mode, zebra-stripe tables
#F1F5F9	gray-100	Input backgrounds, secondary surface (light)
#E2E8F0	gray-200	Borders on light surfaces, dividers
#CBD5E1	gray-300	Disabled borders, skeleton loaders (light)
#94A3B8	gray-400	Placeholder text, disabled text
#64748B	gray-500	Secondary body text, metadata, timestamps
#475569	gray-600	Secondary headings (light mode)
#334155	gray-700	Primary body text (light mode)
#1E293B	gray-800	Primary headings (light mode)
#0F172A	gray-900	Maximum contrast text (light mode)

5. Typography System

Type Stack

The system uses a two-family stack: a humanist sans-serif for all UI text, and a monospace family for data, code, metrics, and system outputs. A third display face is optionally used for marketing and cover materials only.

Role	Family + Weight	When to Use
Display / Hero	Space Grotesk 800–900	Page titles, metric values, hero numbers, the logomark wordmark
UI Body	Sora (primary) / Inter (fallback)	All UI labels, navigation, body copy, descriptions, placeholder text
Data / Code / Timestamps	JetBrains Mono 400–600	Hex values, token IDs, API endpoints, latency values, timestamps, code blocks
Arabic / RTL	IBM Plex Sans Arabic 300–800	All Arabic-language content, RTL layouts

Type Scale

All sizes are defined in a ratio-based scale (1.25 — Major Third). Every size corresponds to a specific semantic role. Do not deviate from the scale for custom sizing.

Property	Value	Usage / Notes
display-2xl	64px / 72px / 900 / -2px	Hero titles, landing page numerals, cover headlines
display-xl	48px / 56px / 800 / -1.5px	Section hero numbers, large KPI values
display-lg	36px / 44px / 800 / -1px	Page headings (H1), modal titles
heading-xl	28px / 36px / 700 / -0.5px	Section headings (H2), panel titles
heading-lg	22px / 30px / 700 / 0	Subsection headings (H3), card titles
heading-md	18px / 26px / 600 / 0	Group labels, sidebar section titles
body-lg	16px / 24px / 400 / 0	Primary body copy, descriptions
body-md	14px / 22px / 400 / 0	Secondary body, table cells, list items

body-sm	13px / 20px / 400 / 0	Captions, helper text, form hints
label-lg	13px / 18px / 700 / 0.3px	Button labels, navigation items, badge text
label-md	12px / 16px / 700 / 0.5px	Table headers, chip labels, small badges
label-sm	11px / 14px / 700 / 0.8px	Eyebrow text, metadata tags, status labels
mono-lg	14px / 22px / 600 / 0	API values, hex codes, large metric outputs
mono-md	13px / 20px / 400 / 0	Timestamps, IDs, code blocks, latency
mono-sm	11px / 16px / 400 / 0	Micro-labels in dense data tables

6. Iconography Guidelines

Icon Set

The primary icon set is Lucide Icons (MIT license, compatible with React via lucide-react). Lucide's geometric, line-based style at 1.5px stroke weight is consistent with the platform's precision aesthetic. Solid fills are used only for active/filled states.

Icon Sizing

Property	Value	Usage / Notes
xs	12px × 12px	Meta icons inside dense table rows, status dots in compact lists
sm	16px × 16px	Inline icons in body text, small badges, breadcrumb separators
md	20px × 20px	Navigation icons, button icons, input adornments, card icons
lg	24px × 24px	Feature icons, empty state icons, section headers
xl	32px × 32px	Agent avatar icons, modal header icons, onboarding illustrations
2xl	48px × 48px	Hero illustrations, empty states, full-bleed feature icons

Agent Icon System

Each of the 7 built-in agents has an assigned emoji icon and a Lucide icon equivalent for production UI. The emoji system is used in prototypes and demos; the Lucide icons are used in the production component library.

Agent	Icon / Lucide Equiv.	Color Token	Role
Executive Agent	 / <code>Compass</code>	D97706	Orchestrator — routes tasks, synthesizes plans
Email Agent	 / <code>Mail</code>	2563EB	Reads, classifies, drafts email responses
Calendar Agent	 / <code>Calendar</code>	8B5CF6	Scheduling, meeting invites, agenda drafting
Finance Agent	 / <code>DollarSign</code>	10B981	Invoice processing, expense tracking
Reporting Agent	 / <code>BarChart3</code>	D97706	Data synthesis, executive report generation
Research Agent	 / <code>Search</code>	3B82F6	Memory retrieval, information gathering
Compliance Agent	 / <code>Shield</code>	EF4444	Policy checks, guardrail verification

7. Spacing System

All spacing values derive from a base-4 scale. Every layout decision — padding, margin, gap, inset — must use a value from this scale. Do not use arbitrary values.

Property	Value	Usage / Notes
space-0	0px	No spacing — flush edges, full-bleed elements
space-px	1px	Border width, hairline separators
space-0.5	2px	Micro-padding inside dense badges
space-1	4px	Minimal padding — icon-to-label gap, chip internals
space-1.5	6px	Badge padding, tight inline spacing
space-2	8px	Small padding — icon button inner, compact list item gap
space-2.5	10px	Narrow padding for dense components
space-3	12px	Standard inner padding for compact inputs and buttons
space-4	16px	Standard padding — card bodies, input fields, list rows
space-5	20px	Modal padding, form section gaps
space-6	24px	Panel padding, section internal spacing
space-8	32px	Panel-to-panel gap, section header bottom margin
space-10	40px	Between major sections in a scrollable view
space-12	48px	Top/bottom padding for hero sections
space-16	64px	Major layout dividers, full-height padding
space-20	80px	Page-level vertical rhythm between sections
space-24	96px	Generous hero vertical padding

Semantic Spacing Aliases

Property	Value	Usage / Notes
component-xs	space-1.5 (6px)	Padding inside badges, chips, compact tags
component-sm	space-2.5 (10px)	Padding inside compact buttons and inputs
component-md	space-3-4 (12-16px)	Standard button, input, row padding

component-lg	space-5 (20px)	Large button padding, modal body padding
gap-xs	space-2 (8px)	Gap between sibling inline elements
gap-sm	space-3 (12px)	Gap inside card headers, row icon-label pairs
gap-md	space-4 (16px)	Grid gap in dense panels
gap-lg	space-6 (24px)	Card-to-card gap, main content column gap
gap-xl	space-8 (32px)	Section-to-section gap
panel-padding	space-5-6 (20-24px)	Inner padding for all panel/card components
page-margin	space-8-12 (32-48px)	Horizontal page gutters

8. Grid System

12-Column Fluid Grid

The layout system uses a 12-column fluid grid with fixed gutters and responsive breakpoints. Column count and gutter size adapt at each breakpoint.

Breakpoint	Range	Columns	Gutter	Margin	Notes
xs	< 480px	4 cols	8px gutter	0px margin	Mobile portrait — single stack
sm	480–767px	4 cols	12px gutter	16px margin	Mobile landscape — single stack
md	768–1023px	8 cols	16px gutter	24px margin	Tablet — sidebar collapses to bottom nav
lg	1024–1279px	12 cols	20px gutter	32px margin	Small desktop — sidebar opens
xl	1280–1535px	12 cols	24px gutter	40px margin	Standard desktop — full layout
2xl	≥ 1536px	12 cols	24px gutter	auto margin	Wide screen — max-width 1400px, centered

Layout Templates

Template Name	Column Allocation	Used In
App Shell	Sidebar (220px fixed) + Main	Primary authenticated layout for all views

	content area (fluid)	
Dashboard	12-col: 3+3+3+3 KPI row / 8+4 content split / 12 full-width tables	Dashboard view
Workflow View	12-col: 12 trigger / 12 pipeline / 12 step outputs (stacked)	Live workflow orchestration
Memory View	12-col: 12 search / 6+6 memory grid	Memory & RAG
Builder	12-col: 6+6 role card grid / 12 provision log	Workforce Builder
Intel View	12-col: 12 data / 6+6 insight card grid	Business Intelligence
Agent Builder	12-col: 12 form (left 7) + preview (right 5)	Custom agent creation
Monitoring	12-col: 3+3+3+3 health / 12 run log table	Monitoring & observability

9. Elevation & Shadows

Because the platform uses a dark foundation, traditional light-from-above box-shadow elevation is replaced by a border-and-glow system. Higher elevation is communicated through a brighter border and a colored ambient glow, not a dropping shadow.

Property	Value	Usage / Notes
elevation-0	No border, no glow	Flat element embedded in the page — background panels, table rows
elevation-1	border: 1px solid navy-500 (#1A2540)	Default card, panel, sidebar — the base resting surface
elevation-2	border: 1px solid navy-400 (#243050)	Hovered card, active panel, focused section
elevation-3	border: 1px solid navy-300 (#2D3D65) + box-shadow: 0 4px 24px rgba(0,0,0,0.4)	Modal backdrop surface, agent output panels
elevation-focus	border: 1.5px solid amber-400 (#F59E0B) + box-shadow: 0 0 0 3px rgba(245,158,11,0.2)	Focused input, selected card, active approval gate
elevation-alert	border: 1.5px solid red-500 (#EF4444) + box-shadow: 0 0 0 3px rgba(239,68,68,0.15)	Error state, compliance blocked, critical notification
elevation-glow	border: 1px solid amber-500 + box-shadow: 0 0 32px rgba(245,158,11,0.15)	Active workflow run, streaming agent panel

Border Radius System

Property	Value	Usage / Notes
radius-none	0px	Full-bleed images, map overlays, edge-to-edge table cells
radius-sm	4px	Chips, badges, small tags, inline code blocks
radius-md	8px	Buttons, inputs, compact cards, dropdown menus
radius-lg	12px	Standard cards, panels, navigation items
radius-xl	16px	Large cards, modals, step panels, workflow output boxes
radius-2xl	20px	Top-level surface containers (main card shell)

radius-full	9999px	Avatar circles, status dots, toggle pills, numeric badges
-------------	--------	---

10. Component Library — Overview

The component library is organized into six layers: Primitives (atoms: color, type, space), Elements (molecules: buttons, inputs, badges), Patterns (organisms: cards, tables, forms), Layouts (templates: dashboard, workflow, monitoring), Feedback (toasts, loading, error states), and Page-level templates.

Layer	Components	Role
Primitives	Color tokens, type scale, spacing, radius, shadow	Design system foundation, not directly rendered
Elements	Buttons, inputs, selects, checkboxes, badges, chips, avatars, icons	Atomic UI building blocks
Patterns	Cards, tables, panels, forms, lists, breadcrumbs, modals	Composed of elements
Widgets	KPI cards, progress bars, mini-charts, agent rows, activity feed, pipeline track	Dashboard-specific data display
Feedback	Toasts, spinners, skeletons, empty states, error boundaries	System state communication
Navigation	Sidebar, topbar, breadcrumbs, tabs, bottom nav (mobile)	Application-level navigation
Layouts	App shell, dashboard, workflow, memory, builder, intel, agent builder, monitoring	Page-level templates

11. Buttons

Button Variants

Variant	Tokens	When to Use
Primary	bg: amber-500 (#D97706), text: navy-900, hover: amber-600, active: amber-500+opacity	Main CTA: Run Orchestration, Approve & Execute, Save, Deploy
Secondary	bg: navy-700, border: navy-400, text: gray-100, hover: navy-600	Secondary actions: Load Example, Test Agent, View History
Ghost	bg: transparent, border: navy-400, text: gray-300, hover: navy-700	Tertiary actions: Cancel, Reset, Close, Copy
Danger	bg: red-600, text: white, hover: red-500	Destructive: Delete agent, Decommission, Clear all data
Success	bg: green-600, text: white, hover: green-500	Post-approval: Executed ✓, Saved ✓
Ghost Amber	bg: transparent, border: amber-500, text: amber-400, hover: amber-500/10	Approval gate: Approve & Execute (pre-click state)

Button Sizes

Property	Value	Usage / Notes
xs	height: 28px, padding: 6px 12px, font: label-sm (11px/700)	Icon-only compact rows, dense table actions
sm	height: 34px, padding: 8px 14px, font: label-md (12px/700)	Sidebar actions, compact panel buttons
md	height: 40px, padding: 10px	Default button size — most UI buttons

	18px, font: label-lg (13px/700)	
lg	height: 48px, padding: 12px 24px, font: body- md (14px/700)	Primary CTA buttons, approval gate, hero actions
xl	height: 56px, padding: 14px 32px, font: heading-md (18px/700)	Landing page CTAs, demo entry points

Button States

State	Trigger	Visual Treatment
Default	Resting state	Standard visual treatment per variant spec
Hover	Cursor: pointer + background shift	Darken primary 10%, lighten secondary 5%
Active	Transform: translateY(1px) + opacity 0.95	Micro-depression on click
Focus	box-shadow: 0 0 0 3px amber-400/30	Keyboard navigation — visible focus ring
Loading	Icon replaced by spinner + opacity 0.75 + cursor: wait	API call in progress
Disabled	opacity: 0.4 + cursor: not- allowed	Action unavailable (not hidden — preserves layout)
Success	Icon → checkmark + green tint (1.5s then revert)	Confirming completed action

12. Inputs

Text Input Anatomy

Element	Token Value	Notes
---------	-------------	-------

Container	bg: navy-800, border: navy-500 (1px), radius: radius-md (8px)	Resting input shell
Label	font: label-md (12px/700), color: gray-400, mb: space-1.5 (6px)	Above the input, always visible
Placeholder	color: navy-300 (#2D3D65), font: body-md (14px/400)	Disappears on focus or input
Input text	color: gray-100, font: body-md (14px/400), padding: 11px 14px	User-entered content
Focus ring	border: 1.5px solid amber-400 + box-shadow: 0 0 0 3px amber-400/20	Keyboard and click focus
Error ring	border: 1.5px solid red-500 + helper text below in red-400	Validation failure
Helper text	font: body-sm (13px/400), color: gray-400, mt: space-1.5	Hint text below field
Leading icon	size: 16px, color: gray-400, left-pad: 12px, icon shifts text right	Search, mail, calendar prefix icons
Trailing action	size: 16px button, right side of input	Clear X, copy, show/hide password

Input Variants

Type	Spec	Use Case
Text	Single line, standard	Name, title, search, email fields
Textarea	Multi-line, resize: vertical	System prompt editor, meeting notes, trigger text
Select	Dropdown, custom styled	Agent type, scenario picker, role selector, difficulty

Checkbox	16px × 16px, amber-400 check on navy-800	Multi-select filters, settings toggles
Toggle	32px × 18px pill, amber-500 when on	Feature flags, memory enabled, agent status
Radio	16px circle, amber-400 fill on selected	Single-select options in forms
Slider	amber track fill, navy thumb, range indicator	Max tokens, threshold values
Tag input	Multi-chip input, enter to add, × to remove	Memory tags, agent tool permissions
Search	Magnifier icon + clear button, instant filter behavior	Memory search, agent log filter

13. Cards

Card Anatomy

All cards share a common anatomy: a header zone, a content zone, and an optional footer zone. The header always contains a label/title and an optional action/badge. Cards never contain other cards (no nesting beyond one level).

Card Variants

Variant	Key Tokens	Used In
Base Panel	bg: navy-800, border: navy-500, radius: 14px, padding: 18-20px	Generic content container — used in all views
Result Panel	bg: gradient(navy-800→navy-600/purple), border: purple-500/30	Agent output display, memory search results
KPI Card	bg: navy-800, border-top: 3px solid [agent-color], center-aligned stat	Dashboard metric panels
Agent Card	hover: border [agent-color]/50 + translateX(-3px), cursor: pointer	Agent selector in Live Workflow view
Role Card	bg: navy-800, border: navy-500, full-width button at bottom	Workforce Builder role selection
Insight Card	border: 1px solid [severity-color]/30, severity badge top-left	Business Intelligence output
Memory Card	bg: navy-700/50, border: [type-color]/30, tags at bottom	Memory record in the Memory view
Step Panel	bg: navy-800, border-right: 3px	Agent pipeline step output in Workflow view

	solid [agent-color]	
Approval Gate	bg: amber-500/5, border: amber-500/30, full-width layout	Human approval checkpoint
Execution Banner	bg: green-500/5, border: green-500/30	Post-approval success state

Card Interaction States

State	Tokens	Notes
Resting	elevation-1 (border: navy-500)	Default display state
Hover	elevation-2 (border: navy-400) + translateX(-3px)	Pointer over clickable card
Active	elevation-focus (border: agent-color) + scale(0.99)	Card selected / being interacted with
Loading	Skeleton shimmer overlay (animation: pulse 1.5s ease-in-out infinite)	Async data loading
Streaming	border: agent-color + glow (box-shadow: 0 0 0 3px agent-color/15)	Agent output streaming live
Error	elevation-alert (border: red-500/40)	Failed agent step, API error

14. Tables

Table Anatomy

Element	Tokens	Notes
---------	--------	-------

Header row	bg: navy-700, text: gray-300 (label-md/700), border-bottom: navy-500 2px	Column identifiers — sticky on scroll
Body row (even)	bg: navy-800	Default row
Body row (odd)	bg: navy-750 (rgba overlay)	Zebra striping for readability in dense tables
Row hover	bg: navy-600/40 + cursor: pointer (if clickable)	Hovered row highlight
Row selected	bg: amber-500/10, border-left: 3px solid amber-500	Checked/selected row state
Cell padding	padding: 10px 16px	All body cells
Cell text	font: body-md (14px/400), color: gray-200	Standard cell content
Cell subtext	font: mono-sm (11px/400), color: gray-400	Timestamps, IDs in cells
Footer row	bg: navy-700, border-top: navy- 500 2px, font: body-sm	Pagination, totals
Sort header	icon: ChevronUp/Down (16px), color: amber-400 when active	Column sort indicator

Table Variants

Variant	Description / Use Case
Data table	Full sortable, filterable, paginated — for activity logs, agent run logs, workflow history
Comparison table	Fixed columns, highlighted differentiators — for pricing, feature comparison, agent comparison
Spec table	Two-column property/value — for component specs, configuration display (this document!)
Monitoring table	Real-time updating rows, status dots, latency sparklines — for /monitoring/agent-runs

15. Dashboard Widgets

KPI Card Widget

Element	Spec
Container	height: 112px, bg: navy-800, border: navy-500, border-top: 3px solid [color], radius: 14px, padding: 18px
Icon	size: 22px, position: top-left, color: [metric-color]
Value	font: display-xl (28px/800/mono), color: [metric-color]
Label	font: label-sm (11px/700), color: gray-400, mt: 4px
Trend	font: label-sm, color: green-400 (up) or red-400 (down), leading arrow icon
Tooltip	On hover: detail popover with sparkline (last 7 data points)

Agent Activity Bar

Element	Spec
Row height	44px per agent
Agent icon	size: 16px, color: agent-color
Agent name	font: body-sm (13px/700), color: gray-100, width: 120px fixed
Role badge	font: mono-sm (10px/700), color: agent-color, border: agent-color/40
Bar track	height: 6px, bg: navy-600, radius: full, flex: 1
Bar fill	bg: agent-color, animated width on mount (0→value, 600ms ease-out)
Run count	font: mono-sm (11px), color: gray-400, width: 24px, text-right

Activity Log Feed Widget

Element	Spec
Row height	52px min

Agent icon	size: 16px, mt: 2px, flex-shrink: 0
Log text	font: body-sm (12.5px/400), color: gray-100, line-height: 1.5
Timestamp	font: mono-sm (10.5px/400), color: gray-500
Tag badge	font: mono-sm (10px), color: agent-color
Row separator	border-bottom: navy-500 1px (except last)
Empty state	Centered text + Run Workflow CTA button

Impact Summary Widget

Element	Spec
Container	bg: gradient(navy-800→navy-700), border: navy-500, radius: 14px, padding: 28px
Stat grid	3-column equal width
Stat value	font: display-xl (26px/900/Sora), color: [green/amber/blue]
Stat unit	font: label-sm (11px), color: gray-400, display block below value
Description	font: body-sm (13px), color: gray-400, center-aligned

16. Agent Status Indicators

Status Dot System

Agent status is always communicated through a combination of a colored dot + a text label. Never use color alone (accessibility). The dot pulses when the agent is actively running.

Property	Value	Usage / Notes
Idle	6px dot, gray-400, static	Agent available but not assigned to a task
Queued	6px dot, amber-400, static	Task assigned, agent waiting its turn in pipeline
Running	8px dot, green-400, pulse animation	Agent currently generating output

Streaming	8px dot, blue-400, fast pulse (0.7s)	Token-by-token output streaming to UI
Done	6px dot, green-500, static	Agent completed its step successfully
Error	6px dot, red-500, static	Agent step failed — error_message available
Blocked	6px dot, red-600, static	Compliance Agent blocked execution
Awaiting	8px dot, amber-500, slow pulse (2s)	Awaiting human approval — the gate state
Offline	6px dot, gray-600, static	Agent unavailable (system health issue)

Pipeline Node Component

In the Live Workflow view, the pipeline is rendered as a horizontal track of nodes. Each node transitions through states as the orchestration progresses.

Element	Spec
Pending node	size: 40px circle, border: 2px navy-500, icon: agent-emoji (gray-500), bg: navy-bg
Running node	border: 2px agent-color, spin-sm icon replaces emoji, glow: agent-color/20
Done node	border: 2px agent-color, icon: agent-emoji (agent-color), bg: agent-color/10
Error node	border: 2px red-500, icon:  , bg: red-500/10
Arrow connector	color: agent-color (after preceding node completes), gray-500 (pending)
Node label	font: label-sm (9.5px/600), color: gray-400 (pending) / gray-100 (active/done), max-width: 70px, text-center

17. Activity Timelines

Timeline Anatomy

The activity timeline is the audit trail for all agent actions. It appears in the Dashboard (recent feed), the Workflow view (post-run), and the Monitoring view (real-time). The design follows a left-gutter connector line pattern.

Element	Spec
Connector line	width: 1px, color: navy-500, position: 20px from left edge, height: 100%
Event dot	size: 8px circle, centered on connector line, color: agent-color, bg: navy-800
Agent icon	size: 14px, left of dot, agent emoji or Lucide icon
Event text	font: body-sm (12.5px), color: gray-100, left of connector + 20px
Timestamp	font: mono-sm (10.5px), color: gray-500, block below event text
Tag chip	font: mono-sm (9.5px), color: agent-color, border: agent-color/40, right-aligned
Row min-height	52px
Separator	border-bottom: navy-500 1px between rows (not after last)

Timeline Entry Types

Entry Type	Visual Treatment
Agent step completed	agent-color dot + step name + output preview (truncated 80 chars)
Workflow approved	amber-400 dot + 'Approved by [user]' + timestamp
Execution action taken	green-400 dot + action description (e.g. 'Calendar event created')
Execution skipped	gray-400 dot + 'Skipped: [reason]' in italic
Memory written	purple-400 dot + 'Memory record saved: [title]'
Error occurred	red-400 dot + error description + 'View details' link

System event	gray-400 dot + system message (org created, agent hired, etc.)
--------------	--

18. Navigation System

Sidebar Navigation

Element	Spec
Sidebar width	220px fixed, not collapsible on desktop (≥ 1024px)
Sidebar bg	bg: navy-800, border-right: navy-500 1px, height: 100vh, sticky
Brand mark	34px × 34px logomark cell (amber gradient bg) + wordmark, padding: 20px 14px 24px
Nav items	font: body-sm (13px/600), padding: 10px 12px, radius: 10px, gap: 2px between items
Nav item: resting	color: gray-400, bg: transparent
Nav item: hover	color: gray-100, bg: navy-700
Nav item: active	color: amber-400, bg: navy-700
Nav icon	size: 14px, width: 18px fixed, text-align: center, font-based icon
Section groups	Semantic grouping with 2px separator between groups, no visible label
Sidebar footer	margin-top: auto, padding-top: 16px, border-top: navy-500 1px
User profile	Avatar (30px circle) + name (12px/700) + subtitle (10.5px)
Tech chips	9.5px mono, navy-600 bg, navy-500 border — display active integrations
Reset button	full width, 11px, transparent, navy-500 border → red-500 on hover

Topbar

Element	Spec
Height	56px, sticky, z-index: 10
Background	bg: navy-900, border-bottom: navy-500 1px
Padding	0 32px (desktop), 0 18px (tablet)

Left: status	Pulse dot (green-400) + agent online count + divider + event label
Right: badge	Country flag + org name badge (navy-700 bg, navy-500 border, 11px mono)
Right: user chip	Avatar (26px) + name (12px white) + logout button (ghost xs)

Breadcrumbs

Element	Spec
Separator	> character, color: gray-500, mx: 8px
Inactive crumb	font: body-sm (13px/400), color: gray-400, cursor: pointer, hover: gray-200
Active crumb	font: body-sm (13px/700), color: gray-100, cursor: default
Max crumbs	3 levels; collapse middle levels with '...' if deeper

19. Mobile Components

Mobile is primarily an approval surface. Operators receive notifications, review agent outputs, and approve or reject workflow runs from their phone. The full workflow creation and monitoring experience is desktop-first.

Mobile Navigation — Bottom Tab Bar

Element	Spec
Height	72px (including safe-area inset), fixed bottom
Background	bg: navy-800, border-top: navy-500 1px, blur: backdrop-filter: blur(12px)
Tab items	5 tabs max: Dashboard, Workflow, Memory, Builder, Status
Tab resting	icon: 22px, label: 10px/700, color: gray-500, stacked
Tab active	icon: 22px (amber-400), label: 10px/700 (amber-400), dot indicator top-right of icon
Safe area	padding-bottom: env(safe-area-inset-bottom) — support iOS Home Indicator

Mobile Cards

Element	Spec
Full-bleed	Cards span full viewport width, no horizontal margin on mobile xs
Touch target	Minimum 44px × 44px tap area for all interactive elements
Swipe actions	Swipe-left on activity log rows reveals: Archive, Pin — using standard iOS/Android gesture conventions
Bottom sheet	Agent output panels render as bottom sheets (slide-up from bottom) on mobile, replacing modals

Approval Flow (Mobile-Optimized)

The approval gate is the most critical mobile interaction. The pattern is:

- Push notification: '💎 SAW — Meeting request ready for approval'
- Tap opens the app directly to the awaiting workflow run

- Scrollable step-output summary (each agent output collapsed to 2 lines, tap to expand)
- Large Approve button (height: 52px, full-width, amber-500) — bottom of screen, thumb-reachable
- Secondary: 'Reject & Discard' ghost button above Approve
- Haptic feedback on Approve tap (iOS: UIImpactFeedbackGenerator.medium)

Responsive Breakpoint Behavior

Component	Responsive Behavior
Sidebar	Desktop: fixed 220px Tablet: hidden, burger-icon toggle overlay Mobile: hidden, bottom tab nav
KPI grid	Desktop: 4-col Tablet: 2×2 grid Mobile: 1-col stack
Pipeline track	Desktop: horizontal with arrows Mobile: vertical stack with down-arrows
Memory grid	Desktop: 2-col Tablet: 2-col Mobile: 1-col
Role/Insight grid	Desktop: 2-col Tablet: 2-col Mobile: 1-col
Tables	Desktop: full columns Mobile: hide secondary columns, show card-mode per row
Modals	Desktop: centered dialog Mobile: bottom sheet

20. Accessibility Standards

Accessibility is not a checklist. It is the standard against which every component is built. The platform targets WCAG 2.1 Level AA compliance across all components, with selected WCAG 2.2 improvements applied to the most critical interaction paths (approval gate, keyboard workflow navigation).

Color Contrast Requirements

Property	Value	Usage / Notes
Body text on dark bg	gray-100 (#F1F5F9) on navy-800 (#080D1A)	Ratio: 15.4:1 — exceeds AAA
Secondary text on dark bg	gray-400 (#94A3B8) on navy-800 (#080D1A)	Ratio: 7.2:1 — meets AA
Primary button (amber bg)	navy-900 (#04060F) on amber-500 (#D97706)	Ratio: 8.1:1 — exceeds AA
Blue links on dark bg	blue-300 (#60A5FA) on navy-800 (#080D1A)	Ratio: 7.8:1 — meets AA
Error text on dark bg	red-400 (#F87171) on navy-800 (#080D1A)	Ratio: 5.4:1 — meets AA
Status dots (text label req)	Dot color + text label always paired (never color alone)	Meets 1.4.1 (non-text contrast)
Disabled state	gray-600 on navy-800	Ratio: 3.2:1 — intentionally below (indicates non-interactive)

Focus Management

Requirement	Implementation	Standard
Focus ring	3px solid amber-400 + 3px offset, visible on all interactive elements	Keyboard navigation

Focus trap	Modals and bottom sheets trap focus within – Tab cycles within the dialog only	WCAG 2.4.3
Skip links	'Skip to main content' and 'Skip to navigation' hidden links at top of page, visible on focus	WCAG 2.4.1
Focus on open	Modal/sheet open: focus moves to first interactive element or modal heading	WCAG 2.4.3
Focus on close	Modal close: focus returns to the triggering element	WCAG 2.4.3
Pipeline steps	Arrow keys navigate between pipeline nodes when container is focused	WCAG 2.1.1

Keyboard Navigation

Key	Action
Tab / Shift+Tab	Move focus forward / backward through all interactive elements
Enter / Space	Activate buttons, links, checkboxes, toggles
Escape	Close modals, bottom sheets, dropdowns, cancel operations
Arrow keys	Navigate within compound components: pipeline track, tabs, dropdown menus
Home / End	Jump to first/last in lists and table rows
Ctrl/Cmd + K	Open global command palette (future: quick agent run / search)

Screen Reader Support

Component	ARIA Implementation
Agent status	aria-label: 'Email Agent – Running' on status dot + label pair

Pipeline nodes	role='list', each node role='listitem', aria-label includes agent name and status
Streaming output	aria-live='polite' on output container – announces text completion, not every token
Approval gate	role='alertdialog', aria-describedby pointing to Executive Agent summary
Loading states	aria-busy='true' on loading regions, aria-label 'Loading agent output...'
Tables	Full th/td markup, scope attributes, caption element, sortable columns aria-sort
Forms	All inputs have associated <label>, error messages linked via aria-describedby
Icon-only buttons	aria-label with descriptive action text on all icon-only interactive elements

Motion & Animation

Concern	Implementation
prefers-reduced-motion	All CSS animations and transitions disabled when OS preference is set
Streaming animation	Replaced by static text display when reduced-motion is active
Pulse animations	All dot pulses and glow animations disabled – static color only
Page transitions	Instant view switches – no slide/fade when reduced-motion is set
Loading spinners	Replaced by static icon + text label when reduced-motion is active

Internationalization & RTL

Concern	Implementation
RTL layout	All flex/grid directions mirror for Arabic, Tamazight, and other RTL languages
Font RTL	IBM Plex Sans Arabic for all Arabic text – full weight range, excellent legibility
Number format	Eastern Arabic numerals (٠١٢٣...) available via locale switch; default Western
Date/time	Hijri calendar option alongside Gregorian for MENA government deployments
Text expansion	UI designed for 30% text expansion – Arabic translations often longer than English

Logical CSS

margin-inline-start/end, padding-inline-start/end used throughout — no hardcoded left/right



Sovereign AI Workforce — Design System v1.0

Boukhalfa Fateh Abderrahim · USTHB · Sovereign AI Engineer · Algeria dz

USAII Global AI Hackathon 2026

Design is the first layer of trust.