



DZPHARM · DZ-PHARM.VERCEL.APP

Motion & Transitions

A focused audit of the motion system: 13 keyframes (6 custom), a 3-tier animation hierarchy (toast 0.15s → palette 0.2s → modal 0.5s), 103/103 interactive elements with transitions, and the one real gap — zero prefers-reduced-motion media queries (WCAG 2.3.3 gap).

13

KEYFRAMES

103/103ELEMENTS W/
TRANSITIONS**3**

ANIMATION TIERS

0REDUCED-MOTION
QUERIES

Executive Summary

DzPharm's motion system is **more sophisticated than typical healthcare platforms**. 13 keyframes (6 custom: floatFall, leafSway, beacon-ping, dot-pulse, dz-bounce, scanLaser). A deliberate 3-tier animation hierarchy (toasts 0.15s → command palette 0.2s → modal 0.5s). 103 of 103 interactive elements have transitions using the standard `cubic-bezier(0.4, 0, 0.2, 1)` easing. The one real gap: **zero prefers-reduced-motion media queries** — a WCAG 2.3.3 (Animation from Interactions) compliance gap.

The Three Major Findings

1 · 3-tier animation hierarchy (deliberate timing)

Measured live: toast notifications use `0.15s enter`, command palette uses `0.2s enter`, modal dialogs use `0.5s enter`. This is a deliberate hierarchy — micro-interactions are fast, structural overlays are slow. The timing follows the "smaller = faster" UX principle that Linear, Vercel, and Raycast use.

2 · 6 custom keyframes for clinical-specific animations

Beyond the standard Tailwind `spin` and `pulse`, DzPharm defines 6 custom keyframes: `beacon-ping` (emergency banner pulsing dot, 2s infinite), `dot-pulse` (20+ safe-status indicators on medication rows, uses color-mix for state-safe glow), `dz-bounce` (typing indicator), `scanLaser` (barcode scanner sweep), `floatFall` (decorative leaves), `leafSway` (botanical mode decoration).

3 · Zero prefers-reduced-motion media queries (WCAG 2.3.3 gap)

A probe of all stylesheets returned 0 `@media (prefers-reduced-motion: reduce)` rules. Users who set "reduce motion" in their OS (macOS System Settings → Accessibility → Display → Reduce Motion, or Windows Settings → Accessibility → Visual Effects → Animation Effects) still receive all animations. This is a WCAG 2.3.3 (Animation from Interactions) Level AAA compliance gap.

What's Verified Working

13

KEYFRAMES DEFINED

6

CUSTOM KEYFRAMES

103/103INTERACTIVE ELEMENTS W/
TRANSITIONS**3**

ANIMATION TIERS

21+

DOT-PULSE INDICATORS

0

REDUCED-MOTION QUERIES

All interactive elements have transitions

A probe of `button, a, input, [role=combobox], [role=dialog]` returned 103 elements — all 103 have non-zero transitions. Buttons transition `color, background-color, border-color, outline-color, text-decoration-color, fill, stroke` at `0.15s cubic-bezier(0.4, 0, 0.2, 1)`. This is the Tailwind v4 default — correct and consistent.

Tailwind v4 enter/exit animation system

Two keyframes `enter` and `exit` use Tailwind's variable-driven pattern: `translate3d(var(--tw-enter-translate-x,0), var(--tw-enter-translate-y,0), 0) scale3d(...) rotate(...) filter: blur(...)`. This lets any component opt into slide/scale/rotate/blur animations by setting CSS variables — no custom keyframe per animation type. This is the modern Tailwind v4 + `tw-animate` pattern.

Emergency banner beacon-ping (rose-500 pulsing dot)

The emergency banner (SAMU 14, Protection Civile 102, Police 17, Anti-Poison) has a `beacon-ping` animation: `2s cubic-bezier(0, 0, 0.2, 1) infinite`. A rose-500 dot scales from 1 to 2.2 with opacity fade — the radar "ping" pattern. Draws attention without being distracting. This is a thoughtful use of motion for a clinical-safety UI element.

20+ dot-pulse status indicators on medication rows

The Répertoire table has 20+ `dot-pulse` spans (one per medication row, on the safe-status indicator). The keyframe uses `color-mix(in srgb, var(--state-safe) 50%, transparent)` for the box-shadow glow — a themed pulse that adapts to the active palette. This is design-system-aware animation.

What's Missing (1 Real Gap)

Zero prefers-reduced-motion media queries

A stylesheet probe returned 0 `@media (prefers-reduced-motion: reduce)` rules. The 2 infinite animations (beacon-ping, dot-pulse) and the enter/exit animations on every modal/toast/dialog will still play for users who have explicitly requested reduced motion. Fix: add a single global `@media (prefers-reduced-motion: reduce)` block that disables animations and sets transitions to 0.01s.

Two infinite animations may cause distraction

The `beacon-ping` (2s infinite) and `dot-pulse` (infinite) animations loop forever. For users with ADHD or vestibular disorders, infinite motion can cause distraction or discomfort. Once the prefers-reduced-motion media query is added, these should be set to `animation: none` or replaced with a static pulse-once-then-stop variant.

Motion Token System

The motion system is built on Tailwind v4's **variable-driven animation architecture**. Three duration tokens, three easing functions, and twelve enter/exit transform variables. Combined with the `enter` and `exit` keyframes, this lets any component opt into slide/scale/rotate/blur animations by setting CSS variables — no custom keyframe per animation type.

2.1 Duration & Easing Tokens

TOKEN	VALUE	USED FOR
<code>--default-transition-duration</code>	<code>.15s</code>	Default button/link/input transitions
<code>animate-pulse</code>	<code>2s cubic-bezier(.4, 0, .6, 1) infinite</code>	Copilot badge pulsing
<code>animate-spin</code>	<code>1s linear infinite</code>	Loading spinners
<code>--default-transition-timing-function</code>	<code>cubic-bezier(.4, 0, .2, 1)</code>	Standard easing (Tailwind default)
<code>--ease-out</code>	<code>cubic-bezier(0, 0, .2, 1)</code>	Exit animations
<code>--ease-in-out</code>	<code>cubic-bezier(.4, 0, .2, 1)</code>	Same as default (alias)

2.2 Enter/Exit Transform Variables (12 tokens)

The enter/exit keyframes are parameterized by 12 CSS variables. Setting any of these on a component opts it into that transform:

```
/* Enter variables (defaults = no transform) */
--tw-enter-opacity: 1 /* 0 = fade in from transparent */
--tw-enter-scale: 1 /* 0.95 = subtle grow */
--tw-enter-translate-x: 0 /* 10px = slide in from left */
--tw-enter-translate-y: 0 /* 10px = slide in from top */
--tw-enter-blur: 0 /* 4px = focus in from blur */
--tw-enter-rotate: 0 /* 5deg = rotate in */

/* Exit variables (same set, used for exit keyframe) */
--tw-exit-opacity: 1
--tw-exit-scale: 1
--tw-exit-translate-x: 0
--tw-exit-translate-y: 0
--tw-exit-blur: 0
--tw-exit-rotate: 0
```

2.3 The enter & exit Keyframes

The two keyframes that consume those variables:

```

/* Tailwind v4 enter keyframe - consumes the --tw-enter-* variables */
@keyframes enter {{
  0% {{
    opacity: var(--tw-enter-opacity, 1);
    transform: translate3d(var(--tw-enter-translate-x, 0), var(--tw-enter-translate-y, 0), 0)
      scale3d(var(--tw-enter-scale, 1), var(--tw-enter-scale, 1), var(--tw-enter-scale, 1))
      rotate(var(--tw-enter-rotate, 0));
    filter: blur(var(--tw-enter-blur, 0));
  }}
}}

/* Exit keyframe - consumes the --tw-exit-* variables */
@keyframes exit {{
  100% {{
    opacity: var(--tw-exit-opacity, 1);
    transform: translate3d(var(--tw-exit-translate-x, 0), var(--tw-exit-translate-y, 0), 0)
      scale3d(var(--tw-exit-scale, 1), var(--tw-exit-scale, 1), var(--tw-exit-scale, 1))
      rotate(var(--tw-exit-rotate, 0));
    filter: blur(var(--tw-exit-blur, 0));
  }}
}}

```

WHY THIS ARCHITECTURE IS EXCELLENT

Instead of defining 12 keyframes (fade-in, slide-up, slide-down, scale-in, etc.), the system defines ONE enter keyframe and ONE exit keyframe, each consuming 6 CSS variables. A component sets `--tw-enter-translate-y: 10px` and gets a slide-up animation for free. This is the modern Tailwind v4 + tw-animate pattern — used by shadcn/ui, Radix UI, and Vercel's own properties. Senior-level architecture.

— CHAPTER 03

The 3-Tier Animation Hierarchy

Measured live by capturing computed styles at 100ms after each trigger, the platform uses a **deliberate 3-tier animation hierarchy**: micro-interactions are fast, structural overlays are slow. This follows the "smaller = faster" UX principle that Linear, Vercel, and Raycast use.

0.15s	Toasts (Sonner notifications) — favorite added, response copied, feedback submitted. 0.15s enter animation + 0.15s cubic-bezier(0.4, 0, 0.2, 1) transition on color/background. Auto-dismiss after 5s.	MICRO
0.2s	Command Palette (Cmd-K) — opens with 0.2s enter animation. Slightly slower than toasts because it's a larger surface area that needs to settle. Listbox appears immediately at opacity 1.	SMALL
0.5s	Modal Dialogs (medication detail, share dialog) — opens with 0.5s cubic-bezier(0.4, 0, 0.2, 1) enter animation + 0.5s transition on color/background/border. Slowest because it's the most structural overlay — the user's attention needs to fully shift.	STRUCTURAL
2s ∞	beacon-ping (emergency banner) — 2s cubic-bezier(0, 0, 0.2, 1) infinite . Rose-500 dot scales 1 → 2.2 with opacity fade. Radar "ping" pattern for the SAMU/Police/Anti-Poison indicator.	AMBIENT
2s ∞	dot-pulse (20+ status indicators on medication rows) — infinite pulse using color-mix(in srgb, var(--state-safe) 50%, transparent) for the box-shadow glow. Themed to the active palette.	AMBIENT
2s ∞	pulse (Copilot IA badge) — 2s cubic-bezier(0.4, 0, 0.6, 1) infinite on the SVG icon. Subtle opacity pulse to indicate "AI is online".	AMBIENT

3.1 Modal Open Animation · Verified




Figure 60.1 — Medication detail modal open. Captured computed style at 100ms post-click: `animation: 0.5s cubic-bezier(0.4, 0, 0.2, 1) enter` + 0.5s transition on color/background/border. Transform started at `matrix(1, 0, 0, 1, 467.849, 0)` (translated) and settled to `none` after 500ms.

A probe at 100ms after clicking a medication row captured the modal mid-animation: `opacity: 1`, `transform: matrix(1, 0, 0, 1, 467.849, 0)`, `animation: 0.5s cubic-bezier(0.4, 0, 0.2, 1) enter`. After 1 second (animation complete), the transform settled to `none`. The 0.5s duration is appropriate for a structural overlay that requires attention shift.

3.2 Toast Enter Animation · Verified




Figure 60.2 – Sonner toast after clicking «Ajouter aux favoris». Captured at 100ms: animation: 0.15s enter + 0.15s cubic-bezier(0.4, 0, 0.2, 1) transition. Fast micro-interaction timing.

A probe at 100ms after clicking "Ajouter ABAVIR OS aux favoris" captured the toast: opacity: 1, transform: none, animation: 0.15s enter, transition: 0.15s cubic-bezier(0.4, 0, 0.2, 1). The 0.15s duration matches the default transition duration — toasts are treated as micro-interactions, not structural overlays.

3.3 Command Palette Animation · Verified




Figure 60.3 — Command palette (Cmd-K) open. Captured at 100ms: `animation: 0.2s enter`. The listbox appeared immediately at opacity 1 — only the dialog container animates.

A probe at 100ms after Ctrl+K captured the palette: `dialogOpacity: 1, dialogTransform: matrix(1, 0, 0, 1, 0, 0), dialogAnimation: 0.2s enter, listboxOpacity: 1, listboxAnimation: none`. The 0.2s duration is between toast (0.15s) and modal (0.5s) — appropriate for a power-user overlay that's structural but fast-paced.

3.4 Emergency Banner beacon-ping




Figure 60.4 — Emergency banner with beacon-ping animation. A rose-500 dot scales from 1 to 2.2 over 2s infinite, opacity fading from 0.8 to 0. The radar «ping» pattern draws attention to the SAMU/Protection Civile/Police/Anti-Poison numbers without being distracting.

The beacon-ping keyframe: `0% { opacity: 0.8; transform: scale(1); } 70%, 100% { opacity: 0; transform: scale(2.2); }`. The dot starts visible at 80% opacity, scales to 2.2× while fading to 0, then loops. This is the same pattern Slack uses for unread indicators — a single ambient pulse that doesn't demand attention but registers peripherally.

CHAPTER 04

Custom Keyframes · 6 Clinical-Specific Animations

Beyond the standard Tailwind `spin` and `pulse`, DzPharm defines **6 custom keyframes** for clinical-specific use cases. Each is purpose-built — not a generic animation library import.

4.1 The 13 Keyframes Catalog

KEYFRAME	SOURCE	DURATION	USED FOR
spin	Tailwind standard	1s linear infinite	Loading spinners
pulse	Tailwind standard	2s cubic-bezier(.4,0,.6,1) infinite	Copilot badge, online indicators
enter	tw-animate	variable	Modal/toast/palette open animations
exit	tw-animate	variable	Modal/toast/palette close animations
beacon-ping	Custom	2s cubic-bezier(0,0,.2,1) infinite	Emergency banner pulsing dot
dot-pulse	Custom	infinite	20+ safe-status indicators on medication rows
dz-bounce	Custom	—	Typing indicator (likely Copilot)
scanLaser	Custom	—	Barcode scanner sweep animation
floatFall	Custom	—	Decorative leaves falling (botanical mode)
leafSway	Custom	—	Botanical mode leaf decoration
accordion-down	tw-animate	variable	Accordion expand (Radix pattern)
accordion-up	tw-animate	variable	Accordion collapse (Radix pattern)
caret-blink	tw-animate	—	Input caret blink

4.2 The Custom Keyframes (defined in code)

BEACON-PING · EMERGENCY BANNER

```
@keyframes beacon-ping {{
  0%      {{ opacity: 0.8; transform: scale(1); }}
  70%, 100% {{ opacity: 0;   transform: scale(2.2); }}
}}
/* Applied to: span.beacon-ping.bg-rose-500 (emergency banner dot) */
```

DOT-PULSE · MEDICATION STATUS INDICATORS

```
@keyframes dot-pulse {{
  0%, 100% {{
    opacity: 1;
    box-shadow: 0 0 0 0 color-mix(in srgb, var(--state-safe) 50%, transparent);
    transform: scale(1);
  }}
  50% {{
    opacity: 0.85;
    box-shadow: 0 0 0 4px color-mix(in srgb, var(--state-safe) 50%, transparent);
    transform: scale(1);
  }}
}}
/* Applied to: 20+ span.dot-pulse.bg-state-safe (medication row status dots)
   Uses --state-safe token, so the pulse color adapts to the active palette */
```

WHY DOT-PULSE IS DESIGN-SYSTEM-AWARE

The `dot-pulse` keyframe uses `color-mix(in srgb, var(--state-safe) 50%, transparent)` for the box-shadow glow. This means the pulse color is derived from the `--state-safe` token — when a user switches to the "Dune & Cèdre de l'Atlas" palette, the safe-status pulse color changes with it. This is design-system-aware animation, not hardcoded.

DZ-BOUNCE · TYPING INDICATOR

```
@keyframes dz-bounce {{
  0%, 80%, 100% {{ opacity: 0.4; transform: translateY(0px); }}
  40%          {{ opacity: 1;   transform: translateY(-5px); }}
}}
/* Likely used for the Copilot typing dots (3 dots bouncing in sequence) */
```

SCANLASER · BARCODE SCANNER

```
@keyframes scanLaser {{
  0%   {{ opacity: 0.8; top: 10%; }}
  50%  {{ opacity: 1;   top: 88%; }}
  100% {{ opacity: 0.8; top: 10%; }}
}}
/* The barcode scanner (Feature #34) sweep animation – laser line moves top to bottom */
```

FLOATFALL & LEAFSWAY · BOTANICAL MODE

```
@keyframes floatFall {{
  0%   {{ transform: translateY(-80px) translate(0px) rotate(0deg); }}
  25%  {{ transform: translateY(28vh) translate(35px) rotate(45deg); }}
  50%  {{ transform: translateY(58vh) translate(...) rotate(...); }}
  ...
}}

@keyframes leafSway {{
  0%, 100% {{ transform: rotateY(0deg) rotate(-12deg) scale(1); }}
  50%     {{ transform: rotateY(180deg) rotate(16deg) scale(0.92); }}
}}
/* Decorative animations for the Botanical mode (Pharmacopée Royale) */
```

The Reduced Motion Gap · WCAG 2.3.3

The one real gap in an otherwise sophisticated motion system: **zero** `prefers-reduced-motion` **media queries**. Users who set "reduce motion" in their OS still receive all animations. This is a WCAG 2.3.3 (Animation from Interactions) Level AAA compliance gap — and a real accessibility issue for users with ADHD, vestibular disorders, or motion sensitivity.

5.1 What Was Tested

A probe iterated every stylesheet's `cssRules` looking for `CSSRule.MEDIA_RULE` with `conditionText.includes('prefers-reduced-motion')`. Result: 0 matches across all accessible stylesheets. The platform has no reduced-motion handling at any level — not for the infinite ambient animations (beacon-ping, dot-pulse, pulse), not for the enter/exit transition animations, not for the hover/focus state changes.

5.2 Who This Affects

USER GROUP	IMPACT
Vestibular disorders (inner ear)	Infinite animations (beacon-ping, dot-pulse) can trigger dizziness or nausea
ADHD	Infinite motion in peripheral vision causes distraction and focus loss
Photosensitive epilepsy	While no flashing animations were found, the dot-pulse box-shadow expansion could be a trigger for sensitive users
Motion-sensitive users	The 0.5s modal enter animation with transform may cause discomfort
Screen reader users	Typically have reduced motion enabled — animations should not play
Battery-conscious users	Infinite animations consume GPU cycles — reduced motion is also a power-saving setting

5.3 The Fix · One Global Media Query Block

The fix is a single global `@media (prefers-reduced-motion: reduce)` block in `globals.css`. Add it once, and every animation on the platform respects the user's OS preference:

```

/* In app/globals.css - add at the end */

@media (prefers-reduced-motion: reduce) {{
  /* Disable all animations */
  *, *::before, *::after {{
    animation-duration: 0.01ms !important;
    animation-iteration-count: 1 !important;
    transition-duration: 0.01ms !important;
    scroll-behavior: auto !important;
  }}

  /* Specifically disable the infinite ambient animations */
  .beacon-ping,
  .dot-pulse,
  .animate-pulse,
  .animate-spin,
  .animate-bounce,
  .animate-ping {{
    animation: none !important;
  }}
}}

/* Optional: respect users who explicitly want MORE motion */
@media (prefers-reduced-motion: no-preference) {{
  /* Animations play normally - this is the default */
}}

```

WHY 0.01MS INSTEAD OF 0S

Using `animation-duration: 0.01ms !important` instead of `0s` preserves the animation's start/end state. Some animations set the element's final state via `animation-fill-mode: forwards` — setting duration to 0s can leave the element stuck in its initial state. 0.01ms is fast enough to be imperceptible but still completes the animation cycle. This is the W3C-recommended pattern.

5.4 Testing the Fix

After adding the media query, verify by:

- ✓ macOS: System Settings → Accessibility → Display → enable "Reduce motion"
- ✓ Windows: Settings → Accessibility → Visual Effects → uncheck "Animation effects"
- ✓ iOS: Settings → Accessibility → Motion → enable "Reduce Motion"
- ✓ Android: Settings → Accessibility → Remove animations
- ▶ Then reload DzPharm — the beacon-ping, dot-pulse, and pulse animations should be static. Modal/toast/palette open should be instant (0.01ms). Hover/focus transitions should be imperceptible.

5.5 WCAG Compliance Status

WCAG CRITERION	LEVEL	STATUS	FIX
2.2.2 Pause, Stop, Hide	A	PARTIAL	The 3 infinite animations (beacon-ping, dot-pulse, pulse) cannot be paused. Adding reduced-motion media query partially addresses this.
2.3.3 Animation from Interactions	AAA	FAIL	Add the reduced-motion media query block above.
2.3.1 Three Flashes	A	PASS	No flashing animations found.
2.3.2 Three Flashes (Threshold)	AAA	PASS	No flashing animations found.

CHAPTER 06

Summary & Next Steps

The motion system is **sophisticated and deliberate**. 13 keyframes (6 custom). A 3-tier animation hierarchy. 103/103 interactive elements with transitions. Design-system-aware ambient animations using color-mix. The one gap — prefers-reduced-motion — is a 5-minute fix that closes a WCAG 2.3.3 compliance gap.

6.1 What's Excellent

Deliberate 3-tier animation hierarchy

Toasts 0.15s (micro), command palette 0.2s (small), modals 0.5s (structural). The "smaller = faster" principle. Matches Linear, Vercel, Raycast conventions.

6 custom keyframes for clinical use cases

beacon-ping (emergency), dot-pulse (status indicators), dz-bounce (typing), scanLaser (barcode), floatFall + leafSway (botanical). Each is purpose-built, not a generic library.

Design-system-aware ambient animations

dot-pulse uses `color-mix(in srgb, var(--state-safe) 50%, transparent)` — the pulse color adapts to the active palette. When a user switches to "Dune & Cèdre de l'Atlas", the safe-status pulse color changes with it.

Tailwind v4 enter/exit variable-driven system

Two keyframes (enter, exit) consume 12 CSS variables for opacity/translate/scale/rotate/blur. Components opt into animations by setting variables — no custom keyframe per animation type. Senior-level architecture.

100% transition coverage on interactive elements

103 of 103 buttons, links, inputs, comboboxes have transitions. All use the same `0.15s cubic-bezier(0.4, 0, 0.2, 1)` timing. Consistent and predictable.

6.2 What's Missing

Zero prefers-reduced-motion media queries

WCAG 2.3.3 (AAA) gap. Users who set "reduce motion" in their OS still receive all animations. Fix: add one global `@media (prefers-reduced-motion: reduce)` block in globals.css. 5 minutes of work.

3 infinite animations cannot be paused

beacon-ping (2s infinite), dot-pulse (infinite), pulse (2s infinite) loop forever. WCAG 2.2.2 (Level A) requires "Pause, Stop, Hide" for auto-moving content. The reduced-motion media query partially addresses this for users who set the preference, but users with the default preference cannot pause these.

6.3 Net Assessment

13

KEYFRAMES

6

CUSTOM

103/103

TRANSITIONS

3

ANIMATION TIERS

0

REDUCED-MOTION QUERIES

5min

TO FIX

THE BOTTOM LINE

DzPharm's motion system is **more sophisticated than typical healthcare platforms**. The 3-tier hierarchy (0.15s / 0.2s / 0.5s) is deliberate. The 6 custom keyframes are purpose-built. The enter/exit variable-driven architecture is senior-level. The only gap — prefers-reduced-motion — is a 5-minute fix that closes a WCAG 2.3.3 compliance gap and makes the platform accessible to users with vestibular disorders, ADHD, and motion sensitivity. This is one of the rare audits where the conclusion is "the motion system is excellent — add one media query block and you're done."

Immediate Next Steps · Today

1. Add the `@media (prefers-reduced-motion: reduce)` block to `app/globals.css` (5 minutes).
2. Test on macOS with "Reduce motion" enabled — verify beacon-ping, dot-pulse, and pulse animations are static (5 minutes).
3. Test modal/toast/palette open — should be instant (5 minutes).
4. Optional: add a per-animation pause button for the emergency banner beacon-ping (1 hour, addresses WCAG 2.2.2).
5. Optional: replace pulse on Copilot badge with a static "online" dot when reduced-motion is active (already handled by the global block).

60

13 keyframes. 3-tier hierarchy. 103/103 transitions. One 5-minute fix closes the only gap.

6

CHAPTERS

6

SCREENSHOTS

13

KEYFRAMES CATALOGUED

5min

TO SHIP FIX
