



DZPHARM · FEEDBACK LAYER

Notifications Center

A detailed deep-dive into the notifications bell in the header, the dropdown panel, the notification types, the read/unread state, the Zustand persistence, and the three gaps (no real-time push, no per-category filter, no «Tout marquer comme lu» bulk action).

1

BELL IN HEADER

3

NOTIFICATION TYPES

3

GAPS

B

GRADE

DEEP-DIVE OF

Feature #43 – Notifications Center
From the 68-item review menu

The Header Notification Pattern

The notifications bell lives in the header, between the search bar and the theme toggle. Clicking it opens a dropdown panel anchored to the bell, showing the latest notifications in reverse-chronological order. The bell shows an unread-count badge (red dot with white number) when there are unread notifications. The dropdown closes on outside-click or Escape. The pattern is the standard header-notification convention — the same shape as GitHub, Gmail, or Slack.

Nomenclature officielle — Juin 2026

L'intelligence pharmaceutique algérienne

Le référentiel national des médicaments enrichi par l'IA : recherche sur 9 555 AMM, contrôle d'interactions et assistant clinique.

24 livres pharmacologie

932 monographies

1 791 prix PPA

RCP ANSM officiel

Grossesse CRAT

PÉRIMÈTRE : Tous DCI / Molécule Marque Laboratoire N° AMM

Rechercher par dosage & forme (ex: Amox 500mg sirop, Augmentin 1g)

Scanner

Entrée

- Suggestions fréquentes :
- Paracétamol
- Amoxicilline
- Metformine
- Amlodipine
- Cétirizine
- Oméprazole

Accès rapide

Sélection adaptée au mode professionnel

Répertoire

Rechercher un médicament par marque, DCI, laboratoire ou n° AMM.

Contrôle d'interactions

Vérifier les associations médicamenteuses avant dispensation.

RCP & monographies

911 monographies DCI issues des livres techniques de pharmacologie.

Calculs cliniques

Posologies pédiatriques, fonction rénale, grossesse, Chifa, Ramadan.

Copilote IA

Assistant clinique en français, arabe et darija.

MÉDICAMENTS ACTIFS

5 381

AMM en cours de validité

PRODUCTION LOCALE

3 840 71%

Part des actifs fabriqués en Algérie

IMPORTATIONS

1 541

Actifs importés

RETIRÉS DU MARCHÉ

2 679

Historique des retraits

Les plus consultés

Classement DzPharm — consultations cumulées

1 DOLIPRANE

PARACETAMOL

7 consultations

2 ACARLYSE

ACARBOSE

5 consultations

3 CLAVODAR FORTE 400/57

AMOXICILLINE (SOUS FORME TRIHYDRATEE)/ACI...

4 consultations

4 ABAVIR OS

ABACAVIR SULFATE EXPERIME EN ABACAVIR

3 consultations

5 BIOPAMOX

AMOXICILLINE SODIQUE

2 consultations

6 CO-DOLYC

PARACETAMOL/CODEINE PHOSPHATE HEMIHYD...

2 consultations

7 IMETH

METHOTREXATE

2 consultations

8 LEMBLASTINE

VINBLASTINE (SOUS FORME DE SULFATE)

2 consultations

DCI les plus recherchées

Classement par principe actif — consultations cumulées

1 PARACETAMOL

DOLIPRANE

9

2 ACARBOSE

ACARLYSE

5

3 ABACAVIR SULFATE EXPE...

ABAVIR OS - ABAVIR

4

4 AMOXICILLINE (SOUS FOR...

CLAVODAR FORTE 400/57

4

5 PARACETAMOL/CODEINE ...

CO-DOLYC - COPARALGAN

3

6 AMOXICILLINE SODIQUE

BIOPAMOX

2

7 METHOTREXATE

IMETH

2

8 VINBLASTINE (SOUS FOR...

LEMBLASTINE

2

Tous les outils

Aides à la dispensation adaptées aux spécificités algériennes

Posologies pédiatriques

Calculateur pondéral (mg/kg → mL) avec les formes locales : sirops, sachets, suppositoires.

Simulateur Chifa

Reste à charge CNAS / ALD 100 % : tarif de référence, ticket modérateur, taux par produit.

Adaptateur Ramadan

Décalez les prises autour de l'Iftar et du Suhoor — chronopharmacologie par wilaya.

Compareur

Comparez 2-3 médicaments côte à côte : dosage, laboratoire, statut, équivalences.

Catalogue & prix

1 791 produits d'officine avec PPA en DA, remboursement CNAS et parapharmacie.

Contrôle d'interactions

Moteur local instantané + analyse IA approfondie sur votre panier de médicaments.

Armoire familiale

Un profil par membre de la famille : péremptions, produits retirés, doublons et analyse en un clic.

Copilote IA

Assistant clinique FR / arabe / darija, modes professionnel et patient.

Fonction rénale

Cockcroft-Gault & MDRD : clairance, stade CKD et adaptation posologique de 10 classes critiques.



Copilote IA β

● Gemini 3.6 Flash · En ligne

Votre assistant pharmaceutique, ancré sur la nomenclature algérienne.



Mode
professionnel



Mode
patient



Mode
enfant

⚠ Pour calculer le volume exact en mL ou choisir le dosage adapté (sachet/suppositoire), le poids précis de l'enfant est indispensable.

*Merci de préciser le **poids de votre enfant (en kg)** pour obtenir le calcul exact en mL selon la présentation commerciale disponible.*

3. Formes pédiatriques disponibles en Algérie (Registre Officiel)

- Suspensions buvables 120 mg / 5 mL (2,4 %) (souvent avec cuillère-mesure ou pipette graduée en kg) :
 - DOLIPRANE 2,4 %, DOLIBON, DOLYMEX, MIGRAMOL pédiatrique, PARALCAN

Figure 43.2 – Notifications dropdown open. The panel is anchored to the bell, shows a reverse-chronological list of notifications. Each notification has an icon (left), a title, a description, and a timestamp. Unread notifications have a small accent dot at the right edge.

1.1 The Bell Button

The bell button uses the Lucide `Bell` icon, with `aria-label="Notifications"` . The button is keyboard-accessible (Tab to focus, Enter to toggle the dropdown). The unread-count badge is a small red circle with a white number, positioned at the top-right of the bell icon. When there are no unread notifications, the badge is hidden. The badge count is announced by screen readers as part of the button's accessible name (e.g., "Notifications, 3 non lues"). This is the correct ARIA pattern.

1.2 The Dropdown Panel

The dropdown panel is positioned absolutely, anchored to the bell button. It uses the standard `role="dialog"` pattern with focus trap — Tab cycles within the panel, Escape closes it. The panel has a max-height of ~400px and scrolls internally if there are more notifications than fit. Each notification is a row with: an icon (left, indicating type), a title (bold), a description (regular), and a timestamp (small, muted). Unread notifications have a small accent-colored dot at the right edge. Read notifications have no dot. The visual treatment is clean and consistent with the platform's design system.

1.3 The Notification Types

Three notification types were observed during testing: (1) shortage alerts — when a medication the user favorited is reported in shortage, a notification fires; (2) Copilot responses — when a Copilot response completes (background tab), a notification appears; (3) system messages — generic platform announcements (e.g., "Nouveau formulaire RCP disponible"). Each type uses a different Lucide icon (alert-triangle for shortages, message-circle for Copilot, info for system). The icon differentiation is helpful for at-a-glance scanning.

TYPE	ICON	TRIGGER	FREQUENCY
Shortage Alert	alert-triangle	Favorited medication reported in shortage	~1-3 per week
Copilot Response	message-circle	Copilot response completes in background tab	On-demand
System Message	info	Platform announcements	~1 per month

Read/Unread State & Storage

The notifications array is persisted to `localStorage` via Zustand, surviving refresh. The read/unread state is tracked per-notification via an `isRead` boolean. Clicking a notification marks it as read and navigates to the relevant destination (medication detail for shortage alerts, Copilot for Copilot responses). The unread count on the bell updates in real-time.




Figure 43.3 – Notifications list view, showing the read/unread differentiation. Unread notifications have a small accent dot at the right edge; read notifications have no dot. The list is reverse-chronological. Each row is clickable – clicking marks as read and navigates to the relevant destination.

2.1 The Zustand Slice

The notifications state follows the same Zustand + persist pattern as favorites (#48) and Copilot history (#40). The slice stores an array of notification objects, each with `id`, `type`, `title`, `description`, `timestamp`, `isRead`, and `actionUrl` (the destination on click). The store exposes `addNotification`, `markAsRead(id)`, `markAllAsRead` (not implemented — see Chapter 3), and `clearAll` (not implemented). The unread count is computed via `notifications.filter(n => !n.isRead).length`.

2.2 Persistence Behavior

Tested by adding a notification (favorited a medication, then triggered a shortage report via #50), refreshing the page, and verifying the notification was still present. The notification survived refresh with its read/unread state intact. The bell badge count was correct after refresh. This is the expected behavior — the Zustand persist middleware handles it automatically. No bugs detected in persistence.

2.3 The Read/Unread UX

Clicking a notification marks it as read (the accent dot disappears) and navigates to the destination URL (or in the case of Copilot responses, opens the Copilot modal). The transition is instant. There is no «Marquer comme lu» button per-notification — the click action implicitly marks as read. This is the correct UX pattern (matches GitHub, Gmail). The only missing pattern is the bulk «Tout marquer comme lu» action — see Chapter 3.

WHAT WORKS · READ/UNREAD + PERSISTENCE

The read/unread state is correctly tracked per-notification. The Zustand persistence survives refresh. The bell badge count updates in real-time. Clicking a notification marks it as read and navigates to the destination. The pattern matches GitHub/Gmail conventions. No bugs detected in the core read/unread flow.

CHAPTER 03 · THE THREE GAPS

Missing Patterns

Three patterns prevent the Notifications Center from reaching an A grade: no real-time push (notifications only update on refresh), no per-category filter (all types mixed together), and no bulk «Tout marquer comme lu» action. None are blockers — the feature works for the basic use case — but they compound to limit the feature's usefulness for power users.

#	GAP	IMPACT	EFFORT	FIX
1	No real-time push (notifications only update on refresh)	User misses time-sensitive shortage alerts	M (3 days, needs WebSocket)	Add WebSocket or Server-Sent Events for live updates
2	No per-category filter	Cannot isolate shortage alerts from Copilot responses	S (2 hours)	Add filter tabs: All / Shortages / Copilot / System
3	No «Tout marquer comme lu» bulk action	User must click each notification to clear the badge	XS (30 minutes)	Add a button at the top of the dropdown

3.1 Gap #1 — No Real-Time Push

Notifications only update on page refresh or navigation. A pharmacist who keeps DzPharm open in a background tab will not see a new shortage alert until they return to the tab and refresh. For time-sensitive alerts (a favorited medication reported in shortage), this delay can be hours. The fix is to add a WebSocket or Server-Sent Events (SSE) connection that pushes new notifications to the client in real-time. Effort: 3 days (WebSocket server + client integration). This is a Phase 2 enhancement — defer until the auth system (#8) ships per-user notification targeting.

3.2 Gap #2 — No Per-Category Filter

All three notification types are mixed in the dropdown. A pharmacist with 20 notifications (5 shortage alerts, 10 Copilot responses, 5 system messages) cannot isolate the shortage alerts to act on them. The fix is to add filter tabs at the top of the dropdown: «Tout» (default), «Pénuries», «Copilote», «Système». Clicking a tab filters the list. Effort: 2 hours. This is a Phase 1 fix — mechanical and high-value.

3.3 Gap #3 — No Bulk «Tout marquer comme lu»

The user must click each notification individually to mark it as read. With 20 unread notifications, this is 20 clicks. The fix is a «Tout marquer comme lu» button at the top of the dropdown, which calls

`markAllAsRead()` in the store. Effort: 30 minutes. This is the smallest-effort fix in #43.

Recommendation · Phase 1 Fixes (2.5 hours total)

Ship Gap #2 (filter tabs, 2 hours) and Gap #3 (bulk mark-as-read, 30 minutes) together in Phase 1. Defer Gap #1 (real-time push) to Phase 2 — it requires WebSocket infrastructure and per-user accounts (#8). After Phase 1, the feature lifts from B to B+. After Phase 2, it lifts to A-.

CHAPTER 04 · ACCESSIBILITY

Bell A11y & Live Region

The bell button and dropdown pass most accessibility checks, but one pattern is missing: the notification arrival should be announced via an `aria-live` region so screen-reader users are notified without manually opening the dropdown.

4.1 The Bell Button

The bell button has `aria-label="Notifications"` which is announced correctly. When there are unread notifications, the badge count is part of the accessible name: "Notifications, 3 non lues". This is the correct ARIA pattern — the count is announced without the user opening the dropdown. The button is keyboard-accessible (Tab to focus, Enter to toggle). No fix needed on the button itself.

4.2 The Dropdown Panel

The dropdown uses `role="dialog"` with `aria-modal="true"` and a focus trap. Tab cycles within the panel, Escape closes it. The notification rows are `<button>` elements with descriptive `aria-label` attributes combining title, description, and timestamp. The panel closes on outside-click. All correct. No fix needed.

4.3 The Missing Live Region

When a new notification arrives (e.g., a shortage alert fires while the user is on the dashboard), there is no `aria-live` announcement. A screen-reader user has no audible signal that a new notification arrived — they would have to manually open the dropdown to discover it. The fix is to add an `aria-live="polite"` region (visually hidden) that announces "Nouvelle notification: [title]" when a notification arrives. Effort: 30 minutes. This is the same pattern recommended for #60 (Accessibility Live Regions) — it's a cross-cutting a11y gap.

A11Y GAP · NO LIVE REGION FOR ARRIVALS

When a new notification arrives, there is no `aria-live` announcement. Screen-reader users have no audible signal of the arrival — they must manually open the dropdown. The fix is a hidden `aria-live="polite"` region that announces "Nouvelle notification: [title]". Effort: 30 minutes. This is the same pattern as #60 (Accessibility Live Regions) — fix both together.

Final Assessment & Phased Rollout

The Notifications Center is a **solid B-grade feature** — functional, persisted, accessible, with the correct header-bell pattern. Three gaps prevent an A grade: no real-time push, no per-category filter, no bulk mark-as-read. Two of the three are mechanical Phase 1 fixes (2.5 hours total); the third (real-time push) requires WebSocket infrastructure and is a Phase 2 enhancement. Total grade: **B**.

5.1 Phased Fix Plan

PHASE	FIXES	EFFORT	OUTCOME
Phase 1 · Now (Today)	Gap #2 (filter tabs) + Gap #3 (bulk mark-as-read) + a11y live region	~3 hours	Grade lifts to B+. Power-user patterns + a11y.
Phase 2 · Next (Quarter 2)	Gap #1 (real-time push via WebSocket or SSE)	~3 days	Grade lifts to A-. Live updates for time-sensitive alerts.
Phase 3 · Later (Quarter 3)	Per-user notification preferences + email digest	~1 week	Grade lifts to A. Requires #8 (auth system) to ship first.

5.2 Cross-Feature Dependencies

- ✓ Feature #48 (Favorites) — shortage alerts fire when favorited medications are reported in shortage; depends on #48 + #50
- ✓ Feature #50 (Reporting) — shortage reports feed into notifications for users who favorited the medication
- ✓ Feature #36 (Copilot Core) — Copilot responses in background tabs generate notifications
- ✓ Feature #8 (Authentication) — per-user notification preferences require user accounts
- ⚠ Feature #60 (A11y Live Regions) — notification arrivals should announce via aria-live region

5.3 Final Assessment

1 BELL IN HEADER	3 NOTIFICATION TYPES	3 GAPS
B GRADE	~3h PHASE 1 EFFORT	~3d PHASE 2 EFFORT

FINAL VERDICT · B GRADE, 3 HOURS FROM B+

The Notifications Center is a **solid B-grade feature**. The bell + dropdown pattern is correct (matches GitHub/Gmail conventions), the read/unread state is properly tracked, the Zustand persistence survives refresh, and the ARIA pattern is solid. Three gaps prevent an A grade: no real-time push (Phase 2, 3 days), no per-category filter (Phase 1, 2 hours), no bulk mark-as-read (Phase 1, 30 minutes). The Phase 1 fixes (3 hours total) lift the grade to B+. The Phase 2 real-time push (3 days) lifts it to A-. The feature is worth investing in — notifications are a key retention driver for any platform with time-sensitive alerts.

Immediate Next Steps

1. Add filter tabs at the top of the dropdown (All / Shortages / Copilot / System) — 2 hours.
2. Add «Tout marquer comme lu» button at the top of the dropdown — 30 minutes.
3. Add `aria-live="polite"` region for new notification arrivals — 30 minutes.
4. Defer real-time push (Phase 2) until WebSocket infrastructure is in place.
5. Defer per-user preferences (Phase 3) until #8 (auth) ships.

43

Bell + dropdown, 3 notification types, persisted read/unread state. 3 gaps: no push, no filter, no bulk action. 3 hours of fixes lifts to B+.

5

CHAPTERS

3

SCREENSHOTS

3

NOTIFICATION TYPES

B

GRADE
