

Deep learning and energy models for fine dead wood segmentation

Jacquelyn Shelton

Hong Kong Polytechnic University


with Przemyslaw Polewski, Marco Heurich and Wei Yao

Maching Learning for Climate
UCSB - KITP

November 4th, 2021




Introduction - The Carbon Cycle



Introduction - Motivation

Why dead trees?

- ▶ **Forests** are a key component in the **global carbon cycle** and the most **efficient CO₂ scrubbers**
- ▶ **Dead wood** is an important part of **forest ecosystems**
 - ▶ **Sequesters** 8% of global forest carbon and 8.5% atmospheric carbon
 - ▶ **Provides habitat** for $\sim \frac{1}{3}$ of plant and animal species
→ imperative for **biodiversity**
- ▶ **Forest biodiversity** helps maintain forest health and shield against **climate change**



Introduction - Motivation


Why dead trees?

- ▶ **Forests** are a **key component** in the **global carbon cycle** and the most **efficient CO₂ scrubbers**
- ▶ **Dead wood** is an important part of **forest ecosystems**
 - ▶ **Sequesters** 8% of global forest carbon and 8.5% atmospheric carbon
- ▶ **Provides habitat** for $\sim \frac{1}{3}$ of plant and animal **species**
→ imperative for **biodiversity**
- ▶ **Forest biodiversity** helps maintain forest health and shield against **climate change**
- ▶ Basically: **indicator of overall forest health**...and* beyond

Now what?

- ▶ Need accurate ways to *measure* and *monitor* dead wood quantities and types...**Machine Learning!**

Data - Color infrared imagery (CIR)




- ▶ Distinguish between **live** and dead vegetation
→ **chlorophyll has high reflectance** in the near-infrared (NIR) spectral band:




- ▶ Color infrared imagery (**CIR**): consists of the **NIR**, **red**, and **green** bands instead of the usual **RGB**

Data - Bavarian Forest National Park




- ▶ Located in southeastern Germany, bordering the Czech Republic
- ▶ Consists of mostly Norway spruce (Picea abies) and European beech (Fagus sylvatica)
- ▶ Suffered bark beetle infestation (Ips typographus): between 1988-2010, total of 5,800 hectares of the Norway spruce stands died
- ▶ Ideal for dead wood studies – decaying wood left undisturbed in forest for scientific purposes

Data - Aerial imagery of Bavarian Forest National Park



- ▶ Flight campaign in June 2017 acquired $\sim 2,500$ images
- ▶ Mean flight altitude: 2879m, resulting in a high resolution ground sampling distance of 10cm → each pixel = $10 \times 10\text{cm}$
- ▶ Image resolution of aerial camera: 14592×25728 pixels, with each image covering $\sim 3.7\text{km}^2$


Approach - Review of classic segmentation tasks



Source: "Splash of color" tutorial by Waleed Abdulla


- ▶ Classification: balloon is present in image (or not)
 - ▶ Semantic Segmentation: find *all* the balloon pixels
 - ▶ Object Detection: find balloon *quantity* and *location*, e.g. 7 balloons here
 - ▶ Instance Segmentation: identify all pixels belonging to *each* of 7 balloons
- Note: encountering objects that overlap – our approach **MUST** account for this

Approach - How to attack this problem?




- ▶ First, let's break the problem down into basic components
- ▶ Next, recognize we can employ state-of-the-art deep learning methods to form the building blocks of our approach

Approach - Build an energy model!



- ▶ First, let's break the problem down into basic components
- ▶ Next, recognize we can employ state-of-the-art deep learning methods to form the building blocks of our approach
- ▶ Combine these methods to formulate a multi-term energy model for refined contour segmentation


Approach - U-net: energy term for image



Build each energy term: $E_{\text{image}}(\text{contour})$:


- ▶ **U-net**: fully convolutional neural network (FCN) with an *encoder-decoder architecture*
→ get class probabilities aka **dense semantic segmentation**
- ▶ Suited for this task: preserves contours, thus fine details of the tree crowns

Approach - U-net: energy term for image




- ▶ **U-net:** FCN with encoder-decoder architecture
 - Encoding branch derives convolutional features at successively coarser scales
 - Decoding branch upsamples through transposed convolution
 - ▶ Preserves detail with high-resolution original feature maps
- Additionally, U-nets can also be used for regression...

Approach - Side-bar: U-net for regression




- **U-net** for regression: remove softmax layer and logistic loss, which gave us the class probabilities

Approach - Side-bar: U-net for regression



- **U-net** for regression: remove softmax layer and logistic loss, which gave us the class probabilities
- Instead, train with least-squares loss directly on the 1×1 convolution output (final layer) for dense/pixel predictions
- Our previous work: using a U-net for regression we successfully predicted dense estimates of atmosphere pollutants (NO_3 , NH_4 , $PM_{2.5}$)


Approach - Mask R-CNN: energy term for location



Build next energy term: E_{location} (contour):

- **Mask R-CNN:** FCN for *instance segmentation* – get separate pixel masks for all object instances present in input image:
 - (1) **region proposal network:** select regions of interest (RoI) likely to contain object instances
 - (2) **fine-grained detection component:** evaluate candidate RoI, predict object class, bounding box, and pixel (instance) mask

Approach - Mask R-CNN: energy term for location




Build next energy term: $E_{location}$ (contour):

- ▶ **Mask R-CNN:** FCN for *instance segmentation* – get separate pixel masks for all object instances present in input image:
 - (1) region proposal network: select regions of interest (RoI) likely to contain object instances
 - (2) fine-grained detection component: evaluate candidate RoI, predict object class, bounding box, and pixel (instance) mask

Approach - Formalize energy model

Begin building our energy model and its terms/potentials:

- ▶ Consider image plane $\Omega \subset \mathbb{R}^2$ and image $I : \Omega \mapsto \mathbb{R}^D$
- ▶ Segmentation of a single contour C :
 C : evolving shape contour, partitions image into foreground Ω_F , background Ω_B ($C \longleftrightarrow \Omega_F, \Omega_B$)



Note: problem easier with only 1 contour and no overlap

Express contour model to optimize (probability or energy):

$$\begin{aligned}\mathcal{P}(\Omega_F, \Omega_B | I) &\propto \mathcal{P}(I | \Omega_F, \Omega_B) P(\Omega_F, \Omega_B) \\ \Leftrightarrow E(C) &= \underbrace{-\log \mathcal{P}(I | \Omega_F, \Omega_B)}_{\text{image term}} - \underbrace{\log P(\Omega_F, \Omega_B)}_{\text{shape term}}\end{aligned}$$

Approach - Formalizing energy model: image term

- Reminder: C uniquely identifies Ω_F, Ω_B ($C \longleftrightarrow \Omega_F, \Omega_B$)

$$E(C) = \underbrace{-\log \mathcal{P}(I|\Omega_F, \Omega_B)}_{\text{image term: } E_{img}} - \underbrace{\log \mathcal{P}(\Omega_F, \Omega_B)}_{\text{shape term}}$$

Simplifying assumption:

- Labelings of **foreground** and **background** regions are independent: $\mathcal{P}(I|\Omega_F, \Omega_B) = \mathcal{P}(I|\Omega_F)\mathcal{P}(I|\Omega_B)$
- Let $\mathbb{1}_X$ denote the indicator function for $\omega \in X$

$$\begin{aligned} E_{img}(C) &= - \int_{\omega \in \Omega} \left[\overbrace{\mathbb{1}_{\Omega_F}}^{\llbracket \omega \in \Omega_F \rrbracket} \log \mathcal{P}(I(\omega)|\Omega_F) + \overbrace{\mathbb{1}_{\Omega_B}}^{\llbracket \omega \in \Omega_B \rrbracket} \log \mathcal{P}(I(\omega)|\Omega_B) \right] d\omega \\ &= - \int_{\omega \in \Omega} \left[\mathbb{1}_{\Omega_F} \log \mathcal{P}(I(\omega)|\Omega_F) + \underbrace{(1 - \mathbb{1}_{\Omega_F})}_{\text{indicator for } \omega \in \Omega_B} \log \mathcal{P}(I(\omega)|\Omega_B) \right] d\omega \end{aligned}$$

Approach - Formalizing energy model: image term

$$\begin{aligned} E_{img}(C) &= - \int_{\omega \in \Omega} [\mathbb{1}_{\Omega_F} \log \mathcal{P}(I(\omega) | \Omega_F) + \underbrace{(1 - \mathbb{1}_{\Omega_F})}_{\text{indicator for } \omega \in \Omega_B} \log \mathcal{P}(I(\omega) | \Omega_B)] d\omega \\ &= - \int_{\omega \in \Omega} [\mathbb{1}_{\Omega_F} \left[\log \frac{\mathcal{P}(I(\omega) | \Omega_F)}{\mathcal{P}(I(\omega) | \Omega_B)} \right]] d\omega + \text{constant} \end{aligned}$$

Simplifying assumption:

- Prior probability of observing foreground/background is equal:
 $P(\Omega_F) = P(\Omega_B)$

$$\frac{\mathcal{P}(I(\omega) | \Omega_F)}{\mathcal{P}(I(\omega) | \Omega_B)} = \frac{\mathcal{P}(\Omega_F | I(\omega)) \mathcal{P}(I(\omega))}{\mathcal{P}(\Omega_B | I(\omega)) \mathcal{P}(I(\omega))} \times \frac{\mathcal{P}(\Omega_B)}{\mathcal{P}(\Omega_F)} \quad (\text{Bayes rule})$$

$$E_{img}(C) = - \int_{\omega \in \Omega} \mathbb{1}_{\Omega_F} \log \frac{\mathcal{P}(\Omega_F | I(\omega))}{\mathcal{P}(\Omega_B | I(\omega))} \frac{\mathcal{P}(\Omega_B)}{\mathcal{P}(\Omega_F)} d\omega + \text{constant}$$

Approach - Formalizing energy model: image term

$$\begin{aligned} E_{img}(C) &= - \int_{\omega \in \Omega} \mathbb{1}_{\Omega_F} \log \underbrace{\frac{\mathcal{P}(\Omega_F | I(\omega))}{\mathcal{P}(\Omega_B | I(\omega))}}_{\text{two classes: } 1 - \mathcal{P}(\Omega_F | I(\omega))} d\omega + \text{constant} \\ &= - \int_{\omega \in \Omega} \mathbb{1}_{\Omega_F} \log \underbrace{\frac{\mathcal{P}(\Omega_F | I(\omega))}{1 - \mathcal{P}(\Omega_F | I(\omega))}}_{\text{arbitrary model of class probs}} d\omega + \text{constant} \end{aligned}$$



Sample CIR image

Posterior probability map

contour positions with:
low energy high energy

Approach - Formalizing energy model: shape term

Denote an approximation of foreground region indicator:

- ▶ $\mathbb{1}_{\Omega_F} \approx G(\alpha, x, y)$, where $G(\dots)$ is parameterized by a **shape coefficient vector** $\alpha \in \mathbb{R}^m$ and center position (x, y)


$$E(C) = E(\alpha, x, y) = \underbrace{-\log \mathcal{P}(I|\alpha, x, y)}_{\text{image term}} \quad \underbrace{-\log \mathcal{P}(\alpha)}_{\text{shape term: } E_{shp}}$$

- ▶ $G(\dots)$ instantiates a **shape** given by **coefficients** α centered at (x, y) in the image
- ▶ Shape term E_{shp} is dependent *only* on the **shape coefficients**, *not* the position (x, y)
- ▶ Standard model: all positions are deemed **equally likely** – no prior knowledge available/used

Approach - Formalizing energy model: prior for shape

- ▶ $\mathcal{P}(\alpha)$ can be modeled in a non-parametric fashion in terms of training shape coefficients
- ▶ Let $T = \alpha_1, \dots, \alpha_N$ be a database of training shape coefficients and $K(x, y)$ denote a kernel function quantifying similarity between two vectors $x, y \in \mathbb{R}^m$
- ▶ The probability of a shape coefficient vector α is given by:

$$\mathcal{P}(\alpha) \propto \frac{1}{N} \sum_{i=1}^N K(\alpha, \alpha_i)$$



Source: Cremers and Rousson, 2007

→ bulk of probability mass concentrated in regions of shape coefficient space with training vectors (black dots), regions far away allocated minimal probability

Approach – Multi-contour segmentation

But we **really** want to model **multiple** contours:

- ▶ C_1, \dots, C_K : simultaneously evolving shape contours representing different object instances
- ▶ Contour C_i is parameterized by shape coefficient vector α_i and position (x_i, y_i)



$$\mathcal{P}(C_1, \dots, C_K | I) \propto \mathcal{P}(I | C_1, \dots, C_K) P(C_1, \dots, C_K)$$

$$\Leftrightarrow E(C_1, \dots, C_K) = \underbrace{-\log \mathcal{P}(I | C_1, \dots, C_K)}_{\text{image term}} - \underbrace{\log P(C_1, \dots, C_K)}_{\text{shape term}}$$

Approach – Multi-contour shape term

$$E(C_1, \dots, C_K) = \underbrace{-\log \mathcal{P}(I | \dots)}_{\text{image term}} - \underbrace{\log \mathcal{P}(C_1, \dots, C_K)}_{\text{shape term}}$$

- ▶ The contours are not independent: **penalize overlap**
- ▶ Include **location** information from **Mask R-CNN**
- ▶ Consider each contour's **shape** independent of position
⇒ Shape term as an undirected graphical model:

$$\mathcal{P}(C_1, \dots, C_K) = \frac{1}{Z} \prod_{\lambda \in \Lambda} \Psi_\lambda(C_\lambda)$$

$\lambda \in \Lambda$: **cliques** of the graph \mathcal{H} induced by object/tree crown
centroids from Mask R-CNN and


Ψ_λ : are **potential functions** defined on **subsets of contours**

Approach – Shape term as a Graphical model

⇒ Remember:

$$\mathcal{P}(C_1, \dots, C_K) = \frac{1}{Z} \prod_{\lambda \in \Lambda} \Psi_\lambda(C_\lambda)$$

⇒ $\lambda \in \Lambda$ are cliques of the graph $\mathcal{H} = (\mathcal{V}, \mathcal{E})$ induced by Mask R-CNN found centroids



- ▶ Left: class probability map of dead tree scene
- ▶ Center: red circles = object centroids detected by Mask R-CNN and green lines connect centroids within d_{thr}
- ▶ Right: graph induced by the connections/edges and centroids/nodes

Approach – Graphical model potentials

$$\mathcal{P}(C_1, \dots, C_K) = \frac{1}{Z} \prod_{\lambda \in \Lambda} \Psi_{\lambda}(C_{\lambda})$$

⇒ Our model includes unary and pairwise potentials Ψ :

$$E_C(C_1, \dots, C_K) = -\log \mathcal{P}(C_1, \dots, C_K) + \text{constant} =$$

$$-\sum_{k=1}^K \log \Psi^{shp}(\alpha_k) - \sum_{k=1}^K \log \Psi_k^{loc}(x_k, y_k) - \sum_{(k,l) \in \mathcal{E}} \log \Psi_{ovp}(C_k, C_l)$$

- ▶ Shape potential: $\Psi^{shp}(\alpha_k) = \mathcal{P}(\alpha_k)$ - global KDE model
- ▶ Location potential: Gaussian centered on k -th centroid


$$\mu_k: \Psi_k^{loc}(z) \propto \exp\left(-\frac{1}{2}(z - \mu_k)^T \Sigma^{-1}(z - \mu_k)\right)$$

- ▶ Overlap potential: overlap area between contours C_k, C_l :


$$\begin{aligned} \log \Psi_{ovp}(C_k, C_l) &= \\ &- \int_{\omega} G(\alpha_k, x_k, y_k)[\omega] \cdot G(\alpha_l, x_l, y_l)[\omega] d\omega \end{aligned}$$

Approach – Put all the pieces together

$$E_{\text{total}}(C_1, \dots, C_K) = \underbrace{-\log \mathcal{P}(I|C_1, \dots, C_K)}_{\text{image term}} - \underbrace{\sum_{k=1}^K \log \Psi^{shp}(\alpha_k)}_{\text{shape term}} \\ - \underbrace{\sum_{(k,l) \in \mathcal{E}} \log \Psi^{ovp}(C_k, C_l)}_{\text{overlap term}} - \underbrace{\sum_{k=1}^K \log \Psi_k^{loc}(x_k, y_k)}_{\text{location term}}$$




Experiments - Data: train and test areas





- We labeled tree crown polygons in forest areas for datasets:
 training = 201 and **testing = 750**

Experiments - Data: labels for training data



- ▶ Labeled 201 individual tree crown polygons for training area

Experiments - Training of the models



U-net

- 200x200 patches
- 200 images
- 2000 epochs

Mask R-CNN

- 256x256 patches
- 70 images
- 100 epochs

Eigenshape model

- 200 images
- 32 top eigenvectors
- $\approx 98\%$ of variance

Experiments - Setting and evaluation metrics

Setting

- ▶ Data: $N = 750$ contours from test area in Bavarian National Forest
- ▶ Goal: experiment to compare polygons learned by (1) Mask R-CNN against contours refined by our active (2) multi-contour model
- ▶ Evaluation: both pixel level and object level of detected vs. reference polygons


Experiments - Setting and evaluation metrics

Setting

- ▶ Data: $N = 750$ contours from test area in Bavarian National Forest
- ▶ Goal: experiment to compare polygons learned by (1) Mask R-CNN against contours refined by our active (2) multi-contour model
- ▶ Evaluation: both pixel level and object level of detected vs. reference polygons

Metrics

- ▶ Pixel level:



→ intersection over union (IoU):
ratio intersection area to union area of compared shapes:

$$IoU(A, B) = \frac{|A \cap B|}{|A \cup B|}$$


- ▶ Object level:

- ▶ mean distance between centroids of reference & detected polygons at $IoU \geq 0.5$
- ▶ precision and recall at $IoU \geq 0.5$:

$$\text{precision} = \frac{\#\text{matched polygons}}{\#\text{detected polygons}}$$

$$\text{recall} = \frac{\#\text{matched polygons}}{\#\text{reference polygons}}$$


Experiments - Results: centroid distance and IoU



Shown: our active contour model (ACM) outperforms Mask R-CNN both in terms of identifying tree crown centers and discerning overlapping tree crowns

- increased mean reference and detected centroid distance from 3.4 to 2.4 pixels (left)
- increased mean matched IoU from 0.66 to 0.75 (right)

Experiments - Results: object-level precision and recall




Shown: our active contour model (ACM) outperforms Mask R-CNN when shown *any* # of tree crowns

- increased recall by 3.5 percentage points (left)
- increased precision by 8 percentage points (right)

Note: in images with many adjacent tree crowns → active contour model (ACM) can handle complex overlapping objects far better than Mask R-CNN


Experiments - Results: extracted contours



Shown: tree contours extracted from a CIR input image by our active contour model (ACM) are more refined and visually match the true contours than Mask R-CNN

- Correctly identified tree crown pixels are shown in white
- False positives are shown in red
- False negatives are shown in cyan

Experiments - Results: extracted contours



Shown: tree contours extracted from a CIR input image by our active contour model (ACM) are more refined and visually match the true contours than Mask R-CNN

- Correctly identified tree crown pixels are shown in white
- False positives are shown in red
- False negatives are shown in cyan

To summer-ize...



- ▶ Dead wood sequesters 8% of global forest carbon, houses $\frac{1}{3}$ of forests biodiversity, and is a key indicator of overall forest health ... but good wood models necessary/lacking
 - ▶ This work:
 - Combines deep learning and instance segmentation
 - Leverages prior knowledge of crown shape and appearance
 - Constructs comprehensive energy functional for multiple, overlapping contours
- Our approach discovers improved, localized and refined contours of dead trees


Outlook

Future/current work:

- ▶ **Goals (always):** efficient, robust, scalable ML methods, **critical to:**
 - **Exploit** modern **remote sensing data** – cheaper, higher quality, larger quantity, freely available
 - Better understand **biodiversity** and the role of dead wood, and **impacts of climate**
- ▶ **Change detection:** high quality contour **delineation** improves estimates of dead wood
 - Model of **decay dynamics, tree type and tree counts**
- ▶ **Advanced priors:** replace vanilla eigenshape prior with **GAN generated shapes**
⇒ **preliminary results show contour improvements**
- ▶ **Sparsity and approximations:** GANs to develop contours using **only pixels on the outline** → save computational resources

Thanks for your attention!

Questions, feedback, suggestions, cats, ideas, musings?
Very eager for all of the above!



Obligitory morbid satire...

Where is Wiley going!?



"We have built a civilization based on a world that doesn't exist anymore."

– Katharine Hayhoe, climate scientist at Texas Tech University
and chief scientist at the Nature Conservancy

Appendix – References

1. A. R. Martin, G. M. Domke, M. Doraisami, and S. C. Thomas: [Carbon fractions in the world's dead wood](#), Nature Communications, vol. 12, 2021.
2. Y. Pan, R. A. Birdsey, J. Fang, ... and D. Hayes: [A large and persistent carbon sink in the world's forests](#), Science, vol. 333, no. 6045, 2011.
3. S. Seibold, W. Rammer, T. Hothorn, ... and J. Mueller: [The contribution of insects to global forest deadwood decomposition](#), Nature, vol. 597, Sep 2021.
4. M. A. Bradford, R. J. Warren II, P. Baldrian, T. W. Crowther, D. S. Maynard, E. E. Oldfield, W. R. Wieder, S. A. Wood, and J. R. King: [Climate fails to predict wood decomposition at regional scales](#), Nature Climate Change, 2014.
5. P. Polewski, J. Shelton, W. Yao, and M. Heurich: Segmentation of single standing dead trees in high- resolution aerial imagery with generative adversarial network-based shape priors, *The International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences*, 2020.
6. D. Cremers, M. Rousson, and R. Deriche: [A review of statistical approaches to level set segmentation: Integrating color, texture, motion and shape](#), Int. J. Comput. Vision, vol. 72, no. 2, 2007.
7. D. Cremers and M. Rousson: [Efficient kernel density estimation of shape and intensity priors for level set segmentation](#), Deformable Models, Topics in Biomedical Engineering. International Book Series, Springer, 2007.
8. O. Ronneberger, P. Fischer, and T. Brox: [U-Net: Convolutional Networks for Biomedical Image Segmentation](#), CoRR, vol. abs/1505.04597, 2015.
9. Leventon, M., Grimson, W. and Faugeras, O.: [Statistical shape influence in geodesic active contours](#), Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, Vol. 1, 2000.
10. Tsai, A., Yezzi, A., III, W. W., Tempany, C., Tucker, D., Fan, A., Grimson, W. and Willsky, A.: [A shape-based approach to the segmentation of medical imagery using level sets](#), IEEE T. Med. Imaging 22(2), 2003.