

The Complete Playwright Cheat Sheet

2026 Edition

Every Method You Need. One Place.

- Navigation
- Locators
- Actions
- Assertions
- API Testing
- Network
- Config
- Advanced
- CLI Commands

NAVIGATION

`page.goto(url)`

Navigate to a URL

`page.goBack()`

Browser back button

`page.goForward()`

Browser forward button

`page.reload()`

Reload current page

`page.waitForURL(url)`

Wait for navigation to complete

`page.waitForLoadState('networkidle')`

Wait until no network requests for 500ms

`page.waitForLoadState('domcontentloaded')`

Wait for DOM content to load

`page.url()`

Get current page URL

`page.title()`

Get current page title

Aston Cook

Senior QA Automation Engineer

LOCATORS

`page.getByRole('button', {name: 'Submit'})`

Find by ARIA role (recommended)

`page.getByText('Welcome')`

Find by visible text content

`page.getByLabel('Email')`

Find by associated label text

`page.getByPlaceholder('Search...')`

Find by placeholder text

`page.getByTestId('login-btn')`

Find by data-testid attribute

`page.getByAltText('Logo')`

Find by image alt text

`page.locator('.class')`

Find by CSS selector

`page.locator('xpath=//div')`

Find by XPath expression

`locator.first`

Get first matching element

`locator.nth(2)`

Get element by index

ACTIONS

locator.click()

Click an element

locator.dblclick()

Double click an element

locator.fill('text')

Clear field and type text

locator.type('text')

Type character by character

locator.press('Enter')

Press a keyboard key

locator.check() / .unchecked()

Toggle checkbox state

locator.selectOption('value')

Select dropdown option

locator.hover()

Hover mouse over element

locator.dragTo(target)

Drag element to target

locator.focus()

Focus the element

locator.scrollToViewIfNeeded()

Scroll element into view

Aston Cook

Senior QA Automation Engineer

ASSERTIONS

`expect(locator).toBeVisible()`

Element is visible on page

`expect(locator).toBeHidden()`

Element is not visible

`expect(locator).toBeEnabled()`

Element is enabled

`expect(locator).toBeDisabled()`

Element is disabled

`expect(locator).toHaveText('text')`

Exact text match

`expect(locator).toContainText('partial')`

Contains text substring

`expect(locator).toHaveValue('val')`

Input has specific value

`expect(locator).toHaveAttribute('n','v')`

Element has attribute

`expect(locator).toHaveLength(n)`

Number of matching elements

`expect(locator).toHaveClass(/regex/)`

CSS class matches pattern

PAGE ASSERTIONS

`expect(page).toHaveTitle('title')`

Page title matches

`expect(page).toHaveURL(/pattern/)`

URL matches pattern

`expect(page).toHaveScreenshot()`

Visual comparison screenshot

`expect(response).toBeOK()`

Response status is 2xx

`expect(value).toBe(expected)`

Exact value match

`expect(value).toContain(sub)`

Value contains substring

`expect(value).toBeTruthy()`

Value is truthy

`expect(value).toBeGreaterThan(n)`

Numeric comparison

`expect(array).toHaveLength(n)`

Array length check

API TESTING

```
request.get(url)
```

Send GET request

```
request.post(url, { data: {} })
```

Send POST with body

```
request.put(url, { data: {} })
```

Send PUT with body

```
request.patch(url, { data: {} })
```

Send PATCH with body

```
request.delete(url)
```

Send DELETE request

```
response.status()
```

Get HTTP status code

```
response.json()
```

Parse response as JSON

```
response.headers()
```

Get response headers

```
response.ok()
```

Check if status is 2xx

```
request.newContext({ baseUrl: url })
```

Create API context with base URL

Aston Cook

Senior QA Automation Engineer

NETWORK

```
page.route('**/api/*', handler)
```

Intercept matching requests

```
route.fulfill({ body: '{}' })
```

Mock response with custom data

```
route.continue()
```

Let request pass through

```
route.abort()
```

Block the request entirely

```
page.waitForResponse('**/api/data')
```

Wait for specific response

```
page.waitForRequest('**/api/data')
```

Wait for specific request

```
page.on('response', callback)
```

Listen for all responses

```
page.unroute('**/api/*')
```

Remove route handler

CONFIGURATION

timeout: 30000

Global test timeout in ms

retries: 2

Auto-retry failed tests

workers: 4

Number of parallel workers

use: { headless: true }

Run without browser UI

use: { trace: 'on-first-retry' }

Record trace on retry

use: { screenshot: 'only-on-failure' }

Screenshot on failure

use: { video: 'retain-on-failure' }

Video on failure only

use: { baseUrl: 'http://localhost' }

Set base URL for tests

fullyParallel: true

Run all tests in parallel

Aston Cook

Senior QA Automation Engineer

ADVANCED

```
test.step('name', async () => {})
```

Named step for reports

```
test.describe('group', () => {})
```

Group related tests

```
test.beforeEach(async () => {})
```

Run before each test

```
test.afterEach(async () => {})
```

Run after each test

```
test.skip() / test.fixme()
```

Skip or mark as broken

```
expect().toPass()
```

Retry assertion until pass

```
page.evaluate(() => {})
```

Execute JS in browser

```
browser.newContext()
```

Create isolated context

```
test.use({ storageState: 'auth.json' })
```

Reuse auth state

CLI COMMANDS

`npx playwright test`

Run all tests

`npx playwright test --ui`

Open interactive UI mode

`npx playwright test --debug`

Run in debug mode

`npx playwright test --trace on`

Record traces for all tests

`npx playwright show-report`

Open HTML test report

`npx playwright show-trace trace.zip`

View recorded trace

`npx playwright codegen url`

Generate code by recording

`npx playwright test --grep 'tag'`

Run tests matching pattern

`npx playwright test --project=chromium`

Run specific browser

`npx playwright test --repeat-each=5`

Repeat each test N times

Aston Cook

Senior QA Automation Engineer

Keep This Open. You'll Need It.

Playwright Project Pack

Put this cheat sheet into practice. Available now.

Follow Aston Cook

for daily QA automation content

Aston Cook

Senior QA Automation Engineer