

Artificial Intelligence

Advanced Topics in AI & ML

Transformers: BERT, GPT, LLM

Aleksandr Petiushko

ML Research



Content

① Transformers

Content

- 1 Transformers
- 2 BERT

Content

- 1 Transformers
- 2 BERT
- 3 GPT

Content


- ① Transformers
- ② BERT
- ③ GPT
- ④ LLM

Transformer Architecture

- Transformer is the architecture with the minimal inductive bias (e.g., in comparison to CNN or RNN): we are looking at the correlation (“attention”) between every pair of input elements
- Super efficient architecture for literally every ML direction: CV, ASR, NLP, etc
- Can be encoder-decoder (machine translation), encoder (language modeling), and decoder (text generation - <http://jalammar.github.io/illustrated-gpt2/>)
- Read material: [link](#)

BERT

Encoder




GPT

Decoder


Transformer: BERT

- BERT = Bidirectional **E**ncoder Representations from **T**ransformers
- It is an encoder-based Transformer, only self-attention, trained by Masked Language Modeling (MLM) and Next Sentence Prediction (NSP)
- For each input there is a vectored output that can be used for a variety of tasks: e.g., text classification, or the key/value parts of cross-attention
- Read material: [link](#)




Transformer: GPT

- GPT = **Generative** Pre-trained **Transformer**
- It is a decoder-based Transformer, trained with **masked** self-attention (temporal causality) by Language Modeling (LM) — likelihood of the next predicted token based on the previous ones
- Generative because it generates autoregressively the new token based on statistical assumptions
- Read material: [link](#)




LLMs

- Large Language Model: A **huge language** model: encoder (e.g., BERT), decoder (e.g., GPT), or an encoder-decoder (e.g. for Machine Translation; although decoder models also can be used for it) pre-trained on a **massive** language corpus
- Main problems with LLMs right now: how to restrict the outputs (e.g., obscene language), how to ensure fairness, and how to avoid hallucinations
- Read material: [link](#)



ChatGPT

- ChatGPT is an auto regressive decoder model trained on a huge amount of textual data (like a half of the Internet) using the RLHF
- The architecture is not known but can be guessed on one of the OpenAI papers - InstructGPT¹
- Read material: [link](#)



¹Training language models to follow instructions with human feedback

Hallucinations

- Hallucination: one of the problems with LLMs
- It's the output that is not a part of the LLM training data
- Can be overcome with chain-of-thoughts, iterative output adjustment, and using external memory (retrieval augmented generation)
- Read material: [link](#)

Passage	Scenario #1 - Hallucination
Original Answer	Philip Hayworth was an English barrister and politician who served as Member of Parliament for Thetford from 1859 to 1868.
Sample 1	<i>Philip Hayworth was a British politician who served as the Member of Parliament for Bolton West from 1931 to 1945. He was also a member of the Free Trade Union and served on several government committees.</i>

Takeaway notes

- 1 Read all the mentioned links

Takeaway notes

- 1 Read all the mentioned links
- 2 Transformers with their self-attention block is the key architectural ingredient of LLMs and beyond

Takeaway notes

- 1 Read all the mentioned links
- 2 Transformers with their self-attention block is the key architectural ingredient of LLMs and beyond
- 3 Encoder, encoder-decoder, and decoder variants can be used for LLMs; decoder is now the dominant one

Takeaway notes

- ➊ Read all the mentioned links
- ➋ Transformers with their self-attention block is the key architectural ingredient of LLMs and beyond
- ➌ Encoder, encoder-decoder, and decoder variants can be used for LLMs; decoder is now the dominant one
- ➍ ChatGPT and successors added human feedback in the loop to make the output more plausible for the human user

Takeaway notes

- ➊ Read all the mentioned links
- ➋ Transformers with their self-attention block is the key architectural ingredient of LLMs and beyond
- ➌ Encoder, encoder-decoder, and decoder variants can be used for LLMs; decoder is now the dominant one
- ➍ ChatGPT and successors added human feedback in the loop to make the output more plausible for the human user
- ➎ It is still unknown how far we are from AGI

Thank you!