REAL PRODUCT EXPERIENCE · SANITISED

Loop EV Charging: Improving the Charging Start Journey

Product case study · Fathima Babuji

CONTEXT AND ROLE

Drawn from my work as iOS lead on an EV-charging app, working with product, design and backend. This case study is sanitised: it contains no confidential screenshots, code, customer data or metrics.

PROBLEM

Users could not tell whether a charger was available, whether the app could connect to it, or whether charging had actually started. Each of these failures created support requests or abandoned attempts.

PROPOSED JOURNEY: "READY TO CHARGE"

1	**Availability**	Show whether the charger is available before the user commits
2	**Charger details**	Make clear which charger the user is about to use
3	**Connection readiness**	Show whether the app can connect to the charger
4	**Start charging**	Make the start action reliable and observable
5	**Charging confirmed**	Confirm clearly that charging has actually started

DECISIONS AND TRADE-OFFS

- **Ask for Bluetooth permission at the moment of need, not at launch.**
- **Make charging start reliable and observable first (P0),** ahead of guidance and discovery.

PRIORITISATION

P0	Make charging start reliable and observable
P1	Permission and connection guidance
P2	Discovery and repeat shortcuts

SUCCESS METRICS

- Start-charging conversion
- Time from charger selection to confirmed charging
- Bluetooth connection success rate
- Charging-start failure and support-contact rate
- Permission-denial recovery rate

OUTCOME

A proposal and prioritisation, not a shipped result. No outcome metrics are claimed.