

```
PS D:\AMET SYLLABUS\docker> docker exec -it postgres psql -U postgres
-d company
company=# insert into employee
values(31, 'Nishanta', 25000);
INSERT 0 1
company=# select * from employee;
 id |  name   | salary
----+-----+-----
 31 | Nishanta |  25000
(1 row)

company=# update employee
set salary=100000
where id=31;
UPDATE 1
company=#
```

Microsoft Windows [Version 10.0.26200.8737]
(c) Microsoft Corporation. All rights reserved.

```
D:\AMET SYLLABUS\docker\yaml>curl -X POST http://localhost:8083/connectors ^
More? -H "Content-Type: application/json" ^
More? -d @register-postgres.json
{"name":"postgres-connector","config":{"connector.class":"io.debezium.connector.postgresql.PostgresConnector","database.
hostname":"postgres","database.port":"5432","database.user":"postgres","database.password":"postgres","database.dbname":
"company","database.server.name":"company_server","topic.prefix":"company_server","plugin.name":"pgoutput","table.includ
e.list":"public.employee","name":"postgres-connector"},"tasks":[],"type":"source"}
```

```
D:\AMET SYLLABUS\docker\yaml>docker exec -it kafka kafka-console-consumer \
--bootstrap-server localhost:9092 \
--topic company_server.public.employee \
--from-beginning
Exactly one of --include/--topic is required. (C)

Option                                     Description
-----
--bootstrap-server <String: server to    REQUIRED: The server(s) to connect to.
connect to>
--consumer-property <String:              A mechanism to pass user-defined
consumer_prop>                           properties in the form key=value to
                                           the consumer.
--consumer.config <String: config file>   Consumer config properties file. Note
                                           that [consumer-property] takes
                                           precedence over this config.
--enable-systest-events                   Log lifecycle events of the consumer
                                           in addition to logging consumed
                                           messages. (This is specific for
                                           system tests.)
--formatter <String: class>               The name of a class to use for
```