

1. Network Security Concepts

Network security refers to the set of policies, procedures, and practices adopted to prevent, detect, and monitor unauthorized access, misuse, modification, or denial of a computer network and network-accessible resources. It encompasses both hardware and software technologies.

Importance:

The objective of network security is to ensure the protection of data and resources by guaranteeing:

- **Confidentiality:** Preventing unauthorized disclosure of information.
- **Integrity:** Preventing unauthorized modification of information.
- **Availability:** Ensuring authorized users have reliable access to information and resources.

Real-World Context:

In today's digital world, businesses, governments, and individuals rely heavily on networks. A breach can lead to financial loss, reputational damage, and even national security threats.

Key Concepts

CIA Triad

Principle	Description
Confidentiality	Ensures that sensitive information is accessed only by authorized individuals. (e.g., encryption)
Integrity	Assures that information remains unaltered during storage, transmission, or processing. (e.g., hashing)
Availability	Guarantees reliable access to information and systems when needed. (e.g., redundancy, backups)

- **Example:** A healthcare system must keep patient records confidential, ensure data is accurate, and be accessible to doctors when required.

Non-repudiation

- **Definition:** Non-repudiation provides proof of the origin and delivery of data to prevent a sender from denying having sent a message or a receiver from denying having received it.
- **Methods:** Digital signatures, secure audit trails.
- **Example:** An online banking transaction log with timestamps and digital signatures.

Accountability

- **Definition:** Accountability ensures that actions of an entity (user, process, or device) can be traced uniquely to that entity.
- **Mechanisms:** Logging, auditing, user authentication.

Risk Management

- **Definition:** Risk management involves identifying, assessing, and controlling threats to an organization's digital assets.

- **Steps:**
 1. **Risk Identification:** Discover potential threats.
 2. **Risk Assessment:** Evaluate the likelihood and impact.
 3. **Risk Mitigation:** Implement measures to reduce risk.
- **Example:** Installing antivirus software to prevent malware infection.

Important Terms

1 Assets

- **Definition:** Resources of value to an organization that must be protected.
- **Examples:** Data, hardware, software, personnel.

2 Vulnerabilities

- **Definition:** Weaknesses or gaps in security that could be exploited.
- **Examples:** Unpatched software, weak passwords, unsecured devices.

3 Threats

- **Definition:** Potential events or actions that could cause harm.
- **Examples:** Cyber-attacks, insider threats, natural disasters.

4 Countermeasures

- **Definition:** Actions, devices, procedures, or techniques that reduce risk.
- **Examples:** Firewalls, antivirus software, employee training, multi-factor authentication.

Additional Concepts to Include

Defense in Depth

- **Definition:** A security strategy that layers multiple security measures to protect data.
- **Principle:** If one layer fails, another layer continues to protect.

Security Policy

- **Definition:** A formal set of rules and practices that regulate how an organization manages and protects its information assets.

Security Architecture

- **Definition:** The overall design of a network's security framework, including hardware, software, policies, and procedures.

Activities

- Identify examples of confidentiality, integrity, and availability in university networks.
- Analyze a public cyberattack case study and map the failure points to vulnerabilities and threats.
- Create a simple risk assessment for a college Wi-Fi network.

References for Further Reading

- Stallings, W. (2020). *Network Security Essentials: Applications and Standards*. Pearson.
- Bishop, M. (2018). *Computer Security: Art and Science*. Addison-Wesley.
- RFC 2196 - Site Security Handbook (IETF)

2. Threats

A **threat** is any potential danger that can exploit a vulnerability to breach security and cause harm to information systems or data integrity, confidentiality, or availability.

- Threats can be **intentional** (e.g., hacking attempts) or **unintentional** (e.g., employee mistakes).
- Threats arise from various actors: hackers, insiders, competitors, nation-states, etc.

Types of Threats

Passive Threats

Passive threats involve attempts to gain unauthorized access to information without affecting system resources.

a) Eavesdropping

- **How it is carried out:**
An attacker secretly listens to private communications over a network (e.g., intercepting unencrypted Wi-Fi traffic).
- **Examples:**
Capturing login credentials sent over HTTP.
- **Prevention and Mitigation:**
 - Use **encryption** (SSL/TLS).
 - Implement **secure Wi-Fi protocols** (WPA3).
 - Use **Virtual Private Networks (VPNs)**.

b) Traffic Analysis

- **How it is carried out:**
Even without understanding the contents, an attacker examines patterns and volumes of traffic to infer sensitive information.
- **Examples:**
Identifying the timing and size of encrypted messages to deduce activity.
- **Prevention and Mitigation:**
 - Use **traffic padding**.
 - Employ **onion routing** (e.g., Tor Network).

Active Threats

Active threats involve altering system resources or affecting operations.

a) Masquerade

- **How it is carried out:**
An attacker pretends to be an authorized user to gain access.
- **Examples:**
Using stolen credentials to log into a corporate network.
- **Prevention and Mitigation:**
 - Implement **multi-factor authentication (MFA)**.
 - Deploy **intrusion detection systems (IDS)**.

b) Replay Attacks

- **How it is carried out:**
An attacker captures legitimate data transmissions and retransmits them later to trick the receiver.
- **Examples:**
Resending a legitimate money transfer message to steal funds.
- **Prevention and Mitigation:**
 - Use **timestamps** and **session tokens**.
 - Apply **challenge-response protocols**.

c) Message Modification

- **How it is carried out:**
An attacker alters a legitimate message in transit between sender and receiver.
- **Examples:**
Changing the recipient's account number in an email requesting a bank transfer.
- **Prevention and Mitigation:**
 - Utilize **message integrity checks** (e.g., digital signatures).
 - Employ **end-to-end encryption**.

d) Denial of Service (DoS)

- **How it is carried out:**
An attacker floods a server or network with traffic to make services unavailable.
- **Examples:**
Sending millions of fake requests to a website causing downtime.
- **Prevention and Mitigation:**
 - Set up **rate limiting**.
 - Deploy **load balancers** and **DoS protection services**.

Common Threat Vectors

Threat Vector	Description	Example	Prevention & Mitigation
Malware (Viruses, Worms, Trojans)	Malicious software designed to damage or disrupt systems.	Email attachment containing ransomware.	Anti-malware software, email filtering, user education.
Phishing	Fraudulent attempts to obtain sensitive information by disguising as a trustworthy entity.	Fake email from a "bank" requesting password update.	Email security filters, user awareness training.
Man-in-the-Middle (MITM) Attacks	Intercepting and potentially altering communication between two parties.	Intercepting login credentials on public Wi-Fi.	SSL/TLS encryption, VPNs.
Insider Threats	Harm caused by individuals within an organization, intentionally or unintentionally.	Employee leaking confidential data.	Access control policies, employee monitoring.
Ransomware	Malware that encrypts data and demands ransom for release.	Locking company files until payment is made.	Regular backups, patch management, endpoint protection.

Threat Modeling

Threat modeling is the structured process of identifying and prioritizing potential threats to a system.

Steps in Threat Modeling

1. **Identify Assets**
 - What are you trying to protect? (e.g., personal data, financial records, intellectual property)
2. **Identify Potential Threats**
 - What could go wrong? (e.g., data breaches, unauthorized access, service disruptions)
3. **Determine and Prioritize Risks**
 - Analyze threats based on **likelihood** and **impact**.
 - Focus on high-risk areas.
4. **Develop Mitigation Strategies**
 - Implement controls to reduce risks (e.g., encryption, firewalls, monitoring).
5. **Continuous Review**
 - Threat landscapes evolve; threat models should be regularly updated.


Example of Threat Modeling: STRIDE Model

Threat Type	Description	Example
Spoofing	Pretending to be someone else.	Impersonating an administrator.
Tampering	Modifying data or code.	Changing a financial record.
Repudiation	Denying an action.	Denying sending a transaction.
Information Disclosure	Unauthorized information access.	Leaking personal data.
Denial of Service	Service interruption.	Crashing a server.
Elevation of Privilege	Gaining unauthorized access.	User becoming an admin.

Activity:

List out all common network threats and vulnerabilities along with prevention and mitigation.

3. Firewalls




A **firewall** is a network security device or software that monitors, filters, and controls incoming and outgoing network traffic based on predetermined security rules. It acts as a barrier between a trusted internal network and untrusted external networks, such as the Internet.

Primary Objective:

To prevent unauthorized access while permitting legitimate communication.

Importance of Firewalls in Network Security



- Acts as the **first line of defense** against external threats.
- **Monitors** network traffic and **enforces security policies**.
- **Prevents** unauthorized users from accessing private networks.
- **Protects** sensitive data and critical infrastructure.
- Helps in **logging and auditing** activities for accountability.

How Firewalls Work

- Firewalls inspect **packets** of data based on **rules** such as IP address, port number, protocol, and content.
- They **accept**, **reject**, or **drop** traffic based on the rules configured.

Simple Packet Filtering Example:

Source IP	Destination IP	Port	Action
192.168.1.10	172.217.3.110	443	Allow
Any	192.168.1.10	23	Deny

Types of Firewalls

1 Packet-Filtering Firewalls

- **Operation:**
Inspects packets independently based on header information (IP addresses, ports, protocols).
- **Advantages:**
 - Fast and simple.
 - Minimal impact on network performance.
- **Limitations:**
 - Cannot inspect packet payload.
 - Vulnerable to IP spoofing.
- **Example:**
Access Control Lists (ACLs) on routers.

2 Stateful Inspection Firewalls

- **Operation:**
Tracks the **state** of active connections and makes decisions based on the context of traffic (not just individual packets).
- **Advantages:**
 - Better security by tracking connections.
 - Identifies legitimate traffic.
- **Limitations:**
 - More resource-intensive than packet filtering.
- **Example:**
Cisco ASA (Adaptive Security Appliance).

3 Application Layer Firewalls (Proxy Firewalls)

- **Operation:**
Operates at the application layer and inspects the contents of traffic for specific applications (e.g., HTTP, FTP).
- **Advantages:**
 - Deep packet inspection.
 - Can block specific content or application behavior.
- **Limitations:**
 - Can cause latency due to high inspection overhead.
- **Example:**
Squid Proxy Server, Microsoft ISA Server.

4 Next-Generation Firewalls (NGFWs)

- **Operation:**
Combines traditional firewall functionalities with advanced features such as **intrusion prevention systems (IPS)**, **deep packet inspection**, and **application awareness**.
- **Advantages:**
 - Comprehensive security coverage.
 - Protection against sophisticated threats.
- **Limitations:**

- Higher cost and complexity.
- **Example:**
Palo Alto Networks, Fortinet FortiGate.

5 Cloud Firewalls (Firewall-as-a-Service)


- **Operation:**
Firewall services hosted in the cloud to protect cloud-based assets and remote users.
- **Advantages:**
 - Scalability and flexibility.
 - Centralized management.
- **Limitations:**
 - Dependent on Internet connectivity.
- **Example:**
AWS Firewall Manager, Azure Firewall.

Firewall Architectures

1. Bastion Host

- A fortified server exposed directly to the Internet, hosting security-critical applications.


Diagram:



2. Screened Subnet (DMZ - Demilitarized Zone)

- A network area that acts as a buffer zone between the external and internal networks.


Diagram:



- **Use:** Hosting public services (web servers, mail servers) while protecting internal resources.

3. Dual-Homed Host

- A firewall system with two network interfaces: one connected to the external network and one to the internal network.



Common Firewall Rules and Policies

Rule Type	Description
Allow Specific Traffic	Permit trusted IP addresses and ports.
Deny All by Default	Block all traffic unless explicitly allowed.
Restrict Outbound Access	Limit internal users' access to external sites.
Port Forwarding	Redirect traffic to specific internal services.

Best Practice:

Follow the principle of **least privilege** — only allow necessary traffic.

Strengths and Limitations of Firewalls

Strengths	Limitations
Protect against external attacks	Cannot protect against insider threats
Centralized access control	Cannot protect against malware from trusted users
Detailed traffic logging	Needs constant updates and monitoring
Supports VPNs and remote access	High-end firewalls can be expensive

Best Practices for Firewall Management

- Regularly **update firewall rules** and **firmware**.
- Perform **periodic security audits**.
- Implement **network segmentation**.
- Enforce **strong authentication** for firewall administration.
- Enable **logging and alerting**.
- Use **intrusion prevention systems (IPS)** alongside firewalls.

Real-World Example

Scenario:

An e-commerce company hosts a public website and an internal database.

- Public website is placed in the **DMZ** and protected by a **stateful firewall**.
- Database server is hidden behind an **internal firewall**.
- Access to the database is allowed only from the website's IP address using specific ports (e.g., 3306 for MySQL).

4. Authentication

Authentication in network security is the process of verifying the identity of a user, device, or entity attempting to access a network. It ensures that only legitimate users or systems are granted access to network resources.

Primary Objective:

- To establish trust between communicating parties.
- To protect resources from unauthorized access.

Importance of Authentication in Network Security

- **Validates identities** to prevent impersonation.
- **Protects sensitive information** from unauthorized access.
- **Forms the foundation** of access control mechanisms.
- **Ensures accountability** by linking actions to authenticated users.

Authentication Factors

Authentication can be based on one or more of the following factors:

Factor Type	Description	Examples
Something You Know	Information only the user should know	Passwords, PINs
Something You Have	A physical object in the user's possession	Smart cards, security tokens
Something You Are	Biological traits of the user	Fingerprints, iris scans, facial recognition
Something You Do	Behavioral characteristics	Typing rhythm, voice patterns
Somewhere You Are	Location-based authentication	GPS location, IP address verification

Multi-Factor Authentication (MFA):

Combines two or more factors to enhance security (e.g., password + fingerprint).

Authentication Methods

1 Password-Based Authentication

- **How it works:**
The user provides a secret password to verify identity.
- **Strengths:**
Simple and widely used.
- **Weaknesses:**
Vulnerable to guessing, phishing, brute-force attacks.
- **Best Practices:**
 - Enforce strong password policies.
 - Regularly update passwords.

- Use password managers.

2 Certificate-Based Authentication

- **How it works:**
Users or devices authenticate using digital certificates issued by a trusted Certificate Authority (CA).
- **Strengths:**
Strong authentication, scalable.
- **Use Cases:**
VPN access, secure email (S/MIME), HTTPS websites.

3 Biometric Authentication

- **How it works:**
Authentication using unique biological traits.
- **Strengths:**
Difficult to forge, convenient.
- **Challenges:**
Privacy concerns, biometric data theft risks.
- **Examples:**
 - Smartphone fingerprint unlock.
 - Facial recognition at airport security.

4 Token-Based Authentication

- **How it works:**
A security token (physical or software) generates a temporary code used for authentication.
- **Strengths:**
Adds a layer of security over passwords.
- **Examples:**
 - RSA SecurID tokens.
 - OTP apps (Google Authenticator).

5 Single Sign-On (SSO)

- **How it works:**
Allows users to authenticate once and access multiple systems without re-authenticating.
- **Strengths:**
Improves user experience, reduces password fatigue.
- **Risks:**
If SSO credentials are compromised, multiple systems are at risk.
- **Examples:**
 - Google SSO for Gmail, Drive, YouTube.
 - Microsoft Azure Active Directory SSO.

Authentication Protocols

Protocol	Purpose	Example Usage
Kerberos	Secure authentication over non-secure networks	Enterprise SSO
RADIUS	Centralized Authentication, Authorization, and Accounting (AAA)	ISP authentication, network access
TACACS+	Enhanced version of RADIUS with more security	Network device administration
OAuth 2.0	Authorization framework for token-based authentication	Logging into third-party apps with Facebook or Google
SAML	XML-based standard for exchanging authentication data	Web SSO in enterprises


Threats to Authentication

Threat Type	Description	Mitigation
Password Attacks	Brute-force, dictionary attacks	Enforce account lockout policies, MFA
Phishing	Deceptive emails to steal credentials	User education, anti-phishing tools
Credential Stuffing	Using leaked credentials to access other services	Monitor for compromised accounts, enable MFA
Replay Attacks	Intercepting and reusing authentication messages	Use nonces, time-stamps, secure protocols (SSL/TLS)

Best Practices for Secure Authentication

- **Use Multi-Factor Authentication (MFA)** wherever possible.
- **Enforce Strong Password Policies:**
Minimum length, complexity requirements, periodic changes.
- **Protect Authentication Data:**
Store hashed and salted passwords.
- **Implement Account Lockout Mechanisms:**
After a defined number of failed attempts.
- **Secure Authentication Channels:**
Always use encrypted protocols (HTTPS, SSL/TLS).
- **Educate Users:**
About phishing, social engineering, and password hygiene.

5. Intrusion Detection and Prevention (IDP)



Intrusion Detection Systems (IDS) and **Intrusion Prevention Systems (IPS)** are network security technologies designed to detect, monitor, and respond to unauthorized or malicious activities on a network or system.

- **IDS:** Monitors network traffic for suspicious activities and issues alerts.
- **IPS:** Monitors, detects, and actively blocks or prevents identified threats.

Primary Objective:


- **IDS:** Detection and alerting of suspicious activities.
- **IPS:** Prevention of attacks by actively blocking threats in real-time.

Importance of IDS/IPS in Network Security

- Provides **real-time threat detection**.
- **Identifies and blocks** known attack patterns.

- Assists in **incident response and forensic analysis**.
- Enhances overall **security posture** of the network infrastructure.
- **Complies** with security regulations and standards (e.g., PCI-DSS, HIPAA).

How IDS/IPS Works



- **Traffic Monitoring:** Continuously monitors network packets or system activities.
- **Pattern Matching:** Compares activities against a database of known attack signatures.
- **Anomaly Detection:** Identifies deviations from normal network behavior.
- **Alerting/Blocking:** Sends alerts (IDS) or blocks traffic (IPS) when malicious activity is detected.

Types of IDS/IPS

Type	Description	Example
Network-based IDS/IPS (NIDS/NIPS)	Monitors network traffic in real-time.	Snort, Cisco Secure IPS
Host-based IDS/IPS (HIDS/HIPS)	Monitors activities on individual devices or hosts.	OSSEC, Tripwire
Wireless IDS/IPS (WIDS/WIPS)	Monitors wireless networks for rogue devices or attacks.	AirMagnet, Aruba WIPS
Network Behavior Analysis (NBA)	Detects unusual traffic patterns.	Darktrace, Vectra AI

Devices and Systems Supported

- **Routers and Switches:** With integrated IDS/IPS features (e.g., Cisco routers with IOS IPS).
- **Firewalls:** Modern firewalls often have IDS/IPS functionality (e.g., Palo Alto Networks, Fortinet).
- **Dedicated Appliances:** Standalone IDS/IPS hardware (e.g., Cisco Firepower, Check Point IPS).
- **Servers and Endpoints:** HIDS/HIPS software installed on individual machines (e.g., OSSEC on Linux servers).
- **Wireless Controllers:** Wireless IPS for monitoring Wi-Fi threats (e.g., Cisco Wireless LAN Controllers).

Deployment Strategies

Strategy	Description
Inline (Active)	IPS placed directly in the traffic path to actively block threats.
Out-of-Band (Passive)	IDS monitors a copy of the traffic without interfering.
Hybrid	Combines both detection and prevention capabilities.

Ways IDS/IPS Prevent Network Attacks

- **Signature-Based Detection:** Identifies attacks based on known patterns (e.g., malware signatures).
- **Anomaly-Based Detection:** Identifies new or unknown attacks based on deviations from normal behavior.
- **Policy-Based Detection:** Monitors traffic based on pre-defined security policies.
- **Protocol Analysis:** Ensures protocol compliance and detects protocol-specific attacks (e.g., HTTP header anomalies).

Common Use Cases:

- Preventing **Denial of Service (DoS)** attacks.
- Blocking **SQL Injection** attempts.
- Detecting **Brute Force login attempts**.
- Monitoring for **Zero-Day Exploits**.

Examples of IDS/IPS in Practice

Tool	Functionality	Deployment
Snort	Open-source NIDS	Enterprise and SMB networks
Suricata	High-performance NIDS/NIPS	Large networks
OSSEC	Host-based IDS (HIDS)	Linux and Windows systems
Cisco Secure IPS	Commercial NIPS	Integrated with Cisco Secure Firewall
Palo Alto Threat Prevention	Cloud-enabled IPS	Next-Gen Firewalls

Advantages of IDS/IPS

- **Early Detection** of threats and vulnerabilities.
- **Automated Prevention** reduces the need for manual intervention.
- **Comprehensive Monitoring** across network segments and endpoints.
- **Enhances Incident Response** by providing detailed logs and forensic data.

Limitations of IDS/IPS

- **False Positives:** Legitimate traffic may be incorrectly flagged.
- **False Negatives:** Sophisticated attacks may go undetected.
- **Performance Impact:** Inline IPS can introduce latency.
- **Signature Updates Required:** Constant updates are needed to detect new threats.

Best Practices for Effective IDS/IPS Deployment

- **Regular Signature Updates:** Ensure the IDS/IPS is always updated against the latest threats.
- **Tuning and Optimization:** Customize rules to minimize false positives.
- **Segmentation:** Deploy multiple IDS/IPS sensors at critical points in the network.
- **Encryption Awareness:** Deploy solutions that can inspect encrypted traffic (e.g., SSL/TLS inspection).
- **Integration with SIEM Systems:** Centralize alert management and correlation with Security Information and Event Management (SIEM) tools.
- **Regular Testing:** Conduct penetration tests and red team exercises to validate the effectiveness of IDS/IPS.

6. Security and Cryptography

Cryptography is the practice and study of techniques for securing communication and data from adversaries. It involves transforming information to make it **confidential**, **authentic**, **integral**, and **non-repudiable**.

Role in Network Security:

Cryptography is fundamental to securing data in transit and at rest, ensuring that only authorized parties can access or alter the information.

Objectives of Cryptography in Network Security

- **Confidentiality:** Prevents unauthorized access to information.
- **Integrity:** Ensures information has not been altered.
- **Authentication:** Confirms the identity of communicating parties.
- **Non-repudiation:** Prevents denial of a previous commitment or action.

These objectives align closely with the CIA triad: Confidentiality, Integrity, and Availability.

How Cryptography Works

Cryptography relies on **algorithms** (set of mathematical functions) and **keys** to encrypt (encode) and decrypt (decode) data.

- **Encryption:** Converting plaintext (readable data) into ciphertext (unreadable format).
- **Decryption:** Converting ciphertext back into plaintext using a secret key.

Basic Process:

1. Sender encrypts the message using an encryption algorithm and key.
2. Ciphertext is transmitted over the network.
3. Receiver decrypts the message using the decryption algorithm and appropriate key.

Types of Cryptography

Type	Description	Example Algorithms
Symmetric Key Cryptography	Same key is used for both encryption and decryption.	AES, DES, 3DES, RC4
Asymmetric Key Cryptography	Different keys are used: public key for encryption, private key for decryption.	RSA, ECC, ElGamal
Hash Functions	No keys; transforms data into a fixed-size hash value.	SHA-256, MD5, SHA-3

1 Symmetric Key Cryptography

- **Features:**
 - Fast and efficient for large volumes of data.
 - Key distribution and management are challenging.
- **Examples:**
 - **AES (Advanced Encryption Standard):** Widely used in securing communications (e.g., Wi-Fi, VPNs).
 - **DES (Data Encryption Standard):** Older, largely obsolete due to vulnerabilities.

2 Asymmetric Key Cryptography

- **Features:**
 - Solves the key distribution problem.
 - Slower than symmetric encryption.
- **Examples:**
 - **RSA:** Used in secure web browsing (HTTPS).
 - **Elliptic Curve Cryptography (ECC):** Provides same security with smaller key sizes, ideal for mobile devices.

3 Hash Functions

- **Features:**
 - Converts input into a unique, fixed-size string.
 - Irreversible (one-way function).
- **Examples:**
 - **SHA-256:** Standard in blockchain technology.
 - **MD5:** Deprecated for security-critical applications.

Cryptographic Protocols in Network Security

Protocol	Purpose	Example Use
SSL/TLS	Secure web communication	HTTPS websites
IPsec	Secure IP communications	VPNs
SSH	Secure remote login	Secure shell access to servers
PGP	Secure email communication	Encrypting and signing emails
Kerberos	Secure authentication within a network	User and service authentication

Applications of Cryptography in Network Security

- **VPNs (Virtual Private Networks):** Encrypt data traveling over insecure networks.
- **Secure Email:** Protects email content from interception.
- **Secure Web Browsing:** SSL/TLS encrypts communications between browsers and servers.
- **Authentication:** Password storage, digital certificates, and digital signatures.

Common Devices and Systems Utilizing Cryptography

- **Routers and Firewalls:** IPsec for secure VPN tunnels.
- **Web Servers:** TLS certificates for HTTPS.
- **Mobile Devices:** End-to-end encryption for messaging apps (e.g., WhatsApp).
- **Smart Cards and Tokens:** Secure authentication using cryptographic methods.

Strengths and Limitations of Cryptography

Strengths	Limitations
Protects confidentiality and integrity of data	Computational overhead can slow down systems
Ensures secure communications over insecure channels	Vulnerabilities in algorithms (e.g., outdated ciphers)
Enables trust through authentication and non-repudiation	Key management is complex and critical
Legal compliance (GDPR, HIPAA)	Human factors (poor password management, phishing)

Best Practices for Secure Cryptographic Implementation

- Use **strong, up-to-date algorithms** (e.g., AES-256, SHA-3).
- Regularly **rotate keys** and **manage them securely**.
- Implement **multi-factor authentication** where possible.
- Ensure **secure key exchange mechanisms** (e.g., Diffie-Hellman).
- **Patch and update** cryptographic libraries and systems regularly.
- Avoid using **deprecated algorithms** (e.g., MD5, SHA-1).

Encryption Process

Plaintext -> [Encryption Algorithm + Key] -> Ciphertext -> Transmission -> [Decryption Algorithm + Key] -> Plaintext