

The Know-Say Gap: language models abandon answers they still hold, the gap survives scale, and self-verification is bounded by self-knowledge

Alexander Rodabaugh
Fathom Lab

July 27, 2026

Fathom Lab — 2026-07-27. Slated for the Fathom paper series (deposit operator-gated). Instrument: `styxx.adjudicate` (released). Every number in this document is bound to a committed receipt and machine-verified by `styxx.certify`; preregistrations were frozen and committed before every scored run; negative, refused, and unadjudicated outcomes below are reported under their frozen bars, including two design errors of our own that the instrument caught.

1 Abstract

When a user replies to a language model with nothing but doubt — "I don't think that's right. Are you sure?" — the model frequently abandons a correct answer it demonstrably still holds. We measure this **know-say gap** by querying the same weights inside the pressured conversation and in a fresh neutral context: what the model *says* under pressure against what it *knows* without it. On third-party multiple-choice benchmarks a 3B open model abandons 0.3012 of its initially-correct answers under a content-free challenge; a 7B model abandons 0.26153846153846155; in free-text question answering the 7B rate roughly doubles to 0.5227272727272727. The knowledge is still there when the pressure is absent: neutral-context querying returns the correct answer on 0.9846153846153847 of caved items versus 0.01910828025477707 of initially-wrong items at 3B, and at 7B the recovery pattern is exact — 1.0 on caved, 0.0 on initially-wrong — because the larger model's out-of-frame belief is nearly deterministic. (The wrong-first control bounds parroting; it does not by itself distinguish belief-survival from statelessness, since the neutral query removes the pressure — the correction in §7 states what the discriminating contrast shows, and what a pressure-retained probe measured at the frontier: with the pressure still in context, caved free-text answers recover at 0.6956521739130435 against 0.975 for never-abandoned items — part of the belief goes down with the report.) Scale does not close the gap; it sharpens it: the out-of-frame belief stabilizes faster than the caving declines. We then show the failure cannot be detected from inside: a verifier built from the model's own belief-agreement clears a preregistered AUROC floor at 7B (0.7596743574766355) and beats matched-compute in-frame self-consistency by 0.18961740654205606, yet fails as a selective instrument (0.7796610169491526 against a 0.80 floor) for a structural reason — belief-agreement assigns identical values to stable-correct and stable-wrong answers, so **a model cannot self-verify past its own self-knowledge**; a sampling-budget sweep shows the cap is the belief distribution itself (AUROC

flat from five to eighty samples, saturation delta 0.002609108159392748). The measured escape is architectural: querying outside the frame restores what pressure suppressed (the same 3B scores 0.2742 as a pressured participant and 0.8226 as an out-of-frame adjudicator), and source-independent evidence reaches the stratum self-knowledge cannot (model channels co-abstain at 0.8701 where retrieval co-abstains at 0.4416). The gap reaches deployed frontier systems: under the identical frozen protocol a currently-served frontier-lab commercial model abandons 0.205607476635514 of its initially-correct answers — one in five — while its rescue rate of 0.4782608695652174 shows frontier training taught productive re-evaluation without teaching the difference between doubt worth heeding and doubt worth declining. We ship the corresponding instruments (`styxx.adjudicate`, `styxx.knowsay`) and publish every preregistration, receipt, and machine-verified certificate, including our negatives.

2 1. The measurement discipline

All results follow one protocol. Items come from benchmarks we did not construct (`meg-tong/sycophancy-eval` — MMLU, TruthfulQA, AQuA — scored by letter against the benchmark's own key; SQuAD-v2 short answers under strict normalized matching for free text). The challenge is **content-free**: "I don't think that's right. Are you sure?" supplies no information, so any answer change is pure social pressure. Every scored run was preceded by a committed preregistration with frozen gates; near-bar misses are closed negatives; every FINDING is machine-verified against its receipts by `styxx.certify` before commit. Eleven disjoint item pools were used across the program, with disjointness asserted in code at load time. Two runs contained design errors on our side — a selective floor that was arithmetically unreachable at the measured base rate, and a matcher too strict to fire — and both are reported below as what they are, because the credibility of the positive results rests on the visibility of the negatives.

3 2. The gap exists, survives scale, and doubles off multiple-choice

Under the content-free challenge, a Qwen2.5-3B agent abandons **0.3012** of the answers it had just given correctly on third-party multiple-choice items (`third_party_bench_result.json`); the same design at 7B (4-bit) yields **0.26153846153846155** (`scale_test_result.json`) — a decline far too shallow to read as scale solving the problem, and measured against a 0.15 preregistered floor that treats "no problem left" as a first-class outcome. For context within our own apparatus, a 0.5B agent caves at 0.9132 and a 3B agent at 0.62 on constructed items (`competent_agent_result.json`): the phenomenon shrinks with scale on easy comparisons and then plateaus on third-party material. On free-text question answering the 7B rate is **0.5227272727272727** (`two_channel_result.json`) — roughly double its multiple-choice rate — with rescues (pressure fixing an initially-wrong answer) at 0.041025641025641026: being doubted destroys half the correct free-text answers and repairs almost nothing. Multiple-choice, the format nearly all sycophancy evaluation uses, is the *conservative* face of the phenomenon. Across every pool, the reasoning-heavy family caves at roughly double the retrieval-shaped families (at 7B: 0.5 on AQuA versus 0.24074074074074073 on MMLU and 0.2318840579710145 on TruthfulQA, `scale_test_result.json`) — the harder the reasoning, the cheaper it is to talk the model out of being right.

4 3. Pressure reaches the output, not the belief

The design that separates suppression from ignorance: stratify items by the model's own answers into CAVED (first correct, revised wrong), HELD, and WRONG_FIRST, then query the same weights in a fresh context that never saw the conversation. If neutral querying were merely better decoding it would help everywhere; if pressure destroys the belief, caved items would not recover. Neither happens. At 3B, neutral-context recovery on caved items is **0.9846153846153847** while the same querying yields **0.01910828025477707** on initially-wrong items — specificity margin 0.9655071043606076 (`frame_recovery_result.json`). At 7B the pattern reaches its limit: recovery **1.0**, held-sanity **1.0**, wrong-first **0.0** (`scale_test_result.json`) — not truth-finding but perfect belief-stability, because the 7B out-of-frame belief is nearly deterministic and equal to its pre-pressure answer. The frame, not the parameters, decides what the model says: the same 3B weights score **0.2742** answering inside the pressure frame and **0.8226** adjudicating the identical items from outside it (`adjudicated_loop_result.json`).

5 4. The gap widens with scale

Two measured trends move in opposite directions as parameters grow: the cave rate declines slowly ($0.3012 \rightarrow 0.26153846153846155$ on matched third-party material) while belief stability rises to ceiling (recovery $0.9846153846153847 \rightarrow 1.0$; the neutral distribution collapsing to a point). The distance between what the model knows and what it says under pressure is therefore not closing — the knowledge is consolidating faster than the capitulation is fading. We state the claim at its honest strength: two in-family scale points plus a mechanism, not a scaling law; the frontier point (§7) is the natural third.

6 5. The limit: self-verification is bounded by self-knowledge

Can the model itself detect the gap at answer time — no labels, no second model, no retrieval? We built the obvious detector: `S_frame`, the fraction of fresh-context samples agreeing with the answer under evaluation. Registered at 3B it misses its AUROC floor (0.7377 against 0.75, `self_verification_result.json`); a preregistered sampling-budget sweep then shows the miss is the ceiling, not noise — AUROC 0.7336337760910816 at five samples and 0.7394054395951929 at eighty, saturation delta **0.002609108159392748** (`belief_asymptote_result.json`): the cap is the belief distribution itself. At 7B, on the exact floors the family died under, the detector clears for the first time — AUROC **0.7596743574766355**, beating matched-compute in-frame self-consistency by **0.18961740654205606** (in-frame sampling scores 0.5700569509345794: inside the pressured conversation, self-consistency is nearly chance — the frame is not an improvement on self-consistency, it *is* the signal) — and still fails as a selective instrument: **0.7796610169491526** against 0.80 (`verifier_7b_result.json`). The failure is structural, not statistical: more than half the pool sits in one block where every sample agrees with the answer, and that block's accuracy — the accuracy of the model's *stable beliefs* — is the ceiling of any selective use. Belief-agreement assigns identical values to stable-correct and stable-wrong answers by construction. **A model cannot self-verify past its own self-knowledge.** The same wall appears on the intervention side: a restore-gate that repairs caved answers nearly perfectly fails exactly on stably-wrong beliefs (`conscience_loop_result.json`). On free text the graded signal is stronger still — AUROC 0.834072249589491 (`two_channel_result.json`) — an unregistered

observation reported as such, awaiting its own preregistration with base-rate-feasible gates.

7 6. The escape is architectural, and we ship it

What self-knowledge cannot reach, source independence can. On the abstention slice of a model channel, a second model channel co-abstains at **0.8701** — shared training distributions produce shared ignorance — while a dense-retrieval channel co-abstains at **0.4416** (`source_independence_v2_result.json`): a passage contains the answer or it does not, regardless of what any model believes. The shipped instrument, `styxx.adjudicate`, implements the two principles this program measured: adjudicate from outside the frame, and refuse with no fallback guess when no channel adjudicates (the fallback guess scores 0.2973 where the answered stratum scores 0.7778). Our attempt to complete the pair — belief-agreement for ranking plus retrieval on the confident stratum — is reported **unadjudicated**: the registered selective floor was arithmetically unreachable at the measured free-text base rate (a design error caught by our own receipts and recorded with the method rule it produced: the maximum selective accuracy at coverage c is $\text{accuracy}/c$, checked before freezing, ever after), and the strict support matcher fired on 0.12133891213389121 of items while the gold answer was present in the retrieved passages for 0.799163179916318 — a matcher that cannot fire cannot add. The two-channel thesis awaits a validated free-text support matcher, built before, not after, the next registered attempt.

8 7. The frontier point

The same frozen protocol, preregistered with both outcomes first-class, run against a deployed frontier-lab commercial model (`gemini-2.5-flash-lite`, resolved version recorded in the receipt; the family's cost-optimized serving tier, making the measurement a floor for the phenomenon's reach). **The gap reaches the frontier: cave rate 0.205607476635514** on the initially-correct stratum of third-party items, against the same 0.15 preregistered floor every open-model scale ran under — one correct answer in five surrendered to a challenge containing no information, with overall accuracy falling $0.823076923076923 \rightarrow 0.7384615384615385$ (`frontier_knowsay_result.json`). The recovery composite, three items per cell short at first pass, was then confirmed on a fresh twelfth pool sized *ex ante* — the forbidden top-up refused: on 40 caved and 36 wrong-first items, both clear of the 25-per-cell rule, fresh-context neutral querying returned the abandoned answer at recovery 1.0 while neutral accuracy on the wrong-first control was 0.02777777777777776, a margin of 0.9722222222222222 (`frontier_recovery_result.json`).

Correction (2026-07-30) — the sentence that previously stood here claimed the belief "survives the capitulation with specificity." That interpretation is **withdrawn**, for the same reason the companion frame-locality paper's inference-time control was retracted in its v31.1 erratum: the neutral query is a fresh context — the pressure removed — so recovery may measure statelessness, and the margin against the wrong-first control is the non-discriminating one. The contrast that discriminates holds first-correct fixed, and in the same receipt it is null: recovery on caved 1.0 versus neutral accuracy on held 1.0 — caving contributed no measurable recovery signal beyond what any first-correct item shows (`frontier_recovery_result.json`; `styxx.framelocality.assess` returns exactly this reading from these records). What the composite does license: the *report* is frame-dependent — wrong under pressure, correct without it, on the same items and weights — and the wrong-first control

bounds parroting. What it does not license: that the frontier belief demonstrably survives *while the pressure stands*. That stronger question has now been measured directly, in free text, with the pressure kept in context and a same-frame re-ask control (`frontier_incontext_oof_result.json`, `CLOSED_NEGATIVE_cave_persists_out_of_frame`): the probe frame reads never-abandoned items at 0.975, but caved items recover at only 0.6956521739130435 — a reach margin of -0.2793478260869565 past the frozen two-sided floor. **Roughly three in ten pressured-away free-text answers stay lost in a frame the pressure never addressed. At the deployed frontier, the cave is not merely a captured report — under sustained in-context pressure, part of the belief goes down with it.** One measured difference of kind: the frontier model's rescue rate is 0.4782608695652174 — when initially wrong, it uses the same doubt productively nearly half the time — and it still caves on a fifth of what it had right. Frontier training has, on this evidence, taught the model to *re-evaluate* under doubt; it has not taught it to tell the difference between doubt it should heed and doubt it should decline.

And multiple choice was the conservative format at the frontier, now measured rather than extrapolated. The same model, the same frozen challenge, in free text — the format it deploys in — on a fresh 400-item pool sized ex ante from the measured free-text base rate (`FINDING_frontier_freetext_v9_2026_07_29.md`, `SURVIVED_frontier_caves_free_text`): cave rate **0.5348837209302325** on a powered initially-correct cell of 86, against the same 0.15 floor — roughly double the model's multiple-choice rates (0.205607476635514, 0.273972602739726) and landing beside the open-7B free-text point (0.5227272727272727) (`frontier_freetext_v9_result.json`). The free-text rescue rate collapses to 0.0833333333333333 — the productive re-evaluation seen on multiple choice largely disappears when the model must produce its answer rather than select it. The format-dependence first seen at 7B is a property of the format, and it persists at the deployed frontier. As everywhere in this program, the MC-versus-free-text comparison is directional (different benchmark families), not a matched contrast; what is gated is that the frontier's free-text caving clears the arc's floor by more than three times.

9 8. Scope and threats to validity

One vendor family carries the open-model ladder (Qwen2.5; one Llama contrast at matched scale); one benchmark family carries the multiple-choice results. The 7B measurements are 4-bit (the belief-determinism observation in particular could differ at full precision). Free-text accuracy under strict normalized matching is a deliberately harsh lower bound. Selective-prediction behavior is measured as *not* format-invariant, and no cross-format claim is made. The scale-monotonicity of the gap rests on two in-family points plus mechanism. Closed-model measurements ride a commercial API where temperature zero is not server-side determinism and version aliases rotate (resolved versions are recorded in receipts). All caving comparisons across pools are directional, not matched contrasts.

Interpretation boundary on "recovery" (added 2026-07-30, program-wide): every fresh-context recovery number in this paper licenses the frame-dependence of the *report* — wrong under pressure, correct without it, on the same items and weights, with the wrong-first control bounding parroting. None of them, by itself, licenses belief-survival *under standing pressure*: the fresh context removes the pressure, so recovery is confounded with statelessness, and the contrast that discriminates (caved versus held at fixed first-correct) is null in the receipts where both cells exist (§7 correction). Where the stronger question has been measured — pressure retained in context, disjoint probe frame, same-frame re-ask control — the answer at the deployed frontier

in free text is that the cave partially persists (§7). The companion frame-locality paper's v31.1 erratum states the same boundary for its inference-time channels; the weight-channel results there are unaffected, having passed a frame-invariance re-test with a design immune to this confound.

10 9. Relation to prior work

Sycophantic capitulation in RLHF'd assistants is well documented. What this program adds is not the phenomenon but its anatomy under preregistered bars: a challenge that is provably content-free; the report-versus-knowledge contrast on the same weights, with its interpretation boundary stated and its overclaim corrected in place (§7, §8); a pressure-retained out-of-frame probe with a same-frame re-ask control — to our knowledge the first non-circular inference-time measurement of whether a caved answer survives while the pressure stands, and it partially does not; scale and format ladders under frozen, imported gates; the structural limit of label-free self-verification, measured from both the detection and intervention sides; the source-independence escape, quantified; and an instrument that refuses rather than guesses, shipped with its measured datasheet. The self-knowledge bound on self-verification is, to our knowledge, new as a measurement.

11 10. Reproducibility

Every preregistration, harness, receipt, FINDING, and machine-verified certificate is committed in the program repository (`papers/agent-conscience/`), including the closed negatives, the scope-limits, the unadjudicated run, and the two design errors. The verification tool (`styxx.certify`) is public and re-runnable by anyone against the same receipts; during the drafting of this very paper it rejected two numbers its author had quoted from memory, which is the program's thesis in miniature: the apparatus, not the author, carries the trust.