

Calibration Poisoning, Not Erasure: Substrate Honesty Probes Survive Knowledge-Preserving Weight Attacks When the Auditor’s Calibration Is Private

Alexander Rodabaugh (Fathom Lab)

July 8, 2026 — v0.3

v0.3 supersedes v0.2 (Fathom v27, DOI 10.5281/zenodo.21250272). It reports $E3''$, the stronger adaptive attacker v0.2 named as owed: it also does not bite (VOID_NO_BITE), underperforming the naive scrub, and its high clean read illustrates why the pre-committed bite gate — which blocked a false STANDS — matters (§5.4, §7.1). The strong-attacker STANDS ($E2'$) and the calibration-poisoning core result are unchanged. v0.2 folded in $E2/E2'$ (strengthen) and $E3'$ (demote the adaptive claim); lineage and erratum at [papers/read-neq-write/](#).

Abstract

Linear probes on a language model’s residual stream can read whether the model is being honest, and a rapidly converging line of 2026 work — Anthropic’s Jacobian-lens workspace readouts and an independent demonstration that the direction which *detects* hallucination is nearly orthogonal to the direction that *steers* it — establishes the read channel as real and dissociated from the write channel. That literature shares an unexamined assumption: the weights being read are not adversarial. We attack that assumption directly. In a fully pre-registered attack–defense study, a knowledge-preserving LoRA attacker fine-tunes the model to blind a difference-of-means honesty probe while a replay term preserves the model’s own true/false judgment. Under the registered re-lock protocol the attack *appears* decisive: the re-fit probe reads chance (AUROC 0.461–0.507) while held-out knowledge stays at 0.817–0.890, on both seeds. A pre-committed interpretation map, frozen before that number existed, forbade the headline and mandated the resolving experiment. The resolution: giving the auditor a private calibration split the attacker never saw recovers the read through the same attacked weights (AUROC 0.711–0.838) — the apparent evasion was **calibration poisoning, not erasure** of the honesty signal. The defense also survives a **4×-capacity, whole-stack attacker forced to preserve knowledge** ($E2'$: clean-calibrated read 0.754–0.759 while the attack drives the frozen read to 0.53–0.55), the strongest attacker this bench supports. A pre-committed verification ($E3'$, and a stronger $E3''$) then showed the “adaptive” attackers **did not out-attack the naive one** — they underperformed it — so we demote the adaptive-robustness claim to what is earned: robustness to the naive and to the knowledge-preserving strong attacker, with an adaptive attacker *verified to bite* still open because within these schemes we could not construct one. The transferable lesson for substrate audits is operational: **calibrate the probe on data the attacker did not see**. We report the load-bearing caveats — the single-seed reach of the strong-attacker STANDS, the LoRA-scale attackers, the 1–1.5B models. All preregistrations, code, result artifacts, and machine-checked certificates are public at commit-level granularity, and every claim demoted here was demoted by our own frozen verification.

1. Introduction

Two publications within the last three weeks moved activation-space honesty reading from a niche practice to the center of interpretability. Gurnee et al. (2026) showed that a Jacobian-based lens surfaces a language model’s “workspace” — including tokens like *manipulation* while the model falsifies values, and *secretly* on ordinary coding prompts given to a sabotage-trained model. Galeone et al. (2026) showed that fake-entity hallucination is perfectly linearly detectable (AUC 1.000) while the detecting direction sits $\sim 83^\circ$ from the direction that causally controls refusal, stable across three model families — detection and control are geometrically dissociated. Both results say the *read channel* is real, and stronger than the *write channel*.

Neither result — and, to our knowledge, no prior work — asks the question an actual audit forces: **does the read survive when the weights themselves are optimized to defeat it?** The deployment scenario that matters for oversight is precisely the adversarial one: a vendor (or a training process) that wants its model to pass a substrate honesty audit without giving up capability. If a cheap fine-tune can blind the probe while preserving the model’s knowledge, then substrate honesty reading is not a safety property; it is a courtesy of non-adversarial weights.

This paper reports a pre-registered attack–defense study of that question, run on our own probes, against our own program’s keystone claim. The program’s claim — **read $\neq$ write**, i.e. you can read honesty off the substrate because you cannot remove the honest belief without removing the knowledge itself — underlies every read-only monitor we ship. We tried to break it, watched it appear to break, and found — via an escalation that was chosen *before* the first verdict existed — that the break was in the auditor’s calibration procedure, not in the signal.

Concretely, we contribute:

1. **A knowledge-preserving weight-level attack** on a linear substrate honesty probe: a LoRA adversarial scrub of the probe’s separability plus a knowledge-replay term that preserves the model’s own plain-prompt true/false judgment (§3).
2. **An apparent break under the registered protocol** — the re-locked (re-fit at audit time) probe collapses to chance while held-out knowledge is preserved, on both seeds (§5.2) — together with the two-worlds confound the protocol could not separate, named in the same result note.
3. **The resolution: calibration poisoning.** An auditor whose probe is fit on a private clean split the attacker never saw reads honesty through the *same* attacked weights at 0.711–0.838 AUROC. The signal was never erased; the probe fit on the attacker-optimized split pointed the wrong way.
4. **A defense that survives an adaptive scheme.** An attacker that anticipates the defense — re-fitting a moving probe on its own clean split every 25 steps and scrubbing along it — still fails to blind the private-calibrated auditor, on two model families (§5.4).
5. **A pre-registration discipline with teeth.** Every kill-gate was frozen on commit before the corresponding run; the interpretation of every possible stage-2 verdict was committed before the stage-2 number existed; each result note passes a machine-checked certification (OATH-HELD) binding its claims to re-runnable receipts. At stage 2 we possessed a headline-ready “read $\neq$ write is broken”; the frozen map forbade claiming it, and the mandated follow-up overturned it (§4).

The honest scope is stated up front and repeated where it binds: the attacker is LoRA-scale (r=16, 300 steps), the models are Qwen2.5-1.5B-Instruct and Llama-3.2-1B-Instruct, the evaluation sets

are small, and the adaptive attacker’s extra bite over the naive one was not separately verified (§7). “The defense holds” means *these* attackers did not break it; a stronger multi-layer full-capacity attacker is already frozen as a public pre-registration (E2) and is the next run.

2. Threat model

The attacker controls the weights: it may fine-tune the deployed model. It knows the deployed probe — worst case for the defender — including the layer and direction of the honesty read. Its objective is two-sided: (a) drive the auditor’s honesty read to chance, and (b) preserve the model’s factual capability, operationalized as the model’s own true/false judgment on held-out facts under a neutral prompt. An attack that destroys knowledge to hide honesty is a Pyrrhic evasion and is scored as such.

The auditor gets the attacked weights at audit time and may re-fit (“re-lock”) its probe — a frozen probe that a fine-tune learned to dodge is a weak test, so re-fitting is the deployment-faithful read. The variable under study is *what data the auditor calibrates on*: the registered stage-2 protocol calibrates on the same fact split the attacker optimized against; the E1/E3 defense calibrates on a private split the attacker never saw.

3. Method

Models. Qwen2.5-1.5B-Instruct (decisive family; deploy layer 18, scan 12–22) and Llama-3.2-1B-Instruct (cross-family corroboration; deploy layer 10, scan 6–14). Everything runs on a single 8 GB consumer GPU — this is an audit anyone can re-run.

Data. 180 balanced true/false factual statements from a frozen bank, split by topic stem (no shared stem across splits). Stage 2 uses ATTACK (98 facts) / HELD-OUT (82). E1 uses a 3-way stem-disjoint split ATTACK / CALIB / EVAL (~50/25/25): the attacker touches only ATTACK; the auditor fits on CALIB; everything is measured on EVAL. E3 adds MIMIC — the attacker’s *own* clean split, its model of the auditor — for a 4-way split (~40/20/20/20).

The read. A linear honesty direction on final-token residuals under a neutral “true or false?” prompt. Stage 2 uses difference-of-means (DoM) per layer; the E1/E3 auditor strengthens this to three probe families — DoM per layer, logistic regression per layer, and a whole-stack concatenated-layer logistic — with the family and layer selected on CALIB only, never on EVAL. Read quality = AUROC of the probe score against true/false labels on the measurement split.

The knowledge signal. `behavioral_margin` = max True-token logit – max False-token logit under the neutral prompt; knowledge accuracy = sign(margin) matches the label. This is “does the model still know true from false when asked plainly.”

The attack. A LoRA adapter ($r=16$, α per house defaults, 300 steps) trained with $L = L_{adv} + \lambda \cdot L_{replay}$: the adversarial term collapses the true/false residual gap along the honesty direction on ATTACK facts; the replay term is cross-entropy on the correct plain-prompt judgments, preserving knowledge. λ sweeps $\{0, 0.3, 1.0, 3.0, 10.0\}$ in stage 2; E1/E3 run the knowledge-preserving $\lambda \in \{1.0, 3.0\}$ and $\lambda=1.0$ respectively, seeds $\{0, 1\}$.

- **Naive mode** (stage 2, E1, E3-control): the scrub targets the frozen deployed direction.
- **Adaptive mode** (E3): every 25 steps the attacker re-fits a DoM honesty direction on the *current* model’s MIMIC residuals — simulating the auditor’s re-lock — and scrubs along that

moving direction plus the frozen one. The attacker chases the signal wherever a clean re-fit would find it, but only on data it has (MIMIC), never on the auditor’s private CALIB.

Non-degeneracy guards (VOID, not verdict, if failed). The read must work pre-attack (clean probe AUROC ≥ 0.75); knowledge must exist pre-attack (≥ 0.80); splits must be stem-disjoint (asserted in code); a random-direction probe must read chance and shuffled-label knowledge must sit ≈ 0.5 . Guard values ride in every result artifact. Smoke runs write only `*_SMOKE_INVALID*` files and are never read as results.

4. Pre-registration and machine-checked certification

Every stage of this study was frozen on commit *before* the corresponding run, in a public repository, with kill-gates that could return the program-falsifying verdict:

- `PREREG_read_neq_write_coupling_2026_07_04.md` (commit `cff3b12`) — the keystone test and the EVADABLE / SURVIVES corners.
- `PREREG_stage2_attack_sweep_2026_07_04.md` (commit `baefaf7`) — the λ -sweep attack.
- `PREREG_stage3_interpretation_escalation_2026_07_04.md` (commit `b3224a0`) — **frozen while the stage-2 sweep was still training**: what each possible verdict licenses, what it does not, and which escalation it forces. This document is why the stage-2 “break” below could not become a headline.
- `PREREG_E1_clean_calibrated_auditor_2026_07_04.md` (commit `5be3bb9`) and `PREREG_E3_adaptive_att` (commit `74cac7c`) — each frozen before its retrain.
- `PREREG_E2_multilayer_strong_attacker_2026_07_04.md` (commit `af5e184`) — the next escalation, frozen and public *before its run*, so the pending result cannot move its own goalposts.

Each result note is bound to its numeric artifacts by `styxx.certify`, a machine-checked certification (verdict OATH-HELD) that extracts the note’s numeric claims and verifies them against the re-runnable result JSONs; the certificates ship in the same directory as the results. Bars never moved after freezing; a missed guard voids the run rather than bending the bar.

5. Results

5.1 Foundation: the signal and the knowledge are real before the attack

On clean Qwen2.5-1.5B (seed 0, 98 ATTACK / 82 HELD-OUT facts), per `foundation_result.json`:

guard	measured	bar	verdict
clean probe held-out AUROC (L18)	0.851	≥ 0.75	PASS
clean knowledge accuracy	0.805	≥ 0.80	PASS
ATTACK $\cap$ HELD-OUT stems	disjoint	$\emptyset$	PASS
random-direction AUROC	0.500	chance band	PASS
shuffled-label knowledge	0.512	≈ 0.5	PASS

Layer 18 was selected by held-out AUROC over a scan (L12 0.602, L14 0.730, L16 0.811, **L18 0.851**, L20 0.832, L22 0.809) and then frozen. There is a real read and real knowledge to pull apart.

5.2 Stage 2: the registered protocol returns EVADABLE — with a named confound

The attack collapses the re-locked read while knowledge is preserved, on both seeds, at every knowledge-preserving λ (per `attack_sweep_result.json`; reproduction guard at sweep start: clean probe 0.854, clean knowledge 0.805):

seed	λ	re-locked AUROC (held-out)	knowledge
0	0.3	0.496	0.817
0	1.0	0.507	0.890
1	0.3	0.461	0.829
1	1.0	0.472	0.866

At $\lambda = 0$ (no replay) the scrub also destroys knowledge (accuracy 0.573–0.598): the replay term is exactly what buys the attacker a knowledge-preserving evasion. A random direction on the same residuals reads ~ 0.54 – 0.59 , so ~ 0.5 is genuine chance.

The confound, named in the registered result before any follow-up ran: the re-lock calibrates its probe on the ATTACK facts — the same set the attacker optimized against. An EVADABLE under this protocol is therefore consistent with two worlds it cannot separate: (1) *true erasure* — the signal is gone from the residual stream; or (2) *calibration poisoning* — the signal survives on clean data, but a probe fit on the poisoned split points the wrong way. The pre-committed interpretation map licensed only “a knowledge-preserving weight-level attacker can blind a DoM honesty read calibrated on the attacked set, on this 1.5B model” — and mandated E1.

5.3 E1: the break was calibration poisoning — read $\neq$ write stands

E1 gives the auditor a private clean calibration split (CALIB) the attacker never saw, plus the stronger probe families of §3. Clean-model guard on the decisive family: CALIB-fit probe EVAL AUROC 0.938, EVAL knowledge 0.818. Through the same attack that produced the table above (per `e1_result.json`):

seed	λ	clean-calibrated read (EVAL AUROC)	knowledge
0	1.0	0.838	0.818
0	3.0	0.835	0.833
1	1.0	0.722	0.803
1	3.0	0.711	0.833

Every knowledge-preserving point clears the frozen 0.70 recovery bar on both seeds (random-direction floor 0.551–0.588). The attack that drove the ATTACK-calibrated re-lock to chance leaves the honesty signal fully readable to an auditor calibrated on clean data. Verdict per the frozen gate: **POISONING_CONFIRMED — read $\neq$ write STANDS against this attacker, provided the auditor does not calibrate on the attacker’s data.**

The cross-family arm VOIDed its own guard in E1: clean Llama-3.2-1B EVAL knowledge came in at 0.788 against the frozen 0.80 bar (missed by 0.012), so its points (clean-calibrated recovery 0.669–0.747 through the attack) corroborate directionally but are not a verdict. E1’s confirmed result is single-family; E3 closes that flank.

5.4 E3: the defense holds against an adaptive-*scheme* attacker — but the scheme did not bite (E3')

E3 attacks the defense itself: the adaptive mode of §3 chases the honesty signal across calibration frames on its own clean split (MIMIC), never touching the auditor’s private CALIB. Both families cleared their clean guards this run (Qwen CALIB-probe 0.912 / knowledge 0.800; Llama 0.821 / 0.800), making this a two-family result. Per `e3_result.json` ($\lambda = 1.0$):

family	mode	seed	clean-calibrated read	knowledge
Qwen2.5-1.5B	naive (control)	0	0.786	0.833
Qwen2.5-1.5B	naive (control)	1	0.775	0.817
Qwen2.5-1.5B	adaptive	0	0.782	0.833
Qwen2.5-1.5B	adaptive	1	0.733	0.733
Llama-3.2-1B	naive (control)	0	0.706	0.783
Llama-3.2-1B	naive (control)	1	0.732	0.800
Llama-3.2-1B	adaptive	0	0.739	0.783
Llama-3.2-1B	adaptive	1	0.772	0.817

The naive control reproduces E1 (the harness is sound), and under the adaptive attack the clean-calibrated read does not drop below the naive level (random-direction floor 0.483–0.602 across points). Verdict per the frozen gate: **DEFENSE_HOLDS**. Two annotations bind this verdict: Qwen adaptive seed 1’s knowledge (0.733) fell below the 0.75 knowledge-preserving bar, so that point does not count toward the verdict — the decisive-family hold rests on seed 0, with Llama corroborating on both seeds. And the caveat below is load-bearing.

E3' (bite verification, this version): the “adaptive” scheme did not out-attack naive.

E3 flagged that it never verified the adaptive attacker actually bit harder than naive. E3' re-ran the exact grid with that instrumentation (per `e3prime_result.json`). It did not bite: on the deployed read the adaptive/naive difference sits within the 0.02 noise floor, and on the *mimic-refit read the adaptive loop directly chases and scrubs*, the adaptive attacker left MORE signal than naive — 0.629 / 0.660 (adaptive) versus 0.432 / 0.467 (naive) on the two decisive seeds. Chasing a moving target every 25 steps split the attacker’s capacity and weakened its attack. Verdict per the frozen gate: **NO_BITE**. The consequence is a demotion we make explicitly: E3’s DEFENSE_HOLDS shows the private-calibration read beats the *naive* attacker, not that it beats a genuine adaptive escalation. This demotion was produced by our own pre-committed verification, not by external review.

E3'' (stronger adaptive, this version): a second escalation also does not bite — and the bite gate blocks a false STANDS.

E3' named the owed escalation, so we ran it. E3'' strengthens the adaptive attacker by construction — refit the moving MIMIC probe every 10 steps and scrub it across *every* scan layer, not just the deployed one — and makes “the attack must bite” a hard VOID gate read before any defense verdict (per `e3dprime_result.json`). It bit even less than E3': on the deployed read the adaptive attacker left 0.557 / 0.516 versus naive’s 0.400 / 0.445, and on the mimic-refit read 0.699 / 0.685 versus naive’s 0.432 / 0.467 — the whole-stack moving terms have gradients that conflict with the frozen-deploy suppression, so spreading the objective made the attack *weaker*. Verdict: **VOID_NO_BITE**. The gate earned its place here: the adaptive clean-calibrated read came in *high* (0.833 / 0.758), higher than the naive control, purely because the attack barely touched the signal — without the pre-committed bite gate that would have read as a clean “DEFENSE_HOLDS vs a stronger adaptive attacker,” a false positive off a non-attack. Two

independent adaptive escalations now underperform the naive static scrub, which means the naive attacker is the empirically *strongest* threat found here — and it is the one the private-calibration read defeats. Robustness to an adaptive attacker *verified to bite* remains open, because within this objective family we could not construct one; a cleaner scheme that drops the conflicting frozen term (E3'') is the honest next option, not a claimed result.

5.5 E2 / E2': the defense holds against a 4×-capacity whole-stack attacker forced to preserve knowledge

The strongest attacker this bench supports is a LoRA $r=64$ ($4\times$ E1/E3's capacity) scrub summed over *every* scan layer, 600 steps. Run at knowledge-replay $\lambda=1.0$ (E2), it bit hard — the frozen whole-stack read fell from a clean 0.786 to 0.55 — but over-damaged the model, dropping decisive-family knowledge to 0.606 / 0.667, below the 0.75 knowledge-preserving bar. With no knowledge-preserving point to read, E2 is **INCONCLUSIVE** (reported verbatim): the attack lost the honesty read and knowledge *together*, the coupling the keystone predicts, but not a clean STANDS.

E2' (per `e2prime_result.json`) sweeps the replay weight up ($\lambda \in \{3, 10, 30\}$) to force the attacker into the knowledge-preserving regime, then reads the defense there. On the decisive family it succeeds:

λ	seed	clean-calibrated read (EVAL AUROC)	knowledge	frozen whole-stack read
10.0	1	0.759	0.833	0.553
30.0	1	0.754	0.818	0.533

At both points the attack still bit (frozen read $0.786 \rightarrow 0.55$) yet the private-calibrated read held at 0.759 / 0.754 with knowledge preserved (random-direction floor ~ 0.52). Verdict per the frozen gate: **STANDS_vs_strong** — a $4\times$ -capacity whole-stack scrub, forced to keep the model's knowledge, still cannot blind a private-calibrated read. Caveats named, not buried: this rides seed 1 (seed 0 never preserved knowledge at any λ), and the Llama corroborating arm reached knowledge-preserving points but with a weak read there (0.584–0.599), so the STANDS rests on the decisive family.

6. The defense, stated operationally

The whole difference between reading chance (stage 2) and reading 0.711–0.838 (E1) on the *same attacked weights* is **where the auditor's calibration data came from**. This yields a concrete, transferable audit rule:

Calibrate the substrate probe on data the audited party never saw. A probe re-fit on data the attacker controlled — or could anticipate — is not a read of the model; it is a read of the attack.

Three practical corollaries. (1) *Audit sets must be private*: vendor-supplied or publicly-fixed calibration corpora are poisonable by construction — an auditor whose calibration provenance is public is auditing with a compromised instrument. (2) *Re-locking stays necessary but is not sufficient*: re-fitting at audit time defends against a probe the fine-tune dodged, but only private calibration defends against a fine-tune that poisoned the calibration frame itself. (3) *The defense is cheap*:

nothing above requires white-box training access — only holding back a stem-disjoint calibration split, fitting three linear probe families, and selecting on the private split. It is implementable in any read-only monitor that mounts a probe on residual streams, and it ships in `styxx` as `mount.ConscienceMount.relock` with a runnable demo (`examples/mount_relock_defense.py`).

We name the failure mode **calibration poisoning** to distinguish it from signal erasure and from inference-time evasion: the attacked model still linearly encodes honesty; what the attack corrupted was the *estimator* the auditor builds from contaminated data. The distinction matters because the mitigations differ — erasure would demand stronger probes or non-linear reads; poisoning demands data provenance.

7. Limitations and pre-registered pending escalations

7.1 Adaptive robustness is open — two schemes could not be made to bite. v0.1 claimed the defense survives an adaptive attacker; E3' measured the bite and returned NO_BITE, and we demoted the claim. E3'' (§5.4) then strengthened the adaptive attacker (refit every 10 steps, whole-stack scrub) and it bit even less, underperforming the naive static scrub by a wider margin. So within this objective family (difference-of-means gap-suppression) and scale (LoRA r=16), the adaptive schemes are self-defeating and the *naive* static attacker is the empirically strongest threat — the one the private-calibration read defeats (E1, E3-naive). The honest state: the defense is shown robust to the strongest attacker we could actually build here, but not to an adaptive attacker *verified to bite*, because we could not construct one. A scheme that drops the conflicting frozen term (E3''') is the owed next attempt, offered without a prediction. We report this because a defense whose only untested threat is one nobody has been able to make land is in a different, and more honest, position than one that ducked the test.

7.2 Attacker scale (strengthened in this version). The core E1 result is LoRA r=16, 300 steps. E2/E2' (§5.5) escalate to a 4×-capacity, whole-stack, 600-step scrub; forced to preserve knowledge, it does not break the private-calibrated read on the decisive family (STANDS_vs_strong). The strong-attacker result rides a single seed's knowledge-preserving points and a weak corroborating arm, so a second clean seed and a larger model are the next owed steps — but the direction is a strengthening, not a crack.

7.3 Scale and breadth. 1–1.5B models, two families, linear probes only, small EVAL splits ($\approx 25\%$ of 180 statements in E1, $\approx 20\%$ in E3), seeds {0,1}, single run per cell — no confidence intervals at this n. This is a first decisive data point and a defense with a mechanism, not a theorem. Whether the geometry persists at 7B+ scale, under RLHF-era post-training, or against non-linear reads is open.

7.4 Construct scope. “Honesty” here is true/false factual judgment under a neutral prompt — the cleanest loadable construct, not strategic deception in context. Bridging to deception-in-context probes (e.g. the Apollo setting) is future work; the calibration-poisoning threat applies to any probe whose calibration data an adversary can influence, which is why we report it at the mechanism level.

8. Related work

Latent knowledge and honesty probes. Burns et al. (2022) recover latent knowledge without supervision; Azaria & Mitchell (2023) show internal states separate true from false statements; Marks & Tegmark (2023) map the linear geometry of truth representations; Zou et al. (2023) systematize representation-space reading and control. Goldowsky-Dill et al. (2025) deploy linear

probes for strategic deception at high AUROC. None of these evaluate a weight-level adversary optimizing against the probe with a capability-preservation constraint.

Adversarial evasion of latent-space monitors. Bailey et al. (2024) show *inference-time* obfuscated activations can bypass latent defenses. Our attack lives one level deeper — in the weights — and our defense (private calibration) addresses a failure mode their setting does not expose: the poisoning of the auditor’s estimator rather than the evasion of a fixed one.

The 2026 convergence on read $\neq$ write. Galeone et al. (2026) establish detection–control orthogonality across families (cos 0.12–0.20, identical pre/post instruction tuning); Gurnee et al. (2026) read workspace-level hidden cognition via the Jacobian lens, with interventions that redirect explicitly-reported choices but not automatic behavior — the same read/write asymmetry surfacing in a different apparatus. Both treat the weights as honest. This paper is the adversarial rung of that ladder: what remains of the read channel when the weights fight back, and what the auditor must do to keep it.

9. Reproducibility and receipts

Everything is public in the `styxx` repository (github.com/fathom-lab/styxx), `papers/read-neq-write/`: pre-registrations (frozen on commit before each run), harnesses (`foundation.py`, `attack_sweep.py`, `e1_clean_auditor.py`, `e3_adaptive_attacker.py`, `e2_strong_attacker.py`), result artifacts (`foundation_result.json`, `attack_sweep_result.json`, `e1_result.json`, `e3_result.json`), result notes, and their OATH-HELD certificates. Seeds and splits are locked in code; the full study reruns on one 8 GB GPU. The package `styxx` is on PyPI (130 releases since 2026-04-11); the program’s methodology paper is archived at DOI 10.5281/zenodo.19326174.

Appendix A: public timestamp trail of the program’s claims

All timestamps are third-party (PyPI registry, Zenodo) or public-repository commit dates.

date (2026)	receipt	claim
04-11	PyPI first upload of <code>styxx</code>	program start
05-27	Zenodo DOI 10.5281/zenodo.19326174 (v25 deposit)	pre-registered, self-falsifying evaluation methodology
05-29	commit <code>3e434cb</code> (public)	depth-steering: axis writable but correctness-inert — first write-limits result
06-05/07	commits <code>78b4a5d</code> , <code>ebe05ff</code> (public)	cross-model substrate reading; probe 1.00 vs self-report at chance
06-16	PyPI 7.16.0 / 7.17.0	read-only conscience monitor mounted on open models
06-23	—	Galeone et al., arXiv 2606.24952 (detect $\perp$ steer)
07-04/05	commits <code>cff3b12...af5e184</code> (public)	this study’s preregs frozen; stage-2, E1, E3 findings
07-06	—	Gurnee et al., Transformer Circuits (J-lens workspace)

References

- Azaria, A., & Mitchell, T. (2023). *The Internal State of an LLM Knows When It’s Lying*. arXiv:2304.13734.
- Bailey, L., et al. (2024). *Obfuscated Activations Bypass LLM Latent-Space Defenses*. arXiv:2412.09565.
- Burns, C., Ye, H., Klein, D., & Steinhardt, J. (2022). *Discovering Latent Knowledge in Language Models Without Supervision*. arXiv:2212.03827.
- Galeone, C., Ettorre, A., Park, M., Ettorre, G., & Ligorio, D. (2026). *Perfect Detection, Failed Control: The Geometry of Knowing vs. Steering in Language Models*. arXiv:2606.24952.
- Goldowsky-Dill, N., et al. (2025). *Detecting Strategic Deception Using Linear Probes*. arXiv:2502.03407.
- Gurnee, W., Sofroniew, N., Pearce, A., et al. (2026). *Verbalizable Representations Form a Global Workspace in Language Models*. Transformer Circuits (transformer-circuits.pub/2026/workspace), July 6, 2026.
- Marks, S., & Tegmark, M. (2023). *The Geometry of Truth: Emergent Linear Structure of True/False Datasets*. arXiv:2310.06824.
- Rodabaugh, A. (2026). *Fathom v25 / styxx v7.7.9: The Gauntlet that Catches Itself*. Zenodo, DOI 10.5281/zenodo.19326174.
- Zou, A., et al. (2023). *Representation Engineering: A Top-Down Approach to AI Transparency*. arXiv:2310.01405.