

# Machine-Level Programming IV: Data

CENG331 - Computer Organization

**Instructor:**

Murat Manguoglu (Sections 1-2)

Adapted from slides of the textbook: <http://csapp.cs.cmu.edu/>

# Today

## ■ Arrays

- One-dimensional
- Multi-dimensional (nested)
- Multi-level

## ■ Structures

- Allocation
- Access
- Alignment


## ■ Floating Point

# Array Allocation

## ■ Basic Principle

$T \ A[L];$

- Array of data type  $T$  and length  $L$
- Contiguously allocated region of  $L * \text{sizeof}(T)$  bytes in memory




# Array Access

## ■ Basic Principle

$T$  **A**[ $L$ ] ;

- Array of data type  $T$  and length  $L$
- Identifier **A** can be used as a pointer to array element 0: Type  $T^*$




■ Reference	Type	Value
<code>val[4]</code>	<code>int</code>	3
<code>val</code>	<code>int *</code>	$x$
<code>val+1</code>	<code>int *</code>	$x+4$
<code>&amp;val[2]</code>	<code>int *</code>	$x+8$
<code>val[5]</code>	<code>int</code>	??
<code>*(val+1)</code>	<code>int</code>	5
<code>val + i</code>	<code>int *</code>	$x+4\ i$

# Array Example

```
#define ZLEN 5
typedef int zip_dig[ZLEN];


zip_dig cmu = { 1, 5, 2, 1, 3 };
zip_dig mit = { 0, 2, 1, 3, 9 };
zip_dig ucb = { 9, 4, 7, 2, 0 };
```



- Declaration “`zip_dig cmu`” equivalent to “`int cmu[5]`”
- Example arrays were allocated in successive 20 byte blocks
  - Not guaranteed to happen in general

# Array Accessing Example

zip\_dig cmu;



```
int get_digit
(zip_dig z, int digit)
{
    return z[digit];
}
```

## IA32

```
# %rdi = z
# %rsi = digit
movl (%rdi,%rsi,4), %eax # z[digit]
```

- Register `%rdi` contains starting address of array
- Register `%rsi` contains array index
- Desired digit at  $4 * \%rdi + \%rsi$
- Use memory reference `(%rdi,%rsi,4)`

# Array Loop Example

```
void zincr(zip_dig z) {  
    size_t i;  
    for (i = 0; i < ZLEN; i++)  
        z[i]++;  
}
```


```
# %rdi = z  
movl    $0, %eax          # i = 0  
jmp     .L3               # goto middle  
.L4:                       # loop:  
    addl    $1, (%rdi,%rax,4) # z[i]++  
    addq    $1, %rax        # i++  
.L3:                       # middle  
    cmpq    $4, %rax        # i:4  
    jbe     .L4             # if <=, goto loop  
rep; ret
```

# Multidimensional (Nested) Arrays

## ■ Declaration

$T \ A[R][C];$

- 2D array of data type  $T$
- $R$  rows,  $C$  columns
- Type  $T$  element requires  $K$  bytes




## ■ Array Size

- $R * C * K$  bytes

## ■ Arrangement

- Row-Major Ordering (in C/C++, Python, Mathematica, ....)
- Column-Major Ordering (in Fortran, Matlab, Octave, OpenGL, Julia, ....)


`int A[R][C];`      – C: Row-Major





# Nested Array Example

```
#define PCOUNT 4
zip_dig pgh[PCOUNT] =
    {{1, 5, 2, 0, 6},
     {1, 5, 2, 1, 3 },
     {1, 5, 2, 1, 7 },
     {1, 5, 2, 2, 1 }};
```




- “zip\_dig pgh[4]” equivalent to “int pgh[4][5]”
  - Variable **pgh**: array of 4 elements, allocated contiguously
  - Each element is an array of 5 **int**’s, allocated contiguously
- “Row-Major” (**C, C++**, ...) or “Column-Major” (**Fortran, Matlab, Julia**, ...) or “other” (others) ordering of all elements in memory

# Nested Array Row Access

## ■ Row Vectors

- $A[i]$  is array of  $C$  elements
- Each element of type  $T$  requires  $K$  bytes
- Starting address  $A + i * (C * K)$

```
int A[R][C];
```




# Nested Array Element Access

## ■ Array Elements

- $A[i][j]$  is element of type  $T$ , which requires  $K$  bytes
- Address  $A + i * (C * K) + j * K = A + (i * C + j) * K$

```
int A[R][C];
```




# Multi-Level Array Example

```
zip_dig cmu = { 1, 5, 2, 1, 3 };  
zip_dig mit = { 0, 2, 1, 3, 9 };  
zip_dig ucb = { 9, 4, 7, 2, 0 };
```

```
#define UCOUNT 3  
int *univ[UCOUNT] = {mit, cmu, ucb};
```

- Variable `univ` denotes array of 3 elements
- Each element is a pointer
  - 8 bytes
- Each pointer points to array of `int`'s



# Element Access in Multi-Level Array

```
int get_univ_digit
(size_t index, size_t digit)
{
    return univ[index][digit];
}
```

```
salq    $2, %rsi          # 1 digit
addq    univ(,%rdi,8), %rsi # p = univ[index] + 4*digit
movl    (%rsi), %eax       # return *p
ret
```


## ■ Computation

- Element access **Mem[Mem[univ+8\*index]+4\*digit]**
- Must do two memory reads
  - First get pointer to row array
  - Then access element within array

# Array Element Accesses


## Nested array

```
int get_pgh_digit
(size_t index, size_t digit)
{
    return pgh[index][digit];
}
```



## Multi-level array

```
int get_univ_digit
(size_t index, size_t digit)
{
    return univ[index][digit];
}
```



Accesses looks similar in C, but address computations very different:

$\text{Mem}[\text{pgh} + 20 * \text{index} + 4 * \text{digit}]$        $\text{Mem}[\text{Mem}[\text{univ} + 8 * \text{index}] + 4 * \text{digit}]$

# N X N Matrix Code

## ■ Fixed dimensions

- Know value of N at compile time

```
#define N 16
typedef int fix_matrix[N][N];
/* Get element a[i][j] */
int fix_ele(fix_matrix a,
            size_t i, size_t j)
{
    return a[i][j];
}
```

## ■ Variable dimensions, explicit indexing

- Traditional way to implement dynamic arrays

```
#define IDX(n, i, j) ((i)*(n)+(j))
/* Get element a[i][j] */
int vec_ele(size_t n, int *a,
            size_t i, size_t j)
{
    return a[IDX(n,i,j)];
}
```

## ■ Variable dimensions, implicit indexing

- Now supported by gcc

```
/* Get element a[i][j] */
int var_ele(size_t n, int a[n][n],
            size_t i, size_t j) {
    return a[i][j];
}
```

# 16 X 16 Matrix Access

## ■ Array Elements

- Address  $\mathbf{A} + i * (\mathbf{C} * \mathbf{K}) + j * \mathbf{K}$
- $\mathbf{C} = 16, \mathbf{K} = 4$

```
/* Get element a[i][j] */  
int fix_ele(fix_matrix a, size_t i, size_t j) {  
    return a[i][j];  
}
```

```
# a in %rdi, i in %rsi, j in %rdx  
salq    $6, %rsi           # 64*i  
addq    %rsi, %rdi          # a + 64*i  
movl    (%rdi,%rdx,4), %eax # M[a + 64*i + 4*j]  
ret
```



# n X n Matrix Access

## ■ Array Elements

- Address  $\mathbf{A} + i * (\mathbf{C} * \mathbf{K}) + j * \mathbf{K}$
- $\mathbf{C} = \mathbf{n}, \mathbf{K} = 4$
- Must perform integer multiplication

```
/* Get element a[i][j] */  
int var_ele(size_t n, int a[n][n], size_t i, size_t j)  
{  
    return a[i][j];  
}
```

```
# n in %rdi, a in %rsi, i in %rdx, j in %rcx  
imulq    %rdx, %rdi          # n*i  
leaq     (%rsi,%rdi,4), %rax  # a + 4*n*i  
movl     (%rax,%rcx,4), %eax  # a + 4*n*i + 4*j  
ret
```

# Today

## ■ Arrays

- One-dimensional
- Multi-dimensional (nested)
- Multi-level


## ■ Structures

- Allocation
- Access
- Alignment

## ■ Floating Point

# Structure Representation


```
struct rec {  
    int a[4];  
    size_t i;  
    struct rec *next;  
};
```



- **Structure represented as block of memory**
  - Big enough to hold all of the fields
- **Fields ordered according to declaration**
  - Even if another ordering could yield a more compact representation
- **Compiler determines overall size + positions of fields**
  - Machine-level program has no understanding of the structures in the source code

# Generating Pointer to Structure Member

```
struct rec {  
    int a[4];  
    size_t i;  
    struct rec *next;  
};
```



## ■ Generating Pointer to Array Element

- Offset of each structure member determined at compile time
- Compute as  $r + 4 \cdot idx$

```
int *get_ap  
(struct rec *r, size_t idx)  
{  
    return &r->a[idx];  
}
```


```
# r in %rdi, idx in %rsi  
leaq (%rdi,%rsi,4), %rax  
ret
```

# Following Linked List

## ■ C Code

```
void set_val
(struct rec *r, int val)
{
    while (r) {
        int i = r->i;
        r->a[i] = val;
        r = r->next;
    }
}
```

```
struct rec {
    int a[3];
    int i;
    struct rec *next;
};
```




Element i

Register	Value
%rdi	r
%rsi	val

```
.L11:                                # loop:
    movslq    16(%rdi), %rax          # i = M[r+16]
    movl      %esi, (%rdi,%rax,4)     # M[r+4*i] = val
    movq      24(%rdi), %rdi          # r = M[r+24]
    testq     %rdi, %rdi              # Test r
    jne       .L11                    # if !=0 goto loop
```

# Structures & Alignment


## ■ Unaligned Data



```
struct S1 {  
    char c;  
    int i[2];  
    double v;  
} *p;
```

## ■ Aligned Data

- Primitive data type requires  $K$  bytes
- Address must be multiple of  $K$



# Alignment Principles

## ■ Aligned Data

- Primitive data type requires  $K$  bytes
- Address must be multiple of  $K$
- Required on some machines; advised on x86-64

## ■ Motivation for Aligning Data

- Memory accessed by (aligned) chunks of 4 or 8 bytes (system dependent)
  - Inefficient to load or store datum that spans quad word boundaries
  - Virtual memory trickier when datum spans 2 pages

## ■ Compiler

- Inserts gaps in structure to ensure correct alignment of fields

# Specific Cases of Alignment (x86-64)

- **1 byte: `char`, ...**
  - no restrictions on address
- **2 bytes: `short`, ...**
  - lowest 1 bit of address must be  $0_2$
- **4 bytes: `int`, `float`, ...**
  - lowest 2 bits of address must be  $00_2$
- **8 bytes: `double`, `long`, `char *`, ...**
  - lowest 3 bits of address must be  $000_2$
- **16 bytes: `long double` (GCC on Linux)**
  - lowest 4 bits of address must be  $0000_2$



# Satisfying Alignment with Structures

## ■ Within structure:

- Must satisfy each element's alignment requirement


## ■ Overall structure placement

- Each structure has alignment requirement **K**
  - **K** = Largest alignment of any element
- Initial address & structure length must be multiples of **K**

```
struct S1 {  
    char c;  
    int i[2];  
    double v;  
} *p;
```

## ■ Example:


- **K** = 8, due to **double** element



# Meeting Overall Alignment Requirement

- For largest alignment requirement K
- Overall structure must be multiple of K


```
struct S2 {  
    double v;  
    int i[2];  
    char c;  
} *p;
```



# Arrays of Structures

- Overall structure length multiple of K
- Satisfy alignment requirement for every element


```
struct S2 {  
    double v;  
    int i[2];  
    char c;  
} a[10];
```



# Accessing Array Elements

- Compute array offset  $12 * \text{idx}$ 
  - `sizeof(S3)`, including alignment spacers
- Element `j` is at offset 8 within structure
- Assembler gives offset `a+8`
  - Resolved during linking

```
struct S3 {  
    short i;  
    float v;  
    short j;  
} a[10];
```



```
short get_j(int idx)  
{  
    return a[idx].j;  
}
```

```
# %rdi = idx  
leaq (%rdi,%rdi,2),%rax # 3*idx  
movzwl a+8(,%rax,4),%eax
```

# Saving Space



- Put large data types first

```
struct S4 {  
    char c;  
    int i;  
    char d;  
} *p;
```



```
struct S5 {  
    int i;  
    char c;  
    char d;  
} *p;
```

- Effect (K=4)



# Today

## ■ Arrays

- One-dimensional
- Multi-dimensional (nested)
- Multi-level

## ■ Structures

- Allocation
- Access
- Alignment

## ■ Floating Point

# Background

## ■ History

- x87 FP
  - Legacy, very ugly
- SSE FP
  - Special case use of vector instructions
- AVX FP
  - Newest version
  - Similar to SSE
  - Documented in book

# Programming with SSE3

## XMM Registers

■ 16 total, each 16 bytes

■ 16 single-byte integers



■ 8 16-bit integers



■ 4 32-bit integers




■ 4 single-precision floats



■ 2 double-precision floats



■ 1 single-precision float



■ 1 double-precision float






# Scalar & SIMD Operations


■ Scalar Operations: Single Precision

**addss** %xmm0, %xmm1




■ SIMD Operations: Single Precision

**addps** %xmm0, %xmm1



■ Scalar Operations: Double Precision

**addsd** %xmm0, %xmm1



# FP Basics

- Arguments passed in `%xmm0`, `%xmm1`, ...
- Result returned in `%xmm0`
- All XMM registers caller-saved

```
float fadd(float x, float y)
{
    return x + y;
}
```

```
double dadd(double x, double y)
{
    return x + y;
}
```

```
# x in %xmm0, y in %xmm1
addss    %xmm1, %xmm0
ret
```

```
# x in %xmm0, y in %xmm1
addsd    %xmm1, %xmm0
ret
```

# FP Memory Referencing

- Integer (and pointer) arguments passed in regular registers
- FP values passed in XMM registers
- Different mov instructions to move between XMM registers, and between memory and XMM registers

```
double dincr(double *p, double v)
{
    double x = *p;
    *p = x + v;
    return x;
}
```

```
# p in %rdi, v in %xmm0
movapd  %xmm0, %xmm1    # Copy v
movsd   (%rdi), %xmm0    # x = *p
addsd   %xmm0, %xmm1    # t = x + v
movsd   %xmm1, (%rdi)    # *p = t
ret
```

# Other Aspects of FP Code

## ■ *Lots of instructions*

- Different operations, different formats, ...

## ■ Floating-point comparisons

- Instructions `ucomiss` and `ucomisd`
- Set condition codes CF, ZF, and PF

## ■ Using constant values

- Set XMM0 register to 0 with instruction `xorpd %xmm0, %xmm0`
- Others loaded from memory

# Summary

## ■ Arrays

- Elements packed into contiguous region of memory
- Use index arithmetic to locate individual elements

## ■ Structures

- Elements packed into single region of memory
- Access using offsets determined by compiler
- Possible require internal and external padding to ensure alignment

## ■ Combinations

- Can nest structure and array code arbitrarily

## ■ Floating Point

- Data held and operated on in XMM registers