

Computer Vision

Degree in Information Technology

2º Semester 2021/2022

Worksheet 3

Goals:

- Image processing – arithmetic and logic operations
- Histograms

Exercises

Part I – Arithmetic operations

1- Write and run the following code in a python file:

```
import numpy as np
import cv2

# Load the image and show it
image = cv2.imread("DCT_img.jpg")
cv2.imshow("image",image)
cv2.waitKey(0)

# OpenCV arithmetic operations
print("max of 255: {}".format(cv2.add(np.uint8([200]), np.uint8([100]))))
print("min of 0: {}".format(cv2.subtract(np.uint8([50]),
np.uint8([100]))))

# NumPy arithmetic operations
print("wrap around: {}".format(np.uint8([200]) + np.uint8([100])))
print("wrap around: {}".format(np.uint8([50]) - np.uint8([100])))
```

- Let us examine the code:
- Import your packages
- Images are NumPy arrays, stored as unsigned 8 bit integers. What does this mean? It means that the values of our pixels will be in the range [0, 255]. When using functions like cv2.add and cv2.subtract, values will be clipped to this range, even if the added or subtracted values fall outside the range of [0, 255].
- If you use NumPy arithmetic operations on these arrays, the values will be modulus (wrap around) instead of being clipped to the [0, 255] arrange.
 - Once a value of 255 is reached, NumPy wraps around to zero, and then starts counting again, until 100 steps have been reached.
 - Once 0 is reached, the modulus operations wraps around and starts counting backwards from 255.

2- Write and run the following code in a python file:

```
import numpy as np
import cv2

# Load the image and show it
image = cv2.imread("DCT_img.jpg")
cv2.imshow("image",image)
cv2.waitKey(0)

M = np.ones(image.shape, dtype = "uint8") * 100
added = cv2.add(image, M)
cv2.imshow("add",added)
cv2.waitKey(0)

M = np.ones(image.shape, dtype = "uint8") * 50
subtracted = cv2.subtract(image, M)
cv2.imshow("Subtracted", subtracted)
cv2.waitKey(0)
```

- a) Let us examine the code:
- b) We defined a NumPy array of ones, with the same size as our image. We use 8-bit unsigned integers as our data type. To fill our matrix with values of 100's rather than 1's, we simply multiplied our matrix of 1's by 100.
- c) We used the cv2.add function to add our matrix of 100's to the original image. The values were clipped or wrapped?
- d) Adding: Used to blend the pixel contents from two images; the resulted image is brighter than the original.
- e) We defined another NumPy array of ones.
- f) We used the cv2.subtract function to subtract 50 from each pixel intensity of the image.
- g) Subtraction: Used to detect differences between two images, decrease its overall brightness, or obtain its negative.

Part II– Logic operations

1- Write and run the following code in a python file

```
import numpy as np
import cv2

# draw a rectangle
rectangle = np.zeros((300, 300), dtype = "uint8")
cv2.rectangle(rectangle, (25, 25), (275, 275), 255, -1)
cv2.imshow("Rectangle", rectangle)

# draw a circle
circle = np.zeros((300, 300), dtype = "uint8")
cv2.circle(circle, (150, 150), 150, 255, -1)
cv2.imshow("Circle", circle)

bitwiseAnd = cv2.bitwise_and(rectangle, circle)
cv2.imshow("AND", bitwiseAnd)
cv2.waitKey(0)

bitwiseOr = cv2.bitwise_or(rectangle, circle)
cv2.imshow("OR", bitwiseOr)
cv2.waitKey(0)

bitwiseXor = cv2.bitwise_xor(rectangle, circle)
cv2.imshow("XOR", bitwiseXor)
cv2.waitKey(0)

bitwiseNot = cv2.bitwise_not(circle)
cv2.imshow("NOT", bitwiseNot)
cv2.waitKey(0)
```

- a) Let us examine the code:
- b) Import the packages that you will need.
- c) We initialize our rectangle image creating a 300X300 NumPy array and then draw a 250X250 white rectangle at the centre of the image.
- d) We initialize our circle image creating a 300X300 NumPy array and then draw a white circle with radius of 150 pixels at the centre of the image.
- e) AND: A bitwise AND is true if and only if both pixels are greater than zero.
- f) OR: A bitwise OR is true if either of the two pixels are greater than zero.
- g) XOR: A bitwise XOR is true if and only if either of the two pixels are greater than zero, but not both.
- h) NOT: A bitwise NOT inverts the “on” and “off” pixels in an image.

Part III– Masking

1- Write and run the following code in a python file

```
image = cv2.imread("DCT_img.jpg ")
cv2.imshow("Original", image)

# Construct a mask with a 150x150 square at the centre of it
mask = np.zeros(image.shape[:2], dtype = "uint8")
(cX, cY) = (270, 110)
cv2.rectangle(mask, (cX - 75, cY - 75), (cX + 75 , cY + 75), 255,-1)
cv2.imshow("Mask", mask)

# Apply the mask to the image
masked = cv2.bitwise_and(image, image, mask = mask)
cv2.imshow("Mask Applied to Image", masked)
cv2.waitKey(0)
```

- a) Let us examine the code:
- b) Import the packages, load the image.
- c) Construct a NumPy array, filled with zeros, with the same width and height of the image.
- d) Apply the mask using the cv2.bitwise_and function. The AND function will be True for all pixels in the image. Look to the keyword mask. By supplying a mask, the cv2.bitwise_and function only examines pixels that are “on” in the mask. In this case, only pixels that are part of the white rectangle.

2- Write and run the following code in a python file:

- a) We can split the channels using cv2.split function.
- b) We can merge the channels back together again using the cv2.merge function.
- c) An alternative method is to construct a NumPy array of zeros, with the same width and height as the original image, and then to construct the Red channel representation of the image, make a call to cv2.merge, specifying zeros array for the Green and Blue channels. Take similar approaches to the other channels.

```
import cv2
import numpy as np

image = cv2.imread("DCT_img.jpg ")
cv2.imshow("Original", image)

(B, G, R) = cv2.split(image)
cv2.imshow("Red", R)
cv2.imshow("Green", G)
cv2.imshow("Blue", B)
cv2.waitKey(0)

merged = cv2.merge([B, G, R])
cv2.imshow("Merged", merged)
cv2.waitKey(0)

cv2.destroyAllWindows()
zeros = np.zeros(image.shape[:2], dtype = "uint8")
cv2.imshow("Red", cv2.merge([zeros, zeros, R]))
cv2.imshow("Green", cv2.merge([zeros, G, zeros]))
cv2.imshow("Blue", cv2.merge([B, zeros, zeros]))
cv2.waitKey(0)
```

3- This experiment will serve as curiosity. Write and run the following code:

```
import cv2
image = cv2.imread("DCT_img.jpg ")
cv2.imshow("Original", image)

# RGB color space to grayscale
gray = cv2.cvtColor(image, cv2.COLOR_BGR2GRAY)
cv2.imshow("Gray", gray)

# RGB color space to HSV
hsv = cv2.cvtColor(image, cv2.COLOR_BGR2HSV)
cv2.imshow("HSV", hsv)

#RGB color space to lab
lab = cv2.cvtColor(image, cv2.COLOR_BGR2LAB)
cv2.imshow("L*a*b*", lab)
cv2.waitKey(0)
```

Part IV – Histograms

1- Write and run the following code in a python file:

```
from matplotlib import pyplot as plt
import cv2
image = cv2.imread("DCT_img.jpg")

#Convert the image from the RGB colorspace to grayscale.
gray = cv2.cvtColor(image, cv2.COLOR_BGR2GRAY)
plt.imshow(gray, cmap='gray')
plt.title('Gray')
plt.show()

# Construct a grayscale histogram
hist = cv2.calcHist([gray], [0], None, [256], [0, 256])
plt.figure()
plt.title("Grayscale Histogram")
plt.xlabel("Bins")
plt.ylabel("# of Pixels")
plt.plot(hist)
plt.xlim([0, 256])
plt.show()
```

- a) Let us examine the code:
- b) First you imported the packages that you need.
- c) Then you convert the image from the RGB Colo space to grayscale.
- d) Function `cv2.calcHist` computes the actual histogram:


```
cv2.calcHist(images, channels, mask, histSize, ranges)
```

 - `images`: This is the image that we want to compute a histogram for.
 - `channels`: This is a list of indexes, where we specify the index of the channel we want to compute a histogram for. To compute a histogram of a grayscale image, the list would be `[0]`. To compute a histogram for all three red, green, and blue channels, the channels list would be `[0,1,2]`.
 - `mask`: If a mask is provided, a histogram will be computed for masked pixels only.
 - If we do not have a mask or do not want to apply one, we can just provide a value of `None`.
 - `histSize`: This is the number of bins we want to use when computing a histogram. Again, this is a list, one for each channel we are computing a histogram for.
 - `ranges`: Here we specify the range of possible pixel values. Normally, this is `[0, 256]` for each channel.
 - **Interpreting the plot:**
 - the bins (0-255) are plotted on the x-axis.
 - the y-axis counts the number of pixels in each bin.

2- Write and run the following code in a python file:

```
from matplotlib import pyplot as plt
import cv2
img = cv2.imread('ponte.jpg')
cv2.imshow("Colour Image", img)
#Split chanel
canais = cv2.split(img)
cores = ("b", "g", "r")
plt.figure()
plt.title("'Colour Histogram")
plt.xlabel("Intensity")
plt.ylabel("Pixels")
#loop for each chanel
for (canal, cor) in zip(canais, cores):
    hist = cv2.calcHist([canal], [0], None, [256], [0, 256])
    plt.plot(hist, cor)
    plt.xlim([0, 256])
plt.show()
```

It is possible to represent the histogram of the three channels at the same time using `zip` function.

3- Write and run the following code in a python file

```
from matplotlib import pyplot as plt
import cv2
import numpy as np
image = cv2.imread("dark.jpg")
gray = cv2.cvtColor(image, cv2.COLOR_BGR2GRAY)
eq = cv2.equalizeHist(gray)
cv2.imshow('Histogram Equalization (Before and After)', np.hstack([gray, eq]))
cv2.waitKey(0)
```

Ideas to the Practical work:

- 1- Define a function to plot a histogram for a colour image. It should have three input parameters: the image, the title, the mask. Give the default None value for the mask.
- 2- Create a python script to load an image which you like. Create a white circle as a mask. Apply the mask with an AND bitwise function to the image.
- 3- A company wants to add its logo to all product images. Using the techniques of image processing (logic, arithmetic, and masking), define a function which add logos to images.



- 4- Pick an image and generate the corresponding histogram. Do a descriptive analysis about the quality. Then, use a dark image as the following example, originate the histogram, and perform the equalization. Report the results and present the main conclusions.

