

ABSTRACT

RNTUPLE FOR ATLAS ANALYSIS WORKFLOWS

Fatima Rodriguez, M.A.
Department of Physics
Northern Illinois University, 2025
Hector de la Torre, Director

RNTuple is the new data storage format set to replace TTree at the start of the High Luminosity LHC. An investigation was conducted on how analysis workflows for ATLAS researchers will change with RNTuple. Additionally, performance studies have been conducted that demonstrate an improvement in speed and memory usage at the analysis front. Finally, different compression algorithms were tested and it was found that blah blah remains to best work with RNTuple.

NORTHERN ILLINOIS UNIVERSITY
DE KALB, ILLINOIS

DECEMBER 2025

RNTUPLE FOR ATLAS ANALYSIS WORKFLOWS

BY

FATIMA RODRIGUEZ
© 2025 Fatima Rodriguez

A DISSERTATION SUBMITTED TO THE GRADUATE SCHOOL
IN PARTIAL FULFILLMENT OF THE REQUIREMENTS
FOR THE DEGREE
MASTER OF PHYSICS

DEPARTMENT OF PHYSICS

Dissertation Director:
Hector de la Torre

ACKNOWLEDGEMENTS

Thanks thanks

DEDICATION

Thanks thanks

TABLE OF CONTENTS

Page

17	LIST OF FIGURES.	vi
	Chapter	
18	1 INTRODUCTION	1
19	1.1 Phenomenology at the LHC	2
20	1.2 Physics Quantities.	5
21	1.2.1 Invariant Mass	5
22	2 THE ATLAS EXPERIMENT	7
23	2.1 The Large Hadron Collider	7
24	2.2 The ATLAS Apparatus	9
25	2.2.1 The Inner Detector	10
26	2.2.2 Calorimeter Systems	11
27	2.2.3 Muon Spectrometer	12
28	2.2.4 Magnet System.	13
29	2.2.5 ATLAS Trigger System	14
30	2.3 HL-LHC and HL-ATLAS.	14
31	3 ATLAS SOFTWARE AND COMPUTING	16
32	3.1 ROOT Introduction	16
33	3.1.1 TTree Introduction	17
34	4 RNTUPLE.	20
35	4.1 Data Structure	20

37	Chapter	Page
36	4.2 UI	21
38	4.2.1 C++	22
39	4.2.2 RDataFrame	22
40	5 RNTUPLE VS. TTREE	23
41	5.1 Readability Speed	23
42	5.2 Writing Speed	24
43	5.2.1 Output Sizes	25
44	5.3 Memory Consumption	27
45	5.4 Compression Algorithms Study	27
46	6 ANALYSIS GRAND CHALLENGE: RNTUPLE IMPLEMENTATION	28
47	6.1 RDataFrame Analysis Workflow	28
48	6.1.1 Event Selections	28
49	6.2 TTree vs. RNTuple AGC	29
50	6.2.1 Timing Measurements	32
51	6.2.1.1 LZ4 vs. ZSTD Input Files	33
52	REFERENCES	34
53	APPENDIX: OBJECTIVE SYMPTOMS	39

LIST OF FIGURES

	Figure	Page
55	1.1 The SM..	4
56	1.2 Summary of SM cross-section Measurements..	5
57	2.1 CERN Complex	8
58	2.2 ATLAS Schematics	10
59	2.3 ATLAS ID Schematics..	11
60	2.4 ATLAS Calorimeter System..	12
61	2.5 ATLAS Muon Spectrometer..	13
62	3.1 DataChain	17
63	3.2 TTree Data Structure	19
64	4.1 RNTupleStructure..	21
65	5.1 Loading Histogram Times	24
66	5.2 Output Histogram Times..	26
67	5.3 Memory Measurements	27
68	6.1 ttbar	29
69	6.2 top mass	30
70	6.3 Ht	31
71	6.4 Ht	32

72	6.5	LZ4	33
----	-----	---------------	----

CHAPTER 1

INTRODUCTION

Our current understanding of the building blocks of our universe is summarized with one model, called the Standard Model (SM) [4]. From the way we power our cities, to the particles that hold them together, the SM explains how the basic building blocks of matter interact, governed by fundamental forces: electromagnetism, the strong force and the weak force. Yet, questions remain about the SM, such as is there a unification theory that includes gravity? Why are there only three generations of fundamental particles? What is the nature of dark matter and dark energy, and how does it fit within the SM? What about the origin of the matter-antimatter asymmetry? Is the SM complete or do other exotic particles exist? Over the years, experimental particle physicists and engineers have built technology to test the SM, either by performing precision measurements of particles and their behaviors, or by colliding particles and measuring their outputs. As a result, we have increased our confidence in the SM theory, but continue to search for answers for these remaining questions through experimental discovery.

A Toroidal LHC Apparatus (ATLAS) [2] is a particle physics experiment designed to detect the high-energy particle collisions from the Large Hadron Collider (LHC) [29]. At the LHC, collisions take place at a rate of more than a billion interactions per second, which is a combined data volume of about 60 million megabytes per second [34]. In order to extend its discovery potential, the LHC will have a major upgrade to increase the number of instantaneous collision rate. This upgrade, called the High-Luminosity LHC (HL-LHC) [35], will require a new data storage format that can handle this increase in data.

RNTuple [32] is the new ROOT [27] data storage format that will be in use at the start of the HL-LHC [24]. RNTuple takes advantage of modern C++ techniques, which have shown to improve read speedability and memory usage when compared to its predecessor, TTree, and other data storage formats such as HDF5 and Parquet [28]. RNTuple is currently under heavy development. Its base format has only recently left the experimental stage and many tools and capabilities built around it are still evolving.

This thesis investigates the performance of RNTuple for ATLAS analysis workflows. This chapter will provide a more detailed introduction of the SM, followed by an introduction to the ATLAS experiment and its detector technology in Chapter 2. In Chapter 3, the ATLAS software and computing system, and data contents are introduced. In Chapter 4, an introduction to RNTuple and TTree is provided along with examples of how RNTuple is applied in comparison to TTree. Performance studies conducted for RNTuple and how they compare with TTree will be presented in Chapter 5. In Chapter 6, the Analysis Grand Challenge (AGC) is introduced along with its RNTuple implementation. A final discussion and conclusions are given in Chapter 7.

1.1 Phenomenology at the LHC

The SM is a quantum field theory that explains and categorizes all observed fundamental particles by their properties and interactions. Quantum field theory (QFT) is the main theoretical tool for describing particle interactions by combining special relativity and quantum mechanics. Due to this combination, QFT is a probabilistic theory where each particle has an associated field that permeates all of space; therefore, forces are simply the interactions between these different fields. For example, the electromagnetic force is just the interaction between the electromagnetic field and charged matter fields, which fall under

quantum electrodynamics (QED). In sum, the SM encompasses all known elementary particle interactions, except for gravity, through a collection of quantum field theories: QED, the Glashow-Weinberg-Salam theory of electroweak processes, and quantum chromodynamics.

The four groups of particles shown in Figure 1.1: quarks, leptons, gauge bosons, and scalar bosons, can be further categorized as *bosons* or *fermions* because of a fundamental property called spin. Similar to the Earth, particles carry orbital angular momentum and spin angular momentum; however, for particles, spin is an intrinsic property. All bosons carry an integer spin; while, fermions carry half-integer spin. As a result from QFT, each fermion has an antiparticle with the same mass and lifetime as the particle itself, but are oppositely charged. The three charged leptons (e , μ , τ) are massive, while their corresponding neutrinos (ν_e , ν_μ , ν_τ), are massless with neutral charge. Due to QCD, there are 8 types of gluons. The Higgs boson has its own section as a scalar boson because unlike the vector bosons with spin 1, the Higgs boson has spin 0. In sum, there are a total of 12 leptons including their antiparticles, 36 quarks including all the flavors and their antiparticles, 12 vector bosons, and 1 scalar boson, which makes a total of 61 fundamental particles.

Collider experiments serve as probes to the SM because they directly test conservation laws through the detection of final state radiation. In colliders, two beams of particles are accelerated to reach high energies and brought together for collision. Each collision is called an event and specific interactions or transformations are called processes. Processes are governed by conservation laws, such as conservation of energy and charge. For example, due to the conservation of energy, the energy in the center of mass frame must be greater than the sum of masses of the produced particles. When high-energy charged particles pass through matter, they ionize atoms along their path, which then serve as "seeds" for cloud chambers or sparks for sparks chambers. Their classification is then calculated by the energy differences detected from those "seeds". For neutral particles, their reconstruction is calculated using the conservation of momentum. Through QFT, the rate of a process,




Figure 1.1: Particle content of the Standard Model [?].

called cross-sections, can be predicted via the particle kinematics, their properties, and the properties of the process. Experimentally, cross-sections can be calculated via Equation 1.1, where N is the number of events for the process being measured and L is the instantaneous luminosity, defined in Equation as 1.2.

$$\sigma = \frac{N}{\int L dt} \quad (1.1)$$

$$L = f \frac{n_1 n_2}{4\pi \sigma_x \sigma_y} \quad (1.2)$$

f is the frequency of collisions, n_1 and n_2 are the number of particles in the colliding bunches. σ_x and σ_y are the root-mean-squared horizontal and vertical beam sizes. Figure 1.2 displays the predicted cross-sections for certain processes and the required center of mass energies for those processes to be observed.

[illegible]

Figure 1.2: Summary of several Standard Model cross-section measurements (a) with associated references (b) [1]. Processes with smaller cross-sections are considered rare-processes because it has a lower probability of being observed. Increasing the probability of these rare-processes would require an increase of energy. The measurements are corrected for branching fractions, compared to the corresponding theoretical expectations.

1.2 Physics Quantities

This section will cover some relevant physics quantities.

1.2.1 Invariant Mass

Invariant mass is a quantity that characterizes a system's total energy and momentum independent of the overall motion of the system [36]. Due to special relativity, space and time coordinates are linked but dependent on a frame of reference. Lorentz transformations are used to convert coordinates from reference frame to another, and 4-vectors are used to simplify these transformations [37]. A 4-vector is a vector in spacetime with 4 quantities, such as the position 4-vector with quantities x,y,z, and time. There is also the 4-momentum vector with energy and momentum in x, y, and z directions as quantities. These 4-vectors are convenient because invariant quantities can be calculated by taking the sum of their quanti-

164 ties squared. Invariant mass is calculated using Equation ??, where p_x, p_y, p_z is momentum
 165 in the x, y, z directions and E is energy.

$$m = \sqrt{\sum E^2 - \sum p_x^2 - \sum p_y^2 - \sum p_z^2} \quad (1.3)$$

CHAPTER 2

THE ATLAS EXPERIMENT

ATLAS was designed to be a general-purpose experiment, optimized to search for the Higgs boson, top quark decays, and supersymmetry. In July 1997, the ATLAS Experiment was approved and by November 2008, ATLAS was the largest detector ever constructed at 44 meters long and 25 meters in diameter. By November 2009, ATLAS recorded its first proton-proton collision and by December 2010, ATLAS was first to observe the production of top quark pairs, which are the heaviest known elementary particle with a strong coupling to the Higgs boson. By July 2012, both ATLAS and the Compact Muon Spectrometer (CMS) experiment successfully observed the Higgs boson [12, 13]. ATLAS is projected to continue operation until 2035 to continue searching for standing questions from the SM. This chapter will serve as an introduction to the LHC, the ATLAS detector, and upgrades occurring for the HL-LHC.

2.1 The Large Hadron Collider

The LHC is a two-ring-superconducting-hadron accelerator and collider built outside of Geneva, Switzerland at the Conseil Européen pour la Recherche Nucléaire (CERN) [29]. It was approved for construction in 1996 to search for beyond the SM physics at energies larger than 10 TeV. Its approval was heavily influenced by the cost-saving idea of reusing the existing 26.5 km tunnels from the Large Electron-Positron (LEP) collider [14]. The LHC has four main collision points that house the ATLAS, CMS, Large Hadron Collider beauty (LHCb) [46], and A Large Ion Collider Experiment (ALICE) [47]. ATLAS and CMS are




Figure 2.1: The CERN accelerator complex [15].

the two high-energy experiments located at diametrically opposite straight sections. LHCb is a low luminosity experiment dedicated to investigate the difference between matter and anti-matter by detecting b quarks. ALICE is an ion experiment dedicated to studying quark-gluon plasma forms.

The LHC is initially supplied with protons from the injector complex, which is a sequence of accelerators shown in Figure 2.1. The three main components within each of these accelerators are magnets, vacuum chambers, and radiofrequency (RF) cavities. Superconducting magnets are responsible for guiding the beams, and vacuum chambers ensure that particles do not interact with external residual gas molecules. RF cavities are metallic chambers located inside the beam vacuum. They are designed to resonate at specific frequencies to provide small energy boosts when particles pass through.

As of Run 3, the LHC has collided protons at a center of mass energy of $\sqrt{s} = 13.6$ TeV and a peak instantaneous luminosity of $L = 2.1 \times 10^{34} \text{ cm}^{-2} \text{ s}^{-1}$, which have surpassed original design. Beams are delivered in bunches with bunch separation of 25 ns, corresponding to a bunch crossing frequency of 40 MHz.

2.2 The ATLAS Apparatus

The ATLAS detector, shown in Figure 2.2, consists of a collection of subsystems confined in a 46m long, 25m in diameter cylinder, 100m below ground. The first subsystem is the Inner Detector (ID), which is responsible for tracking charged-particles. A calorimeter system follows and measures the energy loss of the particles passing through the detector. The final subsystem is the Muon Spectrometer (MS), which measures the deflection of muons within a magnetic field using a trigger and high precision tracking chambers. Additionally, a first-level and high-level trigger system is implemented to select interesting events and record them to disk.

ATLAS uses a cylindrical coordinate system (r, η, ϕ) for detector design, reconstruction and data analysis. The polar coordinates, (r, ϕ) , point in the plane towards the center of the LHC ring and upwards. The pseudorapidity, η , is defined in Equation 2.1, where θ is the polar angle and equal to the true rapidity defined in Equation 2.2.

$$\eta = -\ln\left(\tan\frac{\theta}{2}\right) \quad (2.1)$$

$$y = \frac{1}{2} \ln\left(\frac{E + p_z}{E - p_z}\right) \quad (2.2)$$

The ID tracks particles in the range $|\eta| < 2.5$, the calorimeter system covers $|\eta| < 4.9$, and the MS detects muon in the $|\eta| < 2.7$ range.




Figure 2.2: Computer generated image of the whole ATLAS detector [16].

2.2.1 The Inner Detector

The main components of the ID are the Pixel Detector, Semiconductor Tracker (SCT), and the Transition Radiation Tracker (TRT). This layout is provided in Figure 2.3. The Pixel Detector is first to pick up the energy deposits of the collisions at a precision of $10\mu m$. Their signals determine the origin and momentum of the particles. The SCT surrounds the Pixel Detector, which measures particle tracks with a precision of up to $25\mu m$. The TRT is the final layer that provides particle type information, in combination with the other information gained in the ID.




Figure 2.3: Computer generated image of the ATLAS inner detector [17].

2.2.2 Calorimeter Systems

Calorimeters are detectors that measure the energies and positions of charged and neutral electromagnetically or strongly interacting particles. They consist of highly-dense materials that force particles to deposit their energy. That energy is then converted into a measurable signal using layers of "active" media. The calorimeter system consists of two types of calorimeters as shown in Figure 2.4: electromagnetic and hadronic. Electromagnetic calorimeters are used to measure charged particles like electrons, positrons, and photons. Hadronic calorimeters are designed to detect hadrons, such as quarks, protons, and neutrons.




Figure 2.4: Computer generated image of the ATLAS Liquid Argon [18].

2.2.3 Muon Spectrometer

The muon spectrometer, shown in Figure 2.5, is the outer part of the ATLAS detector, designed to measuring the momentum of muons. Muons are minimally ionizing particles, meaning they can travel to the edge and beyond the ATLAS detector. The magnetic field that bends their directeries is generated by superconducting air-core toroidal magnets. There are also three stations of precision chambers consisting of layers of Monitored Drift Tubes (MDTs). The MDTs allow muons to knock out electrons from gas when passing through, to produce a signal. The New Small Wheels (NSW) sit in these endcap regions to detect charged-particle background that get produced as luminosity increases. Two chambers sit sorounding the central region and ends of the experiment: the Resistive Plate Chambers




Figure 2.5: Computer generated image of the ATLAS Muons subsystems [19].

(RPCs) and Thin Gap Chambers (TGCs). They both detect muons when they ionise the gas mixtures to generate signal.

2.2.4 Magnet System

The two main magnet systems are the Central Solenoid Magnet and the Toroid Magnets. Generally, superconducting magnets are required to bend the directories of charged particles, allowing for the ATLAS detector to to measure their momentum and charge. The Central Solenoid Magnet provides a 2 Tesla magnetic field surrounding the inner detector. The Toroid Magnets are located at the ends of the experiment, and a massive toroid magnet surrounds the center of the experiment. As mentioned in the previous section, the magnets at the ends of the experiment are to bend muons for the Muon spectrometer.

2.2.5 ATLAS Trigger System

The ATLAS Trigger system is a collection of electronics that make rapid decisions of saving certain events into disk. There are two trigger subsystems that help selectively read out and store data from interesting physics events. The first level of the trigger system, called the L1 trigger, uses reduced-granularity information from the calorimeters and muon system to search for signatures of these events. The maximum L1 accept rate is 100 kHz, meaning all processing for an event must be completed within that time window. The second level of the trigger system, called L2 trigger, performs a more thorough reconstruction in just 200 μ s of the events passed in L1 to then finally pass to a data storage system for offline analysis.

2.3 HL-LHC and HL-ATLAS

The HL-LHC was proposed in 2010 to extend the discovery potential of the LHC by increasing its instantaneous luminosity (rate of collisions) by a factor of five beyond the original design value and the integrated luminosity (total number of collisions) by a factor ten. Increasing the total number of collisions will increase the probability for ATLAS and CMS to observe rare processes at higher precision, as highlighted in reference [38]. The HL-LHC configuration relies on innovations in accelerator technology such as cutting edge 11 to 12 Tesla superconducting magnets, novel magnet designs, compact superconducting RF cavities for beam rotation with phase control, new technologies and materials for beam collimation, and high-current superconducting links with almost zero energy dissipation.

The ATLAS experiment will also require an upgrade following the HL-LHC. New sub-detectors will be installed such as the Inner Tracker [39], the High Granularity Timing

277 Detector [40], and additional Muon chambers [41]. There will also be different electronics
278 upgrades such as the Liquid Argon Calorimeter [42], the Tile Calorimeter [43], the Muon
279 Spectrometer [44], and the Trigger and Data Acquisition (TDAQ) system [45].

CHAPTER 3

ATLAS SOFTWARE AND COMPUTING

The data collected from the ATLAS data acquisition system must be compared to a set of simulated data. This dataset aims to mimic the different physics processes: it's production by the colliding beams, the evolution of the collision products within the detector and materials, and the detector's response to ultimately interpret efficiencies and background processes. Except for collision data, the output of all these data processing steps are stored in ROOT files. It starts off with Monte Carlo (MC) simulations, which is a computational technique that uses random sampling to generate events. Given these events, the interactions within the detector and the detector's response is simulated. This reconstructed product is called an Analysis Object Data (AOD), which are then cleaned by compressing the data and cutting any unnecessary events or columns into a finalized product called Derived AOD (DAOD). A ROOT file is produced at each step and are validated using different software tools. These tools collectively encompass the software framework called Athena [31]. The flow of this process is display in Figure 3.1. This chapter will provide an introduction to ROOT, its data storage format TTree and RNTuple.

3.1 ROOT Introduction

ROOT is a unified software package developed for processing, analyzing, visualizing and ultimately storing the massive high-energy physics datasets into a compressed binary file, called a root file. Previously, high-energy experiments used FORTRAN-based libraries; however, an upgrade was needed to handle the scales and complexities of the data from the




Figure 3.1: ATLAS data chain-processing for data and Monte Carlo simulation [20].

LHC. ROOT maintains an object-oriented structure, meaning it is organized around the data rather than the functions and logic. It's features include visualization tools such as histogramming, and statistical tools. ROOT can be used in C++ and python languages. Several subpackages exists for analysis such as RDataFrame.

3.1.1 TTree Introduction

ROOT provides a data structure called the TTree to store large amounts of columnar data efficiently. Usually scientific data is stored in what we call row-oriented formats such as a spreadsheet or CSV table. This format is well organized if one wants to access a single event, but viewing a single column then becomes inefficient, especially with large datasets. A TTree is columnar based, meaning it consists of a list of independent columns, called

311 branches. Examples of branches can be event IDs or particle kinematics such as momentum
312 in the x,y,z coordinates. Branches can hold integers, strings and `std::vector` data types.
313 Buffers are automatically allocated behind each branch. Buffers are temporary storage areas
314 for the independent binary version of the object. This is done to efficiently handle the writing
315 and reading of the data to and from disk. Also, each branch has one or more baskets, which
316 manages the in-memory buffer. In other words, a basket holds the values of a branch for a
317 number of consecutive events. When a buffer is full, it is optionally compressed and then
318 the corresponding basket is written to disk, leading to the creation of a new basket to hold
319 the next entries. ROOT allows users to change `buffersize` parameters of the branch for
320 personalized optimization. Figure 3.2 shows a more detailed flowchart of the TTree data
321 structure.




Figure 3.2: Example of the TTree Data Structure [21].

CHAPTER 4

RNTUPLE

RNTuple is the new columnar data format that will be implemented at the start of the HL-LHC. It's design continues to be columnar based, as its predecessor TTree, but it now uses modern storage technologies for better performance characteristics in data compactness, scalability and read and write speed. For this reason RNTuple classes are backwards-incompatible to TTree both on the file format level and on the API level [23]. It's binary format version follows an *epoch.major.minor.patch* scheme, where *epoch* indicates backward-incompatible changes, *major* indicates forward-incompatible changes, *minor* indicates new optional format features, and *patch* indicates backported features from newer format versions. This chapter will introduce the RNTuple structure and user interfaces (UI) for different workflows using the first public release of RNTuple 1.0.0.0.

4.1 Data Structure

RNTuple organizes data using an internal BLOB-based data layout and an external metadata schema. A BLOB (binary large object) is a collection of binary data stored as a single entity. For example, instead of embedding data directly into a database, data can be stored as a BLOB along with a unique identifier for later retrieval. This is beneficial for managing large unstructured data [25]. RNTuple uses a similar approach internally: Data is organized by columns of a single type and are attached to *fields*, which describes a serialized C++ type. Columns are partitioned into *pages*. Pages are compressed individually, similar to TTree baskets. *Clusters* are sets of pages that contain all the data belonging to an entry




Figure 4.1: TTree Structure vs. RNTuple Structure [22].

range. *Envelopes* are data blocks that contain metadata, such as field and columns types, cluster descriptions, and page locations. Overall, this structure allows for random-access of individual events without decompressing the entire dataset and for "fast merging" or concatenating RNTuples. A simplified diagram of the RNTuple structure in comparison to TTree is shown in Figure 4.1.

4.2 UI

RNTuple API is compatible with RDataFrame analysis workflows and hand-written event loops [24]. The sections below will provide further details and examples.

4.2.1 C++

For hand-written event loops, RNTuple interface uses smart pointers, which simulates a pointer while providing automatic memory management [26]. This feature shortens the amount of code necessary to read and load data by a couple of lines. For example `RNTupleReader::Open` simultaneously loads the ROOT file and the RNTuple. The function `GetView` also simultaneously loads and stores a field. In the example below, the RNTuple is called "EventData" and the field is being stored into the object `electron_pt`, which is the transverse momentum of electrons, "AnalysisElectronsAux:pt".

```
auto ntuple = RNTupleReader::Open("EventData", "DAOD_PHYSLITE.pool.root");
auto electron_pt = ntuple->GetView<std::vector<float>>("
    AnalysisElectronsAux:pt");
```

4.2.2 RDataFrame

Analysis done with RDataFrame will mostly remain unmodified with RNTuple, with the exception of filtering. Due to RNTuple's internal data structure, subfields such as "AnalysisElectronsAux:pt" are separated by their field, "AnalysisElectronsAux" by a column, instead of a period. This slight change confuses the filtering function in RDataFrame, but can be bypassed by assigning an alias name:

```
auto df = ROOT::RDF::RNTuple("EventData", "DAOD_PHYSLITE.pool.root");
auto new_df = df.Alias("electron_pt", "AnalysisElectronsAux:pt");
std::string analysis_cut = "(electron_pt.size()>=1&&electron_pt.at(0)
    >25000";
auto filtered_df = new_df.Filter(analysis_cut);
```

CHAPTER 5

RNTUPLE VS. TTREE

In this section, RNTuple performance is analyzed using RDataFrame in C++ and compared to TTree. First, 92 TTrees stored in DAOD_PHYSLITE files from ATLAS Open Data [30] were converted to RNTuples using its default compression algorithm setting, ZSTD. Speed tests were performed for loading and outputting RNTuples in comparison to TTrees using `std::chrono::high_resolution_clock::now()`. Each performance study contains two version: a TTree version that uses TTree inputs and an RNTuple version that uses the RNTuple inputs. A comparison of peak memory consumption was also performed using both sets of inputs. This entire process was repeated for RNTuple inputs converted with LZ4 compression algorithm as well.

5.1 Readability Speed

The total loading times for 92 RNTuples and their TTree equivalence were measured 100 times. Loading multiple RNTuples in RDataFrame is the same procedure as done for the TTree version:

```
std::string path = "path_to_files";
std::vector<std::string> filenames;
for (const auto& entry: std::filesystem::directory_iterator(path)){
    std::string filename = entry.path().filename().string();
    filenames.push_back(entry.path().string());
}
auto df = ROOT::RDF::FromRNTuple("EventData", filenames);
```




Figure 5.1: Total loading times measured for TTree and RNTuple using RDataFrame in C++.

The timer was stopped after calculating the sum of the column "AnalysisElectrons:pt" to ensure that the data was loaded. These times were recorded into a text file and are shown in Figure 5.1. In comparison, this study finds RNTuple to be 2.38 times faster at loading a column of data over TTree.

5.2 Writing Speed

Writing speed was measured by performing an invariant mass calculation and outputting a new data set with two columns: "ElectronPairsInvMass" and "Muon PairsInvMass". The timer began at the start of an invariant mass calculation and stopped after creating a new dataset. A TTree was written for the TTree version and an RNTuple was written for the RNTuple version. At the start of this study, the lazy function that outputs a TTree in

411 RDataFrame, `df.Snapshot(...)` was not developed to output an RNTuple; therefore, for
 412 consistency, both versions of the script used the RDataFrame function `df.ForEach(...)` to
 413 fill in the new columns. This procedure for RNTuple is shown below:

```

414
415 1 auto model = RNTupleModel::Create();
416 2 auto e_invm = model->MakeField<ROOT::VecOps::RVec<float>>("
417     ElectronPairsInvMass");
418 3 auto m_invm = model->MakeField<ROOT::VecOps::RVec<float>>("
419     MuonPairsInvMass");
420 4 auto ntuple = RNTupleWriter::Recreate(std::move(model), "FatisRNTuple", "
421     rnt_invm.root");
422 5 df_leptons.ForEach([&](ROOT::VecOps::RVec<float> e_vals, ROOT::VecOps::RVec<
423     float> m_vals){
424 6     *e_invm = e_vals;
425 7     *m_invm = m_vals; ntuple->Fill();
426 8 }, {"invm_electrons", "invm_muons"});
427

```

428 The total output times were recorded in a text file and are shown in Figure 5.2. RNTuple
 429 is shown to be 1.51 times faster at writing datasets in RDataFrame C++ than when using
 430 TTrees.

431 5.2.1 Output Sizes

432 After checking the disk sizes of the RNTuple outputs produced and comparing them to
 433 their TTree counterparts, RNTuple




Figure 5.2: Total writing times measured for TTree and RNTuple using RDataFrame in C++.

, measurements taken show that RNTuple varies slightly from TTree.




Figure 5.3: Peak memory measurements of TTree and RNTuple writing scripts [NOTE FOR FATIMA: CONSISTENT HISTOGRAM SHADING].

5.3 Memory Consumption

The peak memory usage when writing out a dataset was also measured for RNTuple and TTree versions. The same procedure using the invariant mass calculation was repeated 100 times, but using the command `usr/bin/time`. Shown in Figure 5.3,

5.4 Compression Algorithms Study

[Under Construction]

CHAPTER 6

ANALYSIS GRAND CHALLENGE: RNTUPLE IMPLEMENTATION

The Analysis Grand Challenge (AGC) is an analysis on t quark production meant to showcase an end-to-end analysis pipeline [49]. Developed and organized by Iris-HEP [48], the AGC has several versions that showcase different cyber infrastructure and workflows, making it a great benchmark to test RNTuple. This section will describe the development of two new AGC versions that use ATLAS Open Data and RDataFrame: TTree and RNTuple versions. These versions were heavily influenced on the existing RDataFrame AGC repository that applies CMS open data and the uproot AGC repository that applies ATLAS open data [49].

6.1 RDataFrame Analysis Workflow

The AGC is divided into two parts: an analysis script and a statistical script. The analysis scripts are written in Python and uses RDataFrame to apply preselections and output histograms of the top quark mass and the scalar sum of the transverse momenta, H_T , into a root file. The statistical script performs a simple statistical analysis using the output root file from the analysis script.

6.1.1 Event Selections

To reconstruct the top quark mass, events are selected from top quark pair production with final states that include a single charged lepton, as shown in Figure 6.1. The leptons




Figure 6.1: The schematic view of a top and anti-top quark collision [50]

must have p_t larger than 30 GeV and $|\eta|$ less than 2.1 Events must include four jets, with two of the four being "b-tagged". Jets that are "b-tagged" are matched to b and \bar{b} . The other two jets are from the W boson decay. The top mass observable is then reconstructed by taking the invariant mass of the trijet with the largest transverse momentum, p_t . The results are shown in Figure 6.2.

To plot the H_T observable, the selected events must have at least one b-tagged jet among the four jets and exactly one lepton. The results are shown in Figure 6.3.

6.2 TTree vs. RNTuple AGC

Both TTree and RNTuple versions of the AGC produced the outputs, confirming that analysis done in RDataFrame with RNTuple will mostly remain unmodified. As previously




Figure 6.2: The trijet mass prefit. This result is the same for both RNTuple and TTree versions of the AGC.




Figure 6.3: The H_T observable prefit. This result is the same for both RNTuple and TTree versions of the AGC.




Figure 6.4: The total execution times of the AGC measured 100 times for TTree and RNTuple versions.

mentioned, RNTuple changes the structure of variable field names. For consistency, alias variable names were applied to both TTree and RNTuple versions.

6.2.1 Timing Measurements

Total execution times were measured 100 times for both TTree and RNTuple versions using the time python library. Both versions used inputs produced with ZSTD compression algorithm. The results, shown in Figure 6.5, show that RNTuple averaged 47.58 seconds to produce the top quark mass and H_T histograms into a root file, while TTree averaged 71.75 seconds. RNTuple was about 1.51 times faster, which is consistent with previous time measurements shown in Chapter ??




Figure 6.5: The total execution times of the AGC measured 100 times with RNTuples produced with LZ4 compression algorithm.

6.2.1.1 LZ4 vs. ZSTD Input Files

The total execution times were remeasured using RNTuple inputs produced with the LZ4 compression algorithm. As shown in Figure ??, LZ4 executes the analysis script of the AGC about a couple seconds faster.

6.2.2 Memory Consumption

Peak memory usage was also measured using `/usr/bin/time`. The results shown in Figure ??, show that RNTuple consumes slightly less memory usage when executing the analysis script than TTree.




Figure 6.6: The peak memory usage when executing the AGC.

REFERENCES

- [1] ATLAS Collaboration. Standard Model summary plots. *ATLAS Public Note ATL-PHYS-PUB-2024-011*, 2024.
- [2] ATLAS Collaboration ATLAS: Letter of intent for a general purpose p p experiment at the large hadron collider at CERN. *CERN-LHCC-92-04*, 1992.
- [3] ATLAS Collaboration. The ATLAS experiment at the CERN Large Hadron Collider: a description of the detector configuration for Run 3. *JINST*, 19:P05063, 2024. URL: <http://dx.doi.org/10.1088/1748-0221/19/05/P05063>
- [4] R. Mann. *An Introduction to Particle Physics and the Standard Model*. Taylor & Francis, 2010. ISBN 978-1-4200-8300-2.
- [5] Wikipedia. Elementary particle. URL: https://en.wikipedia.org/wiki/Elementary_particle. Accessed: October 9, 2025.
- [6] C. N. Yang and R. L. Mills. Conservation of isotopic spin and isotopic gauge invariance. *Phys. Rev.*, 96:191–195, 1954.
- [7] P. W. Higgs. Broken symmetries, massless particles and gauge fields. *Phys. Lett.*, 12:132–133, 1964. DOI: 10.1016/0031-9163(64)91136-9.
- [8] P. W. Higgs. Broken symmetries and the masses of gauge bosons. *Phys. Rev. Lett.*, 13:508–509, 1964. DOI: 10.1103/PhysRevLett.13.508.
- [9] F. Englert and R. Brout. Broken symmetry and the mass of gauge vector mesons. *Phys. Rev. Lett.*, 13:321–323, 1964. DOI: 10.1103/PhysRevLett.13.321.

- [10] G. S. Guralnik, C. R. Hagen, and T. W. B. Kibble. Global conservation laws and massless particles. *Phys. Rev. Lett.*, 13:585–587, 1964. DOI: 10.1103/PhysRevLett.13.585.
- [11] P. W. Higgs. Spontaneous symmetry breakdown without massless bosons. *Phys. Rev.*, 145:1156–1163, 1966. DOI: 10.1103/PhysRev.145.1156.
- [12] ATLAS Collaboration. Observation of a new particle in the search for the Standard Model Higgs boson with the ATLAS detector at the LHC. *Physics Letters B* 716.1 (2012), pp. 1-29
- [13] CMS Collaboration Observation of a new boson at a mass of 125 GeV with the CMS experiment at the LHC. *Physics Letters B* 716.1 (Sept. 2012), pp. 30-61
- [14] L. Evans and P. Bryant. LHC machine. *JINST*, 3:S08001, 2008.
- [15] E. Lopienska. The CERN accelerator complex layout in 2022. Complexe des accélérateurs du CERN en janvier 2022. *CERN-GRAPHICS-2022-001*, 2022. URL: <https://cds.cern.ch/record/2800984>
- [16] J. Pequeno Computer generated image of the whole ATLAS detector. *CERN-GE-0803012*, 2008. URL: <https://cds.cern.ch/record/1095924>
- [17] J. Pequeno Computer generated image of the ATLAS inner detector. *CERN-GE-0803014*, 2008. URL: <https://cds.cern.ch/record/1095926>
- [18] J. Pequeno Computer generated image of the ATLAS Liquid Argon. *CERN-GE-0803016*, 2008. URL: <https://cds.cern.ch/record/1095928>
- [19] J. Pequeno Computer generated image of the ATLAS Muons subsystems. *CERN-GE-0803017*, 2008. URL: <https://cds.cern.ch/record/1095929>

- [20] J. Catmore The ATLAS data processing chain: from collision to paper. Joint Oslo/Bergen/NBI ATLAS Software Tutorial. University of Oslo, 2016. URL: https://indico.cern.ch/event/472469/contributions/1982677/attachments/1220934/1785823/intro_slides.pdf
- [21] ROOT by CERN. TTree Class Reference. *ROOT Reference Guide*. URL: <https://root.cern.ch/doc/v630/classTTree.html>
- [22] A. Serhan Mete,M. Nowak,P. van Gemmeren Persistifying the Complex Event Data Model of the ATLAS Experiment in RNTuple. *22nd International Workshop on Advanced Computing and Analysis Technique in Physics Research*. 11-15 March 2024.
- [23] ROOT Team Collaboration RNTuple Binary Format Specification 1.0.0.0 *CERN-OPEN-2025-001* (2024)
- [24] J. Blomer,P. Canal,A. Naumann,D. Piparo Evolution of the ROOT TreeIO *EPJ Web of Conf.*245 (2020) 02030
- [25] Google Cloud What is binary large object (BLOB) storage? URL: <https://cloud.google.com/discover/what-is-binary-large-object-storage>
- [26] Wikipedia Smart pointer URL: https://en.wikipedia.org/wiki/Smart_pointer
- [27] ROOT Team ROOT Reference Documentation URL: <https://root.cern.ch/doc/master/index.html>
- [28] J. Lopez-Gomez, J. Blomer RNTuple performance: Status and Outlook *J. Phys. Conf. Ser.*2438 (2023) 1, 012118
- [29] O. S. Bruning, P. Collier,P. Lebrun,S. Myers,R. Ostojic,J. Poole,P. Proudlock LHC Design Report *Geneva:CERN,2024-548*

- 549 [30] ATLAS Collaboration URL: <https://opendata.atlas.cern/>
- 550 [31] The ATLAS Collaboration. Athena *Zenodo*, (2019) DOI: [https://doi.org/10.5281/](https://doi.org/10.5281/zenodo.2641996)
551 [zenodo.2641996](https://doi.org/10.5281/zenodo.2641996)
- 552 [32] J. Blomer,P. Canal,F. de Geus,J. Hahnfeld,A. Naumann,J. Lopez-Gomez,G. Laz-
553 zari Miotto,V. E. Padulano ROOT's RNTuple IO Subsystem:The Path to Production
554 *EPJ Web of Conf.*295, 06020 (2024)
- 555 [33] Iris HEP Analysis Grand Challenge URL: [https://iris-hep.org/projects/agc.](https://iris-hep.org/projects/agc.html)
556 [html:S](https://iris-hep.org/projects/agc.html)
- 557 [34] ATLAS Collaboration. The ATLAS Experiment: Trigger and Data Acquisition URL:
558 <https://atlas.cern/Discover/Detector/Trigger-DAQ>
- 559 [35] I. Bejar Alonso et al. "High-Luminosity Large Hadron Collider (HL-LHC): Technical
560 design report."” *CERN Yellow Reports* Vol. 10 (2020)
- 561 [36] ATLAS Collaboration "Mass/Invariant mass" URL: [https://atlas.cern/glossary/](https://atlas.cern/glossary/mass)
562 [mass](https://atlas.cern/glossary/mass)
- 563 [37] ATLAS Collaboration Facts Sheets "4-Vectors and particle mass" URL:
564 [https://cds.cern.ch/record/2919871/files/4-vectors%20and%20invariant%](https://cds.cern.ch/record/2919871/files/4-vectors%20and%20invariant%20mass%20cheat%20sheet.pdf)
565 [20mass%20cheat%20sheet.pdf](https://cds.cern.ch/record/2919871/files/4-vectors%20and%20invariant%20mass%20cheat%20sheet.pdf)
- 566 [38] The ATLAS and CMS Collaborations. Highlights of the HL-LHC physics projections
567 by ATLAS and CMS. *CMS-HIG-25-002* 2025
- 568 [39] ATLAS Collaboration Technical Design Report for the ATLAS Inner Tracker Pixel
569 Detector, *CERN-LHCC-2017-021*, 2017.

- [40] ATLAS Collaboration Technical Design Report: A High-Granularity Timing Detector for the ATLAS Phase-II Upgrade. *CERN-LHCC-2020-007*, 2020
- [41] ATLAS Collaboration Technical Design Report for the Phase-II Upgrade of the ATLAS Muon Spectrometer. *CERN-LHCC-2017-017*, 2017.
- [42] ATLAS Collaboration. ATLAS Liquid Argon Calorimeter Phase-II Upgrade : Technical Design Report. *CERN-LHCC-2017-018*, 2017
- [43] ATLAS Collaboration. Technical Design Report for the Phase-II Upgrade of the ATLAS Tile Calorimeter. *CERN-LHCC-2017-019*, 2017.
- [44] ATLAS Collaboration. Technical Design Report for the Phase-II Upgrade of the ATLAS Tile Calorimeter. *CERN-LHCC-2017-019*, 2017.
- [45] ATLAS Collaboration Technical Design Report for the Phase-II Upgrade of the ATLAS TDAQ System. *CERN-LHCC-2017-020*, 2017
- [46] S. Amato et al. LHCb technical proposal *CERN-LHCC-98-04*
- [47] ALICE Collaboration ALICE: Technical proposal for a Large Ion collider Experiment at the CERN LHC *Geneva: CERN*, 1995 - 237
- [48] URL: <https://iris-hep.org/>
- [49] URL: <https://iris-hep.org/projects/agc.html>
- [50] URL: <https://github.com/alexander-held/PyHEP-2022-AGC/blob/main/talk.ipynb>

589

APPENDIX

590

OBJECTIVE SYMPTOMS

Appendices follow the same page-numbering rules as regular chapters. The first page of a multi-page appendix is not numbered. But the page of a single-page appendix *is* numbered.

Are they slow learners or is it a *REAL* problem? These are classic findings in the hopelessly computer challenged.

1. Can't copy from hard drive to disk.

2. Can't eject disks.

3. The word "disk" has thousands of meanings to them. None are correct.

4. Saving a document in any form is a concept totally unexplainable to them.

5. Desktop covered with Untitled Folders - look again, untitled folders are everywhere.

6. "Lost" documents found often in the Apple Menu.

7. Trash always full. Claim they don't know how to place things in trash.

8. Mysterious things happen to their documents or computer when they are not present.

AKA "computer victims".

9. Highlighting = deleting. Dragging = Oblivion.

10. Selecting, double-clicking a problem? They will always say their mouse is broken.

11. Their double-click mechanics wants you to send them to a neurologist.

12. Computer always on due to fear of having to restart it.

13. Have never read their QuickMail - will say "I prefer a phone call".

14. Have magical beliefs about what computers do.

15. Describes some flaky way computers could REALLY help them, but is not yet available.

- 611 16. Constantly saying they need more “memory”.
- 612 17. Requests gizmos and gadgets, i.e., “mouse leash” or “disk cozy”.
- 613 18. Avoids eye contact when talking about computers.