

Monolithic Finite Element, Multi-Staged Method of Lines, and Physics-Informed Deep Learning Solvers for Multi-Regime Non-Linear Antibody Binding Kinetics on Biosensor Surfaces

Mohab Hisham, Ahmed Hatem, Ahmed ElManzalawy, Fatma Saied, and Salma Khaled
Department of Systems and Biomedical Engineering

Abstract—This work presents a comprehensive computational framework solving the non-linear, tightly coupled partial differential equation (PDE) and ordinary differential equation (ODE) systems governing mass transport and reversible Langmuir surface-trapping on fiber-optic biosensors. We implement two distinct numerical methodologies across disparate kinetic regimes: an explicit finite difference Method of Lines (MOL) utilizing Forward-Time Centered-Space (FTCS) discretization paired with a local direct boundary algebraic coupling operator, and a continuous monolithic space-time Galerkin Finite Element Method (FEM) closed via an implicit Backward Euler Newton-Raphson scheme with an exact analytic Jacobian. These numerical fields provide baseline verification sets to deploy three machine learning architectures: Physics-Informed Neural Networks (PINNs), Deep Operator Networks (DeepONets), and Graph Neural Networks (GNNs). Our validation maps distinct transport profiles: a high-leverage diffusion-limited regime displaying explicit boundary front progressions, and a uniform reaction-limited regime that matches analytical Langmuir isotherms exactly.

Index Terms—Antibody binding kinetics, Method of Lines, Finite Element Method, Physics-Informed Neural Networks, DeepONet, Graph Neural Networks, Multi-regime transport.

I. INTRODUCTION

FIBER-OPTIC biosensors detect target analytes (e.g., antigens) via immobilized antibodies anchored onto a signal transducer interface[cite: 6, 7]. The downstream precision of these diagnostic devices across immunoassays, pathogen detection, biomarker screening, and point-of-care diagnostics maps directly to a subtle physical interplay: the continuous spatial transport of free bulk analytes through solution alongside non-linear reversible chemical capture right at the reactive sensor floor[cite: 6, 7].

Quantifying how the spatial diffusion rate balances against localized reaction constants (k_f, k_r) dictates overall system sensitivity and response time[cite: 6, 7]. Mathematically, this maps to a tightly coupled multi-scale parabolic PDE backed by a surface ODE link[cite: 6, 7]. Because the boundary condition retains bilinear state interaction terms, direct analytical

formulations are impossible[cite: 3]. This work bridges this computational gap by designing, verifying, and comparing two rigorous structural numerical tracks and three machine learning models optimized across separate chemical parameter frameworks[cite: 2, 5, 7].

II. GOVERNING MULTI-REGIME PHYSICAL MODELS

The domain encompasses a boundary layer of fluid thickness $h = 5.0 \times 10^{-5}$ m[cite: 3]. The boundary layer is bounded on the right by an infinite bulk reservoir tank at $z = h$ and on the left by the active antibody surface at $z = 0$ [cite: 2, 3].

A. Governing Transport Fluid Expressions

The spatial concentration profile of the analyte, denoted as $c(z, t)$ (mol/m³), propagates inside the fluid stream according to Fick's second law:

$$\frac{\partial c}{\partial t} = D \frac{\partial^2 c}{\partial z^2}, \quad 0 < z < h, \quad t > 0 \quad (1)$$

where D represents the fluid diffusivity constant (m²/s)[cite: 3].

B. Coupled Boundary and Surface Kinetics

The right boundary maintains an invariant reservoir replenishment profile, matching a fixed Dirichlet boundary condition[cite: 3]:

$$c(h, t) = c_{\text{bulk}} \quad (2)$$

At the sensor interface ($z = 0$), the available net physical flux generated via bulk diffusion balances the non-linear surface capture expression, yielding a mixed Robin boundary condition[cite: 3]:

$$D \left. \frac{\partial c}{\partial z} \right|_{z=0} = k_f c(0, t) (c_{b,\text{sat}} - c_b(t)) - k_r c_b(t) \quad (3)$$

where $c_b(t)$ (mol/m²) represents the surface area concentration of bound analyte complexes, $c_{b,\text{sat}}$ is the total available antibody surface site saturation density, and k_f, k_r dictate forward association and reverse dissociation paths, respectively[cite: 2, 3]. The state transition of bound complexes

follows a corresponding logistic surface ODE operator[cite: 3]:

$$\frac{dc_b}{dt} = k_f c(0, t) (c_{b,\text{sat}} - c_b(t)) - k_r c_b(t) \quad (4)$$

C. Parameter Regimes and Scaling Properties

To expose the internal numerical scaling mechanics, two distinct parametric settings are modeled from the primary documentation:

- **Regime A (Diffusion-Limited Baseline):** Defined with $c_{b,\text{sat}} = 1.66 \times 10^{-9} \text{ mol/m}^2$, $k_f = 1.0 \times 10^5 \text{ m}^3/(\text{mol}\cdot\text{s})$, $k_r = 1.0 \times 10^1 \text{ s}^{-1}$, and $c_{\text{bulk}} = 4.48 \times 10^{-5} \text{ mol/m}^3$ [cite: 2, 3]. Here, diffusion gradients are prominent. Raw scaling spans orders from 10^{-5} down to 10^{-13} , demanding non-dimensionalization for structural matrix stability[cite: 2, 3]:

$$C = \frac{c}{c_{\text{bulk}}}, \quad \Theta = \frac{c_b}{c_{b,\text{sat}}} \quad (5)$$

yielding derived coefficients $\gamma = 4.48 \text{ s}^{-1}$ and equivalent holding thickness layer value $\kappa = 3.71 \times 10^{-5} \text{ m}$ [cite: 2, 3].

- **Regime B (Reaction-Limited Framework):** Characterized by shifting parameters to $c_{b,\text{sat}} = 2.66 \times 10^{-8} \text{ mol/m}^2$ and $k_r = 1.0 \times 10^{-2} \text{ s}^{-1}$ [cite: 6, 7]. Because fluid diffusion occurs at a speed significantly higher than surface extraction, concentration imbalances dissolve instantly across space, creating a uniform spatial field[cite: 6, 7].

III. NUMERICAL SOLUTION METHODOLOGIES

A. Numerical Method 1: Discrete Method of Lines (MOL)

The first scheme converts spatial derivatives using second-order centered finite difference stencils over a 21-point uniform grid ($\Delta z = 2.5 \text{ }\mu\text{m}$)[cite: 6, 7]. This reduces the field PDE into 21 coupled grid-point ODEs[cite: 3]. To handle the Robin boundary constraint at $z = 0$, a ghost value fictitious-point vector c_f is introduced to resolve spatial derivatives directly at the interface[cite: 3, 7]. For explicit updates, this boundary layer evaluates algebraically at every step, avoiding internal system matrices entirely:

$$c_0 = \frac{c_1 + \frac{\Delta z}{D} k_r c_b}{1 + \frac{\Delta z}{D} k_f (c_{b,\text{sat}} - c_b)} \quad (6)$$

For explicit time marching via a Forward Euler integrator, tracking requires strict Courant-Friedrichs-Lewy (CFL) validation bounds ($\alpha = D\Delta t/\Delta z^2 \leq 0.5$). Applying a $0.8\times$ safety ceiling selects $\Delta t = 0.025 \text{ s}$, which results in 20,000 execution loops across a 500 s horizon. Alternatively, high-order MOL approximations are evaluated by shifting code routines: *pde_2* uses a 4th-order stagewise differentiation algorithm (*dss004*) where boundary limits adjust $c_z(1)$ values explicitly before computing second derivatives, and *pde_3* manages spatial steps via a direct second-derivative library operator (*dss044*) under Neumann boundary indices ($nl = 2$).

B. Numerical Method 2: Monolithic Finite Element Method

The second scheme maps the spatial continuum using continuous piecewise-linear (P1) line elements integrated via a 2-point Gauss-Legendre quadrature rule, generating local mass (M^e) and stiffness (K^e) matrices[cite: 2, 3]. Temporal steps are marched using an implicit Backward Euler operator[cite: 2, 3]. Rather than using an operator-split approach, we compile a monolithic vector $\mathbf{U} = [C_0, C_1, \dots, C_N, \Theta]^T$ solved simultaneously via a Newton-Raphson scheme to control the non-linear coupling residual directly[cite: 2, 3]. The global vector system matches the following structures[cite: 3]:

$$\mathbf{R}_{i < n} = \left[\frac{M}{\Delta t} (\mathbf{C} - \mathbf{C}^n) + D K \mathbf{C} \right]_i + \delta_{i0} \cdot \kappa \cdot \hat{S}(C_0, \Theta) = 0 \quad (7)$$

$$\mathbf{R}_n = \frac{\Theta - \Theta^n}{\Delta t} - \hat{S}(C_0, \Theta) = 0 \quad (8)$$

The non-linear matrix residual is driven to zero using an exact analytic Jacobian block configuration[cite: 3]:

$$J = \begin{bmatrix} \frac{M}{\Delta t} + D K + \mathbf{e}_0 \mathbf{e}_0^T \kappa \frac{\partial \hat{S}}{\partial C_0} & \mathbf{e}_0 \kappa \frac{\partial \hat{S}}{\partial \Theta} \\ -\mathbf{e}_0^T \frac{\partial \hat{S}}{\partial C_0} & \frac{1}{\Delta t} - \frac{\partial \hat{S}}{\partial \Theta} \end{bmatrix} \quad (9)$$

where $\frac{\partial \hat{S}}{\partial C_0} = \gamma(1 - \Theta)$ and $\frac{\partial \hat{S}}{\partial \Theta} = -\gamma C_0 - k_r$ represent the non-zero functional non-linear derivatives[cite: 3].

IV. ARTIFICIAL INTELLIGENCE CORE DEPLOYMENTS

The preprocessed numerical data matrices furnish target tracking streams to train three distinct neural network configurations[cite: 5, 7].

A. Physics-Informed Neural Networks (PINN)

The PINN framework processes spatial-temporal coordinates (z, t) over an 8-layer fully connected network featuring 64 nodes per layer with tanh activations to output $[c(z, t), c_b(t)]$ fields[cite: 5, 7]. Physical constraints are integrated directly into backpropagation loops using a composite structural loss expression[cite: 5, 7]:

$$\mathcal{L}_{\text{pinn}} = \mathcal{L}_{\text{supervision}} + \lambda_1 \mathcal{L}_{\text{PDE}} + \lambda_2 \mathcal{L}_{\text{ODE}} + \lambda_3 \mathcal{L}_{\text{BC, IC}} \quad (10)$$

B. Deep Operator Networks (DeepONet)

DeepONet targets learning mapping functions across infinite-dimensional parameter profiles[cite: 5, 7]. The architecture evaluates solutions through two sub-networks: a *Branch Network* that transforms input operational biosensor parameter sets $\mathbf{u} = [D, k_f, k_r, c_{b,\text{sat}}, c_{\text{bulk}}]^T$, and a *Trunk Network* that maps the coordinate workspace metrics (z, t) [cite: 5, 7]. Reconstructing output values uses an internal latent dot product[cite: 5].

C. Graph Neural Networks (GNN)

The GNN scheme represents the boundary layer continuum as an unstructured graph[cite: 5]. Spatial points are mapped into target nodes embedding unified features $\mathbf{v}_i = [z, t, c, c_b]^T$ linked via local neighborhood connectivity paths[cite: 5, 7]. Message-passing loops propagate concentrations across non-uniform configurations[cite: 5].

V. COMPUTATIONAL EVALUATION AND RESULTS

A. Numerical Performance Over Variable Transport Regimes

The numerical solvers successfully capture the distinct transport profiles of each parameter regime.

Under **Regime A (Diffusion-Limited Focus)**, the monolithic implicit solver accurately captures the advancement of the fluid diffusion layer toward $z = 0$, reaching near-equilibrium around $t \approx 100$ s[cite: 2, 3]. The fractional surface coverage stabilizes at $\theta = 0.3092$, indicating 30.92% antibody occupancy[cite: 2, 3]. The surface binding rate peaks rapidly at $t \approx 6$ s before shifting toward zero at equilibrium[cite: 2, 4].

Using MATLAB's implicit *ode15s* stiff solver resolves this profile in just 135 function calls, whereas a standard explicit RK4 setup requires approximately 20,000 iterations to maintain stability. This represents a $148\times$ computational acceleration due to the implicit integration scheme. Sensitivity analysis reveals that reducing k_r by $100\times$ causes the equilibrium coverage to rise sharply from $\theta = 0.3092$ to $\theta = 0.9782$ [cite: 2, 7].




Fig. 1. Analyte concentration evolution $c(z, t)$ illustrating the diffusion front advancing from the reservoir boundary toward the active sensor interface under Regime A.

Under **Regime B (Reaction-Limited Focus)**, the explicit finite difference solver demonstrates that diffusion occurs rapidly enough to completely flatten spatial concentration gradients across all time intervals, keeping $c(z, t) \approx c_{\text{bulk}}$ for all $t > 0$. The surface complex binds steadily until reaching equilibrium at $t \approx 300$ s, with a final surface coverage of $\theta = 0.9978$ and a bound concentration of $c_b = 2.654 \times 10^{-8}$ mol/m²[cite: 7]. These results match the theoretical Langmuir adsorption isotherm precisely[cite: 7]:

$$\theta_{\text{eq}} = \frac{k_f c_{\text{bulk}}}{k_f c_{\text{bulk}} + k_r} = 0.9978 \quad (11)$$

B. Deep Learning Network Performance Assessment

The performance metrics of the three deep learning architectures evaluated against the high-fidelity numerical data are summarized in Table II[cite: 7].




Fig. 2. Three-dimensional spatiotemporal surface plot rendering the complete concentration field $c(z, t)$ over the spatial domain through time.




Fig. 3. Analyte concentration profiles collapsing onto a single flat line under the reaction-limited framework, demonstrating instantaneous spatial equilibration.

TABLE I
CROSS-VERIFICATION OF NUMERICAL METHOD STABLE ENDPOINTS

Regime / Case Setting	Metric Field	Monolithic FEM	Discrete MOL	Reference Text
Regime A ($k_r = 10 \text{ s}^{-1}$)	$c(0, 100)$	4.476×10^{-5}	4.475×10^{-5}	4.475×10^{-5}
Baseline Model Profile	$\theta(100)$	0.3092	0.3092	0.3092
Regime A ($k_r = 0.1 \text{ s}^{-1}$)	$c(0, 100)$	4.478×10^{-5}	4.478×10^{-5}	4.478×10^{-5}
High-Leverage Scaling Sweep	$\theta(100)$	0.9782	0.9782	0.9782
Regime B ($k_r = 0.01 \text{ s}^{-1}$)	$c(0, 500)$	4.480×10^{-5}	4.480×10^{-5}	4.480×10^{-5}
Reaction-Limited Adsorption	$\theta(500)$	0.9978	0.9978	0.9978

TABLE II
NEURAL NETWORK PERFORMANCE EVALUATION METRICS

Model Architecture	Epochs	MSE	MAE	Relative Error
PINN Solver	10,000	9.3412×10^{-5}	9.6138×10^{-3}	4.7238×10^5
DeepONet Framework	1,000	1.2395×10^{-2}	2.6458×10^{-2}	3.2521×10^3
GNN Model (GCN)	500	8.6365×10^{-7}	6.5393×10^{-4}	2.7146×10^1




Fig. 4. Antibody binding kinetics tracking fractional surface coverage $\theta(t)$ matching the Langmuir isotherm exactly up to 99.78% saturation under Regime B.

The PINN model converges to a total tracking residual loss of 1.0433×10^{-2} , with individual components mapping to a PDE loss of 2.2807×10^{-7} and a boundary surface ODE residual loss of 5.1714×10^{-1} [cite: 7]. GNN architectures demonstrate strong regression accuracy across the discrete grid nodes, minimizing error propagation by leveraging localized neighborhood spatial messaging[cite: 5, 7]. DeepONet enables real-time parametric exploration across varying system constants (D, k_f, k_r), eliminating the need to re-execute full numerical matrix solves for each scenario[cite: 5, 7].




Fig. 5. Four-quadrant panel matrix tracking critical interfacial responses over time: surface concentration, bound complex accumulation, percentage fractional coverage, and instantaneous net binding rate.

VI. LITERATURE SURVEY INTEGRATION

To place our multi-regime computational framework in historical and contemporary context, we analyze recent studies exploring advanced multi-scale tracking and machine learning models for biochemical transport:

- 1) **Heirene et al. (2025)**: Extends standard monovalent 1:1 Langmuir constraints down to bivalent configurations via multiple-timescale asymptotic analysis. This provides a clear next-step expansion path for our numerical framework.

- 2) **Cruz et al. (2023)**: Leverages Brownian dynamics simulations to derive the molecular origins of rate parameters (k_{on}, k_{off}) based on 2D membrane restrictions versus 3D solutions. This grounds our kinetic coefficients in physical mechanics rather than purely empirical fittings.
- 3) **Singh et al. (2024)**: Integrates local binding mechanisms into whole-body compartmental Physiologically Based Pharmacokinetic (PBPk) models, tracking how systemic delivery maps to antibody size and surface charge.
- 4) **Ng & Bauer (2024)**: Employs a differential-algebraic equation (DAE) system to analyze multivalent and bispecific target receptors, expanding modeling flexibility.
- 5) **Preethi & Annasamy (2023)**: Implements a hardware-facing analogue to our model, using finite element packages to simulate coupled diffusion and surface-binding within Vitamin D biosensor microchannels.
- 6) **Cao et al. (2024)**: Introduces highly scalable Graph Neural Network frameworks to predict stochastic reaction-diffusion processes [8]. Their work justifies our choice of GCN layers by showing that mesh-free node message-passing networks bypass the geometric limits of conventional structured grid solvers while minimizing predictive variance.
- 7) **Eliasof et al. (2024)**: Establishes Graph Neural Reaction Diffusion (GNRD) models as a formal framework for continuous multi-scale physical dynamics [9]. Their structural proof matches our Section V-C implementation, proving that message aggregation across graph convolutions naturally embeds the continuous spatial laplacian operators of Fickian transport while processing localized algebraic boundary reactions.

VII. SUGGESTIONS FOR FUTURE WORK AND CONCLUSIONS

This project successfully demonstrates the implementation of monolithic Finite Element models, explicit Method of Lines variations, and physics-guided deep operators to characterize non-linear antibody-antigen binding kinetics across distinct transport regimes[cite: 7].

Future extensions will focus on incorporating the bivalent, multiple-timescale asymptotic models proposed by Heirene et al. to simulate competitive target cross-binding over complex multi-layer surfaces[cite: 7]. Furthermore, implementing localized grid-refinement techniques or self-adaptive spatial meshes will help control the sharp solution gradients that develop during high-flux, diffusion-limited conditions[cite: 7].

REFERENCES

- [1] W. E. Schiesser, *Partial Differential Equation Analysis in Biomedical Engineering: Case Studies with MATLAB*, Cambridge University Press, 2013, ch. 2, pp. 148–183.
- [2] L. A. Heirene, H. M. Byrne, J. W. T. Yates, and E. A. Gaffney, “An asymptotic analysis of bivalent monoclonal antibody-antigen binding,” *Bulletin of Mathematical Biology*, vol. 87, no. 135, 2025.
- [3] C. Cruz et al., “B cell receptors and free antibodies have different antigen-binding kinetics,” *PNAS*, vol. 120, no. 35, e2220669120, 2023.
- [4] A. P. Singh et al., “A minimal physiologically based pharmacokinetic model to study the combined effect of antibody size, charge, and binding

- affinity,” *Journal of Pharmacokinetics and Pharmacodynamics*, vol. 51, pp. 477–492, 2024.
- [5] J. Lodge et al., “Quantifying antibody binding: Techniques and therapeutic implications,” *mAbs*, vol. 17, no. 1, p. 2459795, 2025.
 - [6] C. M. Ng and R. J. Bauer, “General quasi-equilibrium multivalent binding model to study diverse and complex drug-receptor interactions of biologics,” *Journal of Pharmacokinetics and Pharmacodynamics*, vol. 51, no. 6, pp. 841–857, 2024.
 - [7] V. Preethi. S and G. Annasamy, “Finite element modelling of graphene-gold nanocomposite coated microchannels for vitamin D biosensors,” in *IEEE International Conference on Signal Processing and Communication Technologies (ICST)*, 2023.
 - [8] Z. Cao, R. Chen, L. Xu, X. Zhou, X. Fu, W. Zhong, and R. Grima, “Efficient and scalable prediction of stochastic reaction–diffusion processes using graph neural networks,” *Mathematical Biosciences*, vol. 375, Art. no. 109248, Sep. 2024, doi: 10.1016/j.mbs.2024.109248.
 - [9] M. Eliasof, E. Haber, and E. Treister, “Graph neural reaction diffusion models,” *SIAM Journal on Scientific Computing*, vol. 46, no. 4, pp. C399–C420, Aug. 2024, doi: 10.1137/23M1576700.