



SEC.A-A

1、 MATERIAL AND FINISH

1. SOCKET LID :PEI
2. SOCKET BASE :PEI
3. CONTACTS :BeCu,SELECTIVE Au-AuFLASH OVER NI PLATING
4. SPRINGS :STAINLESS STEEL ,PASSIVATED

2、PERFORMANCE

- 1、Insulation Resistance : 1000M Ω or more at DC 100V
- 2、Dielectric Withstanding Voltage: 100V AC for one minute
- 3、Contact Resistance 80m Ω , MAX. at 10mA and 20mV MAX. (Initial)
- 4、Operation Temperature -50°C~+150°C
- 5、Life Span 10,000 Times (Mechanical)
- 6、Operation Force 3.0 Kg MAX

△ C				DWG NO		PART NAME	ASS51-BGA24-(B6X8)-1.0-CL
△ B				MATERIAL	SCALE	1:1	TITLE
△ A				QTY	1	UNIT	mm
REV	DESCRIPTION	DATE	CHECK	SHEET	1 OF 1	REV	01
APPLICATION				APPROVE		DATE	
ANGLE	FINISH	ROUGH EDGE	ME TRIC	0.XX:±0.1	CHECK	DATE	
ALL UNSPECIFIED CHAMFERS:0.0				0.XX:±0.05	DEGK	DATE	20150204

