

GRK 2839 Winter School: Corpus & Computational Linguistics

# Regular Expressions

**Andreas Blombach, Stephanie Evert,**

**Philipp Heinrich**

Lehrstuhl für Korpus- und  
Computerlinguistik

<https://www.linguistik.phil.fau.de>



Friedrich-Alexander-Universität  
Philosophische Fakultät und  
Fachbereich Theologie

## Regular expressions

- Regular expressions (**regex/regexp**) are a sophisticated wildcard notation from computer science
- Widely used for full-text search (e.g. **grep**) and by advanced text editors (Emacs, Atom, Notepad++, Kate, ...)
  - task: find substring matching pattern in text
- Corpus queries use regular expressions at two levels
  - for matching word forms and annotations (over characters)
    - always matches complete string ≠ full-text search
  - for describing lexico-grammatical patterns (over tokens)
- Different regexp “flavours”: we will use **PCRE**
  - POSIX, PCRE = Perl-compatible regular expressions, Python, Oniguruma, ...



## Web interfaces to play around with

- CWB Wordlist Explorer:

[http://corpora.linguistik.uni-erlangen.de/cgi-bin/demos/regex/wordlist\\_explorer.perl](http://corpora.linguistik.uni-erlangen.de/cgi-bin/demos/regex/wordlist_explorer.perl)

match CWB regular expressions against frequency lists of different corpora

- Full-text search & debugging of regular expressions

- <https://regexpr.com/>
- <https://regex101.com/>
- <http://regviz.org/> (für JavaScript, nicht PCRE)
- <https://www.debuggex.com/>

- Play the Regular Expression Crossword

<https://regexcrossword.com/>

## PCRE: Perl Compatible Regular Expressions

- `(...)?` = optional (0 or 1)
- `(...)*` = any number of repeats (0 or more)
- `(...)+` = at least once (1 or more)
- `(...){3}` = exactly thrice
- `(...){2,4}` = between two and four times (2, 3, 4)
- `(...){4,}` = beliebig oft, aber mindestens viermal
  - Quantifiers refer to the expression that immediately precedes them – if that's supposed to be a pattern of several characters, don't forget to put it in parentheses!
- `(...|...|...)` = alternatives (matches exactly one)
- `.` = any character ([matchall](#))
  - esp.: `?` (optional character), `*` (arbitrary string), `+`
- escapes: `\.` = `.`, `\*` = `*`, `\?` = `?`, `\+` = `+`, ...

# PCRE

- `[aeiou]` = character class (matches exactly one)
  - `[a-z]` = `[abc ... z]` and `[A-Z]` = `[ABC ... Z]` (NB: no umlauts, <β> etc.)
  - `[0-9]` = `[0123456789]`
- `[^aeiou]` = everything(!) except `[aeiou]`
- Predefined character classes:
  - `\w` = letters, digits and `_` (word character)
  - `\s` = any single whitespace (space, tab, newline, ...)
  - `\d` = digit
  - `\pL` = letter, `\p{Ll}` = lower-case letter, `\p{Lu}` = upper-case letter
  - `\pN` = digit, `\p{Cyrillic}` = cyrillic letter, ...
    - see <https://www.pcre.org/original/doc/html/pcpattern.html#SEC5>

## PCRE

Extension for full-text (substring) search:

- not meaningful in corpus queries (which match entire strings)
- `(...)??`, `(...)*?`, `(...)+?`  
= match as few repetitions as possible
  - regular expressions are **greedy** by default: they try to match as many characters as possible – this behaviour can lead to unexpected and undesirable results
- `^...` = anchor to start of line
- `...$` = anchor to end of line
  - beware: `^(...|...)$`  $\neq$  `^...|...$`
  - in corpus queries, `^` and `$` can usually be used as anchors to the start and end of word forms (reason: one token per line)
- `\b` = anchor matching a “word boundary”
- Cheat sheet for PCRE: <https://www.debuggex.com/cheatsheet/regex/pcre>

## Context-sensitive search: *look-around assertions*

- Find expressions in a specific context without including this context in the result:

---

$\dots(?=\dots)$  = *positive look-ahead* (**context** must follow **search expression**)

$\dots(?!\dots)$  = *negative look-ahead* (**context** must **not** follow **search expression**)

$(?<=\dots)\dots$  = *positive look-behind* (**context** must precede **search expression**)

$(?<!\dots)\dots$  = *negative look-behind* (**context** must **not** precede **search expression**)

---

## Capturing groups and back-references

- Parentheses create so-called *capturing groups*
  - `(\d{2}):(\d{2})` → groups 1 (*hours*) and 2 (*minutes*)
  - can be used for information extraction in e.g. Python or R
  - `(?:...)` = *non-capturing groups* (→ also important to control numbering)
- Back-references to groups: `\1`, `\2`, ...
  - `([a-z]+)-\1` → *fifty-fifty, wah-wah, ack-ack*, ...
- Text editors: replacing text with regular expressions (→ *Find and replace*)
  - captured groups can be inserted into replacement text
  - usually with `$1`, `$2`, ...
  - “text processing for everybody” (→ *Find in Project*)