

SKC-LB Series



SKC-LB1820



SKC-LB1840



SKC-LB1830C



SKC-LB1430



SKC-LB1030S



SKC-LB0730S

Features

- Adopting Japanese and Korea high performance Li-ion (Li-Mn) battery.
- Built in protection device to prevent battery overcharge and over discharge.
- The latch design increases intensity and convenience when assembling or dismantling the rechargeable battery from the cordless screwdriver.
- Fully charged voltage: 21V, low-voltage protection: 13.5V, over-temperature protection (discharge): 72°C.
- Battery ID identification design, which only allows original charge station to recharge the battery to secure battery safety and extend battery lifetime.

Battery charging time reference

Battery Model / Capacity	MYCS-ID120	MYCS-ID80	MYCS-80	MYCS-ID80-D	MYCS-ID70+	MYCS-ID50	MYCS-ID25
SKC-LB1820	40 min.	40 min.	40 min.				
SKC-LB1840	60 min.	80 min.	80 min.				
SKC-LB1830C				45 min.			
SKC-LB1430					70 min.		
SKC-LB1030S						55 min.	
SKC-LB0730S							70 min.

Specifications

Battery Model	SKC-LB1820	SKC-LB1840	SKC-LB1830C	SKC-LB1430	SKC-LB1030S	SKC-LB0730S
Voltage	18V	18V	18V	14.4V	10.8V	7.2V
Capacity	1950mA/hr	3900mA/hr	3000mA/hr	3000mA/hr	3000mA/hr	3000mA/hr
Rated voltage	18V	18V	18V	14.4V	10.8V	7.2V
Power	35Wh	70Wh	54Wh	43.2Wh	32.4Wh	21.6Wh
Cells Permutation	5 series 1 parallel	5 series 2 parallel	5 series 1 parallel	4 series 1 parallel	3 series 1 parallel	2 series 1 parallel
Weight	430g	720g	430g	327g	194g	128g
Dimensions(mm)	119X90X40	119X90X59	92X75X63	107X75X43	51X46X90	51X44X70
Certification	CE,TUV	CE,TUV	CE,TUV	CE,TUV	CE,TUV	CE,TUV
UN38.3 Inspection report	YES	YES	YES	YES	YES	YES