

SCREWDRIVER I/O SIGNAL CONTROL BOX, SLOW START CONTROL MODULE, 90 DEGREE ATTACHMENT

MYTORQ
ANLIDAR INDUSTRIAL CO.,LTD.

【MY-SIO, KL-SSBN, KL-2】

Screwdriver I/O Signal Control Box(For Manual / PLC)

MY-SIO

- Slow Start time (0.0-9.9 second)
- Slow start Speed (30%-100% of normal speed,L0-L9)
- Operation Time (0.0-9.9 second)
- Target Reached Confirm (enable / disable)
- Brake Signal Hold Time (start off / next start off)
- External Start Input Control
- External Reverse Input Control
- Signal output (Start,Stop,Reverse)



MY5

+



MY-SIO

+



MYP series Power Controller



Slow Start Control Module

KL-SSBN

- BYPASS: Automatically disable slow start function when screwdriver in reverse rotation, easier to reverse screws.
- Adjustable slow start speed from 30% to 100% of normal speed, Slow start level setting from L1-L2-L3-...L9-L0
- Provide output start signal/ break signal/ forward and reverse signal with MOS relay switch
- Compatible with MYTORQ Brushless DC MY2 / 5 series
- Slow start time can be set from 0.1 s up to 9.9 second
- Dimension : 58x95x35mm (LxWxH)



90 Degree Attachment

Model	90 Degree Attachment Applicable Model
KL-2	MY5 Series

※ Only for "L" trigger start screwdrivers