




External Dimension



Unit: mm

Specifications

Model	Torque			Free Speed (r.p.m)	Weight (g)	Length (mm)	Power Controller	Bit Type
	(N.m)	(kgf.cm)	(Lbf.in)					
MY-CURRENT Lite 1.2	0.3~1.2	3.06~12.24	2.66~10.62	1000~100	1173	192X92X50	MY-CURRENT Lite	B 9.5、D
MY-CURRENT Lite 2	0.6~2	6.12~20.40	5.31~17.70	1000~100	1173	192X92X50	MY-CURRENT Lite	B 9.5、D
MY-CURRENT Lite 2.5	0.5~2.5	5.1~25.5	4.43~22.13	1000~100	1173	192X92X50	MY-CURRENT Lite	B 9.5、D
MY-CURRENT Lite 3F	1~3	10.2~30.60	8.85~26.55	1700~200	1173	192X92X50	MY-CURRENT Lite	B 9.5、D
MY-CURRENT Lite 5	1.5~5	15.30~51.00	13.28~44.25	1000~100	1173	192X92X50	MY-CURRENT Lite	B 9.5、D
MY-CURRENT Lite 7	2~7	20.40~71.40	17.70~61.96	800~100	1173	192X92X50	MY-CURRENT Lite	B 9.5

