

KTM Series

KTM-1000 / 250 / 150 / 15 / 6 / 50S



KTM-1000



KTM-250



KTM-150 / 15 / 6



KTM-50S



Features

- LED can identify the test range of torque setting by needed user. If the result is not complying to torque range setting, light will be warned.
- USB connector is only used for data output, it is convenient for user to work with computer.
- Auto-zero can be selected and zero reset becomes unnecessary for user.
- Automatically test values about maximum, minimum and mean.
- ✳ KTM-6, KTM-15, KTM-150, KTM-250, KTM-1000 are suitable for shut off type screwdriver only.
- ✳ KTM-50S is for semi-shut off type electric screwdriver only.



Specifications

Model		KTM-1000	KTM-250	KTM-150	KTM-15	KTM-6	KTM-50S
Measuring Ranges	(kgf.cm)	50~1000	3.0~250.0	1.5~150.0	0.15~15.0	0.02~8.0	0.5~50.0
	(Lbf.in)	45~885	3.0~217.0	1.5~130.0	0.15~13.0	0.02~7.0	0.5~43.4
	(N.m)	5~100	0.30~25.00	0.15~15.0	0.015~1.500	0.002~0.8	0.05~4.90
Accuracy		+/- 0.5%(20~100N.m) +/- 1.0%(10~20N.m) +/- 2.0%(5~10N.m)	+/- 0.5%				
Power Supply		3.7V, 4400mAh Lithium Ion	4.8VDC (Ni-MH chargeable battery 1.2VX4 cell 1650mAh)				
Charging Time		8 hours	From empty -3 hours				
Operation Time		8 hours	About 12 hours				
Battery Life		Chargeable for 300 times or more. However, it varies depending on operating conditions.					
Size(mm)		229(W)X102(D)X80(H)	160(W)X210(D)X45(H)	230(W)X125(D)X65(H)			230(W)X123(D)X65(H)
Weight(kg)		2.7	2.0	1.8		1.8	1.8
Exclusive Charger		Input : AC100V~240V 50/60Hz Output : DC5V 1.0A Max	Input : AC100V~240V 50/60Hz Output : DC12V 400mA				
Accessory		Torque measuring adaptorX1 SJ-100N.m	Torque measuring adaptorX1 AJ-250	Torque measuring adaptorX3 AJ-150 / AJ-50 / AJ-15K	Torque measuring adaptorX2 AJ-15 / AJ-3	Torque measuring adaptorX1 AJ-3	Torque measuring adaptorX1 AJ-50S