

KFA-0820A(H) Series



KFA-0820A
(VACUUM PICK UP TYPE)



KFA-0820H
(MANUAL PICK UP TYPE)



Features

- **HOPPER CAPACITY :**
Capacity of hopper : 4000pcs (for M1.4X4) / 1200pcs (for M2.0X5).
- **APPLICABILITY OF SPECIAL SCREW TYPES :**
Applicable Thread length to thread diameter ratio = 1:1 or 1<1.
Screw head minimum thickness 0.2mm.
- **BRUSHLESS MOTOR :**
Adopted durable maintenance free made in Japan brushless motor.
- **CHANGEABLE RAILWAY :**
High precision wire cut changeable railway. Changeable rail, screw size from 1.2 mm up to 2.0mm.
- **CIRCULAR LOOP FEEDING :**
Circular loop feeding, adopting durable aluminum extruded rail. Screws are carried on a Circular track for smooth feeding.
- **COUNTER :**
Material shortage alert and screw taking counting function in digital display.
- **SIGNAL OUTPUT FUNCTION :**
Screws in position signal output .

Specifications

Model Name & Number	KFA-0820A(H)
Size	160(L)X82(W)X112(H) mm
Weight	1.53kg (w/o adapter)
Power Source	AC 100~240V
Switching Adapter	DC 12V Switching Adapter
Delivery Speed	42~90 pcs/min (0.7~1.5 Sec)
Feeding	Chamber Blanking
Scooping Chamber Capacity	4000pcs (for M1.4X4) / 1200pcs (for M2.0X5)

KFA-0820A(H) Applicable screw size

