



TOP QUALITY PALLET TRUCK

- Top class range of pallet trucks with excellent designs
- Professional and ideal storage aid for all variety of manual transport tasks over short distances in stores and warehouse as well as factory plants.
- Reliable, sturdy, torsion-resistant due to its extremely strong high quality steel profile Germany standard WAGNER painting system ensures best powder coatir and painting quality.
- All pivots points are greased ensures excellent maneuverability with effortless steering The chromed bearing bushes and joints ensure quiet running properties and particularly long service life.

Hand pallet truck				1KG=2.2LB 1INCH=25.4MM			
Item/Type		AC20		AC25		AC30	
Capacity Q	kg	2000		2500		3000	
Min. fork height h	mm	85	75	85	75	85	75
Max. fork height h _i	mm	200	190	200	190	200	190
Steering wheel	mm	Ø200x50	Ø180x50	Ø200x50	Ø180x50	Ø200x50	Ø180x50
Load roller Single	mm	Ø80x93	Ø74x93	Ø80x93	Ø74x93	Ø80x93	Ø74x93
Load roller Tandem	mm	Ø80x70	Ø74x70	Ø80x70	Ø74x70	Ø80x70	Ø74x70
Size of fork e*s	mm	160x50				160x60	
Width overall forks B	mm	450/520/540/685					
Fork length l	mm	800/900/1000/1100/1150/1220					

Conforms to EN 1757-2

Parameter

Item/Type		AC20		AC25		AC30	
Capacity Q	kg	2000		2500		3000	
Min.fork height h	mm	85	75	85	75	85	75
Max.fork height h _i	mm	200	190	200	190	200	190
Size of fork e*s	mm	160x50				160x60	
Width overall forks B	mm	450/520/540/685					
Fork length l	mm	800/900/1000/1100/1150/1220					


STANDARD PALLET TRUCK

- Professional and ideal storage aid for all variety of manual transport tasks over short distances in stores and warehouse as well as factory plants.
- Compact and attractive design with maximum loading capacity of 2000–3000kg
- Germany standard WAGNER painting system ensures best powder coating and painting quality.
- All pivots points are greased ensures excellent maneuverability with effortless steering
The chromed bearing bushes and joints ensure quiet running properties and particularly long service life.



Hand Pallet Truck		1KG=2.2LB 1INCH=25.4MM					
Item/Type		DF20		DF25		DF30	
Capacity Q	kg	2000		2500		3000	
Min. fork height h	mm	85	75	85	75	85	75
Max. fork height h ₁	mm	200	190	200	190	200	190
Steering wheel	mm	Ø 200x50	Ø 180x50	Ø 200x50	Ø 180x50	Ø 200x50	Ø 180x50
Load roller Single	mm	Ø 80x93	Ø 74x93	Ø 80x93	Ø 74x93	Ø 80x93	Ø 74x93
Load roller Tandem	mm	Ø 80x70	Ø 74x70	Ø 80x70	Ø 74x70	Ø 80x70	Ø 74x70
Size of fork e*s	mm	160x60					
Width overall forks B	mm	450/520/550/685					
Fork length l	mm	800/900/1000/1100/1150/1220					

Conforms to EN 1757-2



Option of single and tandem fork rollers
Additional entry and exit fork rollers
guarantees for maximum stability and
safety for transporting goods on slopes.



Parameter

Item/Type		DF20		DF25		DF30	
Capacity Q	kg	2000		2500		3000	
Min.fork height h	mm	85	75	85	75	85	75
Max.fork height h ₁	mm	200	190	200	190	200	190
Size of fork e*s	mm	160x60					
Width overall forks B	mm	450/520/540/685					
Fork length l	mm	800/900/1000/1100/1150/1220					