



通水电缆

Secondary Cable

主要特点 Main Characteristics

- ▶ 选用优质铜绞线缆，使得变压器输出至焊钳之间的电阻抗最低。
 - ▶ 工作时保证可挠性更好。
 - ▶ 最小的水压降，冷却效果好。
 - ▶ 选用耐压、耐热、耐磨性能良好的胶套及梅花胶芯，具有最大的挠屈性能。
 - ▶ 电缆更换方便省时。 7.使用寿命长，有良好的经济性。
-
- ▶ High-quality copper wire, making the least electrical impedance between the transformer output and welding gun.
 - ▶ Great flexibility during the work.
 - ▶ Smallest water pressure drop and good cooling effect
 - ▶ The pouches and plum plastic core against the pressure, heat and abrasive, with maximum torsion flexion performance.
 - ▶ lowest magnetic induction impact.
 - ▶ Easy to be replaced.
 - ▶ Long life span and economic



项 目		电缆尺寸规格	300mm ²	400mm ²	备 注
阻 抗	2.0M		480±15μΩ	358±15μΩ	
	2.4M		593±15μΩ	445±15μΩ	
直流阻抗值 (DC)	2.0M		475μΩ	355μΩ	
	2.4M		587μΩ	440μΩ	
电 阻	2.0M		78μΩ	74μΩ	计算值
	2.4M		82μΩ	88μΩ	
功 率			=0.99	=0.99	
冷却水通水量			7.0L/Min	7.0L/Min	压损0.7kg/cm
温度上升特点	2.0M		45°C/5900A	45°C/6800A	
	2.4M		45°C/5400A	45°C/6200A	
重 量	2.0M		10.4kg	13.2kg	平均值
	2.4M		12.2kg	15.3kg	