

气动式点焊机 Pneumatic Spot Welding Machine

主要特点 Main Characteristics

- ▶ 采用微电脑电路控制、精确度高
- ▶ 焊接电流20%-100%的细调
- ▶ 控制系统具有功率因数自适应功能，电极间的压力可调并恒定不变
- ▶ 广泛用于航空、建筑、机械、金属制品、电器开关等行业
- ▶ 用于低碳钢板、线材、不锈钢板等材料的焊接
- ▶ Microcomputer circuit control with high accuracy.
- ▶ Fine adjustment of welding current 20%-100%.
- ▶ The control system has power factor adaptive function, and the pressure between electrodes is adjustable and constant.
- ▶ Widely used in aviation, construction, machinery, metal products, electrical switches and other industries.
- ▶ Being used for welding of low carbon steel plate, wire, stainless steel plate and other materials.



Item(项目) \ Models(型号)	DN3-35	DN3-25	DN3-16
额定功率 Rated Power	35KVA	25KVA	16KVA
电压 Voltage	380V	380V	380V
额定初级电流 Rated Primary Current	92A	66A	42.1A
额定持续负载 Rated Duty Cycle	10%	10%	10%
次级空载电压 Secondary Unload Voltage	4.2V	2.3~3.55V	1.98~3.01V
调节级数 Adjustment Rated	1	4	4
控制器型号 Model of the Controller	TCW-32H	TCW-32H	TCW-32H
臂长 Arm Length	400mm	400mm	400mm
	280mm	280mm	280mm
最大电极压力 Max. Strength at Electrodes	1400N	1400N	860N
最大焊接能力 Max. Welding Capacity	3.5+3.5mm	2.5+2.5mm	2+2mm
冷却方式 Cooling	主变压器:空冷 电极:水冷 Main Transformer: Air Electrode: Water		

脚踏式点焊机 Pedal Spot Welding Machine

主要特点 Main Characteristics

- ▶ 采用杠杆踏板式弹簧加压结构，操作、维护方便
 - ▶ 采用可控硅无触点开关电路
 - ▶ 焊接时间可调，焊接重复性好
 - ▶ 可用于低碳钢板、线材、不锈钢板等材料的焊接。
 - ▶ 广泛用于汽车、航空、建筑、机械、金属制品、电器开关等
-
- ▶ Using lever type spring pressurizing structure and it is easy to operate and maintain.
 - ▶ Using SCR contact-less switching circuit.
 - ▶ Adjustable welding time and good welding repeatability.
 - ▶ Being used for welding low carbon steel plate, wire, stainless steel plate and other materials.
 - ▶ Widely used in automobile, aviation, construction, machinery, metal products, electrical switches and so on.



Item(项目)	Models(型号)	DN-35	DN-25	DN-16	DN-10
额定功率50% Rated Power at 50%		35KVA	35KVA	16KVA	10KVA
电源电压 Supply Voltage		380V	380V	380V	380V
额定电流 Rated Primary Current		92A	66A	42.1A	26.3A
负载持续率 Rated Duty Cycle		10%	10%	10%	10%
空载电压 Secondary Unload Voltage		2.6~4.2V	2.3~3.55V	2.3~3.55V	1.65~2.4V
调节级数 Adjustment Rated		4	4	4	4
焊接时间调节 Welding Time Adjustment		0~9.99s	0~9.99s	0~9.99s	0~9.99s
臂长 Arms Length		280mm	280mm	280mm	260mm
最大焊接能力 Max. Welding Capacity		3.5+3.5mm	2.5+2.5mm	2+2mm	1.5+1.5mm
冷却方式 Cooling Ways		主变压器:空冷 Main Transformer: Air			
		电极:水冷 Electrode: Water			