

FN系列缝焊机 FN Seam welder

FN: 交流缝焊机 AC Seam Welder
H: 横向焊接工件 Horizontal Welding
E: 纵向焊接机 Vertical Weldin

- ▶ 焊接速度均匀，调节方便、稳定
- ▶ 焊机回路均采用内部冷却、焊轮部分采用外冷却方式。
- ▶ 焊机转动导电部分采用内嵌式银瓦结构，导电座内全密封性油浸式导电和润滑，采用内部强制冷却，增强了导电轴的冷却效果。提高导电率的同时有效的防止了轴瓦的“咬死”现象，转动灵活。
- ▶ 缝焊机有纵焊和横焊两种形式。
- ▶ 广泛应用于五金、家电、汽车、油箱等制造行业，最适合焊接低碳钢、不锈钢等材料的盆、桶、箱及密封薄壁容器的焊接。
- ▶ The welding process is stable and easy to adjust.
- ▶ Internal cooling used in the welder, while external cooling of the welding wheel.
- ▶ The rotating part is embedded silver tile structure, the conductive seat is fully sealed and lubricating, which improves the conductivity and the rotation flexibility .
- ▶ Two kinds of welding modes: Horizontal and Vertical
- ▶ Widely used in hardware fittings, electrical, automobile, fuel tank and other manufacturing industries industry.



Item (项目) Models (型号)	额定容量 Rated power	输入电压 Voltage input	额定频率 Frequency	最大 短路电流 Max short circuit current	电极行程 Working stroke	焊接速度 Welding efficiency	电极压力 Max. force	焊接能力 Max. welding capacity	电动机功率 Motor Power	冷却水流量 Cooling consumption	重量 Weight
Unit(单位)	KVA	V	Hz	KA	MM	m/min	N	MM	W	L/min	Kg
FN-80-H	80	380	50	26	100	0.7-3.9	6000	1.2+1.2	550	8	380
FN-100-H	100	380	50	30	100	0.7-3.9	6000	1.5+1.5	750	8	510
FN-160-H	160	380	50	40	100	0.7-3.9	7800	2.0+2.0	750	10	630
FN-100-E	100	380	50	30	100	0.7-3.9	6000	1.5+1.5	750	8	530
FN-160-E	160	380	50	40	100	0.7-3.9	7800	2.0+2.0	400	10	700