



DND3系列移动式单面单点焊机

DND3 MOBILE SINGLE SIDE SPOT WELDING MACHINE

主要特点 Main Characteristics

- ▶ DND3系列移动式单面单点焊机为点焊机的一种，适用于一般低碳钢、不锈钢薄板与低碳钢构架之间的点焊焊接。
- ▶ 本焊机系单点、单人工点焊机。焊机由点焊枪与集电钳通过被焊件构架形成焊接回路，达到点焊的目的，配合微电脑焊接控制器，确保稳定的焊接电流。
- ▶ 本焊机焊接变压器总成可安装在小车上移动，也可像DN3系列焊机一样悬挂移动。焊接时，被焊工件不动，焊枪移动，操作安全、可靠、灵活，可达到全方位焊接要求。
- ▶ 该焊机适用于汽车特别是客车表面蒙皮与构架之间的点焊，以及金属箱柜和门窗等薄板的焊接。
- ▶ The welding machines are used to weld the low carbon steel, stainless steel sheet and low carbon steel structure.
- ▶ It is for single point, manual spot welding, made up of gun and clamp through welding structure formed by welding circuit, achieving the purpose of spot welding. Cooperating with the micro-computer controller, it can ensure the stable welding current.
- ▶ The welding machines can be installed on the cart, which could be movable. And it can also hanged like DN3 series welding machine for moving freely. During the welding, the workpieces are static, while the welding gun is movable. It's safe and reliable and flexible, which can achieve all-round welding requirements completely.
- ▶ The welding machine can be used in the automobile welding, especially for welding the bus skin and the structure, and the sheet welding such as metal box, door or casement.



Item (项目)	Models (型号)	Unit(单位)	DND3-160	DND3-200
额定功率 Rated power		KVA	160	200
额定输入电流 Rated input current		A	400	475
额定负载持续率 Rated duty cycle		%	50	
额定输入电压 Rated input voltage		V	380	
频率 Power supply frequency		Hz	50/60	
次级空载电压 Secondary unload voltage		V	21.7 ~ 19	24.5 ~ 21.7
最大焊接能力 Max welding ability		MM	1.0+ 构架	1.5+ 构架
最大输出电流 Max imum ouput current		A	14800	16200
绝缘等级 Insulating grsde			F	
冷却水量 Cooling water consumption 2.5bar		L/min	14	16
冷却水压力 Pressure of cool water		Mpa	0.15-0.3Mpa	
气源压力 Pressure of compressed air		Mpa	0.5-0.6Mpa	
绝缘电阻 Insulating resistance			500VDC = 500M	
介电强度 Diele ctric intensity			2500V,60S(初级Primary-Secondary)	
重量 Weight		Kg	220	240

移动手持式点焊机 Mobile Handheld Spot Welding Machine

主要特点 Main Characteristics

- ▶ 适用于碳钢、不锈钢、铁皮等金属材料的焊接
 - ▶ 可适应不同位置、结构复杂的板材的焊接
 - ▶ 尤其适合于薄板、丝网、箱、柜、防盗门、汽车保修、钢制家具、不锈钢制品、厨房设备、空调设备行业的焊接
 - ▶ 两把结构不同的焊枪，有利于对工件的焊接
-
- ▶ Suitable for welding of carbon steel, stainless steel, iron sheet and other metal materials
 - ▶ Being able to adapt to different positions, complex structure of the plate welding.
 - ▶ Especially suitable for thin plate, screen, box, cabinet, security door, car warranty, steel furniture, stainless steel products, kitchen equipment, and air conditioning equipment industry.
 - ▶ Two welding guns with different structures are conducive to the welding of the workpieces.



Models(型号)	DNY-80	DNY-50	DNY-35	DNY-25	DNY-16
Parameter(参数)					
额定功率 Rated Power	80KVA	50KVA	35KVA	25KVA	16KVA
电源电压 Supply Voltage	380V	380V	380V	380V	380V
额定电流 Rated Primary Current	211A	132A	92A	66A	42.1A
负载持续率 Rated Duty Cycle	10%	10%	10%	10%	10%
空载电压 Secondary Unload Voltagea	9.5~19V	7.6~15.2V	7.6~12.7V	7.6~12.7V	6.2~11V
调整节数 Adjustment Tated	2	2	1	4	4
焊接时间调节 Welding Time Adjustment	0~250CYC	0~250CYC	0~250CYC	0~9.99s	0~9.99s
二次电缆长度 Secondary Cable Length	2m	2m	2m	2m	2m
焊接厚度 Welding Thickness	(0.2~1.5)+4mm	(0.2~1.5)+3.5mm	(0.2~1.2)+3mm	(0.2~1)+3mm	(0.1~0.6)+2mm
冷却方法 Cooling Method	主变压器:水冷却 电极:水冷却 Main Transformer: Water Cooling Electrode: Water Cooling				