



D(T)N系列固定式点（凸）焊机

D(T)N Stationary Spot And Projection Welding Machine

主要特点 Main Characteristics

- ▶ 稳固的机身结构，上下电极采用带辅助行程的加压方式，焊接效率更高，通用性更强。
- ▶ 焊机变压器采用专用阻焊变压器，硅钢片磁导率高，强制内部水冷。出力强劲，暂载率高。
- ▶ 采用微电脑控制，可存储1-16组焊接规范，非常方便地实现不同工件的准确焊接。
- ▶ 广泛适用于汽车制造、家用电器制造、钣金加工、五金制品、铁线、金属网片、电子及其他领域。
- ▶ Stable machine structure upside and downside of electrodes apply the pressure mode with assistant stroke. The welding efficiency is much higher.
- ▶ The transformer of welding machine adopts the special resistance welding machine, the silicon steel slice is featured of high magnetic; the inner water-cooled by force; stronger power and high duty ratio.
- ▶ Controlled by micro-computer and can saved at most 16 sets of welding settings, which is quite convenient for different kinds of welding sheets.
- ▶ Widely applicable to automobile manufacturing, production of house applications, hardware fittings and so on.



Models (型号)		Unit(单位)	DN-40	DN-63	D(T)N-80	D(T)N-100	D(T)N-125	D(T)N-160	D(T)N-200
Item (项目)									
额定容量 Rated power At 50%		KVA	40	63	80	100	125	160	200
额定初级电压 Rated primary power		V	380	380	380	380	380	380	380
次级电压 Secondary Voltage		V	5.2	6.7	7.9	8.3	8.6	9.1	10.6
额定频率 Rated frequency		HZ	50/60	50/60	50/60	50/60	50/60	50/60	50/60
最大短路电流 Max.Short Circuit Current		KA	14	15	16	18	20	28	34
最大焊接功率 Max. weld power		KVA	62	86	170	280	300	330	410
臂伸尺寸 Throat		MM	400	400	400	450	450	450	450
最大加压力 Max.Froce at electrodes		N	6000	6000	10000	10000	10000	12000	12000
电极行程 Working stroke		MM	20	20	30	40	40	50	50
冷却水量 Cooling Water Consumption 2.5bar		L/min	6	6	8	8	8	10	10
电极尺寸 Electrodes Dimensions	电极 Electrodes tlp	MM	Φ13*45	Φ13*45	Φ16*45	Φ16*45	Φ16*45	Φ20*45	Φ20*45
	电极臂 Arms	MM	Φ50*150	Φ50*150	Φ80*220	Φ80*220	Φ80*220	Φ80*220	Φ80*220
	凸焊台 Projection Clamping Plate	MM	125*125	125*125	200*200	200*200	200*200	200*200	200*200
焊接能力 Max.WeldingCapacity	低碳钢 A3 steel	MM	2.5+2.5	3+3	4+4	4.5+4.5	5+5	5+5	6+6

DN(B)中频固定点焊机

DN(B) MF Stationary Spot Welding Machine

DN(B)系列焊机是中频逆变固定式点焊机，三相380V/50Hz的交流电源输入到焊机，经三相整流器整流，使用逆变技术和反馈控制，实现焊接热量、预压时间、维持时间以及休止时间的控制，从而达到满足焊接规范的要求。其设备广泛应用于汽车制造、家用电器、电子仪表航空航天以及其它有点凸焊工艺的行业中。

DN (B) MF Stationary Spot Welding Machine is working on the 380V/50Hz three-phase AC power supply. By the three-phase rectifier, inverter technology and the feedback control system, to control the welding heat, pre-press time, the maintenance time and cease time, achieving the welding the requirements. The machine is widely used in automobile, home appliances, electronic instrumentation, aerospace and other projection welding process industry.



Item (项目)	Models (型号)	Unit(单位)	DN(B)-160	DN(B)-200	DN(B)-250
额定功率 Rated power		KVA	160	200	250
输入电源 Power input		V	3φAC 380V	3φAC 380V	3φAC 380V
最大短路电流 Max. short circuit current		KA	40	40	45
负载持续率 Duty cycle		%	50	50	50
最大加压力 Max. force		N	6000	10000	15000
臂伸尺寸 Electrode length		MM	450	450	500
电极行程 Working stroke		MM	80	80	80
冷却水量 Cooling consumption		L/min	20	20	20
焊接能力 Max. welding capacity		MM	4.0+4.0	5.0+5.0	6.0+6.0