

储能式螺柱焊机 Energy storage stud welding machine

主要特点 Main Characteristics

- ▶ 电容放电式螺柱焊机具有提高生产效率，减少生产环节，降低生产（材料、人工、电力能源）成本，焊接强度高、工件不变形和各种位置都可以方便焊接的特点，操作方便，一学就会。
- ▶ 可以取代铆接或钻孔等紧固方法，焊接时间仅为3-6毫秒，可以将螺柱焊到厚度仅为0.3毫米的薄板上，不致引起变形，变色或烧穿，不会损坏焊接工件背面的油漆或镀膜层。
- ▶ 该设备广泛地应用在机车车辆，汽车制造，化工工业，电器工业，仪器仪表，厨房用具，金属器皿，五金等行业中，有着较高的经济效益。
- ▶ The capacitor discharge type stud welding machine has the characteristics of improving production efficiency, reducing production links, reducing production (material, labor, power energy) costs, high welding strength, no deformation of the workpiece, and convenient welding at various positions. It is easy to operate and easy to learn.
- ▶ It can replace fastening methods such as riveting or drilling, with a welding time of only 3-6 milliseconds. The studs can be welded to a thin plate with a thickness of only 0.3 millimeters, without causing deformation, discoloration or burning through, and without damaging the paint or coating layer on the back of the welded workpiece.
- ▶ This equipment is widely used in industries such as locomotives and vehicles, automobile manufacturing, chemical industry, electrical industry, instruments and meters, kitchen utensils, metal utensils, and hardware, with high economic benefits.



Item(项目)	Models(型号)	RSR-2500	RSR-3500
充电电容量 Charging Capacitance		108000uf	144000uf
充电电压 Charging Voltage		35-200V	35-200V
焊接时间 Welding Time		0.001-0.003S	0.001-0.003S
输入功率 Input Power		500W	800W
焊接范围: 低碳钢 Welding Range: Low-carbon Steel		2-8mm	2-10mm
焊接范围: 不锈钢 Welding Range: Stainless Steel		2-8mm	2-8mm
焊接范围: 铝合金 Welding Range: Aluminum Alloy		2-8mm	2-8mm
焊接范围: 锌材料 Welding Range: Zinc Material		2-8mm	2-8mm
螺钉焊接直径 Diameter of welding stud		M3-M8	M3-M10
尺寸 Overall dimension (mm)		480*220*300mm	600*220*300mm
电源重量 Dimesion		18Kg	22Kg
输入电源电压/频率 Input Voltage (V)	AC220V-2P(110V/380V/415V) 50/60HZ		
电源 Power Supply	电解电容器 Electrolytic Capacitor		
焊接速度 Welding Speed	最大40只/分钟 Max. 40 Pieces/Minute		