

## SKC-LB Series



SKC-LB1820



SKC-LB1840



SKC-LB1830C



SKC-LB1430



SKC-LB1030S



SKC-LB0730S

## Features

- Adopting Japanese and Korea high performance Li-ion (Li-Mn) battery.
- Built in protection device to prevent battery overcharge and over discharge.
- The latch design increases intensity and convenience when assembling or dismantling the rechargeable battery from the cordless screwdriver.
- Fully charged voltage: 21V, low-voltage protection: 13.5V, over-temperature protection (discharge): 72°C.
- Battery ID identification design, which only allows original charge station to recharge the battery to secure battery safety and extend battery lifetime.

## Battery charging time reference

| Battery Model / Capacity | MYCS-ID120 | MYCS-ID80 | MYCS-80 | MYCS-ID80-D | MYCS-ID70+ | MYCS-ID50 | MYCS-ID25 |
|--------------------------|------------|-----------|---------|-------------|------------|-----------|-----------|
| SKC-LB1820               | 40 min.    | 40 min.   | 40 min. |             |            |           |           |
| SKC-LB1840               | 60 min.    | 80 min.   | 80 min. |             |            |           |           |
| SKC-LB1830C              |            |           |         | 45 min.     |            |           |           |
| SKC-LB1430               |            |           |         |             | 70 min.    |           |           |
| SKC-LB1030S              |            |           |         |             |            | 55 min.   |           |
| SKC-LB0730S              |            |           |         |             |            |           | 70 min.   |

## Specifications

| Battery Model            | SKC-LB1820          | SKC-LB1840          | SKC-LB1830C         | SKC-LB1430          | SKC-LB1030S         | SKC-LB0730S         |
|--------------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| Voltage                  | 18V                 | 18V                 | 18V                 | 14.4V               | 10.8V               | 7.2V                |
| Capacity                 | 1950mA/hr           | 3900mA/hr           | 3000mA/hr           | 3000mA/hr           | 3000mA/hr           | 3000mA/hr           |
| Rated voltage            | 18V                 | 18V                 | 18V                 | 14.4V               | 10.8V               | 7.2V                |
| Power                    | 35Wh                | 70Wh                | 54Wh                | 43.2Wh              | 32.4Wh              | 21.6Wh              |
| Cells Permutation        | 5 series 1 parallel | 5 series 2 parallel | 5 series 1 parallel | 4 series 1 parallel | 3 series 1 parallel | 2 series 1 parallel |
| Weight                   | 430g                | 720g                | 430g                | 327g                | 194g                | 128g                |
| Dimensions(mm)           | 119X90X40           | 119X90X59           | 92X75X63            | 107X75X43           | 51X46X90            | 51X44X70            |
| Certification            | CE,TUV              | CE,TUV              | CE,TUV              | CE,TUV              | CE,TUV              | CE,TUV              |
| UN38.3 Inspection report | YES                 | YES                 | YES                 | YES                 | YES                 | YES                 |