

NERRS / SWMP

Training Workshop: *R Intro & SWMP*

October 25, 2015

SWMP_r analyze

Marcus W. Beck¹ Todd D. O'Brien²

¹ORISE, USEPA NHEERL Gulf Ecology Division

Email: beck.marcus@epa.gov

²NOAA/NMFS COPEPOD Project

Email: todd.obrien@noaa.gov

Objectives for the session

- What are some basic analyses that can be accomplished with SWMPPr?
- What are some plotting functions provided by SWMPPr?
- What are some resources for additional learning?

Interactive portion

We will use the `swmpr2.Rproj` project for this session, double-click to open in RStudio

- location on flash drive
- location online

Interactive portion

We will use the swmpr2.Rproj project for this session, double-click to open in RStudio

- location on flash drive
- location online

You will run examples whenever you see this guy:



Don't forget to use your stickies: **green** for done/ok, **red** for problem

Basic analyses with SWMP_r

How do we want to use the data?

Basic analyses with SWMP_r

How do we want to use the data?

- What has happened at my site over time?
- Are there differences between sites?
- Can we remove seasonal trends?
- Are there differences between parameters?
- Others?

Basic analyses with SWMPPr

Take a few minutes to acquaint yourself with the ***analyze*** functions:

```
help.search('analyze', package = 'SWMPPr')
```

Basic analyses with SWMPPr

Take a few minutes to acquaint yourself with the ***analyze*** functions:

```
help.search('analyze', package = 'SWMPPr')
```

Which functions simplify the data?

Which functions could you use to explore or visualize the data?

Which functions are related to metabolism?

Basic analyses with SWMP_r - missing data

Most datasets will have missing values - how do you deal with those?

Remove? Set as mean? Replace with similar?

SWMP_r provides a function to interpolate missing data: `na.approx`

To start, let's import and plot some data...

Basic analyses with SWMPr - missing data

- Import the 2012 water quality data for cbmmc from the 'zip_ex' folder
- Deal with QAQC columns
- Select two columns of interest
- Plot the data subset (`?plot.swmpr`)

Basic analyses with SWMPr - missing data

- Import the 2012 water quality data for cbmmc from the 'zip_ex' folder

```
mypath <- 'zip_ex'  
dat <- import_local(mypath, 'cbmmcwq2012')
```

- Deal with QAQC columns
- Select two columns of interest
- Plot the data subset (?plot.swmpr)

Basic analyses with SWMPPr - missing data

- Import the 2012 water quality data for cbmmc from the 'zip_ex' folder

```
mypath <- 'zip_ex'  
dat <- import_local(mypath, 'cbmmcwq2012')
```

- Deal with QAQC columns

```
tmp <- qaqc(dat)
```

- Select two columns of interest
- Plot the data subset (?plot.swmpr)

Basic analyses with SWMPPr - missing data

- Import the 2012 water quality data for cbmmc from the 'zip_ex' folder

```
mypath <- 'zip_ex'  
dat <- import_local(mypath, 'cbmmcwq2012')
```

- Deal with QAQC columns

```
tmp <- qaqc(dat)
```

- Select two columns of interest

```
tmp <- subset(tmp, select = 'do_mgl', subset = c('2012-10-01 0:0',  
  '2012-10-31 0:0'))
```

- Plot the data subset (?plot.swmpr)

Basic analyses with SWMP_r - missing data

- Import the 2012 water quality data for cbmmc from the 'zip_ex' folder

```
mypath <- 'zip_ex'  
dat <- import_local(mypath, 'cbmmcwq2012')
```

- Deal with QAQC columns

```
tmp <- qaqc(dat)
```


- Select two columns of interest

```
tmp <- subset(tmp, select = 'do_mgl', subset = c('2012-10-01 0:0',  
  '2012-10-31 0:0'))
```

- Plot the data subset (?plot.swmpr)

```
plot(tmp)
```

Basic analyses with SWMPr - missing data



Notice the missing data around October 12th

The `na.approx` function (`na.approx.swmpr`) has three arguments:

- `object`: `swmpr` data object to fill
- `params`: name(s) of parameter to fill
- `maxgap`: maximum gap size to interpolate

Basic analyses with SWMP_r - missing data

- Use `na.approx` to interpolate the missing data (`na.approx.swmpr`)
- Plot the two to see the differences

Basic analyses with SWMP_r - missing data

- Use `na.approx` to interpolate the missing data (`na.approx.swmpr`)

```
tmp2 <- na.approx(tmp, params = 'do_mgl', maxgap = 100)
```

- Plot the two to see the differences



Basic analyses with SWMP_r - missing data

- Use `na.approx` to interpolate the missing data (`na.approx.swmpr`)

```
tmp2 <- na.approx(tmp, params = 'do_mgl', maxgap = 100)
```

- Plot the two to see the differences

```
plot(tmp)  
plot(tmp2)
```




Basic analyses with SWMPr - smoothing data

Now we know how to fill missing data, let's see how it can help...

Trend evaluation often considers variation at different spatial scales

As an example, we want to evaluate variation in dissolved oxygen at seasonal or annual scales



Analysis 2 - Smoothing and aggregation

The `smoother` function (`?smoother`) calculates a moving window average of a time series

- `x`: Input data object
- `window`: the size of the smoothing window, defaults to five observations at the current time step
- `sides`: what defines the window, centered on an observation (2, default) or use only the preceding observations (1)
- `params`: which parameters to smooth, default all

What would be a good window to look at seasonal or annual variation?

Basic analyses with SWMPr - smoothing data

- Import all years of water quality data for cbmip from the 'zip_ex' folder
- Deal with QAQC columns and subset DO
- Use `smoother` to remove daily and short-term variation, which window to use?
- Plot results (see `?plot.swmpr` and `?lines.swmpr`)

Basic analyses with SWMPr - smoothing data

- Import all years of water quality data for cbmip from the 'zip_ex' folder

```
mypath <- 'zip_ex'  
dat <- import_local(mypath, 'cbmipwq')
```

- Deal with QAQC columns and subset DO
- Use smoother to remove daily and short-term variation, which window to use?
- Plot results (see ?plot.swmpr and ?lines.swmpr)

Basic analyses with SWMP_r - smoothing data

- Import all years of water quality data for cbmip from the 'zip_ex' folder

```
mypath <- 'zip_ex'  
dat <- import_local(mypath, 'cbmipwq')
```

- Deal with QAQC columns and subset DO

```
tmp <- qaqc(dat)  
tmp <- subset(dat, select = 'do_mgl')
```

- Use smoother to remove daily and short-term variation, which window to use?
- Plot results (see ?plot.swmpr and ?lines.swmpr)

Basic analyses with SWMPPr - smoothing data

- Import all years of water quality data for cbmip from the 'zip_ex' folder

```
mypath <- 'zip_ex'  
dat <- import_local(mypath, 'cbmipwq')
```

- Deal with QAQC columns and subset DO

```
tmp <- qaqc(dat)  
tmp <- subset(dat, select = 'do_mgl')
```

- Use smoother to remove daily and short-term variation, which window to use?

```
do_smooth <- smoother(tmp2, window = 5000)
```

- Plot results (see ?plot.swmpr and ?lines.swmpr)

Basic analyses with SWMPPr - smoothing data

- Import all years of water quality data for cbmip from the 'zip_ex' folder

```
mypath <- 'zip_ex'  
dat <- import_local(mypath, 'cbmipwq')
```

- Deal with QAQC columns and subset DO

```
tmp <- qaqc(dat)  
tmp <- subset(dat, select = 'do_mgl')
```


- Use smoother to remove daily and short-term variation, which window to use?

```
do_smooth <- smoother(tmp2, window = 5000)
```

- Plot results (see ?plot.swmpr and ?lines.swmpr)

```
plot(tmp)  
lines(do_smooth)
```

Basic analyses with SWMPr - smoothing data




What happened?

How can we fix the problem?

Basic analyses with SWMPr - smoothing data

Repeat the analysis but use `na.approx` to fill missing data


```
mypath <- 'zip_ex'  
dat <- import_local(mypath, 'cbmipwq')  
tmp <- qaqc(dat)  
tmp <- subset(tmp, select = 'do_mgl')  
tmp <- na.approx(tmp, maxgap = 5000)  
do_smooth <- smoother(tmp, window = 5000)  
plot(tmp)  
lines(do_smooth, col = 'red')
```



Basic analyses with SWMPPr - smoothing data

Repeat the analysis but use `na.approx` to fill missing data

```
mypath <- 'zip_ex'
dat <- import_local(mypath, 'cbmipwq')
tmp <- qaqc(dat)
tmp <- subset(tmp, select = 'do_mgl')
tmp <- na.approx(tmp, maxgap = 5000)
do_smooth <- smoother(tmp, window = 5000)
plot(tmp)
lines(do_smooth, col = 'red')
```



Bonus: Try changing `maxgap` or `window`

Basic analyses with SWMPr - aggregating data

Finally, we can use `aggreswmp` to summarize and plot for an alternative interpretation

`aggreswmp` has five main arguments:

- `swmpr_in`: input data object
- `by`: aggregation period ('years', 'quarters', etc.)
- `FUN`: aggregation function, defaults to mean
- `params`: which parameters to aggregate, defaults all
- `aggs_out`: get the raw data, use this to make plots

Basic analyses with SWMP_r - aggregating data

- Import all years of water quality data for cbmip from the 'zip_ex' folder, QAQC cleanup, and subset DO
- Use `aggreswmp` (`?aggreswmp`) to get quarterly summaries of the data

Basic analyses with SWMPr - aggregating data

- Import all years of water quality data for cbmip from the 'zip_ex' folder, QAQC cleanup, and subset DO

```
mypath <- 'zip_ex'
dat <- import_local(mypath, 'cbmipwq')
tmp <- qaqc(dat)
tmp <- subset(dat, select = 'do_mgl')
```

- Use `aggreswmp` (?aggreswmp) to get quarterly summaries of the data

Basic analyses with SWMPPr - aggregating data

- Import all years of water quality data for cbmip from the 'zip_ex' folder, QAQC cleanup, and subset DO

```
mypath <- 'zip_ex'
dat <- import_local(mypath, 'cbmipwq')
tmp <- qaqc(dat)
tmp <- subset(dat, select = 'do_mgl')
```

- Use `aggreswmp` (?aggreswmp) to get quarterly summaries of the data

```
aggtmp <- aggreswmp(tmp, by = 'quarters')
```


Basic analyses with SWMPr - aggregating data

- Import all years of water quality data for cbmip from the 'zip_ex' folder, QAQC cleanup, and subset DO

```
mypath <- 'zip_ex'  
dat <- import_local(mypath, 'cbmipwq')  
tmp <- qaqc(dat)  
tmp <- subset(dat, select = 'do_mgl')
```

- Use `aggreswmp` (?aggreswmp) to get quarterly summaries of the data

```
aggtmp <- aggreswmp(tmp, by = 'quarters')
```

- Bonus: Try different aggregation periods
- Bonus: Try different aggregation functions

Basic analyses with SWMPPr - aggregating data

- Import all years of water quality data for cbmip from the 'zip_ex' folder, QAQC cleanup, and subset DO

```
mypath <- 'zip_ex'
dat <- import_local(mypath, 'cbmipwq')
tmp <- qaqc(dat)
tmp <- subset(dat, select = 'do_mgl')
```

- Use `aggreswmp` (`?aggreswmp`) to get quarterly summaries of the data

```
aggtmp <- aggreswmp(tmp, by = 'quarters')
```

- Bonus: Try different aggregation periods

```
aggtmp <- aggreswmp(tmp, by = 'years')
aggtmp <- aggreswmp(tmp, by = 'weeks')
```

- Bonus: Try different aggregation functions

Basic analyses with SWMP^r - aggregating data

- Import all years of water quality data for cbmip from the 'zip_ex' folder, QAQC cleanup, and subset DO

```
mypath <- 'zip_ex'  
dat <- import_local(mypath, 'cbmipwq')  
tmp <- qaqc(dat)  
tmp <- subset(dat, select = 'do_mgl')
```

- Use `aggreswmp` (?`aggreswmp`) to get quarterly summaries of the data

```
aggtmp <- aggreswmp(tmp, by = 'quarters')
```

- Bonus: Try different aggregation periods

```
aggtmp <- aggreswmp(tmp, by = 'years')  
aggtmp <- aggreswmp(tmp, by = 'weeks')
```

- Bonus: Try different aggregation functions

```
fun_in <- function(x) var(x, na.rm = TRUE)  
aggreswmp(swmpr_in, FUN = fun_in, 'years')
```

Basic analyses with SWMP_r - aggregating data

Plot the aggregated data by quarters - use `aggs_out = TRUE`

Basic analyses with SWMPPr - aggregating data

Plot the aggregated data by quarters - use `aggs_out = TRUE`

```
# use aggs_out to get all  
aggtmp <- aggreswmp(tmp, by = 'quarters', aggs_out = TRUE)
```

Basic analyses with SWMPr - aggregating data

Plot the aggregated data by quarters - use `aggs_out = TRUE`

```
# use aggs_out to get all  
aggtmp <- aggreswmp(tmp, by = 'quarters', aggs_out = TRUE)
```

Then use `boxplot` (`?boxplot`) from the R stats package


Basic analyses with SWMPPr - aggregating data

Plot the aggregated data by quarters - use `aggs_out = TRUE`

```
# use aggs_out to get all  
aggtmp <- aggreswmp(tmp, by = 'quarters', aggs_out = TRUE)
```

Then use `boxplot` (`?boxplot`) from the R stats package

```
# use boxplot  
boxplot(do_mgl ~ datetimestamp, data = aggtmp, ylab = 'do_mgl', ylim = c(0, 15))
```




Basic analyses with SWMP_r - aggregating data

Plot the aggregated data by quarters - use `aggs_out = TRUE`

```
# use aggs_out to get all  
aggtmp <- aggreswmp(tmp, by = 'quarters', aggs_out = TRUE)
```

Then use `boxplot` (`?boxplot`) from the R stats package

```
# use boxplot  
boxplot(do_mgl ~ datetimestamp, data = aggtmp, ylab = 'do_mgl', ylim = c(0, 15))
```



Have a look at the data from `aggs_out = TRUE` and `aggs_out = FALSE`, how do they differ and why?

Plotting functions in SWMP_r

R provides near limitless options to visualize data - a full coverage of these tools would take days

We will briefly go over some key plotting functions in SWMP_r, each is designed for simplicity and efficiency to summarize lots of data

Plotting functions in SWMP_r:

- `decomp`: time series decomposition
- `decomp_cj`: time series decomposition, alternative
- `map_reserve`: plot a basic map of a reserve
- `overplot`: plot multiple parameters on the same plot
- `plot_metab`: plot metabolism estimates
- `plot_summary`: plot multiple summaries for a parameter

Plotting functions in SWMP_r


The `map_reserve` function can be used to map sites:

- `nerr_site_id`: site(s) to map, usually first three letters
- `zoom`: zoom factor for the map (usually between 5–15)
- `map_type`: 'terrain', 'satellite', 'roadmap', or 'hybrid'

```
# try any of these examples
map_reserve('jac')

map_reserve('elk', zoom = 13,
  map_type = 'hybrid')

map_reserve('gtmss', zoom = 15,
  map_type = 'satellite',
  text_col = 'lightblue')
```



NERRS / SWMP

Training Workshop: *R Intro & SWMP*

October 25, 2015

Questions??